

```
SELECT *  
FROM pax  
ORDER BY PaxName;
```

```
SELECT AirportCode, AirportName  
FROM airport  
WHERE CountryCode = 'ES'  
ORDER BY AirportCode;
```

```
SELECT r.RouteID, r.Duration  
FROM route r, airport a  
WHERE r.Origin = a.AirportID AND a.AirportCode = 'LHR';
```

```
SELECT r.RouteID, o.AirportCode AS OriginCode, d.AirportCode AS DestinationCode  
FROM route r, airport o, airport d  
WHERE r.Origin = o.AirportID AND r.Destination = d.AirportID  
ORDER BY OriginCode, DestinationCode;
```

```
SELECT r.RouteID, o.AirportCode AS Origin, d.AirportCode AS Destination  
FROM route r, airport o, airport d  
WHERE r.Origin = o.AirportID  
AND r.Destination = d.AirportID  
ORDER BY OriginCode DESC, DestinationCode DESC;
```

```
SELECT f.FlightID, t.AircraftName  
FROM flight as f, aircraft as a, aircrafttype as t  
WHERE f.AircraftID = a.AircraftID  
AND a.AircraftTypeID = t.AircraftTypeID  
AND t.AircraftName LIKE 'Airbus %';
```

```
SELECT p.PaxName, p.FlightDate, r.Origin AS Origem, r.Destination AS Destino  
FROM pax p, flight f, route r  
WHERE p.FlightID = f.FlightID  
AND f.RouteID = r.RouteID;
```

```
SELECT p.PaxName, p.FlightDate, o.AirportCode AS Origem, d.AirportCode AS Destino  
FROM pax p, flight f, route r, airport o, airport d  
WHERE p.FlightID = f.FlightID  
AND f.RouteID = r.RouteID  
AND r.Origin = o.AirportID  
AND r.Destination = d.AirportID  
ORDER BY p.PaxName;
```

```
SELECT f.FlightID, a.AirportCode, c.MaxSeats  
FROM flight f, route r, airport a, flightclass c  
WHERE f.FlightID = c.FlightID  
AND f.RouteID = r.RouteID  
AND r.Destination = a.AirportID  
AND c.ClassID = 3  
ORDER BY c.MaxSeats DESC;
```

```
SELECT c.ClassName, f.FlightID, fc.MaxSeats, fc.BasePrice  
FROM class as c, flight as f, flightclass as fc
```

ORDER BY c.ClassName, f.FlightID, fc.BasePrice;