

In-memory Spatial-Aware Framework for Processing Proximity-Alike Queries in Big Spatial Data

Isam Mashhour Al Jawarneh, Paolo
Bellavista, Antonio Corradi, **Luca
Foschini**, Rebecca Montanari,
Andrea Zanotti

DISI, University of Bologna, ITALY
{isam.aljawarneh3, paolo.bellavista,
antonio.corradi, **luca.foschini**,
rebecca.montanari}@unibo.it,
andrea.zanotti@studio.unibo.it

Monday, 17th September 2018, IEEE CAMAD'18



Quality of Service Aware Data Stream Processing for Highly Dynamic and Scalable Applications

Isam Mashhour Hasan Al Jawarneh

PhD Candidate, Cycle XXXII

DISI, University of Bologna, ITALY

isam.aljawarneh3@unibo.it,

Supervisor:


Prof. **Rebecca Montanari**

PhD program coordinator:

Prof. **Davide Sangiorgi**

PhD. Esame finale anno 2020, 2nd





Agenda

- **Smart City and Big Data Context**
 - Geolocated big data
 - MapReduce
 - Spark and GeoSpak
- **Spatial-Aware Big Data Management Strategies**
 - Self-Adaptable Spatial-Aware Partitioner (SASAP)
 - Spatial-aware query optimizations
- **Experimental Results**
 - Partitioning results
 - Proximity, containment and density based clustering query performance results
- **Conclusions & Ongoing Works**

Smart City and Big Data Context

Smart City

Advanced technological services

Geographic Big Data

Huge amount of information


Mobile Sensing

Automatic collection of data




Geo-located Big Data

- Large amounts of geolocated data, **exceeding processing capability** of traditional database management systems
- Characteristics
 - **Volume**: amount of data
 - **Velocity**: streaming data
 - **Variety**: multiple sources, heterogeneous data
- Other characteristics
 - **Veracity**: uncertainty degree
 - **Variability**: possible inconsistency
 - **Complexity**: difficult to establish connection and relationships between data



Advanced Geospatial Queries & Clustering DBSCAN Algorithm

- **Eps (ϵ)** = max distance
- **MinPts** = minimum number of points inside radius ϵ




- **Core points (cp):** $\#(X: \text{dist}(X, Y) \leq \epsilon) \geq \text{MinPts}$
- **Cluster:** $\{X: \text{dist}(X, \text{cp}) \leq \epsilon\} \cup \{\text{cp}\}$

MapReduce


Programming paradigm
for computing and
aggregating **large
amounts of data**


Functions:

- **Map**: for each input data, returns a **key-value pair**
- Intermediate **grouping** and **sorting** by key step
- **Reduce**: final aggregation step



DBSCAN-MR







Apache Spark


Data stored in memory: analyses on in-memory data and use of **Resilient Distributed Dataset (RDD)**

Hadoop Distributed File System




Create RDD






GeoSpark

- **Geospatial-Aware solutions**
 - **GeoSpark** : runs exactly as Spark, but with the awareness for geospatial data, consisting of three layers; Spark, spatial RDD and spatial query processing layers
 - Some other competitors are based on Hadoop like SpatialHadoop and Hadoop-GIS
- **Problem**
 - ***Does not include an integrated support for clustering methods***, or customizable modules for specific application requirements
 - Do not consider specific requirements like ***domain-specific data load balancing for optimizing clustering algorithm execution***




GeoSpark



Main Goals and Requirements


- Realize a **transparent partitioning** support of data, based upon **location information**
- Extend transparently the GeoSpark support
- Realize an effective support to proximity query in a partitioned architecture
- Provide optimizations for complex algorithms, such as the DBSCAN-MR density-based clustering algorithm

Spatial-aware optimizations
Partitioning and advanced query optimizers
Geopark (including spatial representational support)
Spark Core



Layered Spatial-aware In-memory Processing Optimization Architecture



- Our support **does not require to modify GeoSpark** and is a transparent layer atop of it that hides implementation details from application layer
- Our support **includes spatial-aware partitioning strategies** better trading off three challenges, such as load balancing, containment query optimization, and spatial co-locality evaluation
- Our support **includes a DBSCAN-MR implementation** (which belongs to the co-location data mining family) able to work atop GeoSpark



Self-Adaptation


- ***Density-aware spatial data partitioning***, based on spatial object's distribution density
 - Useful with heavily skewed datasets
 - Roughly balances loads across computing resources
- For the execution of new clustering sessions, ***a self-tuning module optimizes cutting factors for subsequent sessions***, gaining performance improvement


Data Partitioning




- Considering the earth flattened out, we can define **DBSCAN-MR** *cutting factors as vertical partitioning lines* in planar geometry
- **Cutting factors configuration has an impact** on partition's loads and spatial boundary objects

Self-Adaptable Spatial-Aware Partitioner (SASAP)






Self-adaptation of vertical cutting factors




- Monitors execution times at each data partition
- Uses a shared Accumulator variable
- CalculateSplits defines the new configuration, using ***threshold-based solutions to decide when to stop configuration tuning***



Experimental Setup

- Our experimental setup utilized **Amazon AWS cloud's computing services**, specifically **AWS EC2** service
- 5 nodes have been used for deployment, one master and four processing
- On each node, spark 1.6.2 was installed, and ganglia 3.7.2 was used for performance analysis. our input database consisted of 250,000 spatial objects collected through ParticipAct project
- Comparison with a MongoDB-based Map-Reduce implementation (w/out using in memory RDDs)



Experimental Setup (cont'ed)


5 instances m3.xlarge using 1vCPU e 15GB RAM

1 Master:



Driver Spark,
ResourceManager
YARN and
NameNode HDFS

4 Slaves:

Executor Spark
and DataNode
HDFS




Self-Adaptable Load Balancing




First running of DBSCAN-MR (≈ 50 mins) Tenth running of DBSCAN-MR (≈ 20 mins)

- CPU load during running sessions 1 and 10
- For 5 nodes configuration, and a dataset consisting of 250000 spatial entries




Query Performance Optimization




Execution time ***continuously improves*** along different processing rounds and goes **from 50.1 minutes** (first iteration) **to 22.7 minutes** (tenth iteration), obtaining a percentage of speed-up improvement equivalent to 54.7%

GeoSpark vs MongoDB



- Performance applying our GeoSpark support compared with DBSCAN-MR implementation over MongoDB
- Speedup gain degrades as we increase the data size,




Conclusions & Ongoing Works

- **Conclusions**

- Current *support of big data tools for compute-intensive geospatial big data* sets is still rather *poor*
- Our framework efficiently supports **querying** and **analyzing big geospatial data** and was plugged on top of GeoSpark, with a motivation to optimize the performance of DBSCAN-MR clustering

- **Future works**

- Incorporating additional services such as integrated geospatial-aware machine learning and data mining service
- Extending our framework so to enable *online processing of geospatial data streams* in **STARK**



Thank you!

In-memory Spatial-Aware Framework for Processing Proximity-Alike Queries in Big Spatial Data


Luca Foschini, Assistant Professor

DISI - University of Bologna

Viale del Risorgimento, 2 - 40136 Bologna - ITALY

Email: luca.foschin@unibo.it

Web: <https://www.unibo.it/sitoweb/luca.foschini>



Contacts

<http://lia.deis.unibo.it/Staff/LucaFoschini/>

<http://middleware.unibo.it/>



ALMA MATER STUDIORUM
UNIVERSITÀ DI BOLOGNA

DIPARTIMENTO DI INFORMATICA - SCIENZA E INGEGNERIA