

# Locality-Preserving Spatial Partitioning for Geo Big Data Analytics in Main Memory Frameworks


**Isam Mashhour Al Jawarneh**, Paolo Bellavista, Antonio  
Corradi, **Luca Foschini**, Rebecca Montanari

Department of Computer Science and Engineering - DISI  
University of Bologna, Italy

*{luca.Foschini, isam.aljawarneh3, paolo.bellavista,  
antonio.corradi, Rebecca.montanari}@unibo.it,*

**IEEE GLOBECOM 2020**  
7th - 11th December 2020





# Agenda

- *Spatial Partitioning*: Background and Motivations
- *QoS-aware Spatial partitioning for in-memory systems*
  - SCAP (Spatial Co-locality-aware Partitioner)
  - Supported spatial queries: proximity-alike
- Deployment
  - Baselines
  - Testing setup
- Results and Discussion
  - Azure Cloud Spark Test
- Concluding remarks



# Smart City and Big Data Context

## Smart City

Advanced technological services

## Geographic Big Data

Huge amount of information

## Mobile Sensing


Automatic collection of data




# Geo-located Big Data


- Large amounts of geolocated data, **exceeding processing capability** of traditional database management systems
- Characteristics
  - **Volume**: amount of data
  - **Velocity**: streaming data
  - **Variety**: multiple sources, heterogeneous data

Requires distributed data processing systems



# Typical data parallelization for IoT in Cloud





# Conflicting Partitioning Challenges

Load  
Balancing


Spatial co-  
locality

Boundary  
objects







# Example: Boundary Spatial Objects (BSO)



# Load Balancing



**In Spark join requires data to reside on the same partition.**

**Only load balancing = shuffling (huge toll) for co-location queries.**






# Spatial Co-locality-aware Partitioner (SCAP)

- **SDL** preservation is a priority
- **BSOs** and **load balancing** to a lesser extent


- **Clump** geometrically co-located objects into single chunks
- **Split** overloaded chunks
- **Map** chunks to partitions




**SCAP**



# DBSCAN-MR






## *Experimental setup*

- Evaluation questions
  - Data size vs Accuracy & BSOs count
  - Adaptability effect
- Testbed
  - Cluster: 6 nodes (Microsoft Azure HDInsight Cluster )
  - Datasets:
    - NY City taxicab trips datasets. 150k points representing a portion of data captured through taxi rides for the first half of 2016
    - 150k spatial points collected during the ParticipAct project




# Data size vs Accuracy & BSOs count



- Running times and number of BSOs of our retrofitted version of DBSCAN-MR over SCAP against SASAP-based version tested on NYC taxicab datasets. Parameters: eps 0.15, minPts 300, geohash 30.
- Better time, but an increased number of bordering replicated points (i.e., BSOs)




# Data size vs Accuracy & BSOs count



- Running times and number of BSOs of our retrofitted version of DBSCAN-MR over SCAP against SASAP-based using the ParticipAct dataset. Parameters: eps 0.15, minPts 300, geohash 30.
- Better time, but an increased number of bordering replicated points (i.e., BSOs)



# Adaptability effect



- The effect of tweaking geohash precision on the number of BSOs generated by SCAP on NYC taxicab dataset. Parameters: eps 0.15, minPts 300, geohash 35
- Changing the geohash precision has a utility in determining the number of BSOs
- changing the tweakable geohash from 30 to 35 precision yields less BSOs for SCAP
- wider geohash precision implies a smaller size of the cells that this geohash order pass through, which then reduces the overlapping areas between bordering cells, thereby reducing the BSOs count.
- we obtain roughly 32% gain by changing the geohash precision.






## *Concluding remarks*

- Communication service provisioning targets designing communication networks that serve as robust infrastructures for the management of huge amounts of data with QoS guarantees.
- Inappropriate configurations of parallel data processing frameworks may deteriorate the benefits we reap by the elasticity .
- Spatial data partitioning in Cloud computing frameworks is a determinant factor that should be prioritized.
- We have designed SCAP, a locality-preserving spatial partitioning scheme for quality spatial analytics in distributed main memory frameworks.
- Focusing on spatial locality problem to help in minimizing the data shuffling around the network while processing costly proximity-alike queries.
- As a future perspective, we could offload a portion of the data partitioning to IoT devices near the edge.
- Also, we plan to exploit porting parts of the spatial processing to Fog computing near the Edge, and possibly thereby sending only summaries to the Cloud for further processing, thus lowering the overall latency.





## ***Q&A and Contacts***

*Thanks for your attention!*

**Questions time...**

*Isam Al Jawarneh*

Email: [isam.aljawarneh3@unibo.it](mailto:isam.aljawarneh3@unibo.it)



ALMA MATER STUDIORUM  
UNIVERSITÀ DI BOLOGNA  
DIPARTIMENTO DI INFORMATICA - SCIENZA E INGEGNERIA

*Luca Foschini*

Email: [luca.foschini@unibo.it](mailto:luca.foschini@unibo.it)

**IEEE GLOBECOM 2020**

**7th - 11th December 2020**

