DATABASE SPECIFICATION / DATA DICTIONARY

# MEDSYS Database Dictionary

Detailed database reference for the MEDSYS backend, covering tables, columns, defaults, primary keys, foreign keys, uniqueness, nullability, indexes, check constraints, enums, and partitioning behavior.

| DOCUMENT TYPE | SYSTEM |
| --- | --- |
| As-built relational database dictionary | MEDSYS API Enterprise Backend |
| **VERSION** | **DATE** |
| 1.5 | March 20, 2026 |
| **SOURCE OF TRUTH** | **AUDIENCE** |
| Flyway migrations V1, V4, V5, V6, V7, V8, V9, and V10 | Developers, QA, BA, reviewers, and client stakeholders |

Prepared from the current repository schema migrations. This document describes the implemented database design, not a proposed future-state model.

## 1. Scope and Reading Guide

This document provides a field-level dictionary for the MEDSYS PostgreSQL schema. It focuses on database-enforced validation and structure: data type, required versus nullable, default values, generated values, primary keys, unique constraints, foreign keys, indexes, and check constraints.

> **Important:** application-level validations may be stricter than the database. This document records what the database itself enforces. Migration `V8` adds client/demo seed data, `V9` adds user-level extra permission storage for effective authorization overrides, and `V10` adds patient codes plus guardian identity fields.

## 2. Global Design Rules

- Most business tables are organization-scoped through `organization_id`.
- Most tables use surrogate numeric primary keys via `BIGSERIAL` or a sequence-backed `BIGINT`.
- Many business tables use soft deletion through nullable `deleted_at`.
- Appointments and audit logs are partitioned for operational scale.
- Authentication uses refresh-token family tracking for replay detection.

## 3. Enum Types

| ENUM TYPE | ALLOWED VALUES | USED BY |
|---|---|---|
| **user_role** | `owner`, `doctor`, `assistant` | `users.role` |
| **gender** | `male`, `female`, `other` | `patients.gender` |
| **allergy_severity** | `low`, `moderate`, `high` | `patient_allergies.severity` |
| **appointment_status** | `waiting`, `in_consultation`, `completed`, `cancelled` | `appointments.status` |
| **priority_level** | `low`, `normal`, `high`, `critical` | `appointments.priority` |
| **test_order_status** | `ordered`, `in_progress`, `completed`, `cancelled` | `test_orders.status` |
| **drug_source** | `clinical`, `outside` | `prescription_items.source` |
| **inventory_category** | `medicine`, `consumable`, `equipment`, `other` | `inventory_items.category` |
| **inventory_movement_type** | `in`, `out`, `adjustment` | `inventory_movements.movement_type` |

## 4. Relationship Summary

| PARENT TABLE | CHILD TABLE | RELATIONSHIP |
|---|---|---|
| **users** | `refresh_tokens` | One user to many refresh tokens via `refresh_tokens.user_id`. |
| **families** | `patients`, `family_members` | Families optionally attach directly to patients and also map through a join table. |
| **patients** | `family_members`, `patient_allergies`, `patient_conditions`, `appointments`, `encounters`, `prescriptions`, `patient_vitals`, `patient_timeline_events`, `patient_history_entries` | Patient is the central clinical entity and is referenced across most domain tables. |
| **appointments** | `encounters` | One encounter per appointment, enforced by unique `encounters.appointment_id` and a composite FK to partitioned appointments. |

| PARENT TABLE | CHILD TABLE | RELATIONSHIP |
|---|---|---|
| **encounters** | `encounter_diagnoses`, `test_orders`, `prescriptions`, `patient_vitals`, `patient_timeline_events` | Encounter is the anchor for diagnoses, test orders, prescriptions, and some clinical observations. |
| **prescriptions** | `prescription_items`, `dispense_records` | One prescription to many items and many dispense events. |
| **inventory_items** | `inventory_movements` | One inventory item to many immutable movement rows. |
| **users** | `appointments`, `encounters`, `prescriptions`, `dispense_records`, `inventory_movements`, `patient_history_entries`, `audit_logs` | Users appear as operational actors throughout the system. |

# 5. Core Security and Identity Tables

## 5.1 users

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant/organization scope key. |
| `uuid` | UUID | Yes | `gen_random_uuid()` | Unique row UUID. |
| `email` | CITEXT | Yes | None | Case-insensitive email; unique with `organization_id`. |
| `password_hash` | TEXT | Yes | None | Hashed password only. |
| `first_name` | VARCHAR(80) | Yes | None | Required given name. |
| `last_name` | VARCHAR(80) | Yes | None | Required surname. |
| `role` | user_role | Yes | None | Enum constrained. |
| `doctor_workflow_mode` | doctor_workflow_mode | No | None | Explicit doctor business-mode identity. Set for doctor users and added in `V11`. |
| `extra_permissions` | JSONB | Yes | `'[]'::jsonb` | Stores per-user permission overrides; added in `V9`. |
| `is_active` | BOOLEAN | Yes | `TRUE` | Operational active flag. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |

**Constraints:** primary key on `id`; unique on `uuid`; unique on `(organization_id, email)`. **Notes:** `extra_permissions` is a required JSONB array column with an empty-array default after `V9`, and `doctor_workflow_mode` was added in `V11` so frontend clients can identify doctor workflow identity directly.

## 5.2 refresh_tokens

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `user_id` | BIGINT | Yes | None | Foreign key to `users.id`. |
| `token_id` | UUID | Yes | `gen_random_uuid()` | Unique token identifier. |
| `family_id` | UUID | Yes | None at DB level | Refresh-token family identifier; added in V6. |
| `parent_token_id` | UUID | No | None | Logical previous token pointer; no FK constraint. |
| `expires_at` | TIMESTAMPTZ | Yes | None | Expiration timestamp. |
| `used_at` | TIMESTAMPTZ | No | None | Marked when refresh token is consumed. |
| `revoked_at` | TIMESTAMPTZ | No | None | Marked when revoked. |
| `replay_detected_at` | TIMESTAMPTZ | No | None | Set when replay is detected. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |

**Constraints:** primary key on `id`; unique on `token_id`; foreign key `user_id -> users.id`. **Indexes:** `refresh_tokens_user_idx`, `refresh_tokens_family_idx`.

# 6. Family and Patient Master Data

### 6.1 families

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `family_code` | VARCHAR(30) | Yes | None | Unique family code. |
| `family_name` | VARCHAR(120) | Yes | None | Required family label. |
| `assigned` | BOOLEAN | Yes | `FALSE` | Operational assignment flag. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Constraints:** primary key on `id` ; unique on `family_code` . **Index:** `families_org_assigned_idx` .

### 6.2 patients

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `uuid` | UUID | Yes | `gen_random_uuid()` | Unique patient UUID. |
| `patient_code` | VARCHAR(24) | Yes | Application generated | Always-present patient identifier added in `V10` ; unique per organization. |
| `nic` | VARCHAR(20) | No | None | Optional identity number; unique per organization when present. |
| `first_name` | VARCHAR(80) | Yes | None | Required. |
| `last_name` | VARCHAR(80) | Yes | None | Required. |
| `full_name` | VARCHAR(170) | Yes | Generated stored | `first_name \|\| ' ' \|\| last_name` . |
| `dob` | DATE | Yes | None | Required date of birth; set `NOT NULL` in `V7` . |
| `age` | SMALLINT | Yes | None | Required explicit age snapshot; set `NOT NULL` in `V7` . |
| `gender` | gender | Yes | None | Enum constrained. |
| `phone` | VARCHAR(30) | No | None | Optional phone. |
| `address` | TEXT | No | None | Optional address. |
| `blood_group` | VARCHAR(5) | No | None | Optional short blood group. |
| `family_id` | BIGINT | No | None | Optional foreign key to `families.id` . |
| `guardian_patient_id` | BIGINT | No | None | Optional link to another patient row used as guardian; added in `V10` . |
| `guardian_name` | VARCHAR(120) | No | None | Optional guardian display name for minors or dependent patients. |
| `guardian_nic` | VARCHAR(20) | No | None | Optional guardian NIC, searchable and not unique. |
| `guardian_phone` | VARCHAR(30) | No | None | Optional guardian phone, searchable and not unique. |
| `guardian_relationship` | VARCHAR(40) | No | None | Optional guardian relationship label such as `mother` , `father` , or `guardian` . |
| `is_active` | BOOLEAN | Yes | `TRUE` | Operational active flag. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Constraints:** primary key on `id`; unique on `uuid`; unique `patients_org_nic_unique` on `(organization_id, nic)`; unique `patients_org_patient_code_unique` on `(organization_id, patient_code)`; foreign key `family_id -> families.id`; foreign key `guardian_patient_id -> patients.id`; `full_name`, `dob`, `age`, and `patient_code` are `NOT NULL` after `V10`. **Indexes:** `patients_org_full_name_idx`, `patients_org_family_idx`, `patients_org_patient_code_idx`, `patients_org_guardian_patient_idx`, `patients_org_guardian_nic_idx`.

**Application behavior note:** the backend can auto-create a related family row during patient registration when no `family_id` or family code is supplied. In that case the application generates a family label such as `Nimal Perera Family` and stores the resulting link in `patients.family_id`.

## 6.3 family_members

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `family_id` | BIGINT | Yes | None | Foreign key to `families.id`. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id`. |
| `relationship` | VARCHAR(40) | No | None | Optional relationship label. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |

**Constraints:** primary key on `id`; unique on `(family_id, patient_id)`; foreign keys to `families.id` and `patients.id`. **Index:** `family_members_org_family_idx`.

# 7. Patient Clinical Detail Tables

## 7.1 patient_allergies

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id` . |
| `allergy_name` | VARCHAR(120) | Yes | None | Required allergy label. |
| `severity` | allergy_severity | No | None | Enum constrained if present. |
| `is_active` | BOOLEAN | Yes | `TRUE` | Active flag. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Index:** `patient_allergies_patient_idx` .

**Application behavior note:** allergy rows can be created inline during patient registration or later through the dedicated allergy endpoint. The allowed severity values remain `low` , `moderate` , and `high` ; values such as `medium` are not valid.

## 7.2 patient_conditions

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id` . |
| `condition_name` | VARCHAR(180) | Yes | None | Required condition label. |
| `icd10_code` | VARCHAR(16) | No | None | Optional mapped code. |
| `status` | VARCHAR(20) | Yes | `'active'` | String status, not enum constrained. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Index:** `patient_conditions_patient_idx` .

## 7.3 patient_vitals

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id` . |
| `encounter_id` | BIGINT | No | None | Optional foreign key to `encounters.id` . |
| `bp_systolic` | SMALLINT | No | None | Optional systolic blood pressure. |
| `bp_diastolic` | SMALLINT | No | None | Optional diastolic blood pressure. |

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `heart_rate` | SMALLINT | No | None | Optional heart rate. |
| `temperature_c` | NUMERIC(4,1) | No | None | Optional Celsius temperature. |
| `spo2` | SMALLINT | No | None | Optional oxygen saturation. |
| `recorded_at` | TIMESTAMPTZ | Yes | None | Measurement timestamp. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Index:** `patient_vitals_patient_recorded_idx` on `(patient_id, recorded_at)`.

**Application behavior note:** vitals writes now follow a fixed typed API contract rather than generic name or value rows. The application requires at least one measurement on create, supports correction via the vitals patch route, soft deletion via the vitals delete route, validates that any supplied `encounter_id` belongs to the same patient, and can create the first vitals row during encounter bundle creation.

## 7.4 patient_timeline_events

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id`. |
| `encounter_id` | BIGINT | No | None | Optional foreign key to `encounters.id`. |
| `event_date` | DATE | Yes | None | Timeline ordering date. |
| `title` | VARCHAR(160) | Yes | None | Required timeline title. |
| `description` | TEXT | No | None | Optional narrative. |
| `event_kind` | VARCHAR(30) | No | None | Optional category string. |
| `tags` | TEXT[] | No | None | Optional tag array. |
| `value` | VARCHAR(80) | No | None | Optional short value. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Index:** `patient_timeline_events_patient_date_idx` on `(patient_id, event_date)`.

## 7.5 patient_history_entries

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key; introduced in V5. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id`. |
| `created_by_user_id` | BIGINT | Yes | None | Foreign key to `users.id`. |
| `note` | TEXT | Yes | None | Check constraint requires length between 1 and 1000. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Constraints:** `patient_history_entries_note_length_chk` enforces `char_length(note) BETWEEN 1 AND 1000`. **Indexes:** `patient_history_entries_org_patient_idx`, `patient_history_entries_patient_created_idx`.

# 8. Scheduling and Encounter Tables

## 8.1 appointments

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGINT | Yes | `nextval('appointments_partitioned_id_seq')` | Sequence-backed identifier. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id` . |
| `doctor_id` | BIGINT | No | None | Optional foreign key to `users.id` . |
| `assistant_id` | BIGINT | No | None | Optional foreign key to `users.id` . |
| `scheduled_at` | TIMESTAMPTZ | Yes | None | Partition key and part of primary key. |
| `status` | appointment_status | Yes | None | Enum constrained. |
| `reason` | TEXT | No | None | Optional reason text. |
| `priority` | priority_level | Yes | `'normal'` | Enum constrained. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Constraints:** partitioned table; primary key is composite `(id, scheduled_at)` ; foreign keys to `patients.id` and optionally `users.id` for doctor/assistant. **Indexes:** `appointments_id_idx` , `appointments_status_scheduled_idx` , `appointments_patient_idx` , `appointments_org_scheduled_idx` .

**Partitioning notes:** V4 creates `appointments_default` and monthly partitions such as `appointments_2026_03` .

**Application behavior note:** the backend now uses `appointments` for both scheduled center visits and small-clinic walk-ins. The `POST /v1/visits/start` workflow reuses an existing active row in `waiting` or `in_consultation` when available, otherwise it creates a new in-consultation visit row for the patient.

## 8.2 encounters

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `appointment_id` | BIGINT | Yes | None | Unique for one encounter per appointment. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id` . |
| `doctor_id` | BIGINT | Yes | None | Foreign key to `users.id` . |
| `checked_at` | TIMESTAMPTZ | Yes | None | Encounter consult time. |
| `notes` | TEXT | No | None | Optional notes. |
| `next_visit_date` | DATE | No | None | Optional follow-up date. |
| `status` | VARCHAR(20) | Yes | `'completed'` | String status, not enum constrained. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |
| `appointment_scheduled_at` | TIMESTAMPTZ | Yes | None | Added in V4 for composite FK to appointments. |

**Constraints:** primary key on `id`; unique on `appointment_id`; foreign keys to `patients.id`, `users.id`, and composite `(appointment_id, appointment_scheduled_at) -> appointments(id, scheduled_at)` with `ON UPDATE CASCADE`. **Indexes:** `encounters_patient_idx`, `encounters_appointment_fk_idx`.

### 8.3 encounter_diagnoses

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `encounter_id` | BIGINT | Yes | None | Foreign key to `encounters.id`. |
| `icd10_code` | VARCHAR(16) | No | None | Optional ICD-10 code. |
| `diagnosis_name` | VARCHAR(255) | Yes | None | Required diagnosis label. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |

### 8.4 test_orders

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `encounter_id` | BIGINT | Yes | None | Foreign key to `encounters.id`. |
| `test_name` | VARCHAR(180) | Yes | None | Required test label. |
| `status` | test_order_status | Yes | `'ordered'` | Enum constrained. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |

**Index:** `test_orders_encounter_idx`.

# 9. Prescription and Dispensing Tables

## 9.1 prescriptions

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `encounter_id` | BIGINT | Yes | None | Foreign key to `encounters.id`. |
| `patient_id` | BIGINT | Yes | None | Foreign key to `patients.id`. |
| `doctor_id` | BIGINT | Yes | None | Foreign key to `users.id`. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Indexes:** `prescriptions_patient_idx`, `prescriptions_encounter_idx`.

## 9.2 prescription_items

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `prescription_id` | BIGINT | Yes | None | Foreign key to `prescriptions.id`. |
| `drug_name` | VARCHAR(180) | Yes | None | Required medicine label. |
| `dose` | VARCHAR(80) | Yes | None | Required dosing string. |
| `frequency` | VARCHAR(80) | Yes | None | Required frequency string. |
| `duration` | VARCHAR(80) | No | None | Optional duration. |
| `quantity` | NUMERIC(12,2) | Yes | None | Required numeric quantity. |
| `source` | drug_source | Yes | None | Enum constrained. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Index:** `prescription_items_prescription_idx`.

## 9.3 dispense_records

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `prescription_id` | BIGINT | Yes | None | Foreign key to `prescriptions.id`. |
| `assistant_id` | BIGINT | Yes | None | Foreign key to `users.id`. |
| `dispensed_at` | TIMESTAMPTZ | Yes | None | Dispense timestamp. |

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `status` | VARCHAR(20) | Yes | `'completed'` | String status, not enum constrained. |
| `notes` | TEXT | No | None | Optional notes. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |

**Index:** `dispense_records_prescription_idx`.

# 10. Inventory Tables

## 10.1 inventory_items

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `sku` | VARCHAR(80) | No | None | Globally unique when present. |
| `name` | VARCHAR(180) | Yes | None | Required item name. |
| `category` | inventory_category | Yes | None | Enum constrained. |
| `unit` | VARCHAR(20) | Yes | None | Required stock unit. |
| `stock` | NUMERIC(12,2) | Yes | `0` | Current stock balance. |
| `reorder_level` | NUMERIC(12,2) | Yes | `0` | Reorder threshold. |
| `is_active` | BOOLEAN | Yes | `TRUE` | Active flag. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Creation timestamp. |
| `updated_at` | TIMESTAMPTZ | Yes | `NOW()` | Update timestamp. |
| `deleted_at` | TIMESTAMPTZ | No | None | Soft delete marker. |

**Constraints:** primary key on `id` ; unique on `sku` . **Index:** `inventory_items_org_name_idx` .

## 10.2 inventory_movements

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |
| `inventory_item_id` | BIGINT | Yes | None | Foreign key to `inventory_items.id` . |
| `movement_type` | inventory_movement_type | Yes | None | Enum constrained. |
| `quantity` | NUMERIC(12,2) | Yes | None | Movement quantity. |
| `reference_type` | VARCHAR(30) | No | None | Optional origin marker. |
| `reference_id` | BIGINT | No | None | Optional referenced row id. |
| `created_by_id` | BIGINT | Yes | None | Foreign key to `users.id` . |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Immutable creation timestamp. |

**Index:** `inventory_movements_item_idx` .

# 11. Audit and Operational Tables

## 11.1 audit_logs

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `id` | BIGSERIAL | Yes | Sequence generated | Part of composite primary key. |
| `organization_id` | UUID | Yes | None | Tenant scope. |

| COLUMN | TYPE | REQUIRED | DEFAULT / GENERATED | CONSTRAINTS AND NOTES |
|---|---|---|---|---|
| `actor_user_id` | BIGINT | No | None | Optional foreign key to `users.id`. |
| `entity_type` | VARCHAR(60) | Yes | None | Target entity category. |
| `entity_id` | BIGINT | No | None | Optional target row id. |
| `action` | VARCHAR(30) | Yes | None | Action verb. |
| `ip` | INET | No | None | Optional client IP. |
| `user_agent` | TEXT | No | None | Optional client string. |
| `request_id` | UUID | No | None | Optional correlation id. |
| `payload` | JSONB | No | None | Optional structured payload. |
| `created_at` | TIMESTAMPTZ | Yes | `NOW()` | Partition key and part of composite primary key. |

**Constraints:** partitioned by range on `created_at`; composite primary key `(id, created_at)`; foreign key `actor_user_id -> users.id`. **Indexes:** `audit_logs_created_idx`, `audit_logs_entity_idx`. **Partitions:** `audit_logs_default`, `audit_logs_2026_03`, `audit_logs_2026_04`.

## 12. Constraint and Validation Highlights

- **NOT NULL enforcement:** identity, relationship, and workflow-critical fields are mandatory in the schema, including `patients.first_name`, `patients.last_name`, `patients.full_name`, `patients.dob`, and `patients.age`.
- **Unique keys:** used for deduplication and natural identifiers such as user email per organization, patient NIC per organization, token id, family code, and SKU.
- **Foreign keys:** enforce patient, appointment, encounter, prescription, inventory, and actor relationships.
- **Enum validation:** several status and category fields are strictly database-constrained enums.
- **Check constraints:** explicit length validation exists on `patient_history_entries.note`.
- **Generated columns:** `patients.full_name` is database-generated and stored.
- **Partitioning:** `appointments` and `audit_logs` are partitioned for scale and maintenance.

## 13. Source Files

- `infra/flyway/sql/V1__init.sql`
- `infra/flyway/sql/V4__partition_appointments.sql`
- `infra/flyway/sql/V5__add_patient_history.sql`
- `infra/flyway/sql/V6__phase4_observability_security.sql`
- `infra/flyway/sql/V7__enforce_patient_required_fields.sql`
- `infra/flyway/sql/V8__seed_additional_patients.sql`
- `infra/flyway/sql/V9__add_user_extra_permissions.sql`
- `infra/flyway/sql/V11__add_doctor_workflow_mode.sql`

---

This dictionary is intended for review, onboarding, QA, and client walkthroughs. When the schema changes, update this document alongside the relevant Flyway migration.