



Installation Guide

SUSE Manager 4.0

April 01, 2019



Table of Contents

GNU Free Documentation License	1
Introduction	8
Requirements	9
Requirements for Installation	10
Obtaining your SUSE Customer Center Credentials	10
Obtaining Installation Media	10
Hardware Requirements	10
Network Requirements	11
Supported Client Systems	13
Installation	14
Installing SUSE Manager Server	14
Proxy Installation and Connecting Clients	16
Enabling PXE Boot via SUSE Manager Proxy	26
Migrating SUSE Manager 3.1 Proxy to Version 4.0 [Management]	27
Setting Up	36

GNU Free Documentation License

Copyright © 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections

then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

-
- D. Preserve all the copyright notices of the Document.
 - E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
 - F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
 - G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
 - H. Include an unaltered copy of this License.
 - I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
 - J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
 - K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
 - L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
 - M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
 - N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
 - O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

Copyright (c) YEAR YOUR NAME.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with...Texts." line with this:

with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Introduction

SUSE Manager provides absolute control over your Linux environment. System administrators often have tens, hundreds, or even thousands of client machines they need to look after, all of which require ongoing maintenance, updates, and lifecycle management. SUSE Manager allows you to manage all your Linux clients in one place, with one easy-to-understand dashboard.

SUSE Manager can be integrated with your network infrastructure in multiple ways, and most tasks can be automated, with reports issued so you always know the status of your client machines. Because SUSE Manager allows you to manage large numbers of systems and automatically keep them up to date, it helps to improve overall security, and provides extensive asset management and provisioning capability.

SUSE Manager can be used in conjunction with Red Hat Satellite Server and offers seamless management of both SUSE Linux Enterprise and Red Hat Enterprise Linux client systems.

DRAFT

Requirements for Installation

Before you begin your installation, check that your environment meets these requirements:

- Current SUSE Customer Center organization credentials
- Access to installation media
- Your environment meets the hardware and networking requirements
- You understand the supported client operating systems

This section contains more information on each of these requirements.



SUSE Manager 4.0 is based on SLES 12 SP3 as the host operating system.

Obtaining your SUSE Customer Center Credentials

You will need to create an account with SUSE Customer Center before you install SUSE Linux Enterprise Server and SUSE Manager. To obtain your SUSE Customer Center credentials:

Procedure: Obtaining Your SCC Organization Credentials

1. Navigate to <https://scc.suse.com/login> in your Web browser.
2. Log in to your SCC account, or follow the prompts to create a new account.
3. If you have not yet done so, click **Connect to an organization** and type or search for your organization.
4. Click **Manage my organizations** and select your organization from the list by clicking on the organization name.
5. Click the **Organization** tab, and then select the **Organization Credentials** tab.
6. Record your login information for use during SUSE Manager setup.

Depending on your organization's setup, you might also need to activate your subscription, using the **Activate subscriptions** menu.

Obtaining Installation Media

From SLES 15 SP1, SUSE Manager Server and Proxy is available as a base product, and can be installed with the SLES Unified Installer.

Download SLES 15 SP1 or higher from [SUSE Linux Enterprise Server - Media Download](#)

Hardware Requirements

This table outlines hardware and software requirements on x86_64 and IBM Power PC architecture. For installation on z Systems, see:

- xref:advanced_topics_suma3_zsystems.adoc#at-zsystems[{productname} and {zseries}]

Table 1. Hardware Requirements for x86_64 Architecture

Hardware	Recommended
CPU	Minimum 4 dedicated 64-bit CPU cores
RAM:	<i>Test Server</i> Minimum 8 GB
	<i>Base Installation</i> Minimum 16 GB
	<i>Production Server</i> Minimum 32 GB
Disk Space:	<i>/ (root)</i> The default JeOS root partition size of 24 GB is sufficient for this guide
	<code>/var/lib/pgsql</code> Minimum 50 GB
	<code>/var/spacwalk</code> Minimum 50 GB per SUSE product and 250 GB per Red Hat product

Table 2. Hardware Requirements for IBM POWER8 or POWER9 Architecture

Hardware	Recommended
CPU	Minimum 4 dedicated cores
RAM:	<i>Test Server</i> Minimum 8 GB
	<i>Base Installation</i> Minimum 16 GB
	<i>Production Server</i> Minimum 32 GB
Disk Space:	<i>/</i> Minimum 100 GB
	<code>/var/lib/pgsql</code> Minimum 50 GB
	<code>/var/spacwalk</code> Minimum 50 GB per SUSE product and 250 GB per Red Hat product

Network Requirements

This section details the networking and port requirements for SUSE Manager.

Fully Qualified Domain Name (FQDN)

The SUSE Manager server must resolve its FQDN correctly or cookies will not work properly on the WebUI.

For more information about configuring the hostname and DNS, see [SUSE Linux Enterprise Server Documentation - Configuring Host Name and DNS](#)

Hostname and IP Address

To ensure that the SUSE Manager domain name can be resolved by its clients, both server and client machines must be connected to a working DNS server.

For more information about setting up a DNS server, see [SUSE Linux Enterprise Server Documentation - The Domain Name System](#)

Using a Proxy When Installing from SUSE Linux Enterprise Media

If you are on an internal network and do not have access to SUSE Customer Center, you can set up and use a proxy during installation.

For more information about configuring a proxy for access to SUSE Customer Center during a SUSE Linux Enterprise installation, see [SUSE Linux Enterprise Server Documentation - Using a Proxy During Installation](#)



Naming Your Server

The hostname of SUSE Manager must not contain uppercase letters as this may cause *jabberd* to fail. Choose the hostname of your SUSE Manager server carefully. Although changing the server name is possible, it is a complex process and unsupported.

In a production environment, SUSE Manager server and its clients should always use a firewall. This table gives an overview of required ports, to be used when you are setting up your firewall rules.

Table 3. Required Server Ports

Port	Protocol	Description
22	TCP	SSH
67	UDP	DHCP
69	UDP	TFTP, used to support PXE services
80	TCP	HTTP, used in some bootstrap cases
123	UDP	NTP time service
443	TCP	HTTPS, used for Web UI, client, Proxy server, and API traffic
4505	TCP	Salt, used by the Salt-master to accept communication requests from minions
4506	TCP	Salt, used by the Salt-master to accept communication requests from minions
5222	TCP	XMPP client, used for communications with the <i>osad</i> daemon on traditional client systems
5269	TCP	XMPP server, used for pushing actions to SUSE Manager Proxy

For more information on disconnected setup and port configuration, see:

- [xref:bp_chap_choosing_dist_scheme.adoc#bp-dist-scheme](#)[Disconnected Setup]
- [xref:advanced_topics_ports.adoc#at-ports](#)[Firewall Ports]

Supported Client Systems

Supported operating systems for traditional and Salt clients are listed in this table.

Table 4. Supported Client Systems

Operating Systems	Architecture	Traditional Clients	Salt Clients
SUSE Linux Enterprise 11 SP4	x86, x86_64, Itanium, IBM POWER, z Systems	Supported	Supported
SUSE Linux Enterprise 12 SP3, 12 SP4	x86_64, IBM POWER (IBM Power PC), z Systems, ARM	Supported	Supported
SUSE Linux Enterprise 15	x86_64, IBM POWER (IBM Power PC), z Systems, ARM	Supported	Supported
<i>Latest minor release Red Hat Enterprise Linux Server 6</i>	x86, x86_64	Supported	Supported
<i>Latest minor release Red Hat Enterprise Linux Server 7</i>	x86_64	Supported	Supported
Open Enterprise Server 2015, 2015 SP1, 2018	x86_64	Supported	Supported



Supported Versions and SP Levels

Client operating system versions and SP levels must be under general support (normal or LTSS) to be supported with SUSE Manager. For details on supported product versions, see <https://www.suse.com/lifecycle>.

Installation

Installing SUSE Manager Server

SUSE Manager Server is a SUSE base product from version 4.0. This section describes how to install SUSE Manager Server from SUSE Linux Enterprise Server installation media. It assumes you have already registered the SUSE Manager product with the SUSE Customer Center and have a registration code.


For information on registering with SUSE Customer Center, or obtaining installation media, see [xref:installation-general-requirements](#).




If you want to install SUSE Manager on a virtual machine, ensure your virtual machine has enough disk space and RAM by checking the requirements at [xref:\[install-hardware-requirements\]](#)

Procedure: Installing SUSE Manager Server from a DVD image

1. Boot your server from the installation image, you might need to adjust the boot order in the BIOS.
2. When prompted, select **Installation**.



3. In the **Language, Keyboard and Product Selection** screen, check the **SUSE Manager Server** checkbox, and click [**Next**].



4. Read and agree to the End User Licence Agreement, and click [**Next**].
5. In the **Registration** screen, check the **Register System via scc.suse.com** checkbox, enter your SUSE Customer Center credentials, and click [**Next**].
6. OPTIONAL: In the **Add On Product** screen, select any additional or add-on products you require, and click [**Next**].
7. In the **System Role** screen, check the **SUSE Manager Server** checkbox, and click [**Next**].
8. In the **Suggested Partitioning** screen, accept the default values, or use the [**Guided Setup**] or [**Expert Partitioner**] options to customize your partitioning model, and click [**Next**].
9. In the **Clock and Time Zone** screen, enter your region and timezone, and click [**Next**].
10. In the **Local Users** screen, create a new user, and click [**Next**].
11. In the **System Administrator "root"** screen, create the "root" user, and click [**Next**].
12. Review the settings on the **Installation Settings** screen, and then click [**Install**].

When the installation procedure has finished, you can check that you have all the required modules by using the **SUSEConnect --status-text** command at a command prompt. For SUSE Manager Server, the expected modules are:

- SUSE Linux Enterprise Server Basesystem Module
- Python 2 Module
- Server Applications Module
- Web and Scripting Module
- SUSE Manager Server Module

Old content below this line. --LKB 2019-03-19

Proxy Installation and Connecting Clients

Requirements

The following section provides SUSE Manager Proxy requirements.

Supported Client Systems

For supported clients and their requirements, see `xref:FILENAME.adoc#quickstart.sect.prereq.clientos[]`.

Hardware Requirements

Hardware requirements highly depend on your usage scenario. When planning proxy environments, consider the amount of data you want to cache on your proxy. If your proxy should be a 1:1 mirror of your SUSE Manager, the same amount of disk space is required. For specific hardware requirements, see the following table.

Hardware	Required
CPU	Multi-core 64-bit CPU (x86_64).
RAM	Minimum 4 GB for a non-production server
	Minimum 16 GB for a production server
Free Disk Space	Minimum 100 GB for base installation and at least 50 GB for caching per SUSE product and +100 GB per Red Hat product; a resizeable partition strongly recommended.



Storage for Proxy Data

SUSE recommends storing the squid proxy caching data on a separate disk formatted with the XFS file system.

SSL Certificate Password

For installing the proxy, you need the SSL certificate password entered during the initial installation of SUSE Manager.

Network Requirements

For additional network requirements, see `xref:FILENAME.adoc#quickstart.sect.prereq.network[]`.

SUSE Customer Center

For using SUSE Manager Proxy, you need an account at SUSE Customer Center (SCC) where your purchased products and product subscriptions are registered. Make sure you have the following subscriptions:

- One or more subscriptions for SUSE Manager Proxy.
- One or more subscriptions for SUSE Manager.

- Subscriptions for the products on the client systems you want to register with SUSE Manager via SUSE Manager Proxy .
- Subscriptions to client entitlements for the client system you want to register with SUSE Manager via SUSE Manager Proxy .

Network Time Protocol (NTP)

The connection to the Web server via Secure Sockets Layer (SSL) requires correct time settings on the server, proxy and clients. For this reason, all systems must use NTP. For more information, see https://www.suse.com/documentation/sles-12/book_sle_admin/data/cha_netz_xntp.html.

Virtual Environments

The following virtual environments are supported:

- http://www.linux-kvm.org/page/Main_Page
- <http://www.vmware.com/>
- <http://www.microsoft.com/en-us/server-cloud/solutions/virtualization.aspx>

For running SUSE Manager Proxy in virtual environments, use the following settings for the virtual machine (VM):

- At least 1 GB of RAM
- Bridged network

Installation and Setup

The following section will guide you through the installation and setup procedure.

SUSE Manager Proxy systems are registered as traditional clients or as Salt clients using a bootstrap script. Migrating a traditionally registered Proxy system to a Salt Proxy system is not possible. Re-install the Proxy if you want to switch to Salt.

Downloading Channels



Before you can select the correct child channels while creating the activation key, ensure you have completely downloaded the channels for SUSE Linux Enterprise 12 SP4.

Procedure: Registering the Proxy

1. Create an activation key based on the SUSE Linux Enterprise 12 SP4 base channel. For more information about activation keys, see `xref:FILENAME.adoc#create.act.keys[]`.

Create Activation Key ?

Activation Key Details

Systems registered with this activation key will inherit the settings listed below.

Description:

SUSE Mgr 3.1 Proxy

Use this to describe what kind of settings this key will reflect on systems that use it. If left blank, this field will be filled in 'None'.

Key:

1- susemgr_3_1_proxy

Activation key can contains only numbers [0-9], letters [a-z A-Z], '-', '_' and ' '.

Leave blank for automatic key generation. Note that the prefix is an indication of the SUSE Manager organization the key is associated with.

Usage:

Leave blank for unlimited use.

Base Channel:

SLES12-SP3-Pool for x86_64

Choose "SUSE Manager Default" to allow systems to register to the default SUSE Manager provided channel that corresponds to the installed SUSE Linux version. Instead of the default, you may choose a particular SUSE provided channel or a custom base channel, but if a system using this key is not compatible with the selected channel, it will fall back to its SUSE Manager Default channel.

Figure 1. Proxy Activation Key

- From the **Child Channels** listing select the SUSE Manager 4.0 Proxy child channel with the matching update channel (**SUSE Manager Proxy-3.2-Pool** and **SUSE-Manager-Proxy-3.2-Updates**). These child channels are required for providing the proxy packages and updates. For normal SLES clients, **SLES12-SP4-Updates** plus **SLE-Manager-Tools12-Pool** and **SLE-Manager-Tools12-Updates** are mandatory.

SUSE Mgr 3.1 Proxy Clone Key Delete Key

Details **Child Channels** Packages Configuration Groups Activated Systems

Any system registered using this activation key will be subscribed to the selected child channels.

The following child channels of **SLES12-SP3-Pool for x86_64** can be associated with this activation key.

<input checked="" type="checkbox"/>	SLE-Manager-Tools12-Pool x86_64 SP3
<input checked="" type="checkbox"/>	SLE-Manager-Tools12-Updates x86_64 SP3
<input type="checkbox"/>	SLE-Module-Adv-Systems-Management12-Pool for x86_64 SP3
<input type="checkbox"/>	SLE-Module-Adv-Systems-Management12-Updates for x86_64 SP3
<input checked="" type="checkbox"/>	SLES12-SP3-Updates for x86_64
<input type="checkbox"/>	SUSE-Manager-Proxy-3.0-Pool for x86_64 SP3
<input type="checkbox"/>	SUSE-Manager-Proxy-3.0-Updates for x86_64 SP3
<input checked="" type="checkbox"/>	SUSE-Manager-Proxy-3.1-Pool for x86_64 SP3
<input checked="" type="checkbox"/>	SUSE-Manager-Proxy-3.1-Updates for x86_64 SP3
<input type="checkbox"/>	SUSE-Manager-Server-3.1-Pool for x86_64 SP3
<input type="checkbox"/>	SUSE-Manager-Server-3.1-Updates for x86_64 SP3

Update Activation Key

Figure 2. Base and Child Proxy Channel

3. Modify a bootstrap script for the proxy if needed. If you want to run the proxy on a traditional client (system type **Management**) uncheck **Bootstrap using Salt**. Using Salt is supported since version 3.2. For more information about bootstrap scripts, see [xref:FILENAME.adoc#modify.bootstrap.script\[\]](#).

SUSE Manager Configuration - Bootstrap

The following information will be used to generate bootstrap scripts. These bootstrap scripts can be used to configure a client to receive updates. Once the bootstrap scripts have been generated, they will be available from [this server](#).

Please note that some manual configuration of these scripts may still be required. The bootstrap script can be found on the server here: `/srv/www/htdocs/pub/bootstrap`

General

Bootstrap Script

Organizations

Restart

Cobbler

Bare-metal systems

Client Bootstrap Script Configuration

SUSE Manager server hostname*	<input type="text" value="manager.example.com"/>
SSL cert location*	<input type="text" value="/srv/www/htdocs/pub/rhn-org-trusted-ssl-cert-1.0-1.noarch.rpm"/>
Bootstrap using Salt	<input checked="" type="checkbox"/>
Enable SSL	<input checked="" type="checkbox"/>
Enable Client GPG checking	<input checked="" type="checkbox"/>
Enable Remote Configuration	<input type="checkbox"/>
Enable Remote Commands	<input checked="" type="checkbox"/>
Client HTTP Proxy	<input type="text"/>
Client HTTP Proxy username	<input type="text"/>
Client HTTP Proxy password	<input type="password"/>

Update

Figure 3. Modifying Bootstrap Script

4. Create the SUSE Manager Tools Repository for bootstrapping, see [xref:FILENAME.adoc#create.tools.repository\[\]](#).
5. Bootstrap the client with the bootstrap script. For more information, see [xref:FILENAME.adoc#connect.first.client\[\]](#).
6. In case of a Salt client, accept the key on the **Main Menu** > **Salt** > **Keys** page by clicking the check mark and it will appear in the **Main Menu** > **Systems** > **Overview**.
7. Check via **System Details** > **Software** > **Software Channels** that the two proxy channels [SUSE Manager Proxy-3.2-Pool](#) and [SUSE-Manager-Proxy-3.2-Updates](#) are selected.




Figure 4. Proxy Channels

A few more steps are still needed:

- Install the `patterns-suma_proxy` pattern (see `xref:FILENAME.adoc#at.manager.proxy.run.pattern[]`)
- Copy the SSL certificate and key from the server (see `xref:FILENAME.adoc#at.manager.proxy.run.copycert[]`)
- Run `configure-proxy.sh` (see `pass:c[xref:FILENAME.adoc#at.manager.proxy.run.confproxy]`)

You will then be able to register your clients against the proxy using the Web UI or a bootstrap script as if it were a SUSE Manager server. For more information, see `xref:FILENAME.adoc#at.manager.proxy.register.saltclients[]`.

Install the `suma_proxy` pattern

On the server select the `pattern_suma_proxy` package for installation, or make sure the `suma_proxy` pattern is installed using the following command on the proxy as root:

```
zypper in -t pattern suma_proxy
```

The new salt-broker service will be automatically started at the end of the package installation. This service forwards the Salt interactions to the SUSE Manager server.



Proxy Chains

It is possible to arrange Salt proxies in a chain. In such a case, the upstream proxy is named “parent”.

Make sure the proxy's TCP ports **4505** and **4506** are open and that the proxy can reach the SUSE Manager server (or another upstream proxy) on these ports.

Copy Server Certificate and Key

The proxy will share some SSL information with the SUSE Manager server, so the next step is to copy the certificate and its key from the SUSE Manager server or the upstream proxy.

As root, enter the following commands on the proxy using your SUSE Manager server or chained proxy named **PARENT**:

```
mkdir /root/ssl-build
cd /root/ssl-build
scp root@PARENT:/root/ssl-build/RHN-ORG-PRIVATE-SSL-KEY .
scp root@PARENT:/root/ssl-build/RHN-ORG-TRUSTED-SSL-CERT .
scp root@PARENT:/root/ssl-build/rhn-ca-openssl.cnf .
```



Known Limitation

The SUSE Manager Proxy functionality is only supported if the SSL certificate was signed by the same CA as the SUSE Manager Server certificate. Using certificates signed by different CAs for Proxies and Server is not supported.

Running `configure-proxy.sh`

The `configure-proxy.sh` script will finalize the setup of your SUSE Manager Proxy.

Now execute the interactive `configure-proxy.sh` script. Pressing **Enter** without further input will make the script use the default values provided between brackets `[]`. Here is some information about the requested settings:

SUSE Manager Parent

A SUSE Manager parent can be either another proxy server or a SUSE Manager server.

HTTP Proxy

A HTTP proxy enables your SUSE Manager proxy to access the Web. This is needed if direct access to the Web is prohibited by a firewall.

Proxy Version to Activate

Normally, the correct value (3.0, 3.1, or 3.2) should be offered as a default.

Traceback Email

An email address where to report problems.

Use SSL

For safety reasons, press **Y**.

Do You Want to Import Existing Certificates?

Answer **N**. This ensures using the new certificates that were copied previously from the SUSE Manager server.

Organization

The next questions are about the characteristics to use for the SSL certificate of the proxy. The organization might be the same organization that was used on the server, unless of course your proxy is not in the same organization as your main server.

Organization Unit

The default value here is the proxy's hostname.

City

Further information attached to the proxy's certificate. Beware the country code must be made of two upper case letters. For further information on country codes, refer to the online [list of alpha-2 codes](#).



Country Code

As the country code enter the country code set during the SUSE Manager installation. For example, if your proxy is in US and your SUSE Manager in DE, you must enter **DE** for the proxy.

Cname Aliases (Separated by Space)

Use this if your proxy server can be accessed through various DNS CNAME aliases. Otherwise it can be left empty.

CA Password

Enter the password that was used for the certificate of your SUSE Manager server.

Do You Want to Use an Existing SSH Key for Proxying SSH-Push Salt Minions?

Use this option if you want to reuse a SSH key that was used for SSH-Push Salt minions on the server.

Create and Populate Configuration Channel `rhn_proxy_config_1000010001`?

Accept default **Y**.

SUSE Manager Username

Use same user name and password as on the SUSE Manager server.

Activate advertising proxy via SLP?

SLP stands for Service Location Protocol.

If parts are missing, such as CA key and public certificate, the script prints commands that you must execute to integrate the needed files. When the mandatory files are copied, re-run `configure-proxy.sh`. Also restart the script if a HTTP error was met during script execution.

`configure-proxy.sh` activates services required by SUSE Manager Proxy, such as `squid`, `apache2`, `salt-broker`, and `jabberd`.

To check the status of the proxy system and its clients, click the proxy system's details page on the Web UI (**Main Menu** > **Systems** > **Proxy**, then the system name). **Connection** and **Proxy** subtabs display the respective status information.

Registering Salt Clients via SUSE Manager Proxy

Proxy servers may now act as a broker and package cache for Salt minions. These minions can be registered with a bootstrap script like the traditional clients, or from the Web UI, or the command line.

Registering Salt clients via SUSE Manager Proxy from the Web UI is done almost the same way as registering clients directly with the SUSE Manager server. The difference is that you specify the name of the proxy in the **Proxy** drop-box on the **Main Menu** > **Systems** > **Bootstrapping** page.

Bootstrap Minions

You can add systems to be managed by providing SSH credentials only. SUSE Manager will prepare the system remotely and will perform the registration.

Host: some-minion.suse.de

SSH Port: 22

User: root

Password: *****

Activation Key: 1-sles12sp2

Proxy: f51.suse.de

☒ Disable SSH strict host key checking during bootstrap process

☐ Manage system completely via SSH (will not install an agent)

+ Bootstrap **Clear fields**

Figure 5. Bootstrapping a Salt Client With a Proxy

Procedure: Register a Salt client through a proxy from the command line

1. Instead of the Web UI, you may use the command line to register a minion through a proxy. Note that this procedure requires that you have installed the salt package on the minion before registration, and have the Advanced systems module activated. Add the proxy FQDN as the master in the minions configuration file located at:


```
/etc/salt/minion
```

or alternatively:

```
/etc/salt/minion.d/NAME.conf
```

2. Add the FQDN to the minion file:

```
master: proxy123.example.com
```

Save and restart the salt-minion service with:

```
systemctl restart salt-minion
```

3. On the Server, accept the new minion key with:

```
salt-key -a 'minion'
```

The minion will now connect to the proxy exclusively for Salt operations and normal HTTP package downloads.

Registering Clients via SUSE Manager Proxy with a Script

Registering clients (either traditional or Salt) via SUSE Manager Proxy with a script is done almost the same way as registering clients directly with the SUSE Manager server. The difference is that you create the bootstrap script on the SUSE Manager Proxy with a command-line tool. The bootstrap script then deploys all necessary information to the clients. The bootstrap script refers some parameters (such as activation keys or GPG keys) that depend on your specific setup.

1. Create a client activation key on the SUSE Manager server using the Web UI. See [xref:FILENAME.adoc#create.act.keys\[\]](#).
2. On the proxy, execute the `mgr-bootstrap` command-line tool as root. If needed, use the additional command-line switches to tune your bootstrap script. An important option is `--traditional` that enables to opt for a traditional client instead of a salt minion.

To view available options type `mgr-bootstrap --help` from the command line:

```
# mgr-bootstrap --activation-keys=key-string
```

3. Optionally edit the resulting bootstrap script. Execute the bootstrap script on the clients as described in [xref:FILENAME.adoc#connect.first.client\[\]](#).

The clients are registered with the SUSE Manager Proxy specified in the bootstrap script.

Additional Information about Client Registration on Proxies

Within the Web UI, standard proxy pages will show information about client, no matter whether minions or traditional clients.

A list of clients connected to a proxy can be seen by clicking on the name of the Proxy in **Main Navigation** > **Systems** > **Systems** > **Proxy**, selecting the **Details** tab, and then selecting the **Proxy** tab.

A list of chained proxies for a minion can be seen by clicking on the name of the minion in **Main Navigation** > **Systems** > **All**, selecting the **Details** tab, and then selecting the **Connection** tab.

If you decide to move any of your clients between proxies or the server you will need to repeat the registration process from scratch.

Enabling PXE Boot via SUSE Manager Proxy

Synchronizing Profiles and System Information

To enable PXE boot via a proxy server, additional software must be installed and configured on both the SUSE Manager server and the SUSE Manager Proxy server.

1. On the SUSE Manager server install `susemanager-tftpsync` :

```
zypper in susemanager-tftpsync
```

2. On the SUSE Manager Proxy server install `susemanager-tftpsync-recv` :

```
zypper in susemanager-tftpsync-recv
```

3. Run the `configure-tftpsync.sh` setup script and enter the requested information:

```
configure-tftpsync.sh
```

It asks for hostname and IP address of the SUSE Manager server and of the proxy itself. Additionally, it asks for the tftpboot directory on the proxy.

4. On the SUSE Manager server, run `configure-tftpsync.sh` to configure the upload to the SUSE Manager Proxy server:

```
configure-tftpsync.sh FQDN_of_Proxy_Server
```

5. To initiate an initial synchronization on the SUSE Manager Server run:

```
cobbler sync
```

Also can also be done after each a change within Cobbler that needs to be synchronized immediately. Otherwise Cobbler synchronization will also run automatically when needed. For more information about Cobbler, see [xref:FILENAME.adoc#advanced.topics.cobbler\[\]](#).

Configuring DHCP for PXE via SUSE Manager Proxy

SUSE Manager is using Cobbler to provide provisioning. PXE (tftp) is installed and activated by default. To enable systems to find the PXE boot on the SUSE Manager Proxy server add the following to the DHCP configuration for the zone containing the systems to be provisioned:

```
next-server: <IP_Address_of_SUSE_Manager_Proxy_Server>  
filename: "pxelinux.0"
```

Migrating SUSE Manager 3.1 Proxy to Version 4.0 [Management]

The recommended order for migrations is to first migrate the server and then the proxies.

For the migration of traditionally managed proxies there are two possible approaches:

- Existing SUSE Manager proxies may be upgraded to version 3.2 with YaST or **zypper** migration.
- Alternatively, the proxies may be replaced by new ones.

This section documents both approaches.



Migrating SUSE Manager 3 Proxy and Earlier

For migrating SUSE Manager 3 Proxy and earlier, see https://www.suse.com/documentation/suse-manager-3/book_suma_advanced_topics_31/data/sect1_chapter_book_suma_advanced_topics_31.html, Chapter "SUSE Manager 3.1 Proxy".

Replacing a SUSE Manager Proxy

A SUSE Manager Proxy is **dumb** in the sense that it does not contain any information about the clients which are connected to it. A SUSE Manager Proxy can therefore be replaced by a new one. Naturally, the replacement proxy must have the same name and IP address as its predecessor.

In order to replace a SUSE Manager Proxy and keeping the clients registered to the proxy leave the old proxy in SUSE Manager. Create a reactivation key for this system and then register the new proxy using the reactivation key. If you do not use the reactivation key, you will need to re-registered all the clients against the new proxy.

Procedure: Replacing a SUSE Manager Proxy and Keeping the Clients Registered

1. Before starting the actual migration procedure, save the data from the old proxy, if needed. Consider copying important data to a central place that can also be accessed by the new server:
 - Copy the scripts that are still needed.
 - Copy the activation keys from the previous server. Of course, it is always better to re-create the keys.
2. Shutdown the server.
3. Install a new SUSE Manager 4.0 Proxy, see [xref:FILENAME.adoc#at.manager.proxy.inst-and-clients\[\]](#).
4. In the SUSE Manager Web UI select the newly installed SUSE Manager Proxy and delete it from the systems list.
5. In the Web UI, create a reactivation key for the old proxy system: On the System Details tab of the old proxy click [Reactivation](#). Then click [Generate New Key](#), and remember it (write it on a piece of paper or copy it to the clipboard). For more information about reactivation keys, see [xref:FILENAME.adoc#s5-sm-system-details-react\[\]](#).
6. After the installation of the new proxy, perform the following actions (if needed):
 - Copy the centrally saved data to the new proxy system.
 - Install any other needed software.
 - If the proxy is also used for autoinstallation, do not forget to setup TFTP synchronization.

*Proxy Installation and Client Connections*

During the installation of the proxy, clients will not be able to reach the SUSE Manager server. After a SUSE Manager Proxy system has been deleted from the systems list, all clients connected to this proxy will be (incorrectly) listed as [directly connected](#) to the SUSE Manager server. After the first successful operation on a client *such as execution of a remote command or installation of a package or patch* this information will automatically be corrected. This may take a few hours.

Upgrading a SUSE Manager Proxy from 3.1 to 4.0


In most situations upgrading the proxy will be your preferred solution as this retains all cached packages. Selecting this route saves time especially regarding proxies connected to SUSE Manager server via low-bandwidth links. This upgrade is similar to a standard client migration.

*Synchronizing Target Channels*

Before successfully initializing the product migration, you first must make sure that the migration target channels are completely mirrored. To upgrade to SUSE Manager 3.2 Proxy, you will require at least the [SUSE Linux Enterprise Server 12 SP4](#) base channel with the [SUSE Manager Proxy 3.2](#) child channel for your architecture.

Procedure: Migrating Proxy to 4.0

1. Direct your browser to the SUSE Manager Web UI where your proxy is registered, and login.
2. On the **Main Menu** > **Systems** > **Systems** > **Proxy** page select your proxy server from the table.



k5-proxy31.tf.local ?


Details Software Configuration Provisioning Groups Audit Events

Overview Properties Remote Command Connection Proxy Reinstall

System Status

✓ System is up to date


System Info

Hostname:	k5-proxy31.tf.local
IP Address:	10.160.65.180
IPv6 Address:	fe80::8d4:c4ff:fe31:4c2c
Virtualization:	KVM/QEMU
UUID:	963aba4851f54708a3a0204150f94fa3
Kernel:	4.4.73-5-default
SUSE Manager System ID:	1000010002
Activation Key:	1-DEFAULT
Installed Products:	<div>SUSE Linux Enterprise Server 12 SP3</div> <div>SUSE Manager Proxy 3.1</div>
Lock Status:	 System is unlocked (Lock system)


Subscribed Channels ([Alter Channel Subscriptions](#))

- [testchannel](#)


3. On the system's detail page select the **Software** > **SP Migration** tab.



4. From this page you will see installed products listed on your proxy client, and the available target products. Select the required **Target Products**. In this case, you will require **SUSE Linux Enterprise Server 12 SP4** with **SUSE Manager Proxy 3.2**.



5. Then confirm with [**Select Channels**].

 k5-proxy31.tf.local [?](#) [Delete System](#)

Details **Software** Configuration Provisioning Groups Audit Events

Patches Packages Software Channels **SP Migration** Software Crashes

Service Pack Migration - Channels

Installed Products: SUSE Linux Enterprise Server 12 SP3
SUSE Manager Proxy 3.1



Target Products: SUSE Linux Enterprise Server 12 SP3
SUSE Manager Proxy 3.2

Target Base Channel: SLES12-SP3-Pool for x86_64

- **Mandatory Child Channels:**
 - ☒ SLE-Manager-Tools12-Pool x86_64 SP3
 - ☒ SLE-Manager-Tools12-Updates x86_64 SP3
 - ☒ SLES12-SP3-Updates for x86_64
 - ☒ SUSE-Manager-Proxy-3.2-Pool for x86_64
 - ☒ SUSE-Manager-Proxy-3.2-Updates for x86_64
- **Optional Child Channels:**
 - ☐ bettertest32
 - ☐ SLE-12-SP3-GA-Desktop-nVidia-Driver WE-SP3
 - ☐ SLE-Module-Adv-Systems-Management12-Pool for x86_64 SP3
 - ☐ SLE-Module-Adv-Systems-Management12-Updates for x86_64
 - ☐ SLE-WE12-SP3-Pool for x86_64
 - ☐ SLE-WE12-SP3-Updates for x86_64
 - ☐ SUSE-Manager-Retail-3.1-Pool for x86_64 SP3
 - ☐ SUSE-Manager-Retail-3.1-Updates for x86_64 SP3
 - ☐ SUSE-Manager-Server-3.2-Pool for x86_64
 - ☐ SUSE-Manager-Server-3.2-Updates for x86_64

[Schedule Migration](#)


6. From the [Schedule Migration](#) menu, select the time and click [**Confirm**].

 k5-proxy31.tf.local 

[Delete System](#) | [Add to SSM](#)

[Details](#) [Software](#) [Configuration](#) [Provisioning](#) [Groups](#) [Audit](#) [Events](#)

[Patches](#) [Packages](#) [Software Channels](#) [SP Migration](#) [Software Crashes](#)

 **Service Pack Migration - Confirm**


Please confirm below to schedule the migration of this system to the following products:


- **SUSE Linux Enterprise Server 12 SP3**
 - SUSE Manager Proxy 3.2

Channel subscriptions after the migration:



- **SLES12-SP3-Pool for x86_64**
 - SLE-Manager-Tools12-Pool x86_64 SP3
 - SLE-Manager-Tools12-Updates x86_64 SP3
 - SLES12-SP3-Updates for x86_64
 - SUSE-Manager-Proxy-3.2-Pool for x86_64
 - SUSE-Manager-Proxy-3.2-Updates for x86_64

Schedule action for no sooner than:

 9/18/18

 10:26 am

CEST

 In order to detect any possible problems it is recommended to always do a **Dry Run** before scheduling the actual Service Pack Migration. 

[Go Back](#) [Dry Run](#) [Confirm](#)

Check the [System Status](#) on the **System Details** > **Overview** when the migration is done.

f51.suse.de ?

Details | Software | Configuration | Provisioning | Groups | Virtualization | Audit

Overview | Properties | Remote Command | Connection | Proxy | Reactivation

System Status

✔ **System is up to date**
 ⚙ The system requires a reboot ([Schedule System Reboot](#))

System Info

Hostname:	f51.suse.de
IP Address:	10.160.66.51
IPv6 Address:	::1
Kernel:	3.12.69-60.64.35-default
SUSE Manager System ID:	1000010006
Activation Key:	1-suma_3_proxy
Installed Products:	<div>SUSE Linux Enterprise Server 12 SP2</div> <div>SUSE Manager Proxy 3.1 x86_64 (BETA)</div>
Lock Status:	🔒 System is unlocked (Lock system)

Subscribed Channels ([Alter Channel Subscriptions](#))

- [SLES12-SP2-Pool for x86_64](#)
- [SLE-Manager-Tools12-Pool x86_64 SP2](#)
- [SLE-Manager-Tools12-Updates x86_64 SP2](#)
- [SLES12-SP2-Updates for x86_64](#)
- [SUSE-Manager-Proxy-3.1-Pool for x86_64](#)
- [SUSE-Manager-Proxy-3.1-Updates for x86_64](#)

Finally consider scheduling a reboot.

SUSE Manager on IBM z Systems

Introduction

This best practice guide is intended for z/VM administrators responsible for operating the IBM z Systems Mainframe. The goal of this guide is to lead an z/VM administrator trained on normal z Systems operating protocols through the installation of SUSE Manager onto an existing mainframe system. The intent of this article is not to cover the variety of hardware configuration profiles available on z Systems

but instead to provide a foundational overview of the procedure and requirements necessary for a successful SUSE Manager server deployment.

Base System Requirements

The z/VM administrator should acquire and prepare the following resources for a successful SUSE Manager installation. SUSE Manager 4.0 is delivered as an extension. These sections will provide you with the minimum and recommended system requirements for SUSE Manager. The base system for SUSE Manager 4.0 is SLES 12SP3.

Hardware	Recommended Hardware
IBM Systems	* IBM zEnterprise System z196 (z196) * IBM zEnterprise System z114 (z114) * IBM zEnterprise EC12 (zEC12) * IBM zEnterprise EC12 (zEC12) * IBM zEnterprise BC12 (zBC12) * IBM z13 (z13) * LinuxOne Rockhopper * LinuxOne Emperor
RAM	<p><i>Split memory requirements across available RAM, VDISK and swap to suit your environment. On a production system the ratio of physical memory to VDISK will need to be re-evaluated based on the number of clients which will be supported.</i></p> <p>Minimum 5 GB+ for test server (3 GB RAM + 2 GB VDISK Swap)</p> <p>Minimum 16 GB+ for base installation</p> <p>Minimum 32 GB+ for a production server</p>
Free Disk Space	<p>Minimum 100 GB for root partition</p> <p>Minimum 50 GB for <code>/var/lib/pgsql</code></p> <p>Minimum 50 GB per SUSE product + 100 GB per Red Hat product <code>/var/spacwalk</code></p>
Network Connection	<p>* OSA Express Ethernet (including Fast and Gigabit Ethernet) * HiperSockets or Guest LAN * 10 GBE, VSWITCH * RoCE (RDMA over Converged Ethernet)</p> <p>The following interfaces are still included but no longer supported:</p> <p>* CTC (or virtual CTC) * IP network interface for IUCV</p>

Media Requirements

- SUSE Linux Enterprise 12SP3 Installation Media for IBM z Systems :

<https://www.suse.com/products/server/download/>

Additional Requirements

There are a few additional resource requirements you will need to prepare before installing the SUSE Manager extension on your system. This section overviews these requirements.

The guest z/VM should be provided with a static IP address and hostname as these cannot be easily changed after initial setup. The hostname should contain less than 8 characters.

For more information on SUSE Manager additional requirements, see https://www.suse.com/documentation/suse-manager-3/book_suma_best_practices/data/mgr_conceptual_overview.html.

You will need to ensure you have sufficient disk storage for SUSE Manager before running `yast2 susemanagersetup`.

This section explains these requirements in more detail.



SUSE Manager Default Volume Groups and Disk Space

By default the file system of SUSE Manager, including the embedded database and patch directories, reside within the root volume. While adjustments are possible once installation is complete, it is the administrator's responsibility to specify and monitor these adjustments.

If your SUSE Manager runs out of disk space, this can have a severe impact on its database and file structure. Preparing storage requirements in accordance with this section will aid in preventing these harmful effects. SUSE technical services will not be able to provide support for systems suffering from low disk space conditions as this can have an effect on an entire system and therefore becomes unresolvable. A full recovery is only possible with a previous backup or a new SUSE Manager installation.

Required Storage Devices

An additional disk is required for database storage. This should be an **zFCP** or **DASD** device as these are preferred for use with **HYPERPAV**. The disk should fulfill the following requirements:

- At least 50 GB for `/var/lib/pgsql`
- At least 50 GB for each SUSE product in `/var/pacewalk`
- At least 100 GB for each Red Hat product in `/var/pacewalk`

Reclaiming Disk Space

If you need to reclaim more disk space, try these suggestions:

- Remove custom channels (you cannot remove official SUSE channels)
- Use the `pacewalk-data-fsck --help` command to compare the pacewalk database to the filesystem and remove entries if either is missing.

SLES 12SP3 Installation and the SUSE Manager Extension

This section covers the installation of SUSE Manager 4.0 as an extension to SLES 12SP3 .

For more information on deploying SLES 12SP3 on your hardware, see https://www.suse.com/documentation/sles-12/book_sle_deployment/data/cha_zseries.html.

During installation of SLES 12SP3 select SUSE Manager as an extension.

After rebooting you will need to set up the additional storage required for `/var/spacwalk` and `/var/lib/pgsql` and swap space using the yast partitioner tool. This step is *required* before running `yast2 susemanagersetup`.

After configuring the storage requirements, having executed a YaST online update and completed a full system reboot, run SUSE Manager setup to finalize the SUSE Manager installation on your z Systems mainframe:

```
{prompt.root}yast2 susemanagersetup
```

This completes the installation of SUSE Manager on your z Systems . For more information on beginning management with SUSE Manager , see [Setup SUSE Manager with YaST](#).

Setting Up

SUSE Manager Setup

Topics

This section covers SUSE Manager setup. You will perform the following procedures:

- Start SUSE Manager setup via YaST or command line
- Create the main administration account with the SUSE Manager Web UI
- Name your base organization and add login credentials
- Sync the SUSE Linux Enterprise product channel from SUSE Customer Center

SUSE Manager Setup

Third Party Software

SUSE Manager is an extension of SUSE Linux Enterprise Server and compatible with the software shipped with SUSE Linux Enterprise Server.



SUSE Manager is a complex system, and therefore installing third party is not allowed. Installing monitoring software provided by a third party vendor is allowed only if you do not exchange basic libraries such as SSL, cryptographic software, and similar tools. In case of emergency, SUSE reserves the right to ask to remove any third party software (and associated configuration changes) and then to reproduce the problem on a clean system.

This section will guide you through SUSE Manager setup procedures.

Procedure: SUSE Manager Setup

1. Login to the SUSE Manager server desktop and perform one of the following actions to begin setup:
 - Select **Applications > System Tools > YaST > SUSE Manager Setup**.
 - Open a terminal as root and type `yast2 susemanager_setup` to begin setup.
2. From the introduction screen select **SUSE Manager Setup > Setup SUSE Manager from scratch** and click [**Next**] to continue.
3. Enter an email address to receive status notifications and click [**Next**] to continue. Note that SUSE Manager can sometimes send a large volume of notification emails. You can disable email notifications in the Web UI after setup, if you need to.
4. Enter your certificate information and a password. Passwords must be at least seven characters in length, and must not contain spaces, single or double quotation marks (' or "), exclamation marks (!), or dollar signs (\$). Always store your passwords in a secure location.



Certificate Password

Without this password it will not be possible to set up a SUSE Manager Proxy Server.

5. Click [**Next**] to continue.



Certificate Setup

Organization
SUSE

Organization Unit
Galaxy

City
NUE

State
BY


Country
DE

SSL Password
••••••••

Repeat Password
••••••••

[Help](#) [Abort](#) [Back](#) [Next](#)

6. From the **SUSE Manager Setup > Database Settings** screen, enter a database user and password and click [**Next**] to continue. Passwords must be at least seven characters in length, and must not contain spaces, single or double quotation marks (' or "), exclamation marks (!), or dollar signs (\$). Always store your passwords in a secure location.



Database Settings

Database User
susemanager

Database Password
••••••••

Repeat Password
••••••••

[Help](#) [Abort](#) [Back](#) [Next](#)

7. Click [**Next**] to continue.
8. Click [**Yes**] to run setup when prompted.
9. Once setup has completed, click [**Next**] to continue. You will see the address of the SUSE Manager Web UI.

10. Click [**Finish**] to complete SUSE Manager setup.

In the next section you will create the administrator's account and synchronize with SUSE Customer Center.

Creating the Main Administration Account

This section will walk you through creating your organizations main administration account for SUSE Manager.




Admin and User Accounts

The main administration account is the *highest authority account* within SUSE Manager and therefore account access information should be stored in a secure location.

For security it is recommended that the main administrator creates *low level admin accounts* designated for administration of organizations and individual groups.

Procedure: Setup the Main Administration Account

1. In the browser, enter the address provided after completing setup and open the SUSE Manager Web UI.
2. Add your organization name to the **Create Organization** > **Organization Name** field.
3. Add your username and password to the **Create Organization** > **Desired Login** and **Create Organization** > **Desired Password** fields.
4. Fill in the Account Information fields including an email for system notifications.
5. Select **Create Organization** to finish creating your administration account.

 Create Organization

Organization Details

Organization Name*:

Tip: Between 3 and 128 characters

Create SUSE Manager Administrator

Create the first SUSE Manager Administrator account. This account will have access to all resources on this SUSE Manager. This account will also be able to create new users and delegate permissions to them.

Desired Login*:

Tip: Between 5 and 64 characters

Desired Password *:

Confirm Password *:

Password Strength:

Email*:

First Name*:

Last Name*:

* - Required Field

Create Organization

You should now be presented with the SUSE Manager Front Page. In the next section you will prepare the server for connecting the first client.

Syncing Products from SUSE Customer Center

SUSE Customer Center (SCC) maintains a collection of repositories which contain packages, software and updates for all supported enterprise client systems. These repositories are organized into channels each of which provide software specific to a distribution, release and architecture. After synchronizing with SCC clients may receive updates, and be organized into groups and assigned to specific product software channels.

This section covers synchronizing with SCC from the Web UI and adding your first client channel.

Procedure: Synchronizing with SUSE Customer Center

1. From the SUSE Manager Web UI start page select **Admin** > **Setup Wizard**.
2. From the **Main Menu** > **Admin** > **Setup Wizard** page select the [**SUSE Products**] tab. Wait a moment for the products list to populate. If you previously registered with SUSE Customer Center a list of products will populate the table. This table lists architecture, channels, and status information. For more information, see:

xref:FILENAME.adoc#vle.webui.admin.wizard.products[]

+

Setup Wizard

HTTP Proxy Organization Credentials SUSE Products

Filter by product Description Filter by architecture 25 items per page

Items 1 - 25 of 94

Product Description	Arch	Channels
<input type="checkbox"/> Open Enterprise Server 2018	x86_64	
<input type="checkbox"/> RHEL Expanded Support 5	i386	
<input type="checkbox"/> RHEL Expanded Support 5	x86_64	
<input type="checkbox"/> > RHEL Expanded Support 6	i386	
<input type="checkbox"/> > RHEL Expanded Support 6	x86_64	
<input type="checkbox"/> > RHEL Expanded Support 7	x86_64	
<input type="checkbox"/> SUSE Container as a Service Platform 1.0	x86_64	
<input type="checkbox"/> SUSE Container as a Service Platform 2.0	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 11 SP2	i586	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 11 SP2	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 11 SP3	i586	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 11 SP3	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 11 SP4	i586	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 11 SP4	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 12	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 12 SP1	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 12 SP2	x86_64	
<input type="checkbox"/> > SUSE Linux Enterprise Desktop 12 SP3	x86_64	
<input checked="" type="checkbox"/> > SUSE Linux Enterprise Desktop 15	x86_64	100%
<input type="checkbox"/> > SUSE Linux Enterprise High Performance Computing 15	aarch64	include recommended
<input type="checkbox"/> > SUSE Linux Enterprise High Performance Computing 15	x86_64	include recommended
<input type="checkbox"/> > SUSE Linux Enterprise Server 10 SP3	i586	
<input type="checkbox"/> > SUSE Linux Enterprise Server 10 SP3	ia64	
<input type="checkbox"/> > SUSE Linux Enterprise Server 10 SP3	ppc	
<input type="checkbox"/> > SUSE Linux Enterprise Server 10 SP3	s390x	

Page 1 of 4 First Prev Next Last

Refresh the product catalog from SUSE Customer Center

☐ Channels
☐ Channel Families
☐ Products
☐ Product Channels
☐ Subscriptions

Refresh

Why aren't all SUSE products displayed in the list?

The products displayed on this list are directly linked to your Organization credentials (Mirror credentials) as well as your SUSE subscriptions.

If you believe there are products missing, make sure you have added the correct Organization credentials in the previous wizard step.

← Prev 3 of 3

+

1. Since Your SUSE Linux Enterprise client is based on **x86_64** architecture scroll down the page and select the check box for this channel now.
 - Add channels to SUSE Manager by selecting the check box to the left of each channel. Click the arrow symbol to the left of the description to unfold a product and list available modules.

- Start product synchronization by clicking the [**Add Products**] button.

After adding the channel SUSE Manager will schedule the channel to be copied. This can take a long time as SUSE Manager will copy channel software sources from the SUSE repositories located at SUSE Customer Center to local `/var/pacewalk/` directory of your server.



PostgreSQL and Transparent Huge Pages

In some environments, *Transparent Huge Pages* provided by the kernel may slow down PostgreSQL workloads significantly.

To disable *Transparent Huge Pages* set the `transparent_hugepage` kernel parameter to `never`. This has to be changed in `/etc/default/grub` and added to the line `GRUB_CMDLINE_LINUX_DEFAULT`, for example:

```
GRUB_CMDLINE_LINUX_DEFAULT="resume=/dev/sda1 splash=silent quiet
showopts elevator=noop transparent_hugepage=never"
```

To write the new configuration run `grub2-mkconfig -o /boot/grub2/grub.cfg`. To update the grub2 during boot run `grub2-install /dev/sda`.

Monitor channel synchronization process in real-time by viewing channel log files located in the directory `/var/log/rhn/reposync`:

```
tailf /var/log/rhn/reposync/<CHANNEL_NAME>.log
```

After the channel sync process has completed proceed to:

```
pass:c[xref:FILENAME.adoc#preparing.and.registering.clients[]]
```

SUSE Manager Proxy Setup

SUSE Manager Proxy requires additional configuration in order to make it useful.

Install the `suma_proxy` pattern

On the server select the `pattern_suma_proxy` package for installation, or make sure the `suma_proxy` pattern is installed using the following command on the proxy as root:

```
zypper in -t pattern suma_proxy
```

The new salt-broker service will be automatically started at the end of the package installation. This service forwards the Salt interactions to the SUSE Manager server.



Proxy Chains

It is possible to arrange Salt proxies in a chain. In such a case, the upstream proxy is named “parent”.

Make sure the proxy's TCP ports **4505** and **4506** are open and that the proxy can reach the SUSE Manager server (or another upstream proxy) on these ports.

Copy Server Certificate and Key

The proxy will share some SSL information with the SUSE Manager server, so the next step is to copy the certificate and its key from the SUSE Manager server or the upstream proxy.

As root, enter the following commands on the proxy using your SUSE Manager server or chained proxy named **PARENT**:

```
mkdir /root/ssl-build
cd /root/ssl-build
scp root@PARENT:/root/ssl-build/RHN-ORG-PRIVATE-SSL-KEY .
scp root@PARENT:/root/ssl-build/RHN-ORG-TRUSTED-SSL-CERT .
scp root@PARENT:/root/ssl-build/rhn-ca-openssl.cnf .
```



Known Limitation

The SUSE Manager Proxy functionality is only supported if the SSL certificate was signed by the same CA as the SUSE Manager Server certificate. Using certificates signed by different CAs for Proxies and Server is not supported.

Running `configure-proxy.sh`

The `configure-proxy.sh` script will finalize the setup of your SUSE Manager Proxy.

Now execute the interactive `configure-proxy.sh` script. Pressing **Enter** without further input will make the script use the default values provided between brackets `[]`. Here is some information about the requested settings:

SUSE Manager Parent

A SUSE Manager parent can be either another proxy server or a SUSE Manager server.

HTTP Proxy

A HTTP proxy enables your SUSE Manager proxy to access the Web. This is needed if direct access to the Web is prohibited by a firewall.

Proxy Version to Activate

Normally, the correct value (3.0, 3.1, or 3.2) should be offered as a default.

Traceback Email

An email address where to report problems.

Use SSL

For safety reasons, press **Y**.

Do You Want to Import Existing Certificates?

Answer **N**. This ensures using the new certificates that were copied previously from the SUSE Manager server.

Organization

The next questions are about the characteristics to use for the SSL certificate of the proxy. The organization might be the same organization that was used on the server, unless of course your proxy is not in the same organization as your main server.

Organization Unit

The default value here is the proxy's hostname.

City

Further information attached to the proxy's certificate. Beware the country code must be made of two upper case letters. For further information on country codes, refer to the online [list of alpha-2 codes](#).



Country Code

As the country code enter the country code set during the SUSE Manager installation. For example, if your proxy is in US and your SUSE Manager in DE, you must enter **DE** for the proxy.

Cname Aliases (Separated by Space)

Use this if your proxy server can be accessed through various DNS CNAME aliases. Otherwise it can be left empty.

CA Password

Enter the password that was used for the certificate of your SUSE Manager server.

Do You Want to Use an Existing SSH Key for Proxying SSH-Push Salt Minions?

Use this option if you want to reuse a SSH key that was used for SSH-Push Salt minions on the server.

Create and Populate Configuration Channel `rhn_proxy_config_1000010001`?

Accept default **Y**.

SUSE Manager Username

Use same user name and password as on the SUSE Manager server.

Activate advertising proxy via SLP?

SLP stands for Service Location Protocol.

If parts are missing, such as CA key and public certificate, the script prints commands that you must execute to integrate the needed files. When the mandatory files are copied, re-run `configure-proxy.sh`. Also restart the script if a HTTP error was met during script execution.

`configure-proxy.sh` activates services required by SUSE Manager Proxy, such as `squid`, `apache2`, `salt-broker`, and `jabberd`.

To check the status of the proxy system and its clients, click the proxy system's details page on the Web UI (**Main Menu** > **Systems** > **Proxy**, then the system name). **Connection** and **Proxy** subtabs display the respective status information.

Enabling PXE Boot via SUSE Manager Proxy

Synchronizing Profiles and System Information

To enable PXE boot via a proxy server, additional software must be installed and configured on both the SUSE Manager server and the SUSE Manager Proxy server.

1. On the SUSE Manager server install `susemanager-tftpsync` :

```
zypper in susemanager-tftpsync
```

2. On the SUSE Manager Proxy server install `susemanager-tftpsync-recv` :

```
zypper in susemanager-tftpsync-recv
```

3. Run the `configure-tftpsync.sh` setup script and enter the requested information:

```
configure-tftpsync.sh
```

It asks for hostname and IP address of the SUSE Manager server and of the proxy itself. Additionally, it asks for the tftpboot directory on the proxy.

4. On the SUSE Manager server, run `configure-tftpsync.sh` to configure the upload to the SUSE Manager Proxy server:

```
configure-tftpsync.sh FQDN_of_Proxy_Server
```

5. To initiate an initial synchronization on the SUSE Manager Server run:

```
cobbler sync
```

Also can also be done after each a change within Cobbler that needs to be synchronized immediately.

Otherwise Cobbler synchronization will also run automatically when needed. For more information about Cobbler, see [xref:FILENAME.adoc#advanced.topics.cobbler\[\]](#).

Configuring DHCP for PXE via SUSE Manager Proxy

SUSE Manager is using Cobbler to provide provisioning. PXE (tftp) is installed and activated by default. To enable systems to find the PXE boot on the SUSE Manager Proxy server add the following to the DHCP configuration for the zone containing the systems to be provisioned:

```
next-server: <IP_Address_of_SUSE_Manager_Proxy_Server>
filename: "pxelinux.0"
```

Replacing a SUSE Manager Proxy

A SUSE Manager Proxy is **dumb** in the sense that it does not contain any information about the clients which are connected to it. A SUSE Manager Proxy can therefore be replaced by a new one. Naturally, the replacement proxy must have the same name and IP address as its predecessor.

In order to replace a SUSE Manager Proxy and keeping the clients registered to the proxy leave the old proxy in SUSE Manager. Create a reactivation key for this system and then register the new proxy using the reactivation key. If you do not use the reactivation key, you will need to re-register all the clients against the new proxy.

Procedure: Replacing a SUSE Manager Proxy and Keeping the Clients Registered

1. Before starting the actual migration procedure, save the data from the old proxy, if needed. Consider copying important data to a central place that can also be accessed by the new server:
 - Copy the scripts that are still needed.
 - Copy the activation keys from the previous server. Of course, it is always better to re-create the keys.
2. Shutdown the server.
3. Install a new SUSE Manager 4.0 Proxy, see [xref:FILENAME.adoc#at.manager.proxy.inst-and-clients\[\]](#).
4. In the SUSE Manager Web UI select the newly installed SUSE Manager Proxy and delete it from the systems list.
5. In the Web UI, create a reactivation key for the old proxy system: On the System Details tab of the old proxy click **Reactivation**. Then click **Generate New Key**, and remember it (write it on a piece of paper or copy it to the clipboard). For more information about reactivation keys, see [xref:FILENAME.adoc#s5-sm-system-details-react\[\]](#).
6. After the installation of the new proxy, perform the following actions (if needed):
 - Copy the centrally saved data to the new proxy system.
 - Install any other needed software.

- If the proxy is also used for autoinstallation, do not forget to setup TFTP synchronization.



Proxy Installation and Client Connections

During the installation of the proxy, clients will not be able to reach the SUSE Manager server. After a SUSE Manager Proxy system has been deleted from the systems list, all clients connected to this proxy will be (incorrectly) listed as **directly connected** to the SUSE Manager server. After the first successful operation on a client *such as execution of a remote command or installation of a package or patch* this information will automatically be corrected. This may take a few hours.