



Chapter 4: Threads





Chapter 4: Threads

- Overview
- Multithreading Models
- Thread Libraries
- Threading Issues
- Operating System Examples
- Windows XP Threads
- Linux Threads





Objectives

- To introduce the notion of a thread — a fundamental unit of CPU utilization that forms the basis of multithreaded computer systems
- To discuss the APIs for the Pthreads, Win32, and Java thread libraries
- To examine issues related to multithreaded programming







Motivation

- Threads run within application
- Multiple tasks with the application can be implemented by separate threads
 - Update display
 - Fetch data
 - Spell checking
 - Answer a network request
- Process creation is heavy-weight while thread creation is light-weight
- Can simplify code, increase efficiency
- Kernels are generally multithreaded






Single and Multithreaded Processes



single-threaded process





multithreaded process





Multithreaded Server Architecture






Benefits

- **Responsiveness** (eg. User Interfaces)
- **Resource Sharing** (The benefit of sharing code, data, and other OS resources such as files and signals is that it allows an application to have several different threads of activity within the same address space))
- **Economy** (It is more economical to create and context-switch threads)
- **Scalability** (In multiprocessor architecture, threads may be running in parallel on different processing cores)







Concurrent Execution on a Single-core System





Parallel Execution on a Multicore System






Multicore Programming

- Multicore systems putting pressure on programmers, challenges include:
 - **Dividing activities**
 - **Balance**
 - **Data splitting**
 - **Data dependency**
 - **Testing and debugging**






User Threads

- Thread management done by user-level threads library
- Three primary thread libraries:
 - POSIX **Pthreads**
 - Win32 threads
 - Java threads






Kernel Threads

- Supported by the Kernel
- Examples
 - Windows XP/2000
 - Solaris
 - Linux
 - Tru64 UNIX
 - Mac OS X






Multithreading Models

- Many-to-One
- One-to-One
- Many-to-Many






Many-to-One

- Many user-level threads mapped to single kernel thread
- Examples:
 - **Solaris Green Threads**
 - **GNU Portable Threads**





Many-to-One Model







One-to-One

- Each user-level thread maps to kernel thread
- Examples
 - Windows NT/XP/2000
 - Linux
 - Solaris 9 and later





One-to-one Model






Many-to-Many Model


- Allows many user level threads to be mapped to many kernel threads
- Allows the operating system to create a sufficient number of kernel threads
- Solaris prior to version 9
- Windows NT/2000 with the *ThreadFiber* package





Many-to-Many Model





Thread Libraries

- **Thread library** provides programmer with API for creating and managing threads
- Two primary ways of implementing
 - Library entirely in user space
 - Kernel-level library supported by the OS





Pthreads

- May be provided either as user-level or kernel-level
- A POSIX standard (IEEE 1003.1c) API for thread creation and synchronization
- API specifies behavior of the thread library, implementation is up to development of the library
- Common in UNIX operating systems (Solaris, Linux, Mac OS X)





Pthreads Example

```
#include <pthread.h>
#include <stdio.h>

int sum; /* this data is shared by the thread(s) */
void *runner(void *param); /* the thread */

int main(int argc, char *argv[])
{
    pthread_t tid; /* the thread identifier */
    pthread_attr_t attr; /* set of thread attributes */

    if (argc != 2) {
        fprintf(stderr, "usage: a.out <integer value>\n");
        return -1;
    }
    if (atoi(argv[1]) < 0) {
        fprintf(stderr, "%d must be >= 0\n", atoi(argv[1]));
        return -1;
    }
}
```





Pthreads Example (Cont.)

```
/* get the default attributes */
pthread_attr_t attr;
pthread_attr_init(&attr);
/* create the thread */
pthread_create(&tid, &attr, runner, argv[1]);
/* wait for the thread to exit */
pthread_join(tid, NULL);

printf("sum = %d\n", sum);
}

/* The thread will begin control in this function */
void *runner(void *param)
{
    int i, upper = atoi(param);
    sum = 0;

    for (i = 1; i <= upper; i++)
        sum += i;

    pthread_exit(0);
}
```

Figure 4.9 Multithreaded C program using the Pthreads API.





Win32 API Multithreaded C Program

```
#include <windows.h>
#include <stdio.h>
DWORD Sum; /* data is shared by the thread(s) */
/* the thread runs in this separate function */

DWORD WINAPI Summation(LPVOID Param)
{
    DWORD Upper = *(DWORD*)Param;
    for (DWORD i = 0; i <= Upper; i++)
        Sum += i;
    return 0;
}

int main(int argc, char *argv[])
{
    DWORD ThreadId;
    HANDLE ThreadHandle;
    int Param;
    /* perform some basic error checking */
    if (argc != 2) {
        fprintf(stderr, "An integer parameter is required\n");
        return -1;
    }
    Param = atoi(argv[1]);
    if (Param < 0) {
        fprintf(stderr, "An integer >= 0 is required\n");
        return -1;
    }
}
```





Win32 API Multithreaded C Program (Cont.)

```
// create the thread
ThreadHandle = CreateThread(
    NULL, // default security attributes
    0, // default stack size
    Summation, // thread function
    &Param, // parameter to thread function
    0, // default creation flags
    &ThreadId); // returns the thread identifier


if (ThreadHandle != NULL) {
    // now wait for the thread to finish
    WaitForSingleObject(ThreadHandle, INFINITE);

    // close the thread handle
    CloseHandle(ThreadHandle);

    printf("sum = %d\n", Sum);
}
}
```

Figure 4.10 Multithreaded C program using the Win32 API.





Java Threads

- Java threads are managed by the JVM
- Typically implemented using the threads model provided by underlying OS
- Java threads may be created by:
 - Extending Thread class
 - Implementing the Runnable interface





Java Multithreaded Program

```
class Sum
{
    private int sum;

    public int getSum() {
        return sum;
    }


    public void setSum(int sum) {
        this.sum = sum;
    }
}

class Summation implements Runnable
{
    private int upper;
    private Sum sumValue;

    public Summation(int upper, Sum sumValue) {
        this.upper = upper;
        this.sumValue = sumValue;
    }

    public void run() {
        int sum = 0;
        for (int i = 0; i <= upper; i++)
            sum += i;
        sumValue.setSum(sum);
    }
}
```






Java Multithreaded Program (Cont.)

```
public class Driver
{
    public static void main(String[] args) {
        if (args.length > 0) {
            if (Integer.parseInt(args[0]) < 0)
                System.err.println(args[0] + " must be >= 0.");
            else {
                // create the object to be shared
                Sum sumObject = new Sum();
                int upper = Integer.parseInt(args[0]);
                Thread thrd = new Thread(new Summation(upper, sumObject));
                thrd.start();
                try {
                    thrd.join();
                    System.out.println
                        ("The sum of " + upper + " is " + sumObject.getSum());
                } catch (InterruptedException ie) { }
            }
        }
        else
            System.err.println("Usage: Summation <integer value>");
    }
}
```

Figure 4.11 Java program for the summation of a non-negative integer.






Threading Issues

- Semantics of **fork()** and **exec()** system calls
- **Thread cancellation** of **target thread**
 - Asynchronous or deferred
- **Signal** handling
 - Synchronous and asynchronous






Threading Issues (Cont.)

- Thread pools
- Thread-specific data
 - Create Facility needed for data private to thread
- Scheduler activations






Semantics of `fork()` and `exec()`

- Does **`fork()`** duplicate only the calling thread or all threads?






Thread Cancellation

- Terminating a thread before it has finished
- Two general approaches:
 - **Asynchronous cancellation** terminates the target thread immediately.
 - **Deferred cancellation** allows the target thread to periodically check if it should be cancelled.






Signal Handling

- Signals are used in UNIX systems to notify a process that a particular event has occurred.
- A **signal handler** is used to process signals
 1. Signal is generated by particular event
 2. Signal is delivered to a process
 3. Signal is handled
- Options:
 - Deliver the signal to the thread to which the signal applies
 - Deliver the signal to every thread in the process
 - Deliver the signal to certain threads in the process
 - Assign a specific thread to receive all signals for the process





Thread Pools

- Create a number of threads in a pool where they await work
- Advantages:
 - Usually slightly faster to service a request with an existing thread than create a new thread
 - Allows the number of threads in the application(s) to be bound to the size of the pool





Thread Specific Data

- Allows each thread to have its own copy of data
- Useful when you do not have control over the thread creation process (i.e., when using a thread pool)






Scheduler Activations


- Both M:M and Two-level models require communication to maintain the appropriate number of kernel threads allocated to the application
- Scheduler activations provide **upcalls** - a communication mechanism from the kernel to the thread library
- This communication allows an application to maintain the correct number kernel threads





Lightweight Processes






Operating System Examples

- Windows XP Threads
- Linux Thread





Windows XP Threads Data Structures






Windows XP Threads

- Implements the one-to-one mapping, kernel-level
- Each thread contains
 - A thread id
 - Register set
 - Separate user and kernel stacks
 - Private data storage area
- The register set, stacks, and private storage area are known as the **context** of the threads
- The primary data structures of a thread include:
 - ETHREAD (executive thread block)
 - KTHREAD (kernel thread block)
 - TEB (thread environment block)





Linux Threads

- Linux refers to them as *tasks* rather than *threads*
- Thread creation is done through `clone()` system call
- `clone()` allows a child task to share the address space of the parent task (process)
- `struct task_struct` points to process data structures (shared or unique)





Linux Threads

- `fork()` and `clone()` system calls
- Doesn't distinguish between process and thread
 - Uses term *task* rather than thread
- `clone()` takes options to determine sharing on process create
- `struct task_struct` points to process data structures (shared or unique)

flag	meaning
<code>CLONE_FS</code>	File-system information is shared.
<code>CLONE_VM</code>	The same memory space is shared.
<code>CLONE_SIGHAND</code>	Signal handlers are shared.
<code>CLONE_FILES</code>	The set of open files is shared.



End of Chapter 4

