WALNUT INTERNAL BRAIN

Conversation history

CodeBuddy, WorkBuddy and Miora, during development

Pages 2-7: CodeBuddy sessions CB1-CB6 (overview of each)

Pages 8-10: WorkBuddy: the three connectors, one question through two people, compliance audit

Pages 11-12: Miora: the cover and thumbnail sessions

Full transcripts: github.com/IshaanSirbhaiya/Tencent, docs/tencent/evidence/

CodeBuddy · session CB1

CodeBuddy session CB1: Trust-boundary diagram (Plan)

Rendered from the CodeBuddy CLI transcript docs/tencent/evidence/codebuddy_cb1.jsonl (working directory e:\Tenecent Hack_Walnut\Tencent)

model: hy3 | turns: 24 | duration: 191 s | outcome: success | session: 01a1386c-71b4...

TASK PROMPT (SENT AFTER THE STANDARD WORKING RULES IN CODEBUDDY_PROMPTS/_RULES.MD)

Read docs/tencent/INTERNAL_BRAIN_PLAN.md section 4 and docs/tencent/CONTRACTS.md (and skim docs/tencent/ARCHITECTURE.md). Produce a Mermaid trust-boundary diagram for the Walnut Internal Brain: employee (web) and WorkBuddy clients, the IB gateway (auth, Gate 1 index pre-filter, Gate 2 live source check, grounding wall, write-ahead access ledger), Tencent TokenHub (hy3, fallback deepseek-v4.1-flash), the four source platforms (Confluence, Jira, Slack, Drive) with signed webhooks, the compliance audit console, the external ledger-head sink, and the Lighthouse public edge (Caddy). Mark every trust boundary TB1-TB5 and label what crosses each one (identity token, permitted passages only, signed webhook, ledger head hash, and so on). Save it to docs/tencent/diagrams/trust_boundaries.mmd (valid Mermaid flowchart syntax that renders on GitHub), and add docs/tencent/diagrams/README.md with a short legend explaining TB1-TB5.

CODEBUDDY

I'll read the required documentation files first.

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\docs\\tencent\\INTERNAL_BRAIN_PLAN.md"}

> 1→# Walnut Internal Brain: end-to-end build and submission plan (v2) 2→ 3→> Tencent Cloud AI CAN DO IT Hackathon Singapore 2026, **FinTech Track (Aspire), "The Internal Brain"**. 4→> Repo `IshaanSirbhaiya/Tencent`, branch `Tencent`. Base: Walnut `implementation-prototype-completed`. 5→> 6→> v1 was written on Tue 2026-10-13 at about 16:00 SGT. A 4-seat panel reviewed it: Haiku 5.5, Sonnet 5.5, 7→>…

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\docs\\tencent\\CONTRACTS.md"}

> 1→# Internal Brain: build contracts (C0) 2→ 3→Every agent builds against this file and against `databridge/apps/internal_brain/databridge_ib/models.py`, 4→which holds the same contracts as code. Only the coordinator changes either one. Paths are relative to 5→`databridge/`. 6→ 7→## 0. Layout and ownership 8→ 9→```
> 10→apps/internal_brain/ Python package databridge_ib (IB app, its own process, port…

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\docs\\tencent\\ARCHITECTURE.md"}

> 1→# Walnut Internal Brain: architecture 2→ 3→> FinTech Track (Aspire), "The Internal Brain". Status as of 13 Oct 2026; `file:line` references are to 4→> commit `4d1887e`. Paths are relative to `databridge/apps/internal_brain/databridge_ib/` unless they start 5→> with `databridge/`, `tests/` (= `databridge/apps/internal_brain/tests/`) or `docs/`. Where a component is 6→> planned but not yet in the…

CODEBUDDY

I have everything I need. The plan's architecture section (§4 and §5 trust-boundary table) defines TB1–TB5. Let me verify the target directory and create it.

⚙ Bash {"command": "ls -la \"e:/Tenecent Hack_Walnut/Tencent/docs/tencent\" && (ls -la \"e:/Tenecent Hack_Walnut/Tencent/docs/tencent/diagrams\" 2>/dev/null || echo \"diagrams dir does not exist yet\")", "description": "Check docs/tencent and diagrams directory"}

> Command: ls -la "e:/Tenecent Hack_Walnut/Tencent/docs/tencent" && (ls -la "e:/Tenecent Hack_Walnut/Tencent/docs/tencent/diagrams" 2>/dev/null || echo "diagrams dir does not exist yet") Stdout: total 216 drwxr-xr-x 1 <user> 197121 0 Oct 14 11:19 . drwxr-xr-x 1 <user> 197121 0 Oct 13 21:32 .. -rw-r--r-- 1 <user> 197121 15592 Oct 14 11:16 ARCHITECTURE.md -rw-r--r-- 1 <user> 197121 6730 Oct 14 01:56 …

CodeBuddy · session CB2

CodeBuddy session CB2: WorkBuddy MCP connector + tests

Rendered from the CodeBuddy CLI transcript docs/tencent/evidence/codebuddy_cb2.jsonl (working directory e:\Tenecent Hack_Walnut\Tencent)

model: default-model | turns: 94 | duration: 258 s | outcome: success | session: 01a1386f-8eaf...

TASK PROMPT (SENT AFTER THE STANDARD WORKING RULES IN CODEBUDDY_PROMPTS/_RULES.MD)

In databridge/apps/internal_brain/databridge_ib/mcp_server.py implement a stdio MCP server using the python `mcp` SDK (already installed in the venv; use mcp.server.fastmcp.FastMCP) named "walnut-internal-brain". It is a thin client of the Internal Brain HTTP API at env IB_URL (default http://127.0.0.1:8100), authenticating with the bearer token in env IB_TOKEN (use httpx). Tools:
  - ask_internal_brain(question: str): POST /ib/ask with JSON {"question": question} and header "x-ib-channel: workbuddy-mcp"; return the answer text, the citations (title, platform, deep_link, version) and a line "answered as <sub>" where <sub> comes from GET /auth/whoami.
  - my_recent_questions(): GET /ib/history, returned as a short readable list.
No tool may take a user / identity / persona argument: identity comes only from IB_TOKEN. Fail clearly (a readable error string) when IB_TOKEN is missing or the API returns an error; never print the token. Provide a main() and `if __name__ == "__main__": main()` so it runs with `python -m databridge_ib.mcp_server`.

Also create databridge/apps/internal_brain/databridge_ib/audit_mcp_server.py, a second stdio MCP server "walnut-ib-audit" for compliance officers, same IB_URL / IB_TOKEN pattern, exposing:
  - audit_events(user: str = "", container: str = "", since_days: int = 30, doc: str = ""): GET /audit/events with those as query parameters (omit empty ones)
  - audit_doc_accessors(doc_id: str): GET /audit/doc/{doc_id}/accessors
  - audit_verify(): GET /audit/verify
(Here `user` is a filter on the audit log, not the caller's identity.) Read databridge/apps/internal_brain/databridge_ib/app.py and databridge_ib/audit/routes.py first to match the real request and response shapes.

Add tests in databridge/apps/internal_brain/tests/test_mcp_server.py: build the IB app in-process the same way tests/test_app_routes.py does, route the MCP tools' HTTP calls to it (for example by injecting an httpx client or transport), and assert (1) ask_internal_brain returns an answer with citations for a permitted question, (2) the tool input schemas of both servers' end-user tools contain no identity argument (no "user", "persona", "sub" or "principal" in ask_internal_brain or my_recent_questions), (3) a missing IB_TOKEN gives a clear error. Run the new tests and fix any failure.

CODEBUDDY

I'll start by exploring the codebase to understand the existing patterns, then implement the MCP servers and tests.

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\app.py"}

> 1→"""The Internal Brain HTTP app — its own process, its own state, an explicit route allowlist (§4.1). 2→ 3→Only these route prefixes may exist (``test_routes_allowlist`` enumerates every mounted route): 4→``/health``, ``/auth/*``, ``/ib/*``, ``/webhooks/*``, ``/audit/*``, ``/sim/*``. The legacy Walnut gateway 5→is never imported or mounted here. 6→""" 7→from __future__ import annotations 8→ 9→im…

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\tests\\test_app_routes.py"}

> 1→"""The IB app exposes only allowlisted routes, all authenticated (Opus B1 / Codex B5), identity only 2→from the signed token (P8), and fails closed (503) when the pipeline cannot ledger.""" 3→from __future__ import annotations 4→ 5→from fastapi.testclient import TestClient 6→ 7→from databridge_ib import auth as authmod 8→from databridge_ib.app import ALLOWED_PREFIXES, Services, create_app, moun…

CODEBUDDY

Now let me read the audit routes and models to understand the shapes.

CodeBuddy · session CB3

CodeBuddy session CB3: Token CLI + WorkBuddy setup guide

Rendered from the CodeBuddy CLI transcript docs/tencent/evidence/codebuddy_cb3.jsonl (working directory e:\Tenecent Hack_Walnut\Tencent)

model: default-model | turns: 139 | duration: 223 s | outcome: success | session: 01a13873-9984...

TASK PROMPT (SENT AFTER THE STANDARD WORKING RULES IN CODEBUDDY_PROMPTS/_RULES.MD)

Create databridge/scripts/ib_mint_token.py: a CLI `python databridge/scripts/ib_mint_token.py <persona> [--hours N]` that loads IB_TOKEN_KEY from databridge/.env.ib.local (parse the file in code; do NOT open or print that file yourself while working, and the script must never print the key), looks the persona up in databridge/fixtures/enterprise/world.json, and prints ONLY a token minted with databridge_ib.auth.mint(key, sub, roles, ttl_s=...). Read databridge/apps/internal_brain/databridge_ib/auth.py and directory.py to get the signature and how roles are derived. Refuse unknown or inactive personas with a non-zero exit, and cap --hours at 8 (default 8). Add a short test databridge/apps/internal_brain/tests/test_mint_token_cli.py that uses a temporary env file and a dev key (never the real file) and checks: a known persona gives a token that databridge_ib.auth.verify accepts with the right sub; an unknown persona exits non-zero; --hours 24 is capped to 8.

Then create docs/tencent/workbuddy/README.md explaining how to connect WorkBuddy (desktop app 5.7.x) to the Internal Brain: one WorkBuddy project per persona, each with a project-level .workbuddy/mcp.json whose stdio server runs the venv python with args ["-m", "databridge_ib.mcp_server"] (cwd databridge, PYTHONPATH apps/internal_brain) and env IB_URL plus IB_TOKEN (minted with the CLI above), plus example files docs/tencent/workbuddy/examples/jdoe.mcp.json, ken.ext.mcp.json and maya.compliance.mcp.json (the last one runs databridge_ib.audit_mcp_server). Use the placeholder "<paste token from ib_mint_token.py>" for tokens in the examples. Run the new test and fix any failure.

CODEBUDDY

I'll start by exploring the codebase to understand the existing structure and the files I need to read.

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\auth.py"}

```
1→"""Signed, short-lived principal tokens (plan §4.9, P8). 2→ 3→Identity is ONLY ever this token's ``sub`` — from the ``ib_session`` cookie (UI) or an 4→``Authorization: Bearer`` header (MCP). No request body, tool argument or model output can name a 5→principal. Tokens are HMAC-SHA256 over canonical JSON: ``{sub, roles, exp, aud:"ib", jti}``. 6→""" 7→from __future__ import annotations 8→ 9→impor…
```

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\directory.py"}

```
1→"""The identity directory — who a principal is, which groups they are in, their native account ids. 2→ 3→It is a CACHE of the company's identity source (for the demo: ``world.json``'s ``directory``; 4→native platforms stay authoritative and Gate 2 asks them). Nested groups are expanded once at load. 5→Every change bumps ``epoch`` so Gate-1 readable-set caches never survive a directory change. 6…
```

⚙ Glob {"pattern": "databridge/fixtures/enterprise/world.json"}

```
["e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\fixtures\\enterprise\\world.json"]
```

⚙ Glob {"pattern": "databridge/.venv/Scripts/python.exe"}

```
No files found
```

⚙ Glob {"pattern": "databridge/.env.ib.local"}

```
No files found
```

CodeBuddy · session CB4

CodeBuddy session CB4: Model-chain tests

Rendered from the CodeBuddy CLI transcript docs/tencent/evidence/codebuddy_cb4.jsonl (working directory e:\Tenecent Hack_Walnut\Tencent)

model: default-model | turns: 92 | duration: 106 s | outcome: success | session: 01a13877-19b2...

TASK PROMPT (SENT AFTER THE STANDARD WORKING RULES IN CODEBUDDY_PROMPTS/_RULES.MD)

Write databridge/apps/internal_brain/tests/test_llm_chain.py covering databridge/apps/internal_brain/databridge_ib/llm.py ModelChain (read llm.py and narrate.py first):
(1) hy3 succeeds: the answer comes from model "hy3" with fallback_used False;
(2) hy3 raises: the chain falls back to "deepseek-v4.1-flash" with fallback_used True;
(3) both models fail: the chain returns no answer, so the pipeline serves the deterministic extractive answer (also assert this end to end through databridge_ib.pipeline.Pipeline using the in-memory fixtures pattern in tests/test_pipeline_core.py, expecting model "extractive-v1");
(4) a model answer containing a number that is NOT present in the context is refused by the grounding wall.
Use databridge_harness FakeBackend (see _capturing_chain in tests/test_pipeline_core.py for how a ModelChain is built over a FakeBackend); never call the network. Run the tests and fix any failure in the TEST file only (do not change llm.py or narrate.py; if you believe there is a bug in them, describe it in your summary instead).

CODEBUDDY

I'll start by reading the relevant files to understand the code structure.

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\llm.py"}

```
1→"""Model access for the Internal Brain — Tencent TokenHub (Hunyuan hy3) first (plan §4.10). 2→ 3→Routing goes through Walnut's harness (the only place a vendor SDK is imported). TokenHub is 4→OpenAI-compatible, so LiteLLM reaches it with ``openai/<model>`` plus ``OPENAI_API_BASE`` = 5→``https://tokenhub-int1.tencentcloudmaas.com/v1`` and ``OPENAI_API_KEY`` = the TokenHub key. 6→ 7→The chain is …
```

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\narrate.py"}

```
1→"""Answer writing: the pinned context contract, the IB system prompt, the grounded narrator wrapper 2→and the deterministic extractive answerer (plan §4.4). 3→ 4→Context contract (locked by test_narrate.py): one line per released passage, 5→``[C<n>] (<platform> · <container_name> · <title> · v<version> · <updated date>) <text>`` — the 6→``[C<n>]`` tag first, so Walnut's ``ground_narration`` / `…
```

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\tests\\test_pipeline_core.py"}

```
1→"""Pipeline core against in-memory connectors: P1 (prompt capture), P2 (differential), S3 refusal 2→shape, S4 revocation at the source, write-ahead ledger, drift read-through. The real connectors, 3→mock platforms and ledger have their own suites; this pins the pipeline's ORDER and guarantees.""" 4→from __future__ import annotations 5→ 6→import json 7→from datetime import datetime, timedelta, t…
```

CODEBUDDY

Now let me read the grounding module, models, and pipeline to understand the grounding wall and how `ModelChain` is used end-to-end.

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\grounding.py"}

```
1→"""Walnut's grounding wall, reused by import WITHOUT importing the legacy gateway (plan §4.1, §4.4). 2→ 3→``databridge_gateway/__init__.py`` imports ``main`` (every legacy route). The grounding functions in 4→``databridge_gateway/llm.py`` need only ``databridge_core`` at import time, so the module is loaded 5→from its file under a private name: the legacy gateway's routes are never imported int…
```

CodeBuddy · session CB5

CodeBuddy session CB5: Security review

Rendered from the CodeBuddy CLI transcript docs/tencent/evidence/codebuddy_cb5.jsonl (working directory e:\Tenecent Hack_Walnut\Tencent)

model: hy3 | turns: 70 | duration: 601 s | outcome: success | session: 01a1390f-8543...

TASK PROMPT (SENT AFTER THE STANDARD WORKING RULES IN CODEBUDDY_PROMPTS/_RULES.MD)

Security review (read-only: do not modify any existing file). Read databridge/apps/internal_brain/databridge_ib/app.py, auth.py, pipeline.py, gates.py, narrate.py and the databridge_ib/audit/ package. List concrete ways a user could (a) see content they are not permitted to read, (b) learn that restricted content exists, or (c) tamper with the audit trail without detection. For each finding give the severity (critical/high/medium/low), the exact file and line, a concrete attack scenario, and a suggested fix. Also list what you checked and found to be correctly defended. Rank findings by severity. Write the full review to docs/tencent/reviews/codebuddy_security_review.md (this is the only file you may create).

CODEBUDDY

I have enough context, but let me quickly check `sensitive.py` (masking on ingest) since it directly bears on finding (a).

⚙ Read {"file_path": "e:/Tenecent Hack_Walnut/Tencent/databridge/apps/internal_brain/databridge_ib/sensitive.py"}

CODEBUDDY

I have all the context needed. Let me ensure the target directory exists, then write the review.

⚙ Bash {"command": "cd /e/Tenecent\\ Hack_Walnut/Tencent && mkdir -p docs/tencent/reviews && ls -la docs/tencent/reviews", "description": "Create reviews output directory"}

> Command: cd /e/Tenecent\ Hack_Walnut/Tencent && mkdir -p docs/tencent/reviews && ls -la docs/tencent/reviews Stdout: total 4 drwxr-xr-x 1 <user> 197121 0 Oct 13 21:54 . drwxr-xr-x 1 <user> 197121 0 Oct 14 11:30 .. drwxr-xr-x 1 <user> 197121 0 Oct 13 16:06 plan-v1 drwxr-xr-x 1 <user> 197121 0 Oct 14 14:30 security-r1
> Stderr: (empty) Exit Code: 0 Signal: (none)

⚙ Write {"file_path": "e:/Tenecent Hack_Walnut/Tencent/docs/tencent/reviews/codebuddy_security_review.md", "content": "# Internal Brain — Security Review (read-only)\n\n**Scope.** `databridge/apps/internal_brain/databridge_ib/`: `app.py`, `auth.py`, `pipeline.py`,\n`…

> Successfully created and wrote to new file: e:\Tenecent Hack_Walnut\Tencent\docs\tencent\reviews\codebuddy_security_review.md

CODEBUDDY'S FINAL SUMMARY

Review written to `docs/tencent/reviews/codebuddy_security_review.md` (only file created; no existing files modified).

Summary (5 lines):
1. Ranked 7 findings: 1 Critical (demo-login passcode bypass → impersonate any persona incl. compliance_officer), 2 High (ledger-key-compromise undetectable post-publication forgery; unsealed answer content store), 1 Medium (unauthenticated/unrated webhook), 3 Low (channel spoofing, source-topology disclosure, dev cookie not secure).
2. Each finding gives severity, exact file:line, a concrete attack scenario, and a suggested fix, across the three required categories (a read, b existence, c audit tampering).
3. Confirmed correctly-defended controls: dual Gate 1/Gate 2 + drift read-through, fail-closed ACLs, masked ingest, generic refusals with no link/existence oracle, hash-chained sealed ledger + external anchor, write-ahead reveal with sha256 mismatch, derived re-synced projection, and HMAC token auth.
4. Root-cause theme: security rests on `IB_TOKEN_KEY`/`IB_LEDGER_KEY`/webhook-secret confidentiality; tightening secret handling and the demo-login gate closes the top

CodeBuddy · session CB6

CodeBuddy session CB6: Harden connectors after Codex review

Rendered from the CodeBuddy CLI transcript docs/tencent/evidence/codebuddy_cb6.jsonl (working directory e:\Tenecent Hack_Walnut\Tencent)

model: default-model | turns: 163 | duration: 630 s | outcome: success | session: 01a13923-dd02...

TASK PROMPT (SENT AFTER THE STANDARD WORKING RULES IN CODEBUDDY_PROMPTS/_RULES.MD)

Apply the fixes from the Codex security review in docs/tencent/reviews/security-r1/codex_track4_mcp_tokens.md (read it first) to the code you wrote earlier.
Only these files may change:
databridge/apps/internal_brain/databridge_ib/mcp_server.py, databridge/apps/internal_brain/databridge_ib/audit_mcp_server.py,
databridge/scripts/ib_mint_token.py, databridge/apps/internal_brain/tests/test_mcp_server.py, databridge/apps/internal_brain/tests/test_mint_token_cli.py.

Required changes:
1. (finding 3) Both MCP servers: handle non-JSON, empty, redirect and wrongly-shaped successful responses without raising. Validate shapes (dict with the expected keys, list of dicts for citations/items/events); return a fixed, sanitized error string otherwise. A malformed /auth/whoami response must not lose a good answer: show "answered as (unavailable)".
2. (finding 4) audit_doc_accessors: percent-encode doc_id as a single path segment (urllib.parse.quote(doc_id, safe="")) and reject empty ids and ids that are "." or "..".
3. (finding 5) audit_events: accept since_days only in 1..3650 (clamp is not enough: return a clear error outside the range); 0 is not allowed.
4. (finding 6) Error strings must contain only the operation and the HTTP status code: never the URL, query string or base URL.
5. (finding 7) Refuse to send the token over plain HTTP to a non-loopback host: IB_URL with scheme http is allowed only for 127.0.0.1, localhost or ::1; otherwise return a clear error and make no request. Reject IB_URL values that contain credentials, a query or a fragment.
6. (finding 9) Refactor both servers so every HTTP call goes through one small helper that creates the client (for example `_client() -> httpx.Client`), and change test_mcp_server.py to patch only that client factory (return fastapi.testclient.TestClient(app), which is an httpx.Client) so the REAL helpers that attach the Authorization header run in tests. Add tests: the Authorization header reaches the app (a request without it would be 401); an employee token calling the audit tools gets a forbidden error while a compliance-officer token succeeds on audit_verify, audit_events and audit_doc_accessors; audit_events(user="jdoe") run by the officer still records the OFFICER as the acting subject in the ledger (an audit.query event whose data["sub"] is the officer); malformed JSON / HTML 200 responses give the sanitized error; doc_id "../verify" is rejected or encoded (never reaches /audit/verify); since_days outside 1..3650 is rejected; plain-http non-loopback IB_URL is refused without a request.
7. (finding 1) ib_mint_token.py must not print the token by default: add `--out FILE` (write the token to FILE, creating it with owner-only permissions where the OS supports chmod, and print only "token written to FILE") and `--print` (explicit opt-in to print the token to stdout, for piping). With neither flag, exit non-zero with a usage message. Also expose a function `mint_for(persona, hours, env_path=..., world_path=...) -> str` that other scripts can import. Update test_mint_token_cli.py accordingly (cover --print, --out and the no-flag error).
Run the two test files plus databridge/apps/internal_brain/tests/test_audit_routes_real_principal.py and fix any failure. Report what you changed per finding.

CODEBUDDY

I'll start by reading the security review document and all the files I need to modify.


⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\docs\\tencent\\reviews\\security-r1\\codex_track4_mcp_tokens.md"}

<tool_use_error>File does not exist.</tool_use_error>

⚙ Read {"file_path": "e:\\Tenecent Hack_Walnut\\Tencent\\databridge\\apps\\internal_brain\\databridge_ib\\mcp_server.py"}

1→"""stdio MCP server ``walnut-internal-brain``: a thin client of the Internal Brain HTTP API. 2→ 3→Identity comes ONLY from the ``IB_TOKEN`` bearer token (P8). No tool accepts a user / persona / 4→sub / principal argument. The token is never logged. When ``IB_TOKEN`` is missing or the API 5→returns an error, the tool returns a readable error string (it does not raise). 6→ 7→Run with:: 8→ 9→ pyth…

WorkBuddy · the three Internal Brain connectors, enabled



WorkBuddy · one question through Jordan's and Ken's connectors

Ask from Tencent WorkBuddy

Same question through the Internal Brain connector. Each connector carries its own signed token.

Connector as Jordan (backend engineer)

Side-by-Side Comparison

Connector: `ib-as-jdoe` (answered as jdoe)

> "priya.sre: Blocker for the migration: Replication lag on the ledger-shard-3 replica climbed past 40 seconds during last night's backfill, so we paused the copy job at batch 1,812. [C1] Wave 4 of the DB Migration Plan [C2] Cutover of the ledger database to the managed Postgres 16 cluster is planned for 24 October 2026, pending sign-off from the payments on-call lead. [C2] The migration moves the ledger from the self-managed Postgres 11 cluster to a managed Postgres 16 cluster in four waves, with the ledger shards moved last. [C13]"

Sources (citations returned):

1. `[slack]` #db-migration — *"Blocker for the migration: Replication lag on the..."* — companya.slack.com/archives/C0DBMIG/p1791335520000101
2. `[jira]` DBMIG-12: Ledger cluster cutover (wave 4) — Jira
3. `[confluence]` DB Migration Plan (v6) — companya.atlassian.net/wiki/spaces/payment-gateway/pages/cf-1001

Connector as Ken (outside contractor)

Connector: `ib-as-ken` (answered as ken.ext)

> "I couldn't find an answer to that in the sources you can access."

Sources (citations returned): *(none)*

Key Takeaway

The two connectors returned very different results despite being asked the identical question:

- **jdoe** had access to Slack, Jira, and Confluence sources covering the database migration project, and returned a detailed answer about a replication-lag blocker on `ledger-shard-3` (copy paused at batch 1,812), plus the cutover target date of **24 October 2026** pending payments on-call sign-off.
- **ken.ext** had no accessible sources matching the question and returned an empty result with zero citations.

This demonstrates that the two connectors are scoped to different identity/permission contexts — `jdoe` appears to have broad access to the migration project's Slack channel, Jira tickets, and Confluence docs, while `ken.ext` does not.

WorkBuddy · compliance connector: access list and audit-chain check

Compliance checks from WorkBuddy

Maya's connector lists what jdoe accessed, then verifies the sealed audit chain.

Audit events (who, when, what happened)

19:49:08	`44cb719c…bbce5`	request.accepted → retrieval.decided → answer.released
19:04:44	`2e289646…b5be4`	request.accepted → retrieval.decided → answer.released
19:04:30	`1cda2246…a7574`	request.accepted → retrieval.decided → answer.released
19:02:36	`b4371d96…bbd4c`	request.accepted → retrieval.decided → answer.released
19:01:08	`c9a31c98…b366b`	request.accepted → retrieval.decided → answer.released
19:00:22	`5b5d6665…a66ac`	request.accepted → retrieval.decided → answer.released

Each request followed the same 3-stage lifecycle: **request accepted → retrieval decided → answer released** — meaning jdoe submitted a query, the system determined what to retrieve, and an answer was returned.


Audit chain verification

Audit Chain Verification

Field	Value
Status	✅ OK
Records	200
Head	`ade969370e963e4752969c0371a4884e3537f7752bf3e3fccec7a31b07acb31f`
Ledgered	True

The audit ledger is **intact and verified**. All 200 records in the chain are sealed correctly, the head hash is consistent, and no tampering or gaps were detected.

Miora · cover image session 1



Miora · cover image session 2

