

CSC e-Governance Services India Ltd.

Web Application Security Testing Assessment Report-

<https://wcd.aeologic.in/>

Date-14th-July-2026

Prepared By: RNR Consulting Pvt Ltd
Website: <https://www.consultrnr.com//>
Email: info@consultrnr.com

Table of Contents

1. Document Control	3
2. Statement of Confidentiality and Limitations	4
3. Timelines	5
4. Scope	5
5. Risk Rating	6
6. Testing Methodology	7
7. Information Gathering	8
8. Executive Summary	9
9. Assessment Overview	10
10. Vulnerability Details	11
11. Risk Evaluation and Conclusion	19
12. Recommendation	19
13. Annexure	19

1. Document Control

Document Name	Web Application Security Testing Assessment Report- https://wcd.aeologic.in/
Report Version	1.0
Pen Tester	Sumit Kumar/Ankit Kumar
Reviewer	Ashish Chauhan
Client	CSC e-Governance Services India Ltd.
Vendor	RNR Consulting Pvt. Ltd.

2. Statement of Confidentiality and Limitations

This report has been prepared by RNR Consulting Private Limited, a CERT-In Empanelled Information Security Auditing Organization, exclusively for the internal use of **CSC e-Governance Services India Ltd.**, in accordance with the terms and conditions of the signed engagement agreement.

The Assessment, including but not limited to Audit, Vulnerability Assessment and Penetration Testing (VAPT), and Governance, Risk & Compliance (GRC) review, has been conducted solely on the basis of the scope, access, and documentation defined and provided by the client. RNR Consulting Private Limited is not responsible for determining or influencing the scope of the audit. Any limitations or exclusions in scope are the sole responsibility of the client, who acknowledges that such limitations may affect the depth, coverage, and overall effectiveness of the Assessment.

This report does not constitute a comprehensive security audit or guarantee the absence of vulnerabilities, misconfigurations, or risks beyond the scope defined in the engagement. The findings and recommendations are based on industry-standard methodologies and the specific systems, applications, and infrastructure presented for Assessment during the audit period. The client acknowledges that any changes to the environment after the audit period are outside the scope of this report.

The client retains full responsibility for all risks arising from its ongoing risk management, remediation, operational, and compliance activities. The implementation and effectiveness of the recommendations made in this report are subject to the client's own governance and internal processes.

This report is based entirely on information, access credentials, configurations, builds, and documentation provided by the client. RNR Consulting Private Limited shall not be liable for any inaccuracies, omissions, or conclusions that result from incomplete, falsified, outdated, or misleading evidence submitted during the engagement.

This report and any associated certificate reflect the state of the assessed systems as of the audit period only and are not valid for any time beyond that. Any future system changes, updates, or operational modifications may alter the risk posture and render the findings outdated or invalid.

RNR Consulting Private Limited, its directors, employees, and affiliates disclaim all liability for any direct, indirect, incidental, consequential, or special damages arising from the use of or reliance upon this report. This document is confidential and may not be distributed, disclosed, or relied upon by any third party without the prior written consent of RNR Consulting Private Limited. Unauthorized use is strictly prohibited.

3. Timelines

Assessment Start Date	13 th July 2026
Assessment End Date	14 th July 2026
Environment	UAT
Assessment Type	White Box

4. Scope

Project Name	Activity	Web application	Hash
CSC e-Governance Services India Ltd.	Web Application Security Testing	https://wcd.aeologic.in/login	659a1b9aa6196105d7cbcc ab759a771d9e6e1567ccb1 d966e59e1569fabab3de

5. Risk Rating

S. No	Risk Rating	Description
1	Critical	This level of vulnerabilities can allow attackers to take complete control Web applications and application servers. By exploiting these vulnerabilities attacker could carry a range of acts includes information stealing, application defacing and tricking users to do unwanted activities. The vulnerability marked as " Critical " is recommended to be handled with utmost priority.
2	High	This level of vulnerabilities indicates maximum risk associated with a vulnerability instance. Such vulnerability can allow attackers to completely compromise the Web applications and its data. Attacker can modify application in such a way that it behaves other than it is intended to do. The vulnerability marked as " High " should be mitigated at the earliest after "Critical risk" vulnerabilities are mitigated.
3	Medium	Such vulnerability may enable an attacker to exploit the application and its data to a particular level so that the attacker can gain low level information about the application. Such information can be used by an attacker to craft more specific attacks based on the information collected. The vulnerability marked with " Medium Risk " should be mitigated at the earliest after "High Risk" vulnerabilities are mitigated.
4	Low	Such vulnerability may allow an attacker to gain some information about the application which was not intended to be known otherwise. The attacker may not have exploiting techniques available at that instance based on the information revealed by the system. The vulnerability marked with " Low Risk " can be mitigated soon after high and medium risk vulnerabilities are mitigated.

6. Testing Methodology

RNR follows recommended approach to web application security testing, helping organizations ensure that their applications are secure from common vulnerabilities and attacks.

- **Preparation:** Define the scope, objectives, and rules of engagement for the testing process.
- **Information Gathering:** Collect data about the application architecture, technologies used, and potential attack vectors.
- **Vulnerability Assessment:** Identify and categorize vulnerabilities using both automated tools and manual testing techniques.
- **Exploitation:** Attempt to exploit identified vulnerabilities to assess their impact and severity.
- **Reporting:** Document findings, including vulnerabilities, risk assessments, and remediation recommendations.

Testing Categories

- **Authentication Testing:** Evaluates user authentication mechanisms, such as password strength and multi-factor authentication.
- **Session Management Testing:** Assesses how sessions are managed, including session fixation and expiration.
- **Access Control Testing:** Checks for proper implementation of authorization controls, ensuring users can only access permitted resources.
- **Input Validation Testing:** Tests how the application handles user inputs to prevent injection attacks and data corruption.
- **Error Handling Testing:** Analyses how errors are reported and handled, ensuring sensitive information is not exposed.
- **Cryptography Testing:** Evaluates the implementation of encryption and secure data storage practices.
- **Business Logic Testing:** Focuses on identifying vulnerabilities that arise from the application's business processes.

Tools & Techniques

- Burpsuite Pro v2025.10.4
- Nikto v2.5.0
- Shcheck

7. Information Gathering

Information gathering is a crucial phase in the security Assessment process, where details about the target web application and its environment are collected. This step helps identify potential vulnerabilities and understand the attack surface.

Objectives

- To collect data that aids in identifying weaknesses in the web application.
- To understand the architecture, technology stack, and dependencies of the application.
- To prepare for subsequent testing phases, such as vulnerability Assessment and penetration testing.

IP Address: 45.249.241.251

Domains: <https://wcd.aeologic.in/>

```
(kali@kali)-[~]
$ nikto -h https://wcd.aeologic.in/
- Nikto v2.6.0

+ Target IP: 45.249.241.251
+ Target Hostname: wcd.aeologic.in
+ Target Port: 443

+ SSL Info: Subject: /CN=cpmb.aeologic.in
            CN: cpmb.aeologic.in
            SAN: cpmb.aeologic.in, nsp-cg.aeologic.in, nsp-jh.aeologic.in, nsp-mota.aeologic.in, nsp-pb.aeologic.in, nsp-py.aeologic.in, nsp.a
            Ciphers: TLS_AES_256_GCM_SHA384
            Issuer: /C=US/O=Let's Encrypt/CN=YR1

+ Platform: Unknown
+ Start Time: 2026-07-14 11:34:01 (GMT5.5)

+ Server: SecureServer
```

8. Executive Summary

RNR has performed Web application security testing. The goal of this Assessment was to uncover any vulnerability in the information system that could lead to unintended access. Additionally, it aimed to evaluate the likelihood of an attacker exploiting these vulnerabilities and the potential impact on CSC e-Governance Services India Ltd., if such an exploitation were to occur.

RNR performed the Web Application Testing and prepared the report as per identified vulnerabilities. The security Assessment included a thorough vulnerability scan, penetration testing. The evaluation focused on key areas such as authentication mechanisms, data handling, and input validation.

The Assessment was conducted in accordance with the guidelines established by various standards and frameworks, including NIST, ISO/IEC, Cyber Security Audit Baseline Requirements, the Open-Source Security Testing Methodology Manual (OSSTMM), and the OWASP Web Security Testing Guide. Additionally, all tests and actions are executed under control conditions.


RNR got the access to the **Web** and Completed the Assessment on **13th July 2026, to 14th July 2026**. The identified vulnerabilities are further tested for possible exploits in a controlled environment and manner which is not intrusive.

This report provides the detailed Assessment of the given scope and identified vulnerabilities are outlined below with their risk severity and impact.

9. Assessment Overview

S. No	Application Name	Assessment URL	Critical	High	Medium	Low	Total
1	Women & Child Development, Chhattisgarh	https://wcd.aeologic.in/login	0	2	1	3	6

Vulnerability Summary




■ Critical ■ High ■ Medium ■ Low


10. Vulnerability Details

S. No	Vulnerability Name	Severity
1	Vulnerable and Outdated Components	High
2	Insecure Communication	High
3	Insufficient Input Validation	Medium
4	Unnecessary Port Open	Low
5	Server Information Disclosure	Low
6	OPTIONS Method Enabled	Low

CONFIDENTIAL

1. Vulnerable and Outdated Components


Vulnerability	Vulnerable and Outdated Components
Severity	High
Affected URL	https://wcd.aeologic.in/login
Description	The use of third-party libraries, frameworks, or software dependencies with known security flaws or abandoned maintenance.
Impact	Introduces severe risks—including data breaches, system takeovers, and remote code execution (RCE)
Assessment POC	 The screenshots illustrate the use of Retine.js for assessing the security of the application. The tool identifies several vulnerabilities, including: Prototype Pollution: The mergeConfig function in aeos creates a TypeError when processing configuration objects containing 'proto' as an own property. Session Token Bypass: Aeos does not correctly normalize hostnames when checking NO_PROXY rules, causing requests to bypass session token requirements. Request Smuggling: Aeos is vulnerable to being used as a gadget in a prototype pollution attack when Object.prototype is polluted with a CRLF-containing header value. Request Smuggling: Aeos merges the polluted properties into request headers without verification, allowing HTTP request smuggling attacks. Request Smuggling: Aeos does not enforce maxBodyLength for stream request bodies when manglefields is set to 0. Request Smuggling: The transformData helper in Aeos recursively walks nested objects without a depth limit or traversal protection. Request Smuggling: Aeos is vulnerable to a prototype pollution gadget that allows header injection in the Headers HTTP adapter. Request Smuggling: The fix for the NO_PROXY hostname normalization bypass (GSA-3688-r08-qg0) is incomplete. Request Smuggling: Aeos has multiple prototype pollution gadgets where config properties are read without mechanism guards.

	 The screenshot shows a web application interface with a banner for 'Woman & Child Development, Chhattisgarh'. Overlaid on the right side is a Retire.js vulnerability report. The report lists several vulnerabilities, including: - Aoos has multiple prototype pollution gadgets where core properties are read without hasOwnProperty guards. - The Aoos 1.5.0 patch for NO_PROXY hostname normalization is incomplete. - Aoos does not enforce maxLength when responseType is set to 'stream'. - Aoos is vulnerable to a prototype pollution gadget via the validateStatus config property.
Recommendation	Secure your applications by maintaining a complete Software Bill of Materials (SBOM) and using Software Composition Analysis (SCA) tools to flag hidden dependencies. Implement automated patching, continuously monitor CVE databases, and use Web Application Firewalls (WAFs) as virtual patches for legacy software.

2. Insecure Communication

Vulnerability	Insecure Communication
Severity	High
Affected URL	http://wcd.aeologic.in/login
Description	The application uses insecure communication, allowing data to be transmitted without adequate encryption or protection.
Impact	Sensitive information may be intercepted, modified, or disclosed through man-in-the-middle (MITM) attacks.
Assessment POC	The screenshot shows a terminal window with Nmap scan results for the host wcd.aeologic.in. The output indicates several open services: - PORT STATE SERVICE VERSION 22/tcp open ssh OpenSSH 8.2p1 Ubuntu Aubuntu0.13 (Ubuntu Linux; protocol 2.0) 80/tcp open http SecureServer 443/tcp open ssl/https SecureServer 1720/tcp open h323q9317 7000/tcp open cisco-sccp 5060/tcp open sip? The scan also notes that 2 services were unrecognized despite returning data. The fingerprinting section provides detailed information about the detected services, including their versions and configurations.
Recommendation	Enforce HTTPS using TLS 1.2/1.3, disable insecure protocols, and ensure all sensitive data is transmitted over encrypted channels.

3. Insufficient Input Validation


Vulnerability	Insufficient Input Validation
Severity	Medium
Affected URL	https://wcd.aeologic.in/public/dashboard
Description	When an application processes untrusted user data without properly verifying its format, length, type, or safety constraints.
Impact	It allows malicious or malformed data to bypass security checks, leading to severe consequences like arbitrary code execution, data breaches, and SQL/Command injections. It causes application crashes and data corruption by processing unexpected formats.
Assessment POC	
Recommendation	- Enforce strict, server-side validation using an allowlist (whitelisting) approach. - Always validate that the data type, length, and format match expected rules on the backend, and never rely solely on client-side controls.

Vulnerability	Unnecessary Port Open
Severity	Low
Affected URL	https://wcd.aeologic.in
Description	The server exposes multiple network ports, including services that may not be required for the web application's intended functionality. Unnecessary open ports increase the attack surface and provide attackers with additional opportunities for service enumeration and exploitation.
Impact	An attacker can identify and target exposed services, potentially exploiting vulnerabilities, performing brute-force attacks, or gaining unauthorized access if the services are outdated or misconfigured.
Assessment POC	<pre>[kali@kali]:~\$ - \$ nmap -SV -o- wcd.aeologic.in Starting Nmap 7.90 (https://nmap.org) at 2026-07-16 11:04 +0530 Nmap scan report for wcd.aeologic.in (45.249.241.251) Host is up (0.00027s latency). Not shown: 65529 filtered tcp ports (no-response) PORT STATE SERVICE VERSION 22/tcp open ssh OpenSSH 8.2p1 Ubuntu 4ubuntu0.13 (Ubuntu Linux; protocol 2.0) 80/tcp open http SecureServer 443/tcp open ssl/http SecureServer 1720/tcp open h32q337 2000/tcp open cisco-scp 5060/tcp open sip # Services unrecognized despite returning data. If you know the service/version, please submit the following fingerprints at https://nmap.org/cgi-bin/submit.cgi?new-service : next SERVICE FINGERPRINT (SUBMIT INDIVIDUALLY): SF-Port80-TCP:V=7.99K1-P=7/1A8Tlme=6A55C6dnp-x86_64-pc-Linux-gnu&r(GetR SF-request,ICB,"HTTP/1.1,x20381x20Movedv20Permanentlyr,vDate:x20Tue,x2 SF-2014x20Julx202026x2005:47:12x20GMTv,rnConnect:v20SecureServerv,rlo SF-cation:x20https://boacw.aeologic.in/v/r/nContent-Length:x20233/v,nCon SF-nnection:v20Closev,rnContent-Type:v20text/html,v20Charset-iso-8859-1, SF-rnIn/v,nIDCTv,rnV20HTMLv20Accept:v20*/x20/*x20//IEFF/DTDv20HTMLv20X/8/E SF-IN"/>nhtml</head>nhtml<title>301x20Movedv20Permanently/</title>n/vn/head/ SF-body>nhtml1 Movedv20Permanently/v/h3AnpTheV20documentV20hasV20mov SF-edv20to:v20href=https://boacw.aeologic.in/v/sherecv20a-v20p/vn/body SF-v=<html>n"/>r(HTTPOptions,ICB,"HTTP/1.1,x20381x20Movedv20Permanenl SF-y/r,vDate:x20Tue,x2014x20Julx202026x2005:47:12x20GMTv,rnServer:x2 SF-20SecureServerv,rnLocation1v20https://boacw.aeologic.in/v/nContent-1 SF-length:x20233/v,nConnection:v20closev,rnContent-Type:v20text/html;x2 SF-RcharSet-iso-8859-1/v,nVn-IDCTv,rnV20HTMLv20Accept:v20*/x20/*x20//IEFF/D SF-Dv20HTMLv20X/8/E/v20"/>nhtml<head>nhtml<title>301x20Movedv20Permanen SF-tty/<title>n/vn/head>body>nhtml1 Movedv20Permanently/v/h3AnpTheV20do SF-contentV20hasV20Movedv20toV20href=https://boacw.aeologic.in/v/shere SF-reqv20a-v20p/vn/body>v20/vn/n"/>r(RTSPRequest,18E,"HTTP/1.1,x20400/x2 SF-0Badv20Requestv,r,vDate:x20Tue,x2014x20Julx202026x2005:47:12x20GMT SF-1/vnServerv20SecureServerv,rnContent-Length:x20220v,rnConnectionV2 SF-20closev,rnContent-Type:v20text/html;x20Charset-iso-8859-1/v,rnVnID</pre>
Recommendation	Close or disable all unnecessary services and restrict access to required management ports using firewall rules or IP allowlists. Ensure only essential ports are publicly accessible and regularly review exposed services as part of security hardening.

5. Server Information Disclosure

Vulnerability	Server Information Disclosure
Severity	Low
Affected URL	https://wcd.aeologic.in
Description	Server responses leak version or framework info.
Impact	Easier exploit targeting with known CVEs.
Assessment POC	
Recommendation	Hide server banners, remove version headers, patch regularly.

6. OPTIONS Method Enabled

Vulnerability	OPTIONS Method Enabled
Severity	Low
Affected URL	https://wcd.aeologic.in
Description	The HTTP OPTIONS method is enabled, allowing clients to identify the HTTP methods supported by the server, which may expose unnecessary information.
Impact	Attackers can use this information for reconnaissance and identify potentially risky HTTP methods if they are enabled.
Assessment POC	
Recommendation	Disable the OPTIONS method if not required and allow only the necessary HTTP methods (e.g., GET and POST) through proper server configuration.

11. Risk Evaluation and Conclusion

RNR conducted the Assessment and identified **0 Critical, 2 High, 1 Medium and 3 Low vulnerabilities**. The organisation intact the process to get the assets security posture assessed on a regular basis to identify any risk in proactive manner to avoid any risk exposure, which can lead to system compromise. This Assessment is limited to the provided scope and Assessment duration.

Basis on the Assessment and identification of the vulnerability and their severity the current risk exposure is **High**.

12. Recommendation

Considering the findings identified during the Assessment this is recommended that organisation must deploy the fixes on immediate basis. Further limit the access to the assets and provide only as per the organisation access control policy and need to know basis.

This is also recommended that organisation should follow the best practice like, secure coding principles, secure design to mitigate the risk.

13. Annexure

CERT-IN Guidelines for Secure Application Design Development Implementation Operations checklist vetted by client.



CERT-IN Guidelines
for Secure Application

Thank you

info@consultrnr.com

<https://consultrnr.com/>

[+91 7678252326](tel:+917678252326)