

Stateful vs. Stateless Architecture



ASHISH PRATAP SINGH

FEB 11, 2025



166



4



5

When a client interacts with a server, there are two ways to handle it:

- **Stateless:** The client includes all necessary data in each request, so the doesn't store any prior information.
- **Stateful:** The server retains some data from previous requests, making : interactions dependent on past state.

In software systems, **state** refers to any data that persists across requests user sessions, shopping carts, or authentication details.

The choice between stateless and stateful architecture can affect scalability performance, complexity, and cost.

In this article, we'll break down both the approaches, their advantages and and when to use each—with real-world examples.

If you're enjoying this newsletter and want to get even more value, consider a [paid subscriber](#).


As a paid subscriber, you'll unlock all **premium** articles and gain full access [premium courses](#) on [algomaster.io](#).

1. Stateful Architecture

In a **stateful architecture**, the system remembers client or process data (state) across multiple requests.

Once a client connects, the server holds on to certain details—like user preferences, shopping cart contents, or authentication sessions—so the client doesn't need to resend everything with each request.

Stateful systems typically store the state data in a database or in-memory storage.




Example: During online shopping, when you add items to your cart, the system remembers your selections. If you navigate away to browse more items and then return to your cart, your items are still there, waiting for you to check out.

Common Patterns in Stateful Architecture

1. Sticky Sessions

If you use **in-memory** session storage (i.e., each app server keeps its own sessions locally), you can configure your load balancer for “sticky sessions.”




This means: Once a client is assigned to **Server A**, all subsequent requests from that client are routed to **Server A**.

Trade-Off: If Server A fails, the user’s session data is lost or the user is forced to log in again.

log in. Sticky sessions are also less flexible when scaling because you can't seamlessly redistribute user traffic to other servers.

2. Centralized Session Store

A more robust approach is to store session data in a **centralized or distributed** (e.g., Redis).



This allows:

- **Shared access:** All servers can access and update session data for any user.

server can handle any request, because the session data is not tied to a specific server's memory.

Trade-Off: You introduce network overhead and rely on an external storage. If centralized storage fails, you lose session data unless you have a fallback.

Advantages:

- **Personalized Experiences:** Stateful systems can deliver highly tailored interactions, as they remember user preferences and past actions.
- **Contextual Continuity:** Users can seamlessly resume activities where they left off, even if they disconnect and reconnect.
- **Reduced Round Trips:** Certain operations can be faster because the server possesses necessary data.

Challenges:

- **Scalability:** Maintaining state for a large number of users can become resource-intensive and complex, as each server needs to keep track of specific session data.
- **Complexity:** Managing and synchronizing state across multiple servers introduces additional challenges.
- **Failure Points:** If a server holding a user's state fails, their session data is lost.

Example Use Cases


- **E-commerce Shopping Carts** – Stores cart contents and user preferences across multiple interactions, even if the user navigates away and returns.
- **Video Streaming Services (Netflix, YouTube)** – Remembers user watch history, recommendations, and session data for a seamless experience.

- **Messaging Apps (WhatsApp, Slack)** – Maintains active user sessions and history for real-time communication.
-

2. Stateless Architecture

In a **stateless** architecture, the server does **not** preserve client-specific data between individual requests.

- Each request is treated as **independent**, with no memory of previous interactions.
- Every request must include **all necessary information** for processing.
- Once the server responds, it **discards any temporary data** used for that request.



Example: Most **RESTful APIs** follow a stateless design. For instance, when you request weather data from a public API, you must provide all required details (like location) in each request. The server processes it, sends a response, and forgets the request after the interaction.

Common Patterns in Stateless Architecture

1. Token-Based Authentication (JWT)

A very popular way to implement statelessness is through tokens, particularly JSON Web Tokens (JWTs):

1. **Client Authenticates Once:** The user logs in using credentials (username/password) for the first time, and the server issues a signed JWT.
2. **Subsequent Requests:** The client includes JWT token in each request (e.g., `Authorization: Bearer <token>` header).
3. **Validation:** The server validates the token's signature and any embedded claims (e.g., user ID, expiry time).
4. **No Server-Side Storage:** The server does **not** need to store session data; it only verifies the token on each request.

Many APIs, including OAuth-based authentication systems, use JWTs to implement stateless, scalable authentication.

2. Idempotent APIs

Stateless architectures benefit from **idempotent operations**, ensuring that multiple requests produce the same result. This prevents inconsistencies due to network issues or client errors.

Example: A `PUT /users/123` request with the same payload **always** updates the user's data but doesn't create duplicates.

Idempotent APIs ensure consistency and reliability, especially in distributed systems where requests might be retried automatically.

Advantages:

- **Scalability:** Stateless systems are inherently easier to scale horizontally.

servers can be added effortlessly, as they don't need to maintain any sessions.

- **Simplicity:** Since servers don't track state, the architecture is generally simpler and easier to manage.
- **Resilience:** The failure of a single server won't disrupt user sessions, as they are not tied to specific servers.
- **Lower Memory Footprint:** With no session data stored on the server, you save memory that would otherwise be reserved for session management.
- **Easier to Cache Responses:** Since requests are self-contained, caching (e.g., CDNs) can more easily store and serve responses.

Challenges:

- **Less Context:** Stateless systems can't provide the same level of personalization or context awareness as stateful systems without additional effort (like using cookies or tokens).
- **Client-Side Complexity:** The client must keep track of the authentication tokens and relevant data. If it loses the token, it must re-authenticate.
- **Large Payloads:** Every request needs to carry all the required information, potentially leading to larger payloads.

Example Use Cases

1. **Microservices Architecture:** Each service handles requests independently, relying on external databases or caches instead of maintaining session data.
2. **Public APIs (REST, GraphQL):** Clients send tokens with each request, eliminating the need for server-side sessions.
3. **Mobile Apps:** Tokens are securely stored on the device and sent with each request to authenticate users.

4. **CDN & Caching Layers:** Stateless endpoints make caching easier since they depend only on request parameters, not stored session data. A CDN can serve repeated requests, improving performance and reducing backend
-

Choosing the Right Approach

There's no one-size-fits-all answer when choosing between stateful and stateless architectures.

The best choice depends on your application's needs, scalability goals, and user experience expectations.

When to Choose Stateful Architecture

Stateful systems are ideal when user context and continuity are critical.

Consider a stateful approach if your application:

- Requires personalization (e.g., user preferences, session history)
- Needs real-time interactions (e.g., chat applications, multiplayer games)
- Manages multi-step workflows (e.g., online banking transactions, checkout processes)
- Must retain authentication sessions for security and convenience

Example: A shopping cart in an e-commerce app should persist, so users can return to re-add items after refreshing the page.

When to Choose Stateless Architecture

Stateless systems work best when scalability, simplicity, and resilience are priorities.

Use a stateless approach if your application:

- Handles a high volume of requests and needs to scale efficiently
- Doesn't require storing client-specific data between requests
- Needs fast, distributed processing without server dependencies
- Must ensure reliability and failover readiness

Example: A weather API doesn't need to remember previous requests. Each request includes the location, and the response is processed independently.

Hybrid Approaches: The Best of Both Worlds


Many modern applications **blend** stateful and stateless components for flexibility.

This hybrid approach allows:

- Stateless APIs for core functionality, ensuring high scalability
- Stateful sessions for personalization, improving user experience
- External session stores (e.g., Redis) to manage state while keeping applications stateless

Example: A video streaming platform (e.g., Netflix) uses a stateless backend for video streaming but retains stateful user sessions to track watch history and recommendations.

Thank you for reading!

If you found it valuable, hit a like  and consider subscribing for more success tips every week.

If you have any questions or suggestions, leave a comment.

This post is public so feel free to share it.

P.S. If you're enjoying this newsletter and want to get even more value, consider becoming a [paid subscriber](#).

As a paid subscriber, you'll unlock all **premium** articles and gain full access to [premium courses](#) on [algomaster.io](#).

There are [group discounts](#), [gift options](#), and [referral bonuses](#) available.

Checkout my [Youtube channel](#) for more in-depth content.

Follow me on [LinkedIn](#) and [X](#) to stay updated.

Checkout my [GitHub repositories](#) for free interview preparation resources.

I hope you have a lovely day!

See you soon,

Ashish



166 Likes • 5 Restacks

← Previous

Discussion about this post

Comments

Restacks



Write a comment...



Simon Chan 20 Mar

♥ Liked by Ashish Pratap Singh

Hi Ashish, your article is definitely clear and straightforward. very useful, Appreciate

♥ LIKE (1) 💬 REPLY



Venkat Sure 5 Aug

Thanks

♥ LIKE 💬 REPLY

2 more comments...