

# Triple sum ☆

Your Triple sum submission got 40.00 points.

Share

Tweet



[Try the next challenge](#)

## Problem

## Submissions

## Leaderboard

## Editorial

Given **3** arrays ***a***, ***b***, ***c*** of different sizes, find the number of distinct triplets ***(p, q, r)*** where ***p*** is an element of ***a***, written as ***p* ∈ *a***, ***q* ∈ *b***, and ***r* ∈ *c***, satisfying the criteria: ***p* ≤ *q* and *q* ≥ *r***.

For example, given ***a* = [3, 5, 7]**, ***b* = [3, 6]**, and ***c* = [4, 6, 9]**, we find four distinct triplets: **(3, 6, 4)**, **(3, 6, 6)**, **(5, 6, 4)**, **(5, 6, 6)**.

### Function Description

Complete the triplets function in the editor below. It must return the number of distinct triplets that can be formed from the given arrays.

triplets has the following parameter(s):

- *a*, *b*, *c*: three arrays of integers .

### Input Format

The first line contains **3** integers ***lena***, ***lenb***, and ***lenc***, the sizes of the three arrays.

The next **3** lines contain space-separated integers numbering ***lena***, ***lenb***, and ***lenc*** respectively.

### Constraints

$$1 \leq lena, lenb, lenc \leq 10^5$$

$$1 \leq \text{all elements in } a, b, c \leq 10^8$$

### Output Format

Print an integer representing the number of distinct triplets.

### Sample Input 0

```
3 2 3
1 3 5
2 3
1 2 3
```

### Sample Output 0

```
8
```

### Explanation 0

The special triplets are **(1, 2, 1)**, **(1, 2, 2)**, **(1, 3, 1)**, **(1, 3, 2)**, **(1, 3, 3)**, **(3, 3, 1)**, **(3, 3, 2)**, **(3, 3, 3)** .

### Sample Input 1

```
3 3 3
1 4 5
2 3 3
1 2 3
```



**Sample Output 1**

5

**Explanation 1**

The special triplets are (1, 2, 1), (1, 2, 2), (1, 3, 1), (1, 3, 2), (1, 3, 3)

**Sample Input 2**

```
4 3 4
1 3 5 7
5 7 9
7 9 11 13
```

**Sample Output 2**

12

**Explanation 2**

The special triplets are (1, 7, 7), (1, 9, 7), (1, 9, 9), (3, 7, 7), (3, 9, 7), (3, 9, 9), (5, 7, 7), (5, 9, 7), (5, 9, 9), (7, 7, 7), (7, 9, 7), (7, 9, 9).

[Change Theme](#)

C++



```
7 // Complete the triplets function below.
8 long triplets(vector<int> a, vector<int> b, vector<int> c) {
9     sort(a.begin(), a.end());
10    sort(b.begin(), b.end());
11    sort(c.begin(), c.end());
12
13    a.erase(unique(a.begin(), a.end()), a.end()); //removing duplicates
14    b.erase(unique(b.begin(), b.end()), b.end());
15    c.erase(unique(c.begin(), c.end()), c.end());
16
17    int i = 0, j = 0, k = 0;
18    long count=0;
19
20    while(i < b.size()){
21        while(a[j]<=b[i] && j<a.size()) // looping through a and checking number<= b[i]
22            j++;
23        while(c[k]<=b[i] && k<c.size()) // looping through c and checking number<= b[i]
24            k++;
25        count+= (long)j*k;
26        i++;
27    }
```

Line: 21 Col: 90

☒ Upload Code as File ☐ Test against custom input[Run Code](#)[Submit Code](#)

## Congratulations

You solved this challenge. Would you like to challenge your friends?

[Next Challenge](#)

✔ Test case 0

✔ Test case 1

✔ Test case 2

✔ Test case 3

✔ Test case 4

✔ Test case 5

✔ Test case 6

Compiler Message

Success

Input (stdin)

1323

2135

323

4123

Expected Output

18

Download

Download

