

▼ PES University, Bangalore

Established under Karnataka Act No. 16 of 2013

UE20CS312 - Data Analytics - Worksheet 5 Course instructor: Gowri Srinivasa, Professor Dept. of CSE, PES University

Designed by Yashas Kadambi, Dept. of CSE - yashasks@pesu.pes.edu

▼ Markov Chains and AB Testing

Prerequisites

- Revise the following concepts
 - Markov Chains
 - Markov Chains with Absorbing states
 - Calculation of eventual probability of absorption
 - A/B Testing
- Install the following software
 - pandas
 - numpy

Points

The problems in this worksheet are for a total of 10 points with each problem having a different weightage.

- Problem 1: 2 points
- Problem 2: 4 points
- Problem 3: 4 points

▼ Scenario 2

It's a freezing day in New York, Commissioner Wench has sent a report to Captain Holt that the 99th precinct has much lower reported crimes compared to other precincts. Upon analysis Captain Holt decides to add a feedback unit along with the 4 major units to analyse this discrepancy. All the units are mentioned below

1. Major Crimes
2. Traffic
3. General crimes

4. Feedback

5. Theft

The initial probability of a person going to a particular unit on a particular day is given as follows

Major Crimes	Traffic	General crimes	Feedback	Theft
0.3	0.4	0.1	0.15	0.05

To measure how many people will go to the feedback unit, the personnel files of all employees are give to the **Move-o-Tron 99** and it gives us the following matrix which shows us the probability of people moving from one unit to another on a particular day . It is known that the **_ Move-o-Tron 99_** alwasy outputs matices which follow a first order Markov chain.

	Major Crimes	Traffic	General crimes	Feedback	Theft
Major Crimes	0.002	0.666	0.31	0.0	0.022
Traffic	0.466	0.102	0.222	0.0	0.21
General crimes	0.022	0.11	0.502	0.0	0.366
Feedback	0.0	0.0	0.0	1.0	0.0
Theft	0.11	0.122	0.066	0.0	0.702

As the people of New York are smart the will learn where all the units are present and hence the next days (day 1) distribution will be the distribution present at the end of the current day (day 0). Captain holt want to check if the matrix given by the **Move-o-Tron** can be used to model the footfall.

Problem 1 (2 points)

1. What technique can be used to model the probability of people going to the correct unit to report thier crime after N days? (0 points)
2. Is the chain irreducible? Justify (0.5 point)
3. What will be the intital probability of a person going to a particular unit after 1 day, 2 days, 10 days, 1000 days and 1001 days. (1 point)

Hint: Use the Chapman–Kolmogorov relationship

```
# C = A.B
matrix_C = np.dot(matrix_A, matrix_B)

# C = A.(B^4) can be replaced by
matrix_C = matrix_A
for _ in range(4):
    matrix_C = np.dot(matrix_C, matrix_B)
```

4. What can you say about the markov chain from state of intital probability of a person going to a particular unit after 1000 and 1001 days? (0.5 points)

```
# Importing Librarire
%matplotlib inline
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# encoding the probabilities as a numpy array
trans_array = np.array([
    [0.002, 0.666, 0.31, 0, 0.022],
    [0.466, 0.102, 0.222, 0, 0.21],
    [0.022, 0.11, 0.502, 0, 0.366],
    [0, 0, 0, 1, 0],
    [0.11, 0.122, 0.066, 0, 0.702]
])

# ensures that the probabilities sum to 1
assert(trans_array[0].sum() == 1.0)
assert(trans_array[1].sum() == 1.0)
assert(trans_array[2].sum() == 1.0)
assert(trans_array[3].sum() == 1.0)
assert(trans_array[4].sum() == 1.0)

# encoding the initial probability of as a numpy array
state = np.array([[0.3, 0.4, 0.1, 0.15, 0.05]])
assert(state[0].sum() == 1.0)
```

After analysing the model Captain holt calls the squad and educates them to ask people to give feedbacks. And the details of the squad are given to the **Move-o-Tron 99**. After reanalysing the report the **Move-o-Tron 99** gave out a new Matrix, which is shown below

	Major Crimes	Traffic	General crimes	Feedback	Theft
Major Crimes	0.002	0.666	0.01	0.02	0.302
Traffic	0.466	0.102	0.02	0.032	0.38
General crimes	0.0	0.0	1.0	0.0	0.0
Feedback	0.0	0.0	0.0	1.0	0.0
Theft	0.11	0.122	0.066	0.004	0.698

Considering the new report the model has to be re-evaluated. The initial probability of a person going to a particular unit on a particular day remains the same.

Problem 2 (4 points)

1. Is the chain irreducible? Justify (0.5 point)
2. What will be the initial probability of a person going to a particular unit after 1 day, 2 days, 10 days, 1000 days and 1001 days. (1 point)

Hint: Use the Chapman–Kolmogorov relationship
3. What can you say about the Markov chain from state of initial probability of a person going to a particular unit after 1000 and 1001 days? (0.5 points)
4. Summer Edgecombe is Confidential Informant (CI) to the Officer Kimbal Cho and comes in every day to the police station. If on the first day she goes to the Major crimes Unit what will be the probability that she gives a feedback? (2 points)

```
# np.delete()
# https://note.nkml.me/en/python-numpy-delete/#:~:text=Using%20the%20NumPy%20function%20np,f

print(a)
# [[ 0  1  2  3]
#   [ 4  5  6  7]
#   [ 8  9 10 11]]

print(np.delete(a, 1, 0))
# [[ 0  1  2  3]
#   [ 8  9 10 11]]

print(np.delete(a, 1, 1))
# [[ 0  2  3]
#   [ 4  6  7]
#   [ 8 10 11]]

# Deleting multiple rows or columns
print(np.delete(a, [0, 3], 1))
# [[ 1  2]
#   [ 5  6]
#   [ 9 10]]

# Deleting rows and columns
print(np.delete(np.delete(a, 1, 0), 1, 1))
# [[ 0  2  3]
#   [ 8 10 11]]
```

```
# encoding the probabilities as a numpy array
trans_array = np.array([
    [0.002, 0.666, 0.01, 0.020, 0.302],
    [0.466, 0.102, 0.02, 0.032, 0.38],
    [0.0, 0.0, 1, 0.0, 0.0],
    [0, 0, 0, 1, 0],
    [0.11, 0.122, 0.066, 0.004, 0.698]
])

# ensures that the probabilities sum to 1
assert(trans_array[0].sum() == 1.0)
assert(trans_array[1].sum() == 1.0)
assert(trans_array[2].sum() == 1.0)
assert(trans_array[3].sum() == 1.0)
assert(trans_array[4].sum() == 1.0)

# encoding the initial probability of as a numpy array
state = np.array([[0.3, 0.4, 0.1, 0.15, 0.05]])
assert(state[0].sum() == 1.0)
```



##Problem 3 (4 points)

It seems that there is a bug in `**_Move-o-Tron 99_*` and feedback units as absorbing states. After updating `**_Move-o-Tron 99_*`, Captain Holt wants to find out the effect that Amy Santiago has on the probability of a person giving feedback. This includes the probability of a person giving feedback, including Santiago and the other one without.

Matrix 1 (With Santiago)

	Major Crimes	Traffic	General crimes	Feedback	Theft
Major Crimes	0.002	0.232	0.31	0.434	0.022
Traffic	0.426	0.102	0.222	0.04	0.21
General crimes	0.03	0.11	0.2	0.294	0.366
Feedback	0.003	0.176	0.321	0.3	0.2
Theft	0.11	0.422	0.166	0.1	0.202

Matrix 2 (Without Santiago)

	Major Crimes	Traffic	General crimes	Feedback	Theft
Major Crimes	0.11	0.222	0.092	0.374	0.202
Traffic	0.03	0.11	0.2	0.294	0.366
General crimes	0.002	0.232	0.31	0.434	0.022
Feedback	0.466	0.102	0.02	0.032	0.38
Theft	0.003	0.176	0.321	0.3	0.2

1. How can you find out the effect that Santiago has on the probability of a person giving feedback? (1 point)

Problem 3 (4 points)

It seems that there is a bug in **Move-o-Tron 99** which makes general crimes and feedback units as absorbing states. After updating the software of **Move-o-Tron 99**, Captain Holt wants to find out the effect that Amy Santiago has on the probability of a person giving feedback. So one matrix is generated including Santiago and the other one without.

Matrix 1 (With Santiago)

	Major Crimes	Traffic	General crimes	Feedback
Major Crimes	0.002	0.232	0.31	0.434
Traffic	0.426	0.102	0.222	0.04
General crimes	0.03	0.11	0.2	0.294
Feedback	0.003	0.176	0.321	0.3
Theft	0.11	0.422	0.166	0.1

Matrix 2 (Without Santiago)

	Major Crimes	Traffic	General crimes	Feedback
Major Crimes	0.11	0.222	0.092	0.374
Traffic	0.03	0.11	0.2	0.294
General crimes	0.002	0.232	0.31	0.434
Feedback	0.466	0.102	0.02	0.032

Feedback: (1 point)

2. What effect does Santiago have on the probability of getting feedback? (1 point)

Note: The initial probability of a person going to a particular unit on a particular day remains the same

3. Name the test Captain Holt is performing. (0.5 points)

Lina Ginetti reports to Captain Holt that there are two kinds of days in the precinct: "There are normal days and then there are days where workflow is dismal with a tiny dash of pathetic." Captain Holt decided to sample the initial probability of a person going to a particular unit on a good day and a bad day.

4. Without the information about these initial probabilities, can you tell if there is any difference in the probability of getting feedback? Explain. (1.5 points)

	Major Crimes	Traffic	General crimes	Feedback
Theft	0.003	0.176	0.321	0.3

1. How can you find out the effect that Santiago has on the probability of feedback? (1 point)

2. What effect does Santiago have on the probability of getting feedback? (1 point)

Note: The initial probability of a person going to a particular unit on a particular day remains the same

3. Name the test Captain Holt is performing. (0.5 points)

Lina Ginetti reports to Captain Holt that there are two kinds of days in the precinct: "There are normal days and then there are days where workflow is dismal with a tiny dash of pathetic." Captain Holt decided to sample the initial probability of a person going to a particular unit on a good day and a bad day.

4. Without the information about these initial probabilities, can you tell if there is any difference in the probability of getting a feedback? Explain. (1.5 points)

```
# encoding the probabilities as a numpy array
```

```
# With Santiago
```

```
trans_array_with_amy = np.array([
    [0.002, 0.232, 0.31, 0.434, 0.022],
    [0.426, 0.102, 0.222, 0.04, 0.21],
    [0.03, 0.11, 0.20, 0.294, 0.366],
    [0.003, 0.176, 0.321, 0.3, 0.2],
    [0.11, 0.422, 0.166, 0.1, 0.202]
])
```

```
# Without Santiago
```

```
trans_array_without_amy = np.array([
    [0.11, 0.222, 0.092, 0.374, 0.202],
    [0.03, 0.11, 0.20, 0.294, 0.366],
    [0.002, 0.232, 0.31, 0.434, 0.022],
    [0.466, 0.102, 0.02, 0.032, 0.38],
    [0.003, 0.176, 0.321, 0.3, 0.2]
])
```

```
# ensures that the probabilities sum to 1
```

```
assert(trans_array_with_amy[0].sum() == 1.0)
assert(trans_array_with_amy[1].sum() == 1.0)
assert(trans_array_with_amy[2].sum() == 1.0)
assert(trans_array_with_amy[3].sum() == 1.0)
assert(trans_array_with_amy[4].sum() == 1.0)

assert(trans_array_without_amy[0].sum() == 1.0)
assert(trans_array_without_amy[1].sum() == 1.0)
assert(trans_array_without_amy[2].sum() == 1.0)
assert(trans_array_without_amy[3].sum() == 1.0)
assert(trans_array_without_amy[4].sum() == 1.0)

# encoding the initial probability of as a numpy array
state = np.array([[0.3, 0.4, 0.1, 0.15, 0.05]])
assert(state[0].sum() == 1.0)
```

[Colab paid products](#) - [Cancel contracts here](#)

