

Презентация по лабораторной работе №4

Архитектура Компьютеров и Операционные Системы

Джаллох Ишмаил

06 марта 2025

Российский университет дружбы народов, Москва, Россия

Информация

- Джаллох Ишмаил
- Студентк НКА-05-24
- Факультет Физико-математический и естественный наук
- Российский университет дружбы народов
- 1032239614pfur.ru
- <https://lsho-jah.github.io/ru/>

Цель работы

Цель данной работы является получением навыков правильной работы с репозиториями git.

Выполнение лабораторной работы

Gitflow Workflow предполагает выстраивание строгой модели ветвления с учётом выпуска проекта. Сначала я включаю репозиторий copr:

```
ijalloh@ijalloh:~$ sudo dnf copr enable elegos/gitflow
[sudo] password for ijalloh:
https://copr.fedorainfracloud.org/api 100% | 206.0 B/s | 652.0 B | 00m03s
Enabling a Copr repository. Please note that this repository is not part
```

Рис. 1: включение copr

Используя dnf install скачаю gitflow:

```
ijalloh@ijalloh:~$ sudo dnf install gitflow
Updating and loading repositories:
Fedora 41 - x86_64 - Updates      100% | 7.3 KiB/s | 25.9 KiB | 00m04s
Fedora 41 - x86_64 - Updates      100% | 112.9 KiB/s | 2.6 MiB | 00m24s
```

Рис. 2: dnf install gitflow

Для семантического версионирования и общепринятых коммитов я устанавливаю Nodejs и npm:

```
ijalloh@ijalloh:~$ sudo dnf install nodejs
Updating and loading repositories:
Repositories loaded.
```

Рис. 3: Установка Nodejs

```
ijalloh@ijalloh:~$ sudo dnf install pnpm  
Updating and loading repositories:  
Repositories loaded
```


Рис. 4: Установка pnpm

Запуская `pnpm setup` я добавляю каталог с исполняемыми файлами, устанавливаемыми `yarn` для работы с Node.js в переменную `PATH`:

```
complete:
ijalloh@ijalloh:~$ pnpm setup
Appended new lines to /home/ijalloh/.bashrc
```

Рис. 5: Запуск `pnpm`

Далее перелогинюсь и выполняю `source ~/.bashrc`:

A terminal window with a dark background. The first line shows a message: "To start using pnpm, run:". The second line shows the command "source /home/ijalloh/.bashrc" being entered. The third line shows the prompt "ijalloh@ijalloh:~\$" followed by the command "sourcr /home/ijalloh/.bashrc" (note the typo 'sourcr' instead of 'source') and a cursor at the end.

```
To start using pnpm, run:
source /home/ijalloh/.bashrc
ijalloh@ijalloh:~$ sourcr /home/ijalloh/.bashrc
```

Рис. 6: `~/.bashrc`

Для помощи в форматировании коммитов добавляю программу commitizen:



```
ijalloh@ijalloh:~$ pnpm add -g commitizen
```

Рис. 7: добавление commitizen

Добавляю standard-changelog для помощи в создании логов:

```
ijalloheijalloh:~$ pnpm add -g standard-changelog
WARN 2 deprecated subdependencies found: glob@7.2.3, inflight@1.0.6
Packages: +39
+++++
Progress: resolved 190, reused 151, downloaded 39, added 39, done
```

Рис. 8: добавление standard-changelog

Создаю репозиторий на GitHub назову его git-extended:

Create a new repository

A repository contains all project files, including the revision history. Already have a project repository elsewhere? [Import a repository.](#)


Required fields are marked with an asterisk ().*

Repository template

No template ▾

Start your repository with a template repository's contents.

Owner * **Repository name ***

 Isho-Jah ▾ / git-extended

✔ git-extended is available.

Great repository names are short and memorable. Need inspiration? How about [bug-free-waddle](#) ?

Рис. 9: Создание git-extended

Делаю первый коммит и выкладываю на github:

```
ijalloh@ijalloh:~/git-extended$ git commit -m "first commit"
[main (root-commit) ff6bc7a] first commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 README.md
ijalloh@ijalloh:~/git-extended$ git remote add origin git@github.com:Isho-Jah/g
it-extended.git
error: remote origin already exists.
ijalloh@ijalloh:~/git-extended$ git remote -v
origin  https://github.com/Isho-Jah/git-extended.git (fetch)
origin  https://github.com/Isho-Jah/git-extended.git (push)
ijalloh@ijalloh:~/git-extended$ git push -u origin master
```

Рис. 10: Первый коммит


Я инициализирую npmt:

```
ijalloh@ijalloh:~/git-extended$ npnm init
Wrote to /home/ijalloh/git-extended/package.json

{
  "name": "git-extended",
  "version": "1.0.0",
  "description": "",
  "main": "index.js",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "keywords": [],
  "author": "",
  "license": "ISC"
}
ijalloh@ijalloh:~/git-extended$
```

Рис. 11: Инициализирование npmt

Заполняю несколько параметров пакета (файл package.json):



```
package.json  [--M-] 3 L: [ 1+12 13/ 15] *(349 / 356b) 0032 0x020 [*][X]
{
  "name": "git-extended",
  "version": "1.0.0",
  "description": "Git repo for educational purposes",
  "main": "index.js",
  "repository": "git@github.com:Isho-Jah/git-extended.git",
  "author": "Isho-Jah <isjalloh6040@gmail.com>",
  "license": "CC-BY-4.0",
  "config": {
    "commitizen": {
      "path": "cz-conventional-changelog"
    }
  }
}
```

Рис. 12: Заполнение пакетов

Добавляю новые файлы и выполняю коммит (указываю тип коммит (feat)) и отправляю на ГИТ:

```
ijalloh@ijalloh:~/git-extended$ git add .  
ijalloh@ijalloh:~/git-extended$ git cz  
cz-cli@4.3.1, cz-conventional-changelog@3.3.0  
  
? Select the type of change that you're committing: feat:      A new feature
```

Рис. 13: Добавление новых файлов

Инициализирую git-flow и указываю ветки:

```
ijalloh@ijalloh:~/git-extended$ git flow init
Already initialized for gitflow.
To force reinitialization, use: git flow init -f
ijalloh@ijalloh:~/git-extended$ git flow init -f


Which branch should be used for bringing forth production releases?
  - develop
  - master
Branch name for production releases: [master] master

Which branch should be used for integration of the "next release"?
  - develop
Branch name for "next release" development: [develop] develop

How to name your supporting branch prefixes?
Feature branches? [feature/] feature/
Bugfix branches? [bugfix/] bugfix/
Release branches? [release/] release/
Hotfix branches? [hotfix/] hotfix/
Support branches? [support/] support/
Version tag prefix? []
Hooks and filters directory? [/home/ijalloh/git-extended/.git/hooks]
```

Рис. 14: Инициализирование git-flow

Проверяю что я на ветке develop с помощью git branch:

A terminal window with a dark background and light green text. The prompt is 'ijalloh@ijalloh:~/git-extended\$'. The command 'git branch' has been executed, and the output shows two branches: '* develop' and 'master'. The asterisk indicates the current branch.

```
ijalloh@ijalloh:~/git-extended$ git branch
* develop
master
```

Рис. 15: Проверка ветки

Загружаю весь репозиторий в хранилище с помощью `git push --all`:

```
ijalloh@ijalloh:~/git-extended$ git push --all
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create a pull request for 'develop' on GitHub by visiting:
remote:   https://github.com/Isho-Jah/git-extended/pull/new/develop
remote:
To github.com:Isho-Jah/git-extended.git
 * [new branch]      develop -> develop
```

Рис. 16: Загрузка репозиторий

Устанавливаю внешнюю ветку как вышестоящую для этой ветки (develop):

```
ijalloh@ijalloh:~/git-extended$ git branch --set-upstream-to=origin/develop develop  
branch 'develop' set up to track 'origin/develop'.
```

Рис. 17: установка внешней ветки

Создаю релиз с версией 1.0.0 и журнал изменений (standard-changelog)::

```
ijalloh@ijalloh:~/git-extended$ git flow release start 1.0.0
Switched to a new branch 'release/1.0.0'

Summary of actions:
- A new branch 'release/1.0.0' was created, based on 'develop'
- You are now on branch 'release/1.0.0'

Follow-up actions:
- Bump the version number now!
- Start committing last-minute fixes in preparing your release
- When done, run:

    git flow release finish '1.0.0'

ijalloh@ijalloh:~/git-extended$ standard-changelog --first-release
✓ created CHANGELOG.md
✓ output changes to CHANGELOG.md
```

Рис. 18: Создание релиза

Добавляю журнал изменений в индекс:

```
ijalloh@ijalloh:~/git-extended$ git add CHANGELOG.md
ijalloh@ijalloh:~/git-extended$ git commit -am 'chore(site): add changelog'
[release/1.0.0 454a830] chore(site): add changelog
1 file changed, 9 insertions(+)
create mode 100644 CHANGELOG.md
```

Рис. 19: Добавление журнала изменений

Залью релизную ветку в основную ветку:

```
ijalloh@ijalloh:~/git-extended$ git flow release finish 1.0.0
Switched to branch 'master'
Your branch is up to date with 'origin/master'.
Merge made by the 'ort' strategy.
  CHANGELOG.md | 9 ++++++++
  1 file changed, 9 insertions(+)
  create mode 100644 CHANGELOG.md
Already on 'master'
Your branch is ahead of 'origin/master' by 2 commits.
  (use "git push" to publish your local commits)
Switched to branch 'develop'
Your branch is up to date with 'origin/develop'.
Merge made by the 'ort' strategy.
  CHANGELOG.md | 9 ++++++++
  1 file changed, 9 insertions(+)
  create mode 100644 CHANGELOG.md
Deleted branch release/1.0.0 (was 454a830).

Summary of actions:
- Release branch 'release/1.0.0' has been merged into 'master'
- The release was tagged '1.0.0'
- Release tag '1.0.0' has been back-merged into 'develop'
- Release branch 'release/1.0.0' has been locally deleted
- You are now on branch 'develop'
```

Рис. 20: Замена ветки

Отправляю данные на github:

```
ijalloh@ijalloh:~/git-extended$ git push --all
Enumerating objects: 6, done.
Counting objects: 100% (6/6), done.
Delta compression using up to 4 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (5/5), 2.80 KiB | 955.00 KiB/s, done.
Total 5 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To github.com:Isho-Jah/git-extended.git
   bd4b24b..8efc236  develop -> develop
   bd4b24b..be0a8e7  master -> master
```

Рис. 21: Отправка на гит

Создаю релиз на github. Для этого использую утилиты работы с github gh (gh release create):

```
ijalloh@ijalloh:~/git-extended$ gh release create v1.0.0 -F CHANGELOG.md  
https://github.com/Isho-Jah/git-extended/releases/tag/v1.0.0
```

Рис. 22: Создание релиза

Создаю ветку для новой функциональности:

```
ijalloh@ijalloh:~/git-extended$ git flow release start feature_branch
Switched to a new branch 'release/feature_branch'

Summary of actions:
- A new branch 'release/feature_branch' was created, based on 'develop'
- You are now on branch 'release/feature_branch'

Follow-up actions:
- Bump the version number now!
- Start committing last-minute fixes in preparing your release
- When done, run:

    git flow release finish 'feature_branch'
```

Рис. 23: Создание ветки feature_branch

Далее, продолжаю работу с git как обычно. Создаю релиз с версией 1.2.3:

```
ijalloh@ijalloh:~/git-extended$ git flow release start 1.2.3
Branches 'develop' and 'origin/develop' have diverged.
And local branch 'develop' is ahead of 'origin/develop'.
Switched to a new branch 'release/1.2.3'


Summary of actions:
- A new branch 'release/1.2.3' was created, based on 'develop'
- You are now on branch 'release/1.2.3'

Follow-up actions:
- Bump the version number now!
- Start committing last-minute fixes in preparing your release
- When done, run:

    git flow release finish '1.2.3'
```

Рис. 24: Создание релиза с версией 1.2.3

Обновляю номер версии в файле package.json в 1.2.3:



```
package.json [-M--] 20 L:[ 1+ 2 3/ 15] *(49 / 369b) 0034 0x022 [
{
  "name": "git-extended",
  "version": "1.2.3",
}
```

Рис. 25: Обновление номера версии

Создаю журнал изменений (standard-changelog):

A terminal window with a dark background. The prompt is '^[[Aijalloh@ijalloh:~/git-extended\$'. The command 'standard-changelog' has been entered. The output is '✓ output changes to CHANGELOG.md'.

```
^[[Aijalloh@ijalloh:~/git-extended$ standard-changelog
✓ output changes to CHANGELOG.md
```

Рис. 26: Создание нового журнала изменений

Добавляю журнал изменений в индекс:

```
ijalloh@ijalloh:~/git-extended$ git add CHANGELOG.md
ijalloh@ijalloh:~/git-extended$ git commit -am 'chore(site): update changelog'
[release/1.2.3 3656596] chore(site): update changelog
2 files changed, 5 insertions(+), 1 deletion(-)
```

Рис. 27: Добавление журнала

Залью релизную ветку в основную ветку:

```
ijalloh@ijalloh:~/git-extended$ git flow release finish 1.2.3
Branches 'master' and 'origin/master' have diverged.
And local branch 'master' is ahead of 'origin/master'.
Branches 'develop' and 'origin/develop' have diverged.
And local branch 'develop' is ahead of 'origin/develop'.
Switched to branch 'master'
Your branch is ahead of 'origin/master' by 2 commits.
  (use "git push" to publish your local commits)
Merge made by the 'ort' strategy.
  CHANGELOG.md | 4 ++++
  package.json | 2 +-
  2 files changed, 5 insertions(+), 1 deletion(-)
Already on 'master'
Your branch is ahead of 'origin/master' by 5 commits.
  (use "git push" to publish your local commits)
Switched to branch 'develop'
Your branch is ahead of 'origin/develop' by 2 commits.
  (use "git push" to publish your local commits)
Merge made by the 'ort' strategy.
  CHANGELOG.md | 4 ++++
  package.json | 2 +-
  2 files changed, 5 insertions(+), 1 deletion(-)
Deleted branch release/1.2.3 (was 3656596).

Summary of actions:
- Release branch 'release/1.2.3' has been merged into 'master'
- The release was tagged '1.2.3'
- Release tag '1.2.3' has been back-merged into 'develop'
- Release branch 'release/1.2.3' has been locally deleted
- You are now on branch 'develop'
```

Отправляю данные на github:

```
ijalloh@ijalloh:~/git-extended$ git push --all
Enumerating objects: 11, done.
Counting objects: 100% (11/11), done.
Delta compression using up to 4 threads
Compressing objects: 100% (8/8), done.
Writing objects: 100% (8/8), 4.50 KiB | 4.50 MiB/s, done.
Total 8 (delta 2), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (2/2), completed with 2 local objects.
To github.com:Isho-Jah/git-extended.git
   8efc236..76ad4b9  develop -> develop
   be0a8e7..6e5ef2c  master -> master
ijalloh@ijalloh:~/git-extended$ git push --tags
```

Рис. 29: Отправка данных

Создаю релиз на github с комментарием из журнала изменений:

```
ection refused  
ijalloh@ijalloh:~/git-extended$ gh release create v1.2.3 -F CHANGELOG.md  
https://github.com/Isho-Jah/git-extended/releases/tag/v1.2.3
```

Рис. 30: Создание релиза

Выводы

При выполнении работы я получил навыки правильной работы с репозиториями git.