



OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Online Transfer with Heterogeneous Source

Yan Yuguang

South China University of Technology

May 12, 2015



Contents

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

1 Introduction

2 Related Work

3 Problem Definition

4 Methods

5 Theoretical Analysis

6 Experiments

7 Conclusion



Introduction

Transfer Learning

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Transfer learning aims to transfer knowledge extracted from the source domain to the target domain.

- Homogeneous transfer

$$\mathcal{X}^{source} = \mathcal{X}^{target} \text{ and } \mathcal{Y}^{source} = \mathcal{Y}^{target}$$

- Heterogeneous transfer

$$\mathcal{X}^{source} \neq \mathcal{X}^{target} \text{ or } \mathcal{Y}^{source} \neq \mathcal{Y}^{target}$$



Introduction

Online Heterogeneous Transfer

OHT

yanyg

Introduction

Related Work

Problem

Definition

Methods


Theoretical

Analysis

Experiments

Conclusion

We investigate online heterogeneous transfer learning problem.



- Heterogeneous transfer
the feature spaces of the source and target domains are completely different
for instance, image-text, English-Chinese-French
- Online transfer
data instances in the target domain arrive sequentially



Introduction

Challenges

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

- Heterogeneous knowledge transfer across the source and target domains
- No prior training data to build a precise relationship across the source and target domains



Introduction

Online Heterogeneous Transfer (OHT) Algorithms

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Procedure of our proposed OHT algorithms

- construct a connection between the source and target domains via co-occurrence data
- adopt weighted K nearest neighbor algorithm using data in the heterogeneous source
- apply traditional online learning algorithm to train a hypothesis in the target domain
- combine two hypotheses to obtain the ensemble classifier



Related Work

Heterogeneous Transfer

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

- Build text features for image ¹
- annotation-based probabilistic latent semantic analysis ²
- Construct representation for image using common semantic view between image and text data ³
- Co-transfer via transition probability ^{4 5}

Above-mentioned studies require prior training data in the source and target domains.

In our problem setting, all the instance in the target domain arrive sequentially.

¹Building text features for object image classification (?, ?)

²Heterogeneous Transfer Learning for Image Clustering via the Social Web (?, ?)

³Heterogeneous Transfer Learning for Image Classification (?, ?)

⁴Co-Transfer Learning via Joint Transition Probability Graph Based Method (?, ?)

⁵Cotransfer Learning Using Coupled Markov Chains with Restart (?, ?)



Related Work

Online Learning

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Only a few works consider transfer learning in an online fashion.

- Ensemble learning method for online homogeneous transfer^{6 7}
- Multi-view method for online heterogeneous transfer

Zhao et al. assume that the feature space of the source domain is a subset of that of the target domain.

In our problem setting, the feature spaces of the source and target domains do not share any common subset (e.g. image and text).

⁶OTL: A Framework of Online Transfer Learning (?, ?)

⁷Online Transfer Learning (?, ?)



Problem Definition

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Suppose that we are given some instances $\{\mathbf{x}_i^s, y_i^s\}_{i=1}^{n^s}$ in the source data space $\mathcal{X}^s \times \mathcal{Y}^s$, where $\mathcal{X}^s = \mathbb{R}^{d^s}$ and $\mathcal{Y}^s = \{+1, -1\}$. The objective of online heterogeneous transfer is to learn a prediction function $f(\mathbf{x}_t)$ to classify the instance on the target domain in an online fashion. The data space of the target domain is $\mathcal{X} \times \mathcal{Y}$, where $\mathcal{X} = \mathbb{R}^d$ and $\mathcal{Y} = \{+1, -1\}$. Specifically, the task of online heterogeneous transfer learning is a sequential process, during which an instance \mathbf{x}_t comes at the t -th trial, and the classifier generates a predicted class label \hat{y}_t . Then the classifier receives the correct class label y_t and update itself to obtain a better classification ability.

In our problem setting, $\mathcal{Y} = \mathcal{Y}^s$, which means the same class label in two domains indicates the same class. For instance, $+1$ indicates vehicle class and -1 represents tree class. While the feature spaces of the source and target domains are completely different. Formally, $\mathcal{X} \cap \mathcal{X}^s = \emptyset$. As We cannot directly



Methods

Heterogeneous Knowledge Transfer

OHT

yanyg

Introduction

Related Work


Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion



Similarity between \mathbf{x}_t and each instance in the heterogeneous source domain

$$Sim_t(j) = \sum_i Sim_t^{(1)}(i) Sim_t^{(2)}(i, j)$$

Weighted K nearest neighbor classifier

$$h_t^s(\mathbf{x}_t) = \sum_{i \in N} \frac{Sim_t(i)}{\sum_{i \in N} Sim_t(i)} y_i$$

where N is the set of identifiers of K nearest neighbors in the heterogeneous source domain.



Online Heterogeneous Transfer Algorithms

OHT

yanyg

Introduction

Related Work

Problem Definition

Methods

Theoretical Analysis

Experiments

Conclusion

Algorithm 1 Online Heterogeneous Transfer Algorithm 1 (OHT1)

Input: aggressiveness parameter $C > 0$

$\eta = \frac{1}{2}$
heterogeneous source data

Output: $\mathbf{v} = \mathbf{0}$, $w_1^s \in (0, 1)$, $w_1 \in (0, 1)$, where $w_1^s + w_1 = 1$

- 1: **for** $t = 1$ to T **do**
- 2: receive instance: $\mathbf{x}_t \in \mathcal{X}$
- 3: normalize: $\theta_t^s = \frac{w_t^s}{w_t^s + w_t}$, $\theta_t = \frac{w_t}{w_t^s + w_t}$
- 4: predict: $\hat{y}_t = \text{sign}(\theta_t^s \Omega(h_t^s(\mathbf{x}_t)) + \theta_t \Omega(\mathbf{v}_t \cdot \mathbf{x}_t) - \frac{1}{2})$
- 5: receive correct label: $y_t \in \mathcal{Y}$
- 6: compute:

Algorithm 2 Online Heterogeneous Transfer Algorithm 2 (OHT2)

Input: aggressiveness parameter $C > 0$

discount parameter $\alpha \in (0, 1)$
heterogeneous source data

Output: $\mathbf{v} = \mathbf{0}$, $w_1^s \in (0, 1)$, $w_1 \in (0, 1)$, where $w_1^s + w_1 = 1$

- 1: **for** $t = 1$ to T **do**
- 2: receive instance: $\mathbf{x}_t \in \mathcal{X}$
- 3: normalize: $\theta_t^s = \frac{w_t^s}{w_t^s + w_t}$, $\theta_t = \frac{w_t}{w_t^s + w_t}$
- 4: predict: $\hat{y}_t = \text{sign}(\theta_t^s \text{sign}(h_t^s(\mathbf{x}_t)) + \theta_t \text{sign}(\mathbf{v}_t \cdot \mathbf{x}_t))$
- 5: receive correct label: $y_t \in \mathcal{Y}$
- 6: compute:



Theoretical Analysis

Hedge(β) Algorithm

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

At t -th trial, **Hedge**(β) algorithm synthesizes opinions from different experts based on a weight vector \mathbf{weight}_t , and updates the weight vector using rule

$$weight_{t+1}^i = weight_t^i \cdot \beta^{loss_t^i}$$

where $\beta \in [0, 1]$ and $loss_t^i \in [0, 1]$.

Hedge (β)	OHT1	OHT2
$loss_t^i$	$\ell_t^s = (\Omega(h_t^s(\mathbf{x}_t)) - \Omega(y_t))^2$ $\ell_t = (\Omega(\mathbf{v}_t \cdot \mathbf{x}_t) - \Omega(y_t))^2$	$\ell_t^s = I(y_t h_t^s(\mathbf{x}_t) \leq 0)$ $\ell_t = I(y_t (\mathbf{v}_t \cdot \mathbf{x}_t) \leq 0)$
β	$\beta = \exp\{-\eta\}$	$\beta = \alpha$

OHT algorithms obey the rule of **Hedge**(β) algorithm.



Theoretical Analysis

Proposition

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Proposition

Given loss $\ell_t^s \in [0, 1]$, $\ell_t \in [0, 1]$ and decay factor $\beta \in (0, 1)$, for any sequence of loss vectors $\{(\ell_t^s, \ell_t) | t = 1, 2, \dots, T\}$, we have

$$\sum_{t=1}^T (\theta_t^s \ell_t^s + \theta_t \ell_t) \leq \frac{1}{1-\beta} \min(\Delta^s, \Delta)$$

where $\Delta^s = \ln(\frac{1}{w_1^s}) + (\ln \frac{1}{\beta}) \sum_{t=1}^T \ell_t^s$ and

$$\Delta = \ln(\frac{1}{w_1}) + (\ln \frac{1}{\beta}) \sum_{t=1}^T \ell_t$$



Theoretical Analysis

Theorem

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Theorem

Let M be the number of mistakes made by OHT1 algorithm, then we have

$$M \leq \frac{4}{1-\beta} \min(\Delta^s, \Delta)$$

where $\Delta^s = \ln(\frac{1}{w_1^s}) + (\ln \frac{1}{\beta}) \sum_{t=1}^T \ell_t^s$ and

$$\Delta = \ln(\frac{1}{w_1}) + (\ln \frac{1}{\beta}) \sum_{t=1}^T \ell_t.$$

Theorem

Let M be the number of mistakes made by OHT2 algorithm, then we have

$$M \leq \frac{2}{1-\beta} \min(\Delta^s, \Delta)$$



Experiments

Dataset

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

NUS-WIDE dataset

- Target domain: Image
- Heterogeneous source: Text
- Co-occurrence data: co-occurred image-tag pairs



Experiments

Baseline Methods

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

- Passive-Aggressive algorithms
 - Do not exploit knowledge from the source domain
- Kernel function
 - Gaussian Kernel
- Number of nearest neighbors
 - $K = 100$



Experiments

Results

OHT

yanyg

Introduction

Related Work


Problem
Definition

Methods


Theoretical
Analysis

Experiments

Conclusion



(a) PA-II vs. OHT1-II





Experiments

Results

OHT

yanyg

Introduction

Related Work


Problem
Definition

Methods


Theoretical
Analysis

Experiments

Conclusion



(a) Task 2





Experiments

Significant Test

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

Paired t -test ($\alpha = 0.01$)

- OHT1 vs. PA: 44/0/1
- OHT2 vs. PA: 42/2/1

Cohen's d value ($d > 0.8$: large promotion, $0.2 < d < 0.8$: middle promotion)

- OHT1: 41/3
- OHT2: 40/3



Experiments

Parameters and Running Time

OHT

yanyg

Introduction

Related Work


Problem
Definition

Methods


Theoretical
Analysis

Experiments

Conclusion



(a)



(b)

Figure: (a) The average rate of mistakes under varying values of K .
(b) The average running time of different algorithms when all instances in heterogeneous source are considered.



Conclusion

OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

- We explore online heterogeneous transfer learning problem.
- We construct a connection across the domains using co-occurrence data, and apply the ensemble strategy to train a classifier.
- We offer the theoretical analysis of our algorithms.
- Experimental results show the effectiveness of our algorithms.

Future works:

- applications with other types of data
- multiple source domains



OHT

yanyg

Introduction

Related Work

Problem
Definition

Methods

Theoretical
Analysis

Experiments

Conclusion

*THANK YOU
FOR
YOUR ATTENTION!*