

MongoDB

Day3



Indexes



Drop Database & Collection



models



export & Import



replica set


Indexes

Indexes support the efficient execution of queries in MongoDB. Without indexes, MongoDB must perform a collection scan, i.e. scan every document in a collection, to select those documents that match the query statement. If an appropriate index exists for a query, MongoDB can use the index to limit the number of documents it must inspect.

The index stores the **value of a specific field or set of fields**, ordered by the value of the field.

MongoDB defines indexes at the collection level and supports indexes on any **field or sub-field** of the documents in a MongoDB collection.

Indexes



Indexes Methods


Show Collection Indexes `db.collection.getIndexes()`

Create Index for specific field in collection

`db.collection.createIndex(<key and index type specification>, <options>)`

Example:

`db.emp.createIndex({score:1})`



a value of **1** specifies an index that orders items in **ascending** order. A value of **-1** specifies an index that orders items in **descending** order

Compound Indexes

MongoDB supports compound indexes, where a single index structure holds references to multiple fields within a collection's documents.

```
db.emp.createIndex({userID:-1,score:1})
```

Modify & Drop Indexes

```
db.emp.dropIndex({key:"index__key"})
```

```
db.emp.dropIndexes()
```

You can modify index using `createIndex` but there are some cases **you will must remove index and rebuild it**

Text Search

MongoDB supports query operations that perform a text search of string content. To perform text search, MongoDB uses a **text index** and the **\$text** operator.

Text Index

MongoDB provides text indexes to support text search queries on string content. text indexes can include any field whose value is a string or an array of string elements.

```
db.emp.createIndex( { name: "text", address: "text" } )
```


Text Search – \$text Operator

Use the **\$text** query operator to perform text searches on a collection with a text index.

\$text will tokenize the search string using whitespace and most punctuation as delimiters, and perform a logical **OR** of all such tokens in the search string.

```
db.emp.find( {$text:{$search: "ahmed ali mahmoud"}})
```

```
db.emp.find( {$text:{$search: "ahmed \"ali mahmoud\""}})
```

Exact Phrase

```
db.emp.find( {$text:{$search: "ahmed ali -mahmoud"}})
```

Term Exclusion

Drop Database & Collection

Use database first then `db.dropDatabase()`

`db.collection.drop ()`

Export & Import

Export :


```
$ mongodump --db HR --collection emp --out dir__path
```

Import :

```
$ mongorestore --db HR path__to__dump__directory
```

Replica Set

A replica set in MongoDB is a group of mongod processes that maintain the same data set. Replica sets provide redundancy and **high availability**, and are the basis for all production deployments.




Replica Set Primary

The primary is the only member in the replica set that receives write operations . MongoDB applies write operations on the primary and then records the operations on the primary's oplog . Secondary members replicate this log and apply the operations to their data sets

All members of the replica set can accept read operations . However, by default, an application directs its read operations to the primary member . See [Read Preference](#) for details on changing the default read behavior .

The replica set can have at most one primary . If the current primary becomes unavailable, an election determines the new primary

Automatic Failover



Replica Set Demo

Demo Time



Thank You

E-mail Address :

ahmedcs2012@gmail.com