

Screw-Terminal Adhesive Surface-Mount

Please visit the SECO-LARM website www.seco-larm.com for complete installation instructions. Please read the manual carefully before beginning installation.

SM-4003-TQ/W

1" (25mm) Gap, Closed Loop, Screw Terminals, White

Features:

- Miniature surface-mount magnetic contacts
- Adhesive mount
- Gold-plated terminals for longer expected life and reliability
- Screw terminals
- Tape to cover screw terminals included
- Contact reed switch is SPST, iridium-plated to have a high melting point and Vickers hardness for higher power handling and longer expected life
- For closed loop circuits
- 1" (25mm) Gap
- Double-sided tape included
- Lifetime limited warranty

Specifications:

Loop type		Closed loop
Electrical configuration		N.O. (SPST)
Operation gap		1" (25mm)
Connectors		Gold-plated screw terminals
Color		White
Mount		Adhesive
Material	Case	High-impact ABS plastic
	Contacts	Iridium-plated
Contact rating		1.0A@10VDC (max.)
		10W (max.)
Operating temperature		-15°~160° F (-25°~70° C)
Switch cycles		50 Million (0.1mA@5VDC)
Switch dimensions		1 ¹ / ₂ "x ³ / ₈ "x ⁵ / ₁₆ " (38x10x8 mm)
Magnet dimensions		11/2"x3/8"x1/4" (38x10x6 mm)
Magnet type		Rare-earth neodymium














Dimensions:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606 **Phone:** (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com





Adhesiva Tornillo-Terminal de Montaje en Superficie Contactos Magnéticos

Por favor visite el sitio web de SECO-LARM www.seco-larm.com para obtener instrucciones de instalación completas. Por favor lea el manual antes de usar el equipo.

SM-4003-TQ/W

1" (25mm) Brecha, Lazo Cerrado, Blanco, Adhesiva Montaje

Características:

- Contactos magnéticos de montaje superficial en miniatura.
- Terminales chapados en oro para una vida útil y confiabilidad más prolongadas
- Terminales de tornillo
- · Incluye cinta para cubrir terminales de tornillo
- El interruptor de lengüeta de contacto es SPST, con baño de iridio para tener un alto punto de fusión y dureza Vickers para un mayor manejo de la potencia y una vida útil más larga
- Brecha de 1 " (25 mm)
- · Para circuitos cerrados
- Incluye cinta de montaje
- Garantía limitada de por vida

Especificaciones:

Tipo de circuito		Lazo Cerrado
Configuración eléctrica		N.A. (SPST)
Brecha de operación		1" (25mm)
Connectores		Terminales Chapados en Oro
Color		Blanco
Montaje		Adhesivo
Material	Caja	Plástico ABS de Alto Impacto
	Contactos	Chapados en Iridio
Puntuación de		1.0A@10V C.C. (max.)
contactos		10W (max.)
Temperatura		-15°~160° F (-25°~70° C)
Ciclos de conmutación		50 Milliones (0.1mA@5V C.C.)
Dimensiones del interruptor		1 ¹ / ₂ "x ³ / ₈ "x ⁵ / ₁₆ " (38x10x8 mm)
Dimensiones del imán		1 ¹ / ₂ "x ³ / ₈ "x ¹ / ₄ " (38x10x6 mm)
Tipo de imán		Neodimio de Tierras Raras








Imán de Tierras Raras Tornillo Terminal Brecha de

Dimensiones:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

