

Miniature Surface-Mount Contacts

Please visit the SECO-LARM website www.seco-larm.com for complete installation instructions. Please read the manual carefully before beginning installation.

SM-205Q/W

3/4" (19mm) Gap, Closed Loop, Side Leads, White


SM-205Q/BR

3/4" (19mm) Gap, Closed Loop, Side Leads, Brown

Features:

- Miniature "flange-type" surface-mount magnetic contacts perfect for sliding doors and windows where space is limited
- Screw or adhesive mount
- Mounting flange breaks off for extra miniature size
- High-impact weatherproof ABS plastic case
- Contact reed switch is SPST, deactivated rhodium on gold underplating for a longer expected life
- For closed loop circuits
- 3/4" (19mm) Gap
- 15" (38cm) Wire leads extend from side of switch
- Double-sided tape included
- Lifetime limited warranty














15" Side Leads 3/4"
Gap

Specifications:

Model		SM-205Q/W	SM-205Q/BR
Loop type		Closed loop	
Electrical configuration		N.O. (SPST)	
Operation gap		³ / ₄ " (19mm)	
Connectors		15" (38cm) Leads from side	
Color		White	Brown
Material	Case	High-impact ABS plastic	
	Contacts	Deactivated rhodium on gold underplating	
Contact rating		1.0A@10VDC (max.)	
		10W (max.)	
Operating temperature		-15°~160° F (-25°~70° C)	
Switch cycles		50 Million (0.1mA@5VDC)	
Dimensions	Switch	1 ¹ / ₄ "x ⁵ / ₁₆ "x ¹ / ₄ " (32x8x6 mm)	
	Magnet	1 ¹ / ₄ "x ⁵ / ₁₆ "x ¹ / ₄ " (32x8x6 mm)	
Magnet type		Alnico 5	

Dimensions:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com





Miniatura de Montaje Superficial Contactos

Por favor visite el sitio web de SECO-LARM www.seco-larm.com para obtener instrucciones de instalación completas. Por favor de lea el manual antes de usar el equipo.

SM-205Q/W

Brecha de 3/4", Lazo Cerrado, Cables laterales, Blanco


SM-205Q/BR

Brecha de 3/4", Lazo Cerrado, Cables laterales, Café

Features:

- Contactos magnéticos en miniatura de "montaje en superficie" tipo "brida," perfecto para puertas corredizas y ventanas donde el espacio es limitado
- Montaje de tornillo o adhesivo (cinta adhesiva incluida)
- La brida de montaje se rompe para obtener un tamaño extra en miniatura
- Caja de plástico ABS resistente a la intemperie de alto impacto
- El interruptor de lengüeta de contacto es SPST, rodio desactivado en la capa inferior de oro para una vida útil más larga
- Para circuitos cerrados
- Brecha de ³/₄" (19mm)
- Los cables de 15" (38 cm) se extienden desde el lado del interruptor
- Cinta de montaje incluidos
- Garantía limitada de por vida










Contactos chapados en oro Imán **5** Alnico 15" Cables del lado

3/4"
Brecha

Especificaciones:

Modelo		SM-205Q/W	SM-205Q/BR
Circuito tipo		Lazo Cerrado	
Electrical configuration		N.A. (SPST)	
Espacio de operación		³ / ₄ " (19mm)	
Terminales		15" (38cm) Leads from side	
Color		Blanco	Café
Material	Caja	plástico ABS de alto impacto	
	Contactos	Desactivado rodio sobre chapado en oro	
Puntuación de contactos		1.0A@10V C.C. (max.)	
		10W (max.)	
Temperatura		-15°~160° F (-25°~70° C)	
Ciclos de Conmutación		50 millones (0.1mA@5V C.C.)	
Dimensiones	Interruptor	1 ¹ / ₄ "x ⁵ / ₁₆ "x ¹ / ₄ " (32x8x6 mm)	
	lmán	1 ¹ / ₄ "x ⁵ / ₁₆ "x ¹ / ₄ " (32x8x6 mm)	
Tipo de Imán		Alnico 5	

Dimensiones:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com



