FINITE-VALUED STREAMING STRING TRANSDUCERS

Emmanuel Filiot, Ismaël Jecker, Christof Löding, Anca Muscholl, Gabriele Puppis, Sarah Winter



ismaeljecker.github.io

Finite-valued regular relations form a class of binary relations that enjoys good algorithmic properties



ismaeljecker.github.io

Theorem: We can decide in polynomial space whether a given SST defines a finite-valued regular relation

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**



ismaeljecker.github.io


Transducers are abstract machines that recognise **relations**

$$R \subseteq \Sigma^* \times \Gamma^*$$

Transducers are abstract machines that recognise **relations**

Regular relations


Transducers are abstract machines that recognise **relations**




Input: a b b a a a b b b a b a a a

Output:

 T_1 produces one of the b-blocks of its input




Transducers are abstract machines that recognise **relations**



Input: a b b a a a a b b b a b a a a


Output:

 T_1 produces one of the b-blocks of its input



Rational relations
Regular relations


Transducers are abstract machines that recognise **relations**



Input: a b b a a a a b b b a b a a a


Output:

 T_1 produces one of the b-blocks of its input



Rational relations
Regular relations


Transducers are abstract machines that recognise **relations**



Input: abbaaaabbbabaaa


Output:

 T_1 produces one of the b-blocks of its input



Rational relations
Regular relations


Transducers are abstract machines that recognise **relations**



Input: a b b a a a b b b a b a a a


Output:

 T_1 produces one of the b-blocks of its input



Rational relations
Regular relations


Transducers are abstract machines that recognise **relations**



Input: abbaaa bbbabaaa


Output:

 T_1 produces one of the b-blocks of its input




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**



Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**



Rational relations
Regular relations


Transducers are abstract machines that recognise **relations**



Input: a b b a a a b b b a b a a a


Output: bbb

 T_1 produces one of the b-blocks of its input



Rational relations
Regular relations


Transducers are abstract machines that recognise **relations**



Input: a b b a a a a b b b a b a a a


Output: bbb

 T_1 produces one of the b-blocks of its input




Rational relations recognised by finite st

Transducers are abstract machines that recognise **relations**




Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**



Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**



Rational relations
Regular relations

Transducers are abstract machines that recognise **relations**

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

R₂:

R₁:

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

R₁: a

R₂:

 $a \mid R_1 = R_1 a$

Regular relations

 T_2 sorts its input

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a a

R₁: a

R₂: b

 T_2 sorts its input

$$a \mid R_1 := R_1 a$$

$$T_2 : \longrightarrow R_1 R_1$$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a

R₁: a

R₂: b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a

R₁: a a R₂: b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a

R₁: a a a R₂: b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a

R₁: a a a a R₂: b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a

R₁: a a a a R₂: b b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a a

R₁: a a a a R₂: b b b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a

R₁: a a a a R₂: bbbbb

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Rational relations recognised by finite state transducers Regular relations

recognised by streaming string transducers

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a

R₁: a a a a a R₂: b b b b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a

R₁: a a a a a R₂: b b b b b b

 T_2 sorts its input

 $a \mid R_1 = R_1 a$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a a a

R₁: aaaaaa R₂: bbbbbb

 T_2 sorts its input

 $a \mid R_1 := R_1 a$ $T_2 : \longrightarrow R_1 R$

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b b a b a a

R₁: aaaaaaa R₂: bbbbbb

 T_2 sorts its input

 $a \mid R_1 := R_1 a$ $T_2 : \longrightarrow R_1 F$

Rational relations re

recognised by finite state transducers recognised by streaming string transducers

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

Input: a b b a a a b b

R₁: a a a a a a a a R₂: b b b b b b

 T_2 sorts its input

$$a \mid R_1 := R_1 a$$

$$T_2 : \longrightarrow R_1 F_2$$

$$h \mid R_2 := R_2 h$$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

 T_2 sorts its input

$$a \mid R_1 := R_1 a$$

$$T_2 : \longrightarrow R_1 R_2$$
 $b \mid R_2 := R_2 b$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

 T_2 sorts its input

$$a \mid R_1 := R_1 a$$

$$T_2 : \longrightarrow R_1 R_2$$
 $b \mid R_2 := R_2 b$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

 T_2 sorts its input

$$a \mid R_1 := R_1 a$$

$$T_2 : \longrightarrow R_1 R_2$$
 $b \mid R_2 := R_2 b$

Regular relations

Transducers are abstract machines that recognise **relations**

Streaming string transducer (SST)

 T_2 sorts its input

$$a \mid R_1 := R_1 a$$

$$T_2 : \longrightarrow R_1 R_2$$
 $b \mid R_2 := R_2 b$

Regular relations

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Equivalence of rational relations is undecidable

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Equivalence of rational relations is undecidable

Equivalence of regular functions is decidable

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

functions

Equivalence of rational relations is undecidable

Equivalence of **regular functions** is **decidable**

→ each input is mapped to at most 1 output

Equivalence of finite-valued regular relations is decidable

 $\exists \mathbf{k} \in \mathbb{N} \text{ s.t. each input is mapped to at most } \mathbf{k} \text{ outputs}$

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Theorem: We can decide in polynomial space whether a given

SST defines a finite-valued regular relation

Theorem: Every finite-valued regular relation can be decomposed

into a finite union of regular functions

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Theorem: We can decide in polynomial space whether a given SST defines a finite-valued regular relation

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

⇒ The equivalence problem for finite-valued SST is in Elementary

⇒ Finite-valued 2-way FST are as expressive as finite-valued SST

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Theorem: We can decide in polynomial space whether a given

SST defines a finite-valued regular relation

Theorem: Every finite-valued regular relation can be decomposed

into a finite union of regular functions

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Theorem: We can decide in polynomial space whether a given SST defines a finite-valued regular relation

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

Raised as open problems by [2011. Alur, Deshmukh] Known to hold for FST [1989. Weber], [1993. Weber]; ...and for SST with a single register [2017. Gallot et al.]

Rational relations
Regular relations


recognised by finite state transducers recognised by streaming string transducers

DECIDING FINITE VALUEDNESS

Theorem: We can decide in polynomial space whether a given

SST defines a finite-valued regular relation

Forbidden pattern: (inspired by [2008. De Souza])



- The relation recognised by the pattern is not 1-valued
- The substitutions produced on the loops have idempotent structure

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

Proof: (inspired by [2008. Sakarovitch, de Souza] and relying on [2023. FJLW]) **k**-valued (at most **k** outputs per input) **k**-ambiguous (at most **k** runs per input) $\mathcal{T}_1',\,...,\,\mathcal{T}_k'$ unambiguous (at most 1 run per input) $\stackrel{\cdot}{\mathcal{T}_1,\;\ldots,\;\mathcal{T}_k} \quad \text{functional} \qquad \text{(at most 1 output per input)}$

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

Proof: (inspired by [2008. Sakarovitch, de Souza] and relying on [2023. FJLW]) K-valued (at most k outputs per input) \mathcal{T}' only keeps the runs of \mathcal{T} that are **far** from each other T' k-ambiguous (at most k runs per input) $\mathcal{T}'_1, ..., \mathcal{T}'_k$ unambiguous (at most 1 run per input) $\label{eq:total_total} \mathcal{T}_1, \stackrel{\cdot}{\dots}, \mathcal{T}_k \quad \text{functional} \qquad \text{(at most 1 output per input)}$

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

```
Proof: (inspired by [2008. Sakarovitch, de Souza] and relying on [2023. FJLW])
                \mathcal{T} k-valued (at most k outputs per input)
               T' k-ambiguous (at most k runs per input)
               \Psi \mathcal{T}'_i copies the ith lexicographically smallest run of \mathcal{T}'
        \mathcal{T}'_1, ..., \mathcal{T}'_k unambiguous (at most 1 run per input)
         \stackrel{\cdot}{\mathcal{T}_1},\stackrel{\cdot}{...},\stackrel{\cdot}{\mathcal{T}_k} \quad \text{functional} \qquad \text{(at most 1 output per input)}
```

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

```
Proof: (inspired by [2008. Sakarovitch, de Souza] and relying on [2023. FJLW])

\mathcal{T} k-valued (at most k outputs per input)

\mathcal{T}' k-ambiguous (at most k runs per input)

\mathcal{T}'_1, \ldots, \mathcal{T}'_k unambiguous (at most 1 run per input)

\mathcal{T}'_1, \ldots, \mathcal{T}'_k functional (at most 1 output per input)
```

Theorem: We can decide in polynomial space whether a given SST defines a finite-valued regular relation

Theorem: Every **finite-valued regular relation** can be decomposed into a finite union of **regular functions**

⇒ The equivalence problem for finite-valued SST is in Elementary

⇒ Finite-valued 2-way FST are as expressive as finite-valued SST

Rational relations
Regular relations

recognised by finite state transducers recognised by streaming string transducers

Besançon is hiring

The University of Franche-Comté is recruiting for

3 Maître de conférences positions

set to begin in the academic year 2025-2026

Contact me for more information:

ismael.jecker@gmail.com