

SIMULAR TRAFICO EN WORDPRESS

HERRAMIENTAS NECESARIAS

Tener **2 máquinas virtuales** (atacante y WordPress).

Apache Benchmark en la atacante para generar tráfico.

Htop para la de WordPress y poder monitorear los procesos.

```
(kali㉿kali)-[~]  
$ sudo apt-get install apache2-utils
```

Lo instalamos y comprobamos que funciona con el comando htop

```
debian@debian:~$ sudo apt-get install htop
```

CONFIGURACION DE LAS MV

Las ponemos en adaptador puente de esta manera obtienen automáticamente una dirección IP.

The screenshot shows the 'Red' network configuration window. It has tabs for 'Adaptador 1', 'Adaptador 2', 'Adaptador 3', and 'Adaptador 4'. Under 'Adaptador 1', the 'Habilitar adaptador de red' checkbox is checked. The 'Conectar a' dropdown is set to 'Adaptador puente'. The 'Nombre' dropdown is 'Realtek PCIe GbE Family Controller'. The 'Tipo de Adaptador' dropdown is 'Intel PRO/1000 MT Desktop (82540EM)'. The 'Promiscuous Mode' dropdown is 'Denegar'. The 'Dirección MAC' text box contains '0800275A87BC'. The 'Virtual Cable Connected' checkbox is also checked.

DIRECCIONES IP

En la maquina Kali atacante, miramos la interfaz eth0: 192.168.18.71

```
kali@kali: ~  
Session Actions Edit View Help  
(kali㉿kali)-[~]  
$ ip addr show  
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc  
    ault qlen 1000  
    link/loopback 00:00:00:00:00:00 brd 00:00:  
    inet 127.0.0.1/8 scope host lo  
        valid_lft forever preferred_lft forever  
    inet6 ::1/128 scope host noprefixroute  
        valid_lft forever preferred_lft forever  
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu  
    roup default qlen 1000  
    link/ether 08:00:27:5a:87:bc brd ff:ff:ff:  
    inet 192.168.18.71/24 brd 192.168.18.255
```

Para la maquina Debian miramos la interfaz enp0s3: 192.168.18.44

```
debian@debian: ~  
File Edit View Search Terminal Help  
debian@debian:~$ ip addr show  
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue  
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00  
    inet 127.0.0.1/8 scope host lo  
        valid_lft forever preferred_lft forever  
    inet6 ::1/128 scope host noprefixroute  
        valid_lft forever preferred_lft forever  
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500  
    link/ether 08:00:27:d1:65:c7 brd ff:ff:ff:ff:ff:ff  
    inet 192.168.18.44/24 brd 192.168.18.255 scope
```

CONEXIÓN ENTRE MAQUINAS

Hacemos ping respectivamente desde cada máquina para confirmar conexión.

```
debian@debian:~$ ping 192.168.18.71  
PING 192.168.18.71 (192.168.18.71) 56(84) bytes of data.  
64 bytes from 192.168.18.71: icmp_seq=1 ttl=64 time=0.657 ms  
64 bytes from 192.168.18.71: icmp_seq=2 ttl=64 time=0.733 ms  
^C  
--- 192.168.18.71 ping statistics ---  
2 packets transmitted, 2 received, 0% packet loss, time 1020ms  
rtt min/avg/max/mdev = 0.657/0.695/0.733/0.038 ms
```

```
(kali㉿kali)-[~]  
$ ping 192.168.18.44  
PING 192.168.18.44 (192.168.18.44) 56(84) bytes of data.  
64 bytes from 192.168.18.44: icmp_seq=1 ttl=64 time=0.729 ms  
64 bytes from 192.168.18.44: icmp_seq=2 ttl=64 time=0.492 ms  
^C  
--- 192.168.18.44 ping statistics ---  
2 packets transmitted, 2 received, 0% packet loss, time 1028ms  
rtt min/avg/max/mdev = 0.492/0.610/0.729/0.118 ms
```

SIMULAR TRAFICO EN EL SITIO WEB

Vemos en la Debian como el tráfico está tranquilo:

```
debian@debian: ~  
File Edit View Search Terminal Help  
  
0[||||| 6.8%] Tasks: 84, 160 thr, 64 kthr; 1 running  
1[||||| 6.9%] Load average: 0.01 0.03 0.03  
Mem[||||| 684M/1.92G] Uptime: 00:33:22  
Swp[ 0K/975M]
```

Le metemos carga con la Kali:

```

(kali@kali)-[~]
$ ab -n 10000 -c 10 http://192.168.18.44/
This is ApacheBench, Version 2.3 <$Revision: 1934973 $>
Copyright 1996 Adam Twiss, Zeus Technology Ltd, http://www.zeustech.net/
Licensed to The Apache Software Foundation, http://www.apache.org/

Benchmarking 192.168.18.44 (be patient)
Completed 1000 requests
Completed 2000 requests
Completed 3000 requests
Completed 4000 requests
Completed 5000 requests
Completed 6000 requests
Completed 7000 requests
Completed 8000 requests
Completed 9000 requests
Completed 10000 requests
Finished 10000 requests


Server Software:      Apache/2.4.68
Server Hostname:      192.168.18.44
Server Port:          80

Document Path:        /
Document Length:      10701 bytes

Concurrency Level:     10
Time taken for tests:   17.392 seconds
Complete requests:      10000
Failed requests:         0
Total transferred:      109750000 bytes
HTML transferred:       107010000 bytes
Requests per second:    574.99 [#/sec] (mean)
Time per request:       17.392 [ms] (mean)
Time per request:       1.739 [ms] (mean, across all concurrent requests)
Transfer rate:          6162.62 [Kbytes/sec] received


Connection Times (ms)
      min     mean[+/-sd] median   max
Connect:    0      6   2.5      7    14
Processing:  1     10   3.6     11    41
Waiting:    0      5   2.5      5    24
Total:       2     17   5.1     18    48

```

Y vemos en la Debian la sobrecarga:

```

debian@debian: ~
File Edit View Search Terminal Help

0[|||||] 31.8%] Tasks: 92, 160 thr, 64 kthr; 2 running
1[|||||] 89.9%] Load average: 0.64 0.40 0.17
Mem[|||||] 684M/1.92G Uptime: 00:37:11
Swp[      ] 0K/975M

```

EXTRAS

Puedes modificar tanto los parámetros de tráfico en la Kali, como bajarle la RAM a la Debian para que se sature mas todavia.