

Vision Detector PCB Panel Assembly Functional Test

Test Date: 2025-06-10 13:53:52

Supplier: Jabil Technician: User1 Customer: Siemens

Test Station: OSP_PCB_FT_01
Test Software Revision: 04

Test Parameters Match Initialization File: TRUE

Year of Manufacture: 2017

Siemens PCBA Part Number: 10748016

Siemens PCBA Revision: 04

Panel Serial Number: OBI04W30173 - Fail PCB D Serial Number: OBI04W30173D - Fail PCB C Serial Number: OBI04W30173C - Pass PCB B Serial Number: OBI04W30173B - Pass PCB A Serial Number: OBI04W30173A - Fail Test Description: Test 1 - Voltage Detector On, Range (VDC) PCB Serial Number: OBI04W30173D **Test Lower Limit:** 4.90 Test Upper Limit: 5.10 Test Measurement: 0.00 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.312, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 2 - Current Detector On, Range (A) PCB Serial Number: OBI04W30173D Test Lower Limit: 2.45 Test Upper Limit: 2.65 Test Measurement: 0.00 Units: **Amps** Starting Temperature (Max 50.00 C): IC1: 26.312, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 3 - Voltage ASIC Registers Loaded, Range (VDC) PCB Serial Number:

OBI04W30173D

| Test Lower Limit: |
|---|
| 4.90 |
| Test Upper Limit: |
| 5.10 |
| Test Measurement: |
| 5.00 |
| Units: |
| VDC |
| Starting Temperature (Max 50.00 C): |
| IC1: 26.312, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| |
| |
| Test Description: |
| Test 4 - Current ASIC Registers Loaded, Range (A) |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| 2.70 |
| Test Upper Limit: |
| 3.00 |
| Test Measurement: |
| 2.89 |
| Units: |
| Amps |
| Starting Temperature (Max 50.00 C): |
| IC1: 26.312, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| |
| |
| Test Description: |
| Test 5 - Voltage Detector On, Range (VDC) |
| PCB Serial Number: |
| OBI04W30173C |
| Test Lower Limit: |
| 4.90 |
| Test Upper Limit: |

5.10

Test Measurement: 5.00 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 26.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.250; Temp OK - Pass Test Result: **Pass Test Description:** Test 6 - Current Detector On, Range (A) PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.45 **Test Upper Limit:** 2.65 **Test Measurement:** 2.56 Units: **Amps** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 26.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.250; Temp OK - Pass Test Result: **Pass Test Description:** Test 7 - Voltage ASIC Registers Loaded, Range (VDC) PCB Serial Number: OBI04W30173C Test Lower Limit: 4.90 **Test Upper Limit:** 5.10 Test Measurement: 5.00 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 26.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.250; Temp OK - Pass Test Result:

Pass

Test Description: Test 8 - Current ASIC Registers Loaded, Range (A) PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.70 Test Upper Limit: 3.00 **Test Measurement:** 2.89 Units: Amps Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 26.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.250; Temp OK - Pass Test Result: Pass Test Description: Test 9 - Voltage Detector On, Range (VDC) PCB Serial Number: OBI04W30173B **Test Lower Limit:** 4.90 Test Upper Limit: 5.10 **Test Measurement:** 5.00 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.000, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.125; Temp OK - Pass Test Result: **Pass** Test Description: Test 10 - Current Detector On, Range (A) PCB Serial Number: OBI04W30173B Test Lower Limit: 2.45 **Test Upper Limit:** 2.65 Test Measurement:

2.56 Units: **Amps** Starting Temperature (Max 50.00 C): IC1: 27.000, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.125; Temp OK - Pass Test Result: Pass **Test Description:** Test 11 - Voltage ASIC Registers Loaded, Range (VDC) PCB Serial Number: OBI04W30173B **Test Lower Limit:** 4.90 Test Upper Limit: 5.10 Test Measurement: 5.00 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.000, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.125; Temp OK - Pass Test Result: Pass Test Description: Test 12 - Current ASIC Registers Loaded, Range (A) PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.70 Test Upper Limit: 3.00 Test Measurement: 2.89 Units: **Amps** Starting Temperature (Max 50.00 C): IC1: 27.000, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.125; Temp OK - Pass Test Result: **Pass**

Test Description: Test 13 - Voltage Detector On, Range (VDC) PCB Serial Number: OBI04W30173A **Test Lower Limit:** 4.90 Test Upper Limit: 5.10 Test Measurement: 5.00 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.250, IC2: 26.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 26.750, IC2: 26.500; Temp OK - Pass Test Result: **Pass** Test Description: Test 14 - Current Detector On, Range (A) PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.45 **Test Upper Limit:** 2.65 **Test Measurement:** 2.55 Units: **Amps** Starting Temperature (Max 50.00 C): IC1: 26.250, IC2: 26.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 26.750, IC2: 26.500; Temp OK - Pass Test Result: Pass Test Description: Test 15 - Voltage ASIC Registers Loaded, Range (VDC) PCB Serial Number: OBI04W30173A **Test Lower Limit:** 4.90 Test Upper Limit: 5.10 Test Measurement: 5.00

| Units: |
|--|
| VDC |
| Starting Temperature (Max 50.00 C): |
| IC1: 26.250, IC2: 26.187; Temp OK - Pass |
| Ending Temperature (Max 50.00 C): |
| IC1: 26.750, IC2: 26.500; Temp OK - Pass Test Result: |
| Pass |
| 1 433 |
| Test Description: |
| Test 16 - Current ASIC Registers Loaded, Range (A) |
| PCB Serial Number: |
| OBI04W30173A |
| Test Lower Limit: |
| 2.70 |
| Test Upper Limit: |
| 3.00 |
| Test Measurement: |
| 2.89 |
| Units: |
| Amps |
| Starting Temperature (Max 50.00 C): |
| IC1: 26.250, IC2: 26.187; Temp OK - Pass |
| Ending Temperature (Max 50.00 C): |
| IC1: 26.750, IC2: 26.500; Temp OK - Pass |
| Test Result: |
| Pass |
| Toot Description: |
| Test Description: Test 17 - High Voltage Continuity Test |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low |
| High |
| Units: |
| N/A |
| Starting Temperature N/A |
| Ending Temperature N/A |
| Test Result: |
| Pass |
| Notes: |
| N/A |

| Test 18 - High Voltage Continuity Test |
|--|
| PCB Serial Number: |
| OBI04W30173C |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low |
| High |
| Units: |
| N/A |
| Starting Temperature N/A |
| Ending Temperature N/A |
| Test Result: |
| Pass |
| Notes: |
| N/A |
| |
| Test Description: |
| Test 19 - High Voltage Continuity Test |
| PCB Serial Number: |
| OBI04W30173B |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low |
| High |
| Units: |
| N/A |
| Starting Temperature N/A |
| Ending Temperature N/A |
| Test Result: |
| |
| Pass |
| Pass Notes: |
| |
| Notes: |
| Notes: |
| Notes: N/A |
| Notes: N/A Test Description: |
| Notes: N/A Test Description: Test 20 - High Voltage Continuity Test |
| Notes: N/A Test Description: Test 20 - High Voltage Continuity Test PCB Serial Number: |
| Notes: N/A Test Description: Test 20 - High Voltage Continuity Test PCB Serial Number: OBI04W30173A |
| Notes: N/A Test Description: Test 20 - High Voltage Continuity Test PCB Serial Number: OBI04W30173A Test Lower Limit: |

Test Description:

| Test Measurement: |
|---|
| Low |
| High |
| Units: |
| N/A |
| Starting Temperature N/A |
| Ending Temperature N/A |
| Test Result: |
| Pass |
| Notes: |
| N/A |
| N/A |
| Test Description: |
| Test 21 - EEPROM Test |
| |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| N/A |
| Units: |
| N/A |
| Starting Temperature (Max 50.00 C): |
| IC1: 26.625, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 27.500, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| PCB EEPROM Check Fail |
| Failed Read/Write Check at memory location 0X |
| , |
| Test Description: |
| Test 22 - EEPROM Test |
| PCB Serial Number: |
| OBI04W30173C |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| N/A |
| |
| Units: |
| |
| N/A Starting Temperature (Max 50.00 C): |

IC1: 27.125, IC2: 27.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.062, IC2: 27.812; Temp OK - Pass Test Result: **Pass Test Description:** Test 23 - EEPROM Test PCB Serial Number: OBI04W30173B **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: N/A Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.250, IC2: 27.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.750, IC2: 28.250; Temp OK - Pass Test Result: Pass Test Description: Test 24 - EEPROM Test PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: N/A Units: N/A Starting Temperature (Max 50.00 C): IC1: 26.562, IC2: 26.437; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.687, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 25 - TLE Out - IOUTA Y P Off

6/10/2025 1:58:57

PCB Serial Number: OBI04W30173D

-0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** 0.000239 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 26 - TLE Out - IOUTA_Y_P On PCB Serial Number: OBI04W30173D **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.708738 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 27 - TLE Out - IOUTA_Y_N Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000

Test Lower Limit:

| Test Measurement: -0.000406 Units: VDC Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 |
|--|
| Test Description: Test 28 - TLE Out - IOUTA_Y_N On PCB Serial Number: OBI04W30173D Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.731612 Units: VDC |
| Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 |
| Test Description: Test 29 - TLE Out - IOUTA_X_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC |

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 30 - TLE Out - IOUTA X P On

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.703261

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 31 - TLE Out - IOUTA_X_N Off

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

0.000561

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

| Fail |
|--|
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| |
| |
| Test Description: |
| Test 32 - TLE Out - IOUTA_X_N On |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| |
| 2.500000 |
| Test Upper Limit: |
| 2.800000 |
| Test Measurement: |
| 2.733867 |
| Units: |
| VDC |
| Starting Temperature (Max 50.00 C): |
| IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| |
| |
| Toot Descriptions |
| Test Description: |
| Test 33 - TLE Out - IOUTA_E0_P Off |
| · |
| Test 33 - TLE Out - IOUTA_E0_P Off |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC Starting Temperature (Max 50.00 C): |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test |
| Test 33 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: VDC Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: |

Test Result:

Test Description: Test 34 - TLE Out - IOUTA_E0_P On PCB Serial Number: OBI04W30173D **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.693596 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 35 - TLE Out - IOUTA_E0_N Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000883 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 36 - TLE Out - IOUTA_E0_N On

PCB Serial Number: OBI04W30173D **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.697462 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 37 - TLE Out - IOUTA_E1_P Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000561 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 38 - TLE Out - IOUTA_E1_P On PCB Serial Number: OBI04W30173D

2.500000

Test Lower Limit:

| Test Upper Limit: | |
|---|--|
| 2.800000 | |
| Test Measurement: | |
| 2.713248 | |
| Units: | |
| VDC | |
| Starting Temperature (Max 50.00 C): | |
| IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test | |
| Ending Temperature (Max 50.00 C): | |
| IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test | |
| Test Result: | |
| Fail | |
| Notes: | |
| I2C Communication Error: PCB1 Temp Sensor 0x48 | |
| | |
| Test Descriptions | |
| Test 20. TIE Out IOUTA 51 N Off | |
| Test 39 - TLE Out - IOUTA_E1_N Off PCB Serial Number: | |
| OBI04W30173D | |
| Test Lower Limit: | |
| -0.100000 | |
| Test Upper Limit: | |
| 0.100000 | |
| Test Measurement: | |
| -0.00084 | |
| Units: | |
| VDC | |
| Starting Temperature (Max 50.00 C): | |
| IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test | |
| Ending Temperature (Max 50.00 C): | |
| IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test | |
| Test Result: | |
| Fail | |
| Notes: | |
| I2C Communication Error: PCB1 Temp Sensor 0x48 | |
| | |
| | |
| Test Description: | |
| Test 40 - TLE Out - IOUTA_E1_N On | |
| PCB Serial Number: | |
| OBI04W30173D | |
| Test Lower Limit: | |
| 2.500000 | |

Page 18 of 112

2.800000

2.728713

Test Upper Limit:

Test Measurement:

Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 41 - TLE Out - IOUTB Y P Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000239 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 **Test Description:** Test 42 - TLE Out - IOUTB_Y_P On PCB Serial Number: OBI04W30173D Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.703583 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 **Test Description:** Test 43 - TLE Out - IOUTB_Y_N Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000084 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 44 - TLE Out - IOUTB_Y_N On PCB Serial Number: OBI04W30173D Test Lower Limit: 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.715826 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result:

Ending Temperature (Max 50.00 C):

Page 20 of 112

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 45 - TLE Out - IOUTB X P Off

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

-0.000084

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 46 - TLE Out - IOUTB_X_P On

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.700361

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description: Test 47 - TLE Out - IOUTB_X_N Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000084 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 48 - TLE Out - IOUTB X N On PCB Serial Number: OBI04W30173D Test Lower Limit: 2.500000 **Test Upper Limit:** 2.800000 **Test Measurement:** 2.714537 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes:

Test Description:

Test 49 - TLE Out - IOUTB E0 P Off

I2C Communication Error: PCB1 Temp Sensor 0x48

PCB Serial Number:

OBI04W30173D

-0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** 0.000239 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 50 - TLE Out - IOUTB_E0_P On PCB Serial Number: OBI04W30173D **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.696173 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 51 - TLE Out - IOUTB_E0_N Off PCB Serial Number: OBI04W30173D **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000

Test Lower Limit:

Test Measurement: 0.000883 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 52 - TLE Out - IOUTB_E0_N On PCB Serial Number: OBI04W30173D **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.716792 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 53 - TLE Out - IOUTB E1 P Off PCB Serial Number: OBI04W30173D Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000561 Units: **VDC**

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 54 - TLE Out - IOUTB_E1_P On

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.720980

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 55 - TLE Out - IOUTB_E1_N Off

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

-0.000084

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Test

Vision Detector PCB Assembly Test Report OBI04W30173_20250610135352.pdf

| Fail Notes: |
|--|
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| Test Description: Test 56 - TLE Out - IOUTB_E1_N On PCB Serial Number: OBI04W30173D Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.730968 Units: VDC Starting Temperature (Max 50.00 C): |
| IC1: 26.812, IC2: 0.000; Temp Check Fail - Abort Tes Ending Temperature (Max 50.00 C): IC1: 27.312, IC2: 0.000; Temp Check Fail - Abort Tes Test Result: Fail |
| Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 |
| Test Description: Test 57 - TLE Out - IOUTA_Y_P Off PCB Serial Number: OBI04W30173C Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000770 Units: VDC Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass |
| |

Test Description:

Test 58 - TLE Out - IOUTA_Y_P On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.728376 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 59 - TLE Out - IOUTA_Y_N Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000196 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 60 - TLE Out - IOUTA_Y_N On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.744481 Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 27.312; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 61 - TLE Out - IOUTA_X_P Off

PCB Serial Number:

OBI04W30173C

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

0.000770

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 27.312; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 62 - TLE Out - IOUTA_X_P On

PCB Serial Number:

OBI04W30173C

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.713881

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 27.312; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 63 - TLE Out - IOUTA_X_N Off

PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000126 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 64 - TLE Out - IOUTA_X_N On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.714525 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 65 - TLE Out - IOUTA E0 P Off PCB Serial Number: OBI04W30173C Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000126 Units: **VDC**

Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass **Test Description:** Test 66 - TLE Out - IOUTA_E0_P On PCB Serial Number: OBI04W30173C Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.720967 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 67 - TLE Out - IOUTA_E0_N Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000196 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result:

Pass

Test Description:

Test 68 - TLE Out - IOUTA_E0_N On

PCB Serial Number:

OBI04W30173C **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.730308 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 69 - TLE Out - IOUTA_E1_P Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 **Test Measurement:** -0.000196 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 70 - TLE Out - IOUTA_E1_P On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.720645 Units: **VDC** Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 27.312; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 71 - TLE Out - IOUTA_E1_N Off

PCB Serial Number:

OBI04W30173C

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

0.000770

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 27.312; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 72 - TLE Out - IOUTA_E1_N On

PCB Serial Number:

OBI04W30173C

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.742548

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 27.312; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 73 - TLE Out - IOUTB Y P Off

PCB Serial Number:

OBI04W30173C

Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** 0.000126 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 74 - TLE Out - IOUTB_Y_P On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.696165 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 75 - TLE Out - IOUTB_Y_N Off PCB Serial Number: OBI04W30173C Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000126 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass **Test Description:** Test 76 - TLE Out - IOUTB_Y_N On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.740938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 77 - TLE Out - IOUTB_X_P Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000770 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 78 - TLE Out - IOUTB_X_P On PCB Serial Number:

OBI04W30173C
Test Lower Limit:

2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.708405 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 79 - TLE Out - IOUTB X N Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000448 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 80 - TLE Out - IOUTB X N On PCB Serial Number: OBI04W30173C Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.728698 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 81 - TLE Out - IOUTB_E0_P Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000126 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 82 - TLE Out - IOUTB_E0_P On PCB Serial Number: OBI04W30173C **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.714203 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 83 - TLE Out - IOUTB_E0_N Off PCB Serial Number: OBI04W30173C Test Lower Limit:

-0.100000

0.100000 Test Measurement: 0.000448 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 84 - TLE Out - IOUTB_E0_N On PCB Serial Number: OBI04W30173C Test Lower Limit: 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.722900 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass Test Description: Test 85 - TLE Out - IOUTB_E1_P Off PCB Serial Number: OBI04W30173C **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000126 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass

Test Upper Limit:

| Test Result: Pass |
|---|
| Test Description: Test 86 - TLE Out - IOUTB_E1_P On PCB Serial Number: OBI04W30173C Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.728698 Units: VDC Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass |
| Test Description: Test 87 - TLE Out - IOUTB_E1_N Off PCB Serial Number: OBI04W30173C Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000126 Units: VDC Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: Pass |
| Test Description: Test 88 - TLE Out - IOUTB_E1_N On PCB Serial Number: OBI04W30173C Test Lower Limit: 2.500000 Test Upper Limit: |

2.800000 Test Measurement: 2.710015 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 27.312; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 27.562; Temp OK - Pass Test Result: **Pass** Test Description: Test 89 - TLE Out - IOUTA Y P Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** -0.000318 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 90 - TLE Out - IOUTA_Y_P On PCB Serial Number: OBI04W30173B Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.731169 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description: Test 91 - TLE Out - IOUTA_Y_N Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** -0.000962 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass** Test Description: Test 92 - TLE Out - IOUTA_Y_N On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.733747 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 93 - TLE Out - IOUTA_X_P Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit:

0.100000

Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 94 - TLE Out - IOUTA_X_P On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 **Test Measurement:** 2.708294 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass** Test Description: Test 95 - TLE Out - IOUTA_X_N Off PCB Serial Number: OBI04W30173B Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: -0.000640 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass

Test Measurement:

-0.000318

Test Description: Test 96 - TLE Out - IOUTA X N On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 **Test Measurement:** 2.716026 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 97 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000326 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 98 - TLE Out - IOUTA_E0_P On PCB Serial Number: OBI04W30173B Test Lower Limit: 2.500000

Page 42 of 112

Test Measurement:

Test Upper Limit:

2.800000

2.697340 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 99 - TLE Out - IOUTA_E0_N Off PCB Serial Number: OBI04W30173B Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000326 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 100 - TLE Out - IOUTA_E0_N On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.728592 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass**

PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000004 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass Test Description:** Test 102 - TLE Out - IOUTA_E1_P On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.712482 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass **Test Description:** Test 103 - TLE Out - IOUTA_E1_N Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000326

Test Description:

Test 101 - TLE Out - IOUTA_E1_P Off

VDC Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass** Test Description: Test 104 - TLE Out - IOUTA E1 N On PCB Serial Number: OBI04W30173B Test Lower Limit: 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.726336 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 105 - TLE Out - IOUTB Y P Off PCB Serial Number: OBI04W30173B Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.000004 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass

Units:

6/10/2025 1:58:57

Test Description:

Test 106 - TLE Out - IOUTB_Y_P On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.709905 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 107 - TLE Out - IOUTB_Y_N Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000318 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass **Test Description:** Test 108 - TLE Out - IOUTB_Y_N On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.738257 Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 28.000, IC2: 27.750; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 109 - TLE Out - IOUTB_X_P Off

PCB Serial Number:

OBI04W30173B

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

0.000326

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 28.000, IC2: 27.750; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 110 - TLE Out - IOUTB_X_P On

PCB Serial Number:

OBI04W30173B

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.697017

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 28.000, IC2: 27.750; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 111 - TLE Out - IOUTB_X_N Off

PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000318 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 112 - TLE Out - IOUTB_X_N On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.725048 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 113 - TLE Out - IOUTB E0 P Off PCB Serial Number: OBI04W30173B Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000004 Units: **VDC**

Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass **Test Description:** Test 114 - TLE Out - IOUTB_E0_P On PCB Serial Number: OBI04W30173B Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.704106 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 115 - TLE Out - IOUTB_E0_N Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: -0.000640 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass** Test Description:

6/10/2025 1:58:57

PCB Serial Number:

Test 116 - TLE Out - IOUTB_E0_N On

OBI04W30173B **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.745990 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: **Pass** Test Description: Test 117 - TLE Out - IOUTB_E1_P Off PCB Serial Number: OBI04W30173B **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 **Test Measurement:** 0.000326 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.000; Temp OK - Pass Test Result: Pass Test Description: Test 118 - TLE Out - IOUTB_E1_P On PCB Serial Number: OBI04W30173B **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.706683 Units: **VDC** Starting Temperature (Max 50.00 C):

IC1: 28.000, IC2: 27.750; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 119 - TLE Out - IOUTB_E1_N Off

PCB Serial Number:

OBI04W30173B

Test Lower Limit:

-0.100000

Test Upper Limit:

0.100000

Test Measurement:

-0.000318

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 28.000, IC2: 27.750; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 120 - TLE Out - IOUTB_E1_N On

PCB Serial Number:

OBI04W30173B

Test Lower Limit:

2.500000

Test Upper Limit:

2.800000

Test Measurement:

2.722148

Units:

VDC

Starting Temperature (Max 50.00 C):

IC1: 28.000, IC2: 27.750; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 28.375, IC2: 28.000; Temp OK - Pass

Test Result:

Pass

Test Description:

Test 121 - TLE Out - IOUTA Y P Off

PCB Serial Number:

OBI04W30173A

Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 122 - TLE Out - IOUTA_Y_P On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.722830 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 123 - TLE Out - IOUTA_Y_N Off PCB Serial Number: OBI04W30173A Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 124 - TLE Out - IOUTA_Y_N On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.716705 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 125 - TLE Out - IOUTA_X_P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 126 - TLE Out - IOUTA_X_P On

PCB Serial Number:

OBI04W30173A

Test Lower Limit:

2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.710580 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 127 - TLE Out - IOUTA X N Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 128 - TLE Out - IOUTA X N On PCB Serial Number: OBI04W30173A Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.730567 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass** Test Description: Test 129 - TLE Out - IOUTA_E0_P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 **Test Measurement:** 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 130 - TLE Out - IOUTA_E0_P On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.710257 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass** Test Description: Test 131 - TLE Out - IOUTA_E0_N Off PCB Serial Number: OBI04W30173A Test Lower Limit:

-0.100000

0.100000 Test Measurement: 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 132 - TLE Out - IOUTA_E0_N On PCB Serial Number: OBI04W30173A Test Lower Limit: 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.704132 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 133 - TLE Out - IOUTA_E1_P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.002260 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass

Test Upper Limit:

| Test Result: Pass |
|--|
| Test Description: Test 134 - TLE Out - IOUTA_E1_P On PCB Serial Number: OBI04W30173A Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.719284 Units: VDC Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass |
| Test Description: Test 135 - TLE Out - IOUTA_E1_N Off PCB Serial Number: OBI04W30173A Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.001293 Units: VDC Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass |
| Test Description: Test 136 - TLE Out - IOUTA_E1_N On PCB Serial Number: OBI04W30173A Test Lower Limit: 2.500000 Test Upper Limit: |

2.800000 Test Measurement: 2.733147 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 137 - TLE Out - IOUTB Y P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 138 - TLE Out - IOUTB_Y_P On PCB Serial Number: OBI04W30173A Test Lower Limit: 2.500000 Test Upper Limit: 2.800000 **Test Measurement:** 2.692526 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass

Test Result:

Pass

Test Description: Test 139 - TLE Out - IOUTB_Y_N Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 **Test Upper Limit:** 0.100000 **Test Measurement:** 0.002260 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 140 - TLE Out - IOUTB_Y_N On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.692849 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 141 - TLE Out - IOUTB_X_P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 Test Upper Limit:

0.100000

VDC Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 142 - TLE Out - IOUTB_X_P On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 **Test Measurement:** 2.687046 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 143 - TLE Out - IOUTB_X_N Off PCB Serial Number: OBI04W30173A Test Lower Limit: -0.100000 **Test Upper Limit:** 0.100000 Test Measurement: 0.000971 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass

Test Measurement:

0.002260 Units: Test Description: Test 144 - TLE Out - IOUTB_X_N On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 **Test Measurement:** 2.703810 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 145 - TLE Out - IOUTB_E0_P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.001293 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 146 - TLE Out - IOUTB E0 P On PCB Serial Number: OBI04W30173A

6/10/2025 1:58:57 PM

Page 61 of 112

Test Lower Limit:

Test Upper Limit:

Test Measurement:

2.500000

2.800000

2.715093 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 147 - TLE Out - IOUTB_E0_N Off PCB Serial Number: OBI04W30173A Test Lower Limit: -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.001938 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 148 - TLE Out - IOUTB_E0_N On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 **Test Upper Limit:** 2.800000 Test Measurement: 2.733791 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result:

Pass

Test 149 - TLE Out - IOUTB_E1_P Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.002583 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass Test Description:** Test 150 - TLE Out - IOUTB_E1_P On PCB Serial Number: OBI04W30173A **Test Lower Limit:** 2.500000 Test Upper Limit: 2.800000 Test Measurement: 2.716705 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass **Test Description:** Test 151 - TLE Out - IOUTB_E1_N Off PCB Serial Number: OBI04W30173A **Test Lower Limit:** -0.100000 Test Upper Limit: 0.100000 Test Measurement: 0.001293

Test Description:

Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: **Pass** Test Description: Test 152 - TLE Out - IOUTB E1 N On PCB Serial Number: OBI04W30173A Test Lower Limit: 2.500000 **Test Upper Limit:** 2.800000 **Test Measurement:** 2.726054 Units: **VDC** Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.000; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.187; Temp OK - Pass Test Result: Pass Test Description: Test 153 - RF Amp & ASIC Trigger Test, ASIC 0 PCB Serial Number: OBI04W30173D Test Lower Limit: N/A Test Upper Limit: 100.000000 (mV) Test Measurement: Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description: Test 154 - RF Amp & ASIC Trigger Test, ASIC 1 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 **Test Description:** Test 155 - RF Amp & ASIC Trigger Test, ASIC 2 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes:

Test Description:

Test 156 - RF Amp & ASIC Trigger Test, ASIC 3

I2C Communication Error: PCB1 Temp Sensor 0x48

Vision Detector PCB Assembly Test Report OBI04W30173_20250610135352.pdf

PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Fail Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: 0 Pulse(s), Pulse Width (ns): 0 I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 157 - RF Amp & ASIC Trigger Test, ASIC 4 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) Test Measurement: Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 **Test Description:**

Test 158 - RF Amp & ASIC Trigger Test, ASIC 5

PCB Serial Number: OBI04W30173D

Test Lower Limit:

Vision Detector PCB Assembly Test Report OBI04W30173_20250610135352.pdf

| N/A |
|---|
| Test Upper Limit: |
| 100.000000 (mV) |
| Test Measurement: |
| Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments |
| Units: |
| mVDC |
| Starting Temperature (Max 50.00 C): |
| IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| 120 Communication Ends. 1 CB1 Temp Censor 0x40 |
| |
| Test Description: |
| Test 159 - RF Amp & ASIC Trigger Test, ASIC 6 |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| 100.000000 (mV) |
| Test Measurement: |
| Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: |
| mVDC |
| Starting Temperature (Max 50.00 C): |
| IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| |
| Total Descriptions |
| Test Description: Test 160 - PE Amp & ASIC Trigger Test ASIC 7 |
| Test 160 - RF Amp & ASIC Trigger Test, ASIC 7 PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| 100.000000 (mV) |

Test Measurement:

Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 27.062, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 28.625, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 **Test Description:** Test 161 - RF Amp & ASIC Trigger Test, ASIC 0 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.562, IC2: 27.437; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.312, IC2: 29.000; Temp OK - Pass Test Result: **Pass Test Description:** Test 162 - RF Amp & ASIC Trigger Test, ASIC 1 PCB Serial Number: OBI04W30173C **Test Lower Limit:** N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.562, IC2: 27.437; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 29.312, IC2: 29.000; Temp OK - Pass

| Test Result: |
|--|
| Pass |
| |
| Test Description: |
| · |
| Test 163 - RF Amp & ASIC Trigger Test, ASIC 2 |
| PCB Serial Number: |
| OBI04W30173C |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| • • |
| 100.000000 (mV) |
| Test Measurement: |
| Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments |
| Units: |
| mVDC |
| Starting Temperature (Max 50.00 C): |
| |
| IC1: 27.562, IC2: 27.437; Temp OK - Pass |
| Ending Temperature (Max 50.00 C): |
| IC1: 29.312, IC2: 29.000; Temp OK - Pass |
| Test Result: |
| Pass |
| |
| Test Description: |
| · |
| Test 164 - RF Amp & ASIC Trigger Test, ASIC 3 |
| PCB Serial Number: |
| OBI04W30173C |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| 100.000000 (mV) |
| , |
| Test Measurement: |
| Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments |
| Units: |
| mVDC |
| Starting Temperature (Max 50.00 C): |
| IC1: 27.562, IC2: 27.437; Temp OK - Pass |
| Ending Temperature (Max 50.00 C): |
| |
| IC1: 29.312, IC2: 29.000; Temp OK - Pass |
| Test Result: |
| Pass |
| |
| Test Description: |
| Test 165 - RF Amp & ASIC Trigger Test, ASIC 4 |
| PCB Serial Number: |
| |
| OBI04W30173C |
| Test Lower Limit: |
| N/A |

Test Upper Limit:

```
100.000000 (mV)
Test Measurement:
Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments
Units:
mVDC
Starting Temperature (Max 50.00 C):
IC1: 27.562, IC2: 27.437; Temp OK - Pass
Ending Temperature (Max 50.00 C):
IC1: 29.312, IC2: 29.000; Temp OK - Pass
Test Result:
Pass
Test Description:
Test 166 - RF Amp & ASIC Trigger Test, ASIC 5
PCB Serial Number:
OBI04W30173C
Test Lower Limit:
N/A
Test Upper Limit:
100.000000 (mV)
Test Measurement:
Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments
Units:
mVDC
Starting Temperature (Max 50.00 C):
IC1: 27.562, IC2: 27.437; Temp OK - Pass
Ending Temperature (Max 50.00 C):
IC1: 29.312, IC2: 29.000; Temp OK - Pass
Test Result:
Pass
Test Description:
Test 167 - RF Amp & ASIC Trigger Test, ASIC 6
PCB Serial Number:
OBI04W30173C
Test Lower Limit:
N/A
Test Upper Limit:
100.000000 (mV)
Test Measurement:
Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments
Units:
mVDC
Starting Temperature (Max 50.00 C):
IC1: 27.562, IC2: 27.437; Temp OK - Pass
Ending Temperature (Max 50.00 C):
```

Test Result:

IC1: 29.312, IC2: 29.000; Temp OK - Pass

Pass

Test Description: Test 168 - RF Amp & ASIC Trigger Test, ASIC 7 PCB Serial Number: OBI04W30173C **Test Lower Limit:** N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.562, IC2: 27.437; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.312, IC2: 29.000; Temp OK - Pass Test Result: **Pass** Test Description: Test 169 - RF Amp & ASIC Trigger Test, ASIC 0 PCB Serial Number: OBI04W30173B **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 27.875, IC2: 27.625; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.000; Temp OK - Pass Test Result: **Pass Test Description:** Test 170 - RF Amp & ASIC Trigger Test, ASIC 1 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit:

100.000000 (mV)

```
Test Measurement:
Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments
Units:
mVDC
Starting Temperature (Max 50.00 C):
IC1: 27.875, IC2: 27.625; Temp OK - Pass
Ending Temperature (Max 50.00 C):
IC1: 29.500, IC2: 29.000; Temp OK - Pass
Test Result:
Pass
Test Description:
Test 171 - RF Amp & ASIC Trigger Test, ASIC 2
PCB Serial Number:
OBI04W30173B
Test Lower Limit:
N/A
Test Upper Limit:
100.000000 (mV)
Test Measurement:
Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments
Units:
mVDC
Starting Temperature (Max 50.00 C):
IC1: 27.875, IC2: 27.625; Temp OK - Pass
Ending Temperature (Max 50.00 C):
IC1: 29.500, IC2: 29.000; Temp OK - Pass
Test Result:
Pass
Test Description:
Test 172 - RF Amp & ASIC Trigger Test, ASIC 3
PCB Serial Number:
OBI04W30173B
Test Lower Limit:
N/A
Test Upper Limit:
100.000000 (mV)
Test Measurement:
Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments
Units:
mVDC
Starting Temperature (Max 50.00 C):
IC1: 27.875, IC2: 27.625; Temp OK - Pass
Ending Temperature (Max 50.00 C):
IC1: 29.500, IC2: 29.000; Temp OK - Pass
```

Pass

Test Result:

Page 72 of 112

Test Description: Test 173 - RF Amp & ASIC Trigger Test, ASIC 4 PCB Serial Number: OBI04W30173B **Test Lower Limit:** N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 27.875, IC2: 27.625; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.000; Temp OK - Pass Test Result: Pass Test Description: Test 174 - RF Amp & ASIC Trigger Test, ASIC 5 PCB Serial Number: OBI04W30173B **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) Test Measurement: Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 27.875, IC2: 27.625; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.000; Temp OK - Pass Test Result: **Pass** Test Description: Test 175 - RF Amp & ASIC Trigger Test, ASIC 6 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: 100.000000 (mV)

Test Measurement:

Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 27.875, IC2: 27.625; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.000; Temp OK - Pass Test Result: **Pass Test Description:** Test 176 - RF Amp & ASIC Trigger Test, ASIC 7 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A **Test Upper Limit:** 100.000000 (mV) Test Measurement: Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 27.875, IC2: 27.625; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.000; Temp OK - Pass Test Result: Pass **Test Description:** Test 177 - RF Amp & ASIC Trigger Test, ASIC 0 PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: **Pass**

Test Description: Test 178 - RF Amp & ASIC Trigger Test, ASIC 1 PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) Test Measurement: Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: **Pass Test Description:** Test 179 - RF Amp & ASIC Trigger Test, ASIC 2 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: 100.000000 (mV) Test Measurement: Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: **Pass** Test Description: Test 180 - RF Amp & ASIC Trigger Test, ASIC 3 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:**

Page 75 of 112

Fail

Units: mVDC Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: Fail Notes: 0 Pulse(s), Pulse Width (ns): 0 Test Description: Test 181 - RF Amp & ASIC Trigger Test, ASIC 4 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: Pass Test Description: Test 182 - RF Amp & ASIC Trigger Test, ASIC 5 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: mVDC Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result:

Pass

Test Description: Test 183 - RF Amp & ASIC Trigger Test, ASIC 6 PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A **Test Upper Limit:** 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: **Pass** Test Description: Test 184 - RF Amp & ASIC Trigger Test, ASIC 7 PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: 100.000000 (mV) **Test Measurement:** Pass - Successfully triggered from 100.000000 to 10.000000 (mV) in 10.000000 (mV) Increments Units: **mVDC** Starting Temperature (Max 50.00 C): IC1: 26.937, IC2: 26.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.125; Temp OK - Pass Test Result: **Pass Test Description:** Test 185 - I2C Reset Test PCB Serial Number: OBI04W30173D Test Lower Limit:

Page 77 of 112

N/A

N/A

Test Upper Limit:

Test Measurement: I2C Reset failed on Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.250, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 186 - I2C Reset Test PCB Serial Number: OBI04W30173C **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: I2C Reset Successful Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.062, IC2: 27.937; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.500, IC2: 28.250; Temp OK - Pass Test Result: **Pass** Test Description: Test 187 - I2C Reset Test PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: I2C Reset Successful Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.375, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 28.875, IC2: 28.437; Temp OK - Pass Test Result: Pass Test Description: Test 188 - I2C Reset Test PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: I2C Reset Successful Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.500, IC2: 27.437; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.750; Temp OK - Pass Test Result: Pass Test Description: Test 189 - External LED Reset Test, ASIC 0 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered

I2C Communication Error: PCB1 Temp Sensor 0x48

Test 190 - External LED Reset Test, ASIC 1 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 191 - External LED Reset Test, ASIC 2 PCB Serial Number: OBI04W30173D Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test Description: Test 192 - External LED Reset Test, ASIC 3 PCB Serial Number: OBI04W30173D Test Lower Limit: N/A **Test Upper Limit:** N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: Initial Trigger: 0 Pulse(s), Pulse Width (ns): 0 Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): 0 Pulse(s), Pulse Width (ns): 0 I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 193 - External LED Reset Test, ASIC 4 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 194 - External LED Reset Test, ASIC 5 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 195 - External LED Reset Test, ASIC 6 PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test Test Result:

Fail Notes: Initial Trigger: ASIC Successfully Triggered

Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0

Third Trigger (Reset): ASIC Successfully Triggered I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 196 - External LED Reset Test, ASIC 7

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

N/A

Test Upper Limit:

N/A

Test Measurement:

Fail

Units:

N/A

Starting Temperature (Max 50.00 C):

IC1: 27.375, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 29.562, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

Initial Trigger: ASIC Successfully Triggered

Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0

Third Trigger (Reset): ASIC Successfully Triggered I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 197 - External LED Reset Test, ASIC 0

PCB Serial Number:

OBI04W30173C

Test Lower Limit:

N/A

Test Upper Limit:

N/A

Test Measurement:

Pass

Units:

N/A

Starting Temperature (Max 50.00 C):

IC1: 27.937, IC2: 27.812; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 29.500, IC2: 29.125; Temp OK - Pass

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 198 - External LED Reset Test, ASIC 1 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: **Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 199 - External LED Reset Test, ASIC 2 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: **Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 200 - External LED Reset Test, ASIC 3 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: **Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 201 - External LED Reset Test, ASIC 4 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: **Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 202 - External LED Reset Test, ASIC 5 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 203 - External LED Reset Test, ASIC 6 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 204 - External LED Reset Test, ASIC 7 PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.937, IC2: 27.812; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.500, IC2: 29.125; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 205 - External LED Reset Test, ASIC 0 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 206 - External LED Reset Test, ASIC 1 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Pass Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.812, IC2: 29.312; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 207 - External LED Reset Test, ASIC 2 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 208 - External LED Reset Test, ASIC 3 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Pass Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.812, IC2: 29.312; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 209 - External LED Reset Test, ASIC 4 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 210 - External LED Reset Test, ASIC 5 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Pass Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.812, IC2: 29.312; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 211 - External LED Reset Test, ASIC 6 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 212 - External LED Reset Test, ASIC 7 PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Pass Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.125, IC2: 27.875; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.812, IC2: 29.312; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 213 - External LED Reset Test, ASIC 0 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 214 - External LED Reset Test, ASIC 1 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Pass Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.062; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 215 - External LED Reset Test, ASIC 2 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 216 - External LED Reset Test, ASIC 3 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Fail Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.062; Temp OK - Pass Test Result: Fail Notes: Initial Trigger: 0 Pulse(s), Pulse Width (ns): 0 Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): 0 Pulse(s), Pulse Width (ns): 0 Test Description: Test 217 - External LED Reset Test, ASIC 4 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 218 - External LED Reset Test, ASIC 5 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement:** Pass Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.062; Temp OK - Pass Test Result: Pass Notes: Initial Trigger: ASIC Successfully Triggered Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0 Third Trigger (Reset): ASIC Successfully Triggered Test Description: Test 219 - External LED Reset Test, ASIC 6 PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A **Test Measurement: Pass** Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.125, IC2: 27.062; Temp OK - Pass Ending Temperature (Max 50.00 C):

Test Result:

Pass

Notes:

Initial Trigger: ASIC Successfully Triggered

Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0

Third Trigger (Reset): ASIC Successfully Triggered

Test Description:

Test 220 - External LED Reset Test, ASIC 7

PCB Serial Number:

OBI04W30173A

Test Lower Limit:

N/A

Test Upper Limit:

N/A

Test Measurement:

Pass

Units:

N/A

Starting Temperature (Max 50.00 C):

IC1: 27.125, IC2: 27.062; Temp OK - Pass

Ending Temperature (Max 50.00 C):

IC1: 29.375, IC2: 29.062; Temp OK - Pass

Test Result:

Pass

Notes:

Initial Trigger: ASIC Successfully Triggered

Second Trigger (Not Reset): 0 Pulse(s), Pulse Width (ns): 0

Third Trigger (Reset): ASIC Successfully Triggered

Test Description:

Test 221 - ASIC 0 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

N/A

Test Upper Limit:

N/A

Test Measurement:

Low 0x41, Mid 0x93, High 0xC7

Units:

N/A

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test

Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 **Test Description:** Test 222 - ASIC 1 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A **Test Measurement:** Low 0x40, Mid 0x91, High 0xC6 Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 223 - ASIC 2 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173D **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x92, High 0xC8 Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test Test Result:

6/10/2025 1:58:57

I2C Communication Error: PCB1 Temp Sensor 0x48

Fail Notes: Test Description:

Test 224 - ASIC 3 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

N/A

Test Upper Limit:

N/A

Test Measurement:

Low 0x41, Mid 0x92, High 0xC6

Units:

N/A

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 225 - ASIC 4 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC

PCB Serial Number:

OBI04W30173D

Test Lower Limit:

N/A

Test Upper Limit:

N/A

Test Measurement:

Low 0x40, Mid 0x91, High 0xC6

Units:

N/A

Starting Temperature (Max 50.00 C):

IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test

Ending Temperature (Max 50.00 C):

IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test

Test Result:

Fail

Notes:

I2C Communication Error: PCB1 Temp Sensor 0x48

Test Description:

Test 226 - ASIC 5 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC

PCB Serial Number:

| Test Lower Limit: |
|---|
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low 0x3F, Mid 0x8F, High 0xC3 |
| Units: |
| N/A |
| Starting Temperature (Max 50.00 C): |
| IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| · |
| |
| Test Description: |
| Test 227 - ASIC 6 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low 0x3F, Mid 0x8F, High 0xC3 |
| Units: |
| N/A |
| Starting Temperature (Max 50.00 C): |
| IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test |
| Ending Temperature (Max 50.00 C): |
| IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test |
| Test Result: |
| Fail |
| Notes: |
| I2C Communication Error: PCB1 Temp Sensor 0x48 |
| |
| |
| Test Description: |
| Test 228 - ASIC 7 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC |
| PCB Serial Number: |
| OBI04W30173D |
| Test Lower Limit: |
| N/A |

Test Upper Limit:

OBI04W30173D

N/A Test Measurement: Low 0x41, Mid 0x94, High 0xCA Units: N/A Starting Temperature (Max 50.00 C): IC1: 27.437, IC2: 0.000; Temp Check Fail - Abort Test Ending Temperature (Max 50.00 C): IC1: 27.812, IC2: 0.000; Temp Check Fail - Abort Test Test Result: Fail Notes: I2C Communication Error: PCB1 Temp Sensor 0x48 Test Description: Test 229 - ASIC 0 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x94, High 0xC9 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: Pass **Test Description:** Test 230 - ASIC 1 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x90, High 0xC4 Units: N/A

Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass

Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: Pass **Test Description:** Test 231 - ASIC 2 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x8F, High 0xC3 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: Pass Test Description: Test 232 - ASIC 3 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x3E, Mid 0x90, High 0xC3 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: **Pass Test Description:** Test 233 - ASIC 4 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C

Test Lower Limit:

N/A Test Upper Limit: N/A Test Measurement: Low 0x41, Mid 0x92, High 0xC7 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: Pass **Test Description:** Test 234 - ASIC 5 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x93, High 0xC8 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: **Pass** Test Description: Test 235 - ASIC 6 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x91, High 0xC6 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: Pass Test Description: Test 236 - ASIC 7 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173C **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x90, High 0xC5 Units: N/A Starting Temperature (Max 50.00 C): IC1: 28.312, IC2: 28.125; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 28.562, IC2: 28.312; Temp OK - Pass Test Result: Pass Test Description: Test 237 - ASIC 0 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173B **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x90, High 0xC4 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.375; Temp OK - Pass Test Result: **Pass** Test Description: Test 238 - ASIC 1 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173B Test Lower Limit:

N/A

Test Upper Limit: N/A Test Measurement: Low 0x3F, Mid 0x93, High 0xC7 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.375; Temp OK - Pass Test Result: **Pass Test Description:** Test 239 - ASIC 2 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x91, High 0xC5 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.375; Temp OK - Pass Test Result: **Pass Test Description:** Test 240 - ASIC 3 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173B **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x90, High 0xC3 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.187; Temp OK - Pass Ending Temperature (Max 50.00 C):

IC1: 29.687, IC2: 29.375; Temp OK - Pass

| Test Result: |
|---|
| Pass |
| Test Description: |
| Test 241 - ASIC 4 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC |
| PCB Serial Number: |
| OBI04W30173B |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low 0x41, Mid 0x94, High 0xC9 |
| Units: |
| N/A |
| Starting Temperature (Max 50.00 C): |
| IC1: 29.375, IC2: 29.187; Temp OK - Pass |
| Ending Temperature (Max 50.00 C): |
| IC1: 29.687, IC2: 29.375; Temp OK - Pass |
| Test Result: |
| Pass |
| Test Description: |
| Test 242 - ASIC 5 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC |
| PCB Serial Number: |
| OBI04W30173B |
| Test Lower Limit: |
| N/A |
| Test Upper Limit: |
| N/A |
| Test Measurement: |
| Low 0x40, Mid 0x96, High 0xCE |
| Units: |
| N/A |
| Starting Temperature (Max 50.00 C): |
| IC1: 29.375, IC2: 29.187; Temp OK - Pass |
| Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.375; Temp OK - Pass |
| Test Result: |
| Pass |
| 1 433 |
| Test Description: |
| Test 243 - ASIC 6 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC |
| PCB Serial Number: |
| OBI04W30173B |
| Test Lower Limit: |
| N/A |

Test Upper Limit:

N/A Test Measurement: Low 0x41, Mid 0x93, High 0xC8 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.375; Temp OK - Pass Test Result: **Pass** Test Description: Test 244 - ASIC 7 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x3D, Mid 0x8A, High 0xBD Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.375, IC2: 29.187; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.375; Temp OK - Pass Test Result: Pass Test Description: Test 245 - ASIC 0 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x41, Mid 0x95, High 0xCB Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C):

6/10/2025 1:58:57

Test Result:

IC1: 29.687, IC2: 29.687; Temp OK - Pass

Pass

Test Description:

Test 246 - ASIC 1 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A Test Lower Limit: N/A **Test Upper Limit:** N/A Test Measurement: Low 0x40, Mid 0x8F, High 0xC3 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result: Pass Test Description: Test 247 - ASIC 2 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x42, Mid 0x96, High 0xCF Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result: **Pass Test Description:** Test 248 - ASIC 3 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A

Test Measurement: Low 0x40, Mid 0x8E, High 0xC3 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result: **Pass Test Description:** Test 249 - ASIC 4 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x41, Mid 0x93, High 0xC8 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result: **Pass** Test Description: Test 250 - ASIC 5 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x92, High 0xC6 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result:

Pass

Test Description: Test 251 - ASIC 6 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x91, High 0xC4 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result: Pass Test Description: Test 252 - ASIC 7 Calibrate Register Values at 1.0VDC, 2.0VDC, 2.6VDC PCB Serial Number: OBI04W30173A **Test Lower Limit:** N/A Test Upper Limit: N/A Test Measurement: Low 0x40, Mid 0x8E, High 0xC1 Units: N/A Starting Temperature (Max 50.00 C): IC1: 29.562, IC2: 29.687; Temp OK - Pass Ending Temperature (Max 50.00 C): IC1: 29.687, IC2: 29.687; Temp OK - Pass Test Result: Pass Test Description: Test 253 - Write Data to EEPROM PCB Serial Number: OBI04W30173D Test Lower Limit: N/A Test Upper Limit: N/A

Test Measurement:

| Starting Temperature : N/A Ending Temperature : N/A Test Result: Fail |
|--|
| Test Description: Test 254 - Write Data to EEPROM PCB Serial Number: OBI04W30173C Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Data Write to EEPROM Successful Units: N/A Starting Temperature: N/A Ending Temperature: N/A Test Result: Pass |
| Test Description: Test 255 - Write Data to EEPROM PCB Serial Number: OBI04W30173B Test Lower Limit: N/A Test Upper Limit: N/A Test Measurement: Data Write to EEPROM Successful Units: N/A Starting Temperature : N/A Ending Temperature : N/A Test Result: Pass |
| Test Description: Test 256 - Write Data to EEPROM PCB Serial Number: OBI04W30173A Test Lower Limit: N/A |

Data Write to EEPROM Failed

Units: N/A

Test Upper Limit:

N/A

Test Measurement:

Data Write to EEPROM Failed

Units:

N/A

Starting Temperature : N/A Ending Temperature : N/A

Test Result:

Fail

Test Parameters:

Test Station="OSP_PCB_FT_01"

[PCB Current]

Set DC Voltage (V)="5.000"

Set DC Current Limit (A)="4.000"

Upper Voltage Limit="5.100"

Lower Voltage Limit="4.900"

Power Off Upper Current Limit="2.300"

Power Off Lower Current Limit="2.100"

Power On Upper Current Limit="2.650"

Power On Lower Current Limit="2.450"

ASIC Loaded Upper Current Limit="3.000"

ASIC Loaded Lower Current Limit="2.700"

[DAC Calibration]

DAC Calibration Tolerance="0.015"

Low Voltage Value="1.000"

Mid Voltage Value="2.000"

High Voltage Value="2.600"

Overtemp Threshold="50.000"

Detector Power On Delay="0.100"

[TLE In/Out]

ASIC Off High Limit="0.100"

ASIC Off Low Limit="-0.100"

ASIC On High Limit="0.700"

ASIC On Low Limit="0.480"

ASIC Bias High Limit="2.800"

ASIC Bias Low Limit="2.500"

[RF Amp & ASIC Test & LED Reset]

Starting Pulse Amplitude (mV)="100.000"

Decreasing Trigger Delta (mV)="10.000"

Pulse Width (ns)="10.000"

Trigger Width Lower Limit (ns)="40.000"

Trigger Width Upper Limit (ns)="60.000"

Number of Acceptable Pulses="1.000"

[File Locations]

Test Report Folder Location="C:\Test Reports"

.tar File Folder Location="C:\Tars"

[Tests to Perform]

PCB Current Test="TRUE"

EEPROM Test="TRUE"

TLE In Test="FALSE"
TLE Out Test="TRUE"
RF Amps & ASICs Test="TRUE"
Reset Test="TRUE"
Calibrate DACs Test="TRUE"

[PCBs to Test]
Test PCB1="TRUE"
Test PCB2="TRUE"
Test PCB3="TRUE"
Test PCB4="TRUE"

[Part Number]

O="10748016"

R="10752680"

[Manufacturer]

A="IES"

B="Jabil"

C="Epic"

D="CV"

Z="Prototype"

[Year]

A="2009"

B="2010"

C="2011"

D="2012"

E="2013"

F="2014"

G="2015"

0= 2010

H="2016"

I="2017"

J="2018"

K="2019"

L="2020"

M="2021"

N="2022"

O="2023"

P="2024"

Q="2025"

[Dogbone]

10748016="standard"

10752680="dogbone"