

Valid Expressions

$S \rightarrow$ HELP
 | PRINT
 | LEVELS AEXP₁
 | LIST
 | SUBSET_DATAFRAME AEXP₂
 | REMOVE
 | ELEMENT_NAMES
 | READ
 | WRITE
 | SAVE

$V \rightarrow$ VAR V'

$V' \rightarrow V_1 \mid [V_2]$

$V_1 \rightarrow$ ASSIGN EXP
 | eps
 | AFTER_VAR
 | SL
 | SD

$V_2 \rightarrow$ -EE₂
 | SE₂
 | SM₁
 | S₂
 | EX₂

AEXP₁ \rightarrow ASSIGN VECTOR | eps

AEXP₂ \rightarrow ASSIGN VAR | eps

Help

$$\begin{aligned} \text{HELP} &\rightarrow \text{?CHaine} \mid \text{help(H1} \\ \text{H1} &\rightarrow \text{CHaine)} \\ &\mid \text{"H2} \\ \text{H2} &\rightarrow \text{CHaine")} \mid \text{"*")} \end{aligned}$$

Basic arithmetic operations

$$\begin{aligned} E &\rightarrow E E' \mid \text{VAR} \mid \text{NUMERIC} \\ E' &\rightarrow + T \mid - T \mid T \\ T &\rightarrow T T' \mid F \mid \text{VAR} \mid \text{NUMERIC} \\ T' &\rightarrow * F \mid / F \mid ^ F \mid \% \% F \\ F &\rightarrow (E) \mid D \end{aligned}$$

Basic arithmetic functions

```
FUNCTION → mode (VAR)

cat (VAR)

length (VAR)

log2 (VAR) # logarithms base 2 of x

log10 (VAR) # logarithms base 10 of x

exp (VAR) # Exponential of x

cos (VAR) # Cosine of x

sin (VAR) # Sine of x

tan (VAR) #Tangent of x

acos (VAR) # arc-cosine of x

asin (VAR) # arc-sine of x

atan (VAR) #arc-tangent of x
```

`abs (VAR) # absolute value of x`

`sqrt (VAR) # square root of x`

STAT_FUNCTION → `max (VAR)`

`min (VAR)`

`range (VAR)`

`length (VAR)`

`sum (VAR)`

`prod (VAR)`

`mean (VAR)`

`sd (VAR) # Standard deviation`

`var (VAR)`

`sort (VAR)`

Assigning values to variables

VARs → VAR VAR2

VAR2 → `eps|,VAR`

VAR → CHARACTER COMB
| .VAR3

VAR3 → `_COMP | CHARACTER COMB`

COMB → . COMB1
| CHARACTER COMB1
| D COMB1
| *eps*

COMB1 → `eps | COMB`

A → | RENAME ASSIGN VECTOR
| LEVELS ASSIGN VECTOR
| SUBSET_DATAFRAME ASSIGN VAR

ASSIGN → <- | =

EXP -> V
BASIC_TYPE
| VECTOR
| FUNCTION
| STAT_FUNCTION
| TYPE
| TEST_TYPE
| CONVERT
| CREATE_MATRIX
| TRANSPOSE
| DIMENSION
| SPEC_MATRIX_FUNCTION
| CREATE_FACTOR
| INDIVID_PER_LEVEL
| SPEC_FACTOR_FUNC
| LEVELS
| CREATE_DATAFRAME
| SUBSET_DATAFRAME
| SEQ
| RSEQ
| CREATE_LIST

PRINT → print(VAR)

LIST → ls()

REMOVE → rm(VARS)

Basic data types

BASIC_TYPE \rightarrow LOGICAL
| NUMERIC
| STRING
| COMPLEX

COMPLEX \rightarrow Di

LOGICAL \rightarrow T LOGICAL₃ | F LOGICAL₂

LOGICAL₂ \rightarrow eps | ALSE

LOGICAL₃ \rightarrow eps | RUE

NUMERIC \rightarrow INTEGER | DOUBLE

INTEGER \rightarrow D INTEGER₂ | NEG_INT | POS_INT

INTEGER₂ \rightarrow L | e dL

NEG_INT \rightarrow - D INTEGER₂

POS_INT \rightarrow +D INTEGER₂

d \rightarrow 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

D \rightarrow d D₂

D₂ \rightarrow D | eps

DOUBLE \rightarrow .D | D DOUBLE₂
| POS_DOUBLE
| NEG_DOUBLE

DOUBLE₂ \rightarrow eps | .D | .Ded

POS_DOUBLE \rightarrow +D DOUBLE₂ | +.D

NEG_DOUBLE \rightarrow -D DOUBLE₂ | -.D

STRING \rightarrow "CHaine"
| 'CHaine'

CHaine \rightarrow CHARACTER CHaine
| CHARACTER\ CHaine₂
| CHARACTER

CHaine₂ \rightarrow eps | 'CHaine | \"CHaine

CHARACTER → a | b | c ... | z | A | ... | Z

TYPE → typeof(TYPE2)
| class(VAR)

TYPE2 → BASIC_TYPE
| VAR

TEST_TYPE → is.IS

IS → numeric(VAR)
| character(VAR)
| logical(VAR)
| complex(VAR)
| na(VAR)
| nan(VAR)
| factor(VAR)
| dataframe(VAR)

CONVERT → as.AS

AS → numeric(VAR)
| character(VAR)
| logical(VAR)
| factor(VAR)
| dataframe(VAR)

/*

* Conversion d'un string to numeric est possible : returns NA (not available)

*/

Vectors

VECTOR → c(VECTOR2)

VECTOR2 → CL

| CN VECTOR 4
 | CS VECTOR 3
 | CV
 | CNAMED

VECTOR₃ → eps

| ,VECTOR₃₃

VECTOR 33 → CN VECTOR₃₃₃

| CL

VECTOR 333 → ,CL

| eps

VECTOR 4 → eps

| ,CL

CNAMED → CNAMED_N

| CNAMED_L

| CNAMED_S

CNAMED_N → CHAINE = CNAMED_N1

CNAMED_N1 → NA CNAMED_N2

| NUMERIC CNAMED_N3

CNAMED_N2 → eps

| ,CNAMED_N

CNAMED_N3 → eps

| ,CNAMED_N

CNAMED_L → CHAINE = CNAMED_L1

CNAMED_L1 → NA CNAMED_L2

| LOGICAL CNAMED_L3

CNAMED_L2 → eps

| ,CNAMED_L

CNAMED_L3 → eps

| ,CNAMED_L

CNAMED_S → CHAINE = NA
 | CHAINE = STRING
 | CHAINE = STRING , CNAMED_S
 | CHAINE = NA, CNAMED_S
CNAMED_S1 → NA CNAMED_S2
 | STRING CNAMED_S3
CNAMED_S2 → eps
 | ,CNAMED_S
CNAMED_S3 → eps
 | ,CNAMED_S

CV → VECTOR CV2
CV2 → eps
 | ,CV

CL → LOGICAL CL2
CL2 → eps
 | ,CL

CN → NUMERIC CN2
CN2 → eps
 | ,CN

CS → STRING CS2
CS2 → eps
 | , CS

ELEMENT_NAMES → names(VAR)

AFTER_VAR → [AFTER_VAR2]
AFTER_VAR2 → D AFTER_VAR3
 | c(D,D)
 | STRING

AFTER_VAR3 → eps
 | :D

EE2 → D
 | c(D,D)
 | (D:D)

SE2 → VAR LOG_OP BASIC_TYPE
 | !CHECK_NA
 | CHECK_NA

LOG_OP → ==
 | !=
 | >=
 | <=

Matrices

VECTORS → VECTOR VECTORS2

VECTORS2 → eps | ,VECTORS

CREATE_MATRIX → rbind(RC)
 | cbind(RC)
 # c for column and r for row
 | matrix(data = VECTOR ,nrow = D , ncol
= D , byrow = LOGICAL , dimnames = list(VECTORS))

RC → VARS | VECTORS

RENAME → rownames(VAR)
 | colnames(VAR)

TRANPOSE → t(VAR)

DIMENSION → ncol(VAR)
| nrow(VAR)
| dim(VAR)

SM₁ → SMD | SMP | SMV

SMP → , SMP₂

SMP₂ → D SMP₃ | VECTOR

SMP₃ → eps | :D

SMD → D, SMD₂

SMD₂ → ,D | :D SMD₃ | eps | :D,

SMD₃ → eps | ,SMD₄

SMD₄ → eps | D:D

SMV → VECTOR SMV₂

SMV₂ → ,VECTOR | eps

S₂ → S₄ | S₂ | S₃ | S₅

S₃ → STRING S₃₃ | ,STRING |

S₃₃ → , | ,STRING | ,D

S₄ → D , S₄₄

S₄₄ → D | eps | STRING

S₅ → VAR[S₅₅]

S₅₅ → VAR LOG_OP BASIC_TYPE, S₅₅₅ | ,VAR LOG_OP BASIC_TYPE

S₅₅₅ → eps | ,VAR LOG_OP_BASIC_TYPE

EX₂ → -EX₃ | ,-D

EX₃ → D EX₃₃ | ,D

EX₃₃ → ,D | ,

SPEC_MATRIX_FUNCTION → rowSums(VAR)
 | colSums(VAR)
 | colMeans(VAR)
 | rowMeans(VAR)
 | apply(VAR,APP)

APP → 1,STAT_FUNCTION
 | 2,STAT_FUNCTION

Factors

CREATE_FACTOR → factor(FP)
FP → VECTOR VAR VAR,levels = VECTOR
FP 2 → eps | ,levels = VECTOR

INDIVID_PER_LEVEL → summary(VAR)

LEVELS → levels(VAR)

SPEC_FACTOR_FUNC → tapply(VAR,VAR,STAT_FUNCTION)
 | table(TP)

TP → VAR TP2
TP2 → eps | ,VAR

Data frames

CREATE_DATAFRAME → data.frame(COLS)

COLS → COL COLS2
COLS2 → eps | ,COLS

COL → CHAINE=COL2
COL2 → VECTOR | VAR | BASIC_TYPE

/* You can use t() as same as Matrix to transpose a data frame*/

SUBSET_DATAFRAME → subset(VAR, CHAINE LOG_OP
BASIC_TYPE)

| attach(VAR),detach(VAR)

SD → \$SD1 | [SD2]

SD2 → ,SDP
| VAR SD22

SD22 → ,VAR | \$CHAINE LOG_OP BASIC_TYPE, SD222

SD222 → eps | VECTOR | VAR,VAR

SDP → D | STRING | VECTOR | -D

SD1 → CHAINE SD11

SD11 → eps | LOG_OP BASIC_TYPE

Sequences

SEQ → | seq(SEQP)
| rep(D,D)
| sequence(c(CN))

SEQP → SEQ_PARAM | D SEQD

SEQ_PARAM → length=D
| label = c(CS)
| from = D
| to =D

SEQD → :D | ,D,D.D

SEQR → eps

Random sequences :

RSEQ → PFUNC(DISTRIB_PARAMS)

P → r
| d
| p
| q

FUNC → norm | exp | gamma | nbinom | unif | geom | cauchy | pois | f |
t | logis

DISTRIB_PARAMS → | D.D DPD
| scale = D
| location = D
| mean = D
| rate = D

DPD → ,DISTRIB_PARAMS | eps | .D

Lists

CREATE_LIST → list(COLS)

/* element_names and length already exists */

SL → \$CHaine | [[SL2]

SL2 → STRING]] | D SLD

SLD →]] SLD2

SLD 2 → eps | [D

Importing Data

READ → read.READ2

READ2 → delim(file.choose(STRING)) | csv(file.choose(STRING)) |
csv2(file.choose(STRING))

Exporting Data

WRITE → data(STRING)
| write WRITE2

WRITE2 → table(VAR,PARAMS) | csv(VAR,PARAMS) |
csv2(VAR,PARAMS)

SAVE → saveRDS(VAR,STRING)
| readRDS(STRING)
| load(STRING)

| save SAVE2

SAVE2 → (VARS,file=STRING) | .image(file=STRING)

PARAMS → file = STRING

| sep = "SEP"

| row.names = RCN

| col.names = RCN

RCN → LOGICAL | NA

SEP → , | ; | \t