

Help

HELP → ?CHAINED
| help(CHAINED)
| help("CHAINED")
| help("*")

Basic arithmetic functions

FUNCTION → mode (VAR)

 cat (VAR)

 length (VAR)

 log2 (VAR) # logarithms base 2 of x

 log10 (VAR) # logarithms base 10 of x

 exp (VAR) # Exponential of x

 cos (VAR) # Cosine of x

 sin (VAR) # Sine of x

 tan (VAR) #Tangent of x

 acos (VAR) # arc-cosine of x

 asin (VAR) # arc-sine of x

 atan (VAR) #arc-tangent of x

 abs (VAR) # absolute value of x

 sqrt (VAR) # square root of x

STAT_FUNCTION → max (VAR)

 min (VAR)

 range (VAR)

 length (VAR)

 sum (VAR)

```

prod (VAR)

mean (VAR)

sd (VAR) # Standard deviation

var (VAR)

sort (VAR)

```

Assigning values to variables

VAR → VAR
 | VAR,VAR
VAR → CHARACTER COMB
 | ._COMB
 | .CHARACTER COMB

COMB → . | _
 | CHARACTER
 | D
 | COMB COMB
 | *eps*

/*
 • VAL → VECTOR # to add at the end
 */

A → VAR ASSIGN EXP
ASSIGN → <- | =

PRINT → VAR | print(VAR)
LIST → ls()
REMOVE → rm(VARS)

Basic data types

BASIC_TYPE → LOGICAL
| NUMERIC
| STRING
| COMPLEX

COMPLEX → Di

LOGICAL → TRUE
| FALSE
| T
| F

NUMERIC → INTEGER | DOUBLE

INTEGER → DL
| DedL
| -DL
| -DedL
| +DL
| +DedL

d → 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

D → dD
| d

DOUBLE → D | .D | D.D | D.Ded
| +D | +.D | +D.D | +D.Ded
| -D | -.D | -D.D | -D.Ded

STRING → “CHAINE”
| ‘CHAINE’

CHAINE → CHARACTER CHAINE
| CHAINE\’CHARACTER
| CHAINE\”CHARACTER
| CHARACTER

CHARACTER → a | b | c ... | z | A | ... | Z

TYPE → typeof(BASIC_TYPE)
 | typeof(VAR) | class(VAR)

TEST_TYPE → is.numeric(VAR)
 | is.character(VAR)
 | is.logical(VAR) | is.complex(VAR)

CONVERT → as.numeric(VAR)
 | as.character(VAR)
 | as.logical(VAR)

/*

* Conversion d'un string to numeric est possible : returns NA (not available)

*/

Vectors

VECTOR → c(CL)
 | c(CN)
 | c(CS)
 | c(CL)
 | c(CV)
 | c(CS,CN,TL)
 | c(CS,CN)
 | c(TS,TL)
 | c(CN,CL)
 | c(CNAMED)

CNAMED → CNAMED_N
 | CNAMED_L
 | CNAMED_S

CNAMED_N → CHAINE = NA
| CHAINE = NUMERIC
| CHAINE = NUMERIC , CNAMED_N
| CHAINE = NA, CNAMED_N

CNAMED_L → CHAINE = NA
| CHAINE = LOGICAL
| CHAINE = LOGICAL , CNAMED_L
| CHAINE = NA, CNAMED_L

CNAMED_S → CHAINE = NA
| CHAINE = STRING
| CHAINE = STRING , CNAMED_S
| CHAINE = NA, CNAMED_S

CHECK_NA → is.na(VAR)
CHECK_NAN → is.nan(VAR)

CV → VECTOR, CV
| VECTOR
CL → LOGICAL, CL
| LOGICAL
CN → NUMERIC, CN
| NUMERIC
CS → STRING, CS
| STRING

ELEMENT_NAMES → names(VAR) |

SUBSET_VECTOR → var[D]
| var[D:D]
| var[c(D,D)]
| var[STRING]

EXCLUDE_ELEMENT → var[-D]

| var[-c(D,D)]
| VAR [-(D:D)]

SELECT_ELEMENT → var[var LOG_OP BASIC_TYPE]
| var [!CHECK_NA]

LOG_OP → ==
| !=
| >=
| <=
| <
| >

Matrices

VECTORS → VECTOR
| VECTOR,VECTORS

CREATE_MATRIX → rbind(VARS)
| rbind(VECTORS)
| cbind(VARS)
| cbind(VECTORS)
c for column and r for row
| matrix(data = VECTOR ,nrow = D , ncol
= D , byrow = LOGICAL , dimnames = list(VECTORS))

RENAME → rownames(VAR)
| colnames(VAR)

TRANSPOSE → t(VAR)

DIMENSION → ncol(VAR)
| nrow(VAR)
| dim(VAR)

SUBSET_MATRIX → VAR[D,D]

- | VAR[D,]
- | VAR[D:D,]
- | VAR[D:D,D:D]
- | VAR[VECTOR,]
- | VAR[,D]
- | VAR[,D:D]
- | VAR[,VECTOR]
- | VAR[VECTOR,VECTOR]

SELECT → VAR[D,D]
| VAR[D,]
| VAR[,D]
| VAR[STRING,STRING]
| VAR[STRING,]
| VAR[,STRING] VAR[STRING,D]
| VAR[D,STRING]
| VAR[VAR LOG_OP BASIC_TYPE,]
| VAR[VAR LOG_OP BASIC_TYPE,VAR LOG_OP BASIC_TYPE]
| VAR[,VAR LOG_OP BASIC_TYPE]

EXCLUDE → VAR[-D,-D]
| VAR[-D,]
| VAR[, -D]

SPEC_MATRIX_FUNCTION → rowSums(VAR)
| colSums(VAR)
| colMeans(VAR)
| rowMeans(VAR)
| apply(VAR,1,STAT_FUNCTION)
| apply(VAR,2,STAT_FUNCTION)

Factors

CREATE_FACTOR → factor(VECTOR)
| factor(VAR,levels = VECTOR)
| factor(VAR)

CHECK_FACTOR → is.factor(VAR)

CONVERT_FACTOR → as.factor(VAR)

INDIVID_PER_LEVEL → summary(VAR)

LEVELS → levels(VAR)

SPEC_FACTOR_FUNC → tapply(VAR,VAR,STAT_FUNCTION)
| table(VAR)| table(VAR,VAR)

Data frames

CREATE_DATAFRAME → data.frame(COLS)

COLS → COL
| COL,COLS

COL → CHAINE=VECTOR
| CHAINE = VAR
| CHAINE = BASIC_TYPE

CHECK_DATAFRAME → is.data.frame(VAR)

CONVERT_DATAFRAME → as.data.frame(VAR)

/* You can use t() as same as Matrix to transpose a data frame*/

SUBSET_DATAFRAME → VAR\$CHAINED
 |VAR[,D]
 | VAR[,STRING]
 | VAR[,VECTOR]
 | VAR[, -D]
 | VAR\$CHAINED LOG_OP
 BASIC_TYPE
 | VAR[VAR\$CHAINED LOG_OP
 BASIC_TYPE,]
 | VAR[VAR\$CHAINED LOG_OP
 BASIC_TYPE, VECTOR]
 | VAR[VAR,VAR]
 | subset(VAR, CHAINED LOG_OP
 BASIC_TYPE)
 | attach(VAR),detach(VAR)

SPEC_DATAFRAME_FUNCTION (same as
 SPEC_MATRIX_FUNCTION)

Sequences

SEQ → seq(D,D,D.D)
 | seq(SEQ_PARAM)
 | rep(D,D)
 | seq(D:D) | sequence(c(CN))

SEQ_PARAM → length=D
 | label = c(CS)
 | from = D
 | to =D
 | SEQ_PARAM,SEQ_PARAM

Random sequences :

RSEQ → PFUNC(DISTRIB_PARAMS)

P → r
| d
| p
| q

FUNC → norm | exp | gamma | nbinom | unif | geom | cauchy | pois | f |
t | logis

DISTRIB_PARAMS → DISTRIB_PARAMS
| DISTRIB_PARAMS, DISTRIB_PARAMS
| D
| D.D
| scale = D
| location = D
| mean = D
| rate = D

Lists

CREATE_LIST → list(COLS)

/* element_names and length already exists */

SUBSET_LIST → VAR\$CHaine
| VAR[[STRING]]
| VAR[[D]]
| VAR[[D]][D]

Importing Data

READ → read.delim(file.choose(STRING))
| read.csv(file.choose(STRING))
| read.csv2(file.choose(STRING))
| read.tsv(file.choose(STRING))

Exporting Data

WRITE → data(STRING)
| write.table(VAR,PARAMS)
| write.csv(VAR,PARAMS)
| write.csv2(VAR,PARAMS)

SAVE → saveRDS(VAR,STRING)
| readRDS(STRING)
| load(STRING)
| save(VARS,file=STRING)
| save.image(file=STRING)

PARAMS → file = STRING
| sep = "SEP"
| row.names = LOGICAL
| col.names = LOGICAL

```
| row.names = NA
```

```
| col.names = NA
```

SEP → , | ; | \t