

Lecture 4: A posteriori error analysis for Variational Inequalities

Pr. Ismail MERABET

Kasdi Merbah University /Department of Mathematics
Ouargla University 2021

Outline

- 1 Introduction
- 2 Abstract framework
- 3 Second order contact problems
 - Timoshenko's beam
 - Elastic membrane with rigid obstacle
 - The Reissner-Mindlin plate
- 4 Fourth order contact problems
 - Bernoulli's beam
 - The Kirchhoff plate
- 5 Numerical Tests
- 6 Conclusions

Introduction

Many physical phenomena involving thin structures are accurately and concisely described by **variational inequalities** instead of PDEs.

Introduction

Many physical phenomena involving thin structures are accurately and concisely described by **variational inequalities** instead of PDEs. While we can often write down the model in terms of inequalities,

Introduction

Many physical phenomena involving thin structures are accurately and concisely described by **variational inequalities** instead of PDEs. While we can often write down the model in terms of inequalities, most of the time **we cannot exactly solve them** in cases of practical interest.

Introduction

Many physical phenomena involving thin structures are accurately and concisely described by **variational inequalities** instead of PDEs. While we can often write down the model in terms of inequalities, most of the time **we cannot exactly solve them** in cases of practical interest. We, therefore, turn **to numerical methods** for the approximation of their solutions.

Introduction

Many physical phenomena involving thin structures are accurately and concisely described by **variational inequalities** instead of PDEs. While we can often write down the model in terms of inequalities, most of the time **we cannot exactly solve them** in cases of practical interest. We, therefore, turn **to numerical methods** for the approximation of their solutions. **The finite element method** is the most **popular, general, powerful and elegant** approach for **approximating the solutions** of contact problems **because**

Introduction

Many physical phenomena involving thin structures are accurately and concisely described by **variational inequalities** instead of PDEs. While we can often write down the model in terms of inequalities, most of the time **we cannot exactly solve them** in cases of practical interest. We, therefore, turn **to numerical methods** for the approximation of their solutions. **The finite element method** is the most **popular, general, powerful and elegant** approach for **approximating the solutions** of contact problems **because** they are "naturally" **variational** problems.

The purpose of this talk is to provide:

The purpose of this talk is to provide:

- a robust a priori error analysis and

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The a posteriori indicators are **computable** quantities, they must depend only on **known quantities**, such as :

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The a posteriori indicators are computable quantities, they must depend only on known quantities, such as :

- the size of the mesh cells,

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The a posteriori indicators are computable quantities, they must depend only on known quantities, such as :

- the size of the mesh cells,
- the problem data, and

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The a posteriori indicators are computable quantities, they must depend only on known quantities, such as :

- the size of the mesh cells,
- the problem data, and
- the approximate solution.

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The a posteriori indicators are computable quantities, they must depend only on known quantities, such as :

- the size of the mesh cells,
- the problem data, and
- the approximate solution.

and they must yield:

- global upper and

The purpose of this talk is to provide:

- a robust a priori error analysis and
- a reliable and an efficient a posteriori error estimator

By a robust a priori error analysis we mean a concrete error estimate proving the convergence of the error.

The a posteriori indicators are computable quantities, they must depend only on known quantities, such as :

- the size of the mesh cells,
- the problem data, and
- the approximate solution.

and they must yield:

- global upper and
- local lower bounds for the error.

When the error estimator, say, $\eta \equiv \eta(h, u_h, f)$ provides an upper bound for the error, i.e.,

$$\|u - u_h\| \lesssim \eta$$

we say, that our estimator η is "reliable".

When the error estimator, say, $\eta \equiv \eta(h, u_h, f)$ provides an upper bound for the error, i.e.,

$$\|u - u_h\| \lesssim \eta$$

we say, that our estimator η is "reliable".

An error estimator is called (locally) efficient

When the error estimator, say, $\eta \equiv \eta(h, u_h, f)$ provides an upper bound for the error, i.e.,

$$\|u - u_h\| \lesssim \eta$$

we say, that our estimator η is "reliable".

An error estimator is called (locally) **efficient** if it provides a (local) lower bound for the (local) error apart from (local) data resolution i.e.,

$$\eta_T \lesssim \|u - u_h\|$$

Different types of a posteriori estimators are available in the literature

When the error estimator, say, $\eta \equiv \eta(h, u_h, f)$ provides an upper bound for the error, i.e.,

$$\|u - u_h\| \lesssim \eta$$

we say, that our estimator η is "reliable".

An error estimator is called (locally) **efficient** if it provides a (local) lower bound for the (local) error apart from (local) data resolution i.e.,

$$\eta_T \lesssim \|u - u_h\|$$

Different types of a posteriori estimators are available in the literature but, here we interest on the **residual type estimator**.

When the error estimator, say, $\eta \equiv \eta(h, u_h, f)$ provides an upper bound for the error, i.e.,

$$\|u - u_h\| \lesssim \eta$$

we say, that our estimator η is "reliable".

An error estimator is called (locally) **efficient** if it provides a (local) lower bound for the (local) error apart from (local) data resolution i.e.,

$$\eta_T \lesssim \|u - u_h\|$$

Different types of a posteriori estimators are available in the literature but, here we interest on the **residual type estimator**. Efficient a posteriori estimators are **successfully used for adaptive algorithms** that involve local mesh refinements.

When the error estimator, say, $\eta \equiv \eta(h, u_h, f)$ provides an upper bound for the error, i.e.,

$$\|u - u_h\| \lesssim \eta$$

we say, that our estimator η is "reliable".

An error estimator is called (locally) **efficient** if it provides a (local) lower bound for the (local) error apart from (local) data resolution i.e.,

$$\eta_T \lesssim \|u - u_h\|$$

Different types of a posteriori estimators are available in the literature but, here we interest on the **residual type estimator**. Efficient a posteriori estimators are **successfully used for adaptive algorithms** that involve local mesh refinements.

Note that the proof of the **efficiency** estimate (up to possible data resp. obstacle oscillations) **is an open problem** (see [4] for instance).

Abstract framework

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

- \mathcal{K} is a closed convex set of a Hilbert space V .

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

- \mathcal{K} is a closed convex set of a Hilbert space V .
- $a(\cdot, \cdot)$ is a symmetric continuous and coercive bilinear form on V .

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

- \mathcal{K} is a closed convex set of a Hilbert space V .
- $a(\cdot, \cdot)$ is a symmetric continuous and coercive bilinear form on V .
- $\ell(\cdot)$ is a linear continuous form on V .

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

- \mathcal{K} is a closed convex set of a Hilbert space V .
- $a(\cdot, \cdot)$ is a symmetric continuous and coercive bilinear form on V .
- $\ell(\cdot)$ is a linear continuous form on V .

Since \mathcal{K} is a closed convex set the the minimization problem (1) is **equivalent** to the following variational inequality:

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

- \mathcal{K} is a closed convex set of a Hilbert space V .
- $a(\cdot, \cdot)$ is a symmetric continuous and coercive bilinear form on V .
- $\ell(\cdot)$ is a linear continuous form on V .

Since \mathcal{K} is a closed convex set the the minimization problem (1) is **equivalent** to the following variational inequality:

$$\begin{cases} \text{Find } u \in \mathcal{K} \text{ such that} \\ a(u, v - u) \geq \ell(v - u), \quad \forall v \in \mathcal{K} \end{cases} \quad (2)$$

In this work we consider some constrained minimisation problems of the form:

$$\text{Find } u := \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (1)$$

with:

- \mathcal{K} is a closed convex set of a Hilbert space V .
- $a(\cdot, \cdot)$ is a symmetric continuous and coercive bilinear form on V .
- $\ell(\cdot)$ is a linear continuous form on V .

Since \mathcal{K} is a closed convex set the the minimization problem (1) is **equivalent** to the following variational inequality:

$$\begin{cases} \text{Find } u \in \mathcal{K} \text{ such that} \\ a(u, v - u) \geq \ell(v - u), \quad \forall v \in \mathcal{K} \end{cases} \quad (2)$$

The the existence and uniqueness of the solution is a direct consequence of Stampacchia's theorem (see [1]).

The problems considered here are of **obstacle-type** i.e., the set \mathcal{K} is of the form:

The problems considered here are of **obstacle-type** i.e., the set \mathcal{K} is of the form:

$$\mathcal{K} := \{u \in V; \quad Bu \geq \psi \text{ a.e in } \Omega\}$$

for some given smooth function ψ and a linear bounded operator B .

The problems considered here are of **obstacle-type** i.e., the set \mathcal{K} is of the form:

$$\mathcal{K} := \{u \in V; \quad Bu \geq \psi \text{ a.e in } \Omega\}$$

for some given smooth function ψ and a linear bounded operator B . Then the strong form of (2) reads:

$$\begin{aligned}\mathcal{A}(u) &\geq \ell && \text{in } \Omega \\ Bu - \psi &\geq 0 && \text{in } \Omega \\ (\mathcal{A}(u) - \ell)(Bu - \psi) &= 0 && \text{in } \Omega\end{aligned}$$

The problems considered here are of **obstacle-type** i.e., the set \mathcal{K} is of the form:

$$\mathcal{K} := \{u \in V; \quad Bu \geq \psi \text{ a.e in } \Omega\}$$

for some given smooth function ψ and a linear bounded operator B . Then the strong form of (2) reads:

$$\begin{aligned}\mathcal{A}(u) &\geq \ell && \text{in } \Omega \\ Bu - \psi &\geq 0 && \text{in } \Omega \\ (\mathcal{A}(u) - \ell)(Bu - \psi) &= 0 && \text{in } \Omega\end{aligned}$$

with a linear continuous operator \mathcal{A} .

The problems considered here are of **obstacle-type** i.e., the set \mathcal{K} is of the form:

$$\mathcal{K} := \{u \in V; \quad Bu \geq \psi \text{ a.e in } \Omega\}$$

for some given smooth function ψ and a linear bounded operator B . Then the strong form of (2) reads:

$$\begin{aligned}\mathcal{A}(u) &\geq \ell && \text{in } \Omega \\ Bu - \psi &\geq 0 && \text{in } \Omega \\ (\mathcal{A}(u) - \ell)(Bu - \psi) &= 0 && \text{in } \Omega\end{aligned}$$

with a linear continuous operator \mathcal{A} .

We then rewrite the problem using the Lagrange multiplier λ

$$\lambda = \mathcal{A}(u) - \ell. \tag{3}$$

as an independent unknown

Form (2) it follows that the reaction force λ is non-negative,

Form (2) it follows that the reaction force λ is non-negative, i.e. it belongs to the set

$$\Lambda = \{\mu \in Q \subset V' : b(v, \mu) \geq 0 \quad \forall v \in V \text{ s.t. } v \geq 0 \quad \text{a.e in } \Omega\},$$

Form (2) it follows that the reaction force λ is non-negative, i.e. it belongs to the set

$$\Lambda = \{\mu \in Q \subset V' : b(v, \mu) \geq 0 \quad \forall v \in V \text{ s.t } v \geq 0 \quad \text{a.e in } \Omega\},$$

Then we can reformulate the variational inequalities (2) as :

Form (2) it follows that the reaction force λ is non-negative, i.e. it belongs to the set

$$\Lambda = \{\mu \in Q \subset V' : b(v, \mu) \geq 0 \quad \forall v \in V \text{ s.t } v \geq 0 \quad \text{a.e in } \Omega\},$$

Then we can reformulate the variational inequalities (2) as :

$$\left\{ \begin{array}{l} \text{Find } (u, \lambda) \in V \times \Lambda \text{ such as that} \\ a(u, v) - b(v, \lambda) = \ell(v), \quad \forall v \in V, \\ b(u, \mu - \lambda) \geq g(\mu - \lambda), \quad \forall \mu \in \Lambda. \end{array} \right. \quad (4)$$

Form (2) it follows that the reaction force λ is non-negative, i.e. it belongs to the set

$$\Lambda = \{\mu \in Q \subset V' : b(v, \mu) \geq 0 \quad \forall v \in V \text{ s.t } v \geq 0 \quad \text{a.e in } \Omega\},$$

Then we can reformulate the variational inequalities (2) as :

$$\left\{ \begin{array}{l} \text{Find } (u, \lambda) \in V \times \Lambda \text{ such as that} \\ a(u, v) - b(v, \lambda) = \ell(v), \quad \forall v \in V, \\ b(u, \mu - \lambda) \geq g(\mu - \lambda), \quad \forall \mu \in \Lambda. \end{array} \right. \quad (4)$$

where $b(\cdot, \cdot)$ is a continuous bilinear form satisfies the following inf-sup condition:

Form (2) it follows that the reaction force λ is non-negative, i.e. it belongs to the set

$$\Lambda = \{\mu \in Q \subset V' : b(v, \mu) \geq 0 \quad \forall v \in V \text{ s.t. } v \geq 0 \quad \text{a.e in } \Omega\},$$

Then we can reformulate the variational inequalities (2) as :

$$\left\{ \begin{array}{l} \text{Find } (u, \lambda) \in V \times \Lambda \text{ such as that} \\ a(u, v) - b(v, \lambda) = \ell(v), \quad \forall v \in V, \\ b(u, \mu - \lambda) \geq g(\mu - \lambda), \quad \forall \mu \in \Lambda. \end{array} \right. \quad (4)$$

where $b(\cdot, \cdot)$ is a continuous bilinear form satisfies the following inf-sup condition:

$$\exists C_b > 0, \quad \sup_{v \in V} \frac{b(v, \xi)}{\|v\|_V} \geq C_b \|\xi\|_{V'} \quad \xi \in Q \quad (5)$$

Until now, for the **continuous** problem, if

Until now, for the **continuous** problem, if

- $a(\cdot, \cdot)$ is coercive.

Until now, for the **continuous** problem, if

- $a(\cdot, \cdot)$ is coercive.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5)

Until now, for the **continuous** problem, if

- $a(\cdot, \cdot)$ is coercive.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5)

Then every thing is well !!, existence, uniqueness, ...

Until now, for the **continuous** problem, if

- $a(\cdot, \cdot)$ is coercive.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5)

Then every thing is well !!, existence, uniqueness, ...

But, for the discrete problem, the situation is complicated, because

Until now, for the **continuous** problem, if

- $a(\cdot, \cdot)$ is coercive.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5)

Then every thing is well !!, existence, uniqueness, ...

But, for the discrete problem, the situation is complicated, because **it** is not easy to find a uniformly stable pairing $V_h \subset V$ and $Q_h \subset Q$ such that the bilinear form $b(\cdot, \cdot)$ satisfies a **discrete** inf-sup condition (the analogous of (5) on $V_h \times Q_h$) (see [1] for some concrete examples).

Until now, for the **continuous** problem, if

- $a(\cdot, \cdot)$ is coercive.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5)

Then every thing is well !!, existence, uniqueness, ...

But, for the discrete problem, the situation is complicated, because **it** is not easy to find a uniformly stable pairing $V_h \subset V$ and $Q_h \subset Q$ such that the bilinear form $b(\cdot, \cdot)$ satisfies a **discrete** inf-sup condition (the analogous of (5) on $V_h \times Q_h$) (see [1] for some concrete examples).

New approaches are needed.

A new formulation

Defining on $\mathcal{H} = V \times Q$ the bilinear and linear forms

$$\mathcal{B} : \mathcal{H} \times \mathcal{H} \longrightarrow \mathbb{R} \quad \text{and} \quad \mathcal{L} : \mathcal{H} \longrightarrow \mathbb{R}$$

through

A new formulation

Defining on $\mathcal{H} = V \times Q$ the bilinear and linear forms

$$\mathcal{B} : \mathcal{H} \times \mathcal{H} \longrightarrow \mathbb{R} \quad \text{and} \quad \mathcal{L} : \mathcal{H} \longrightarrow \mathbb{R}$$

through

$$\mathcal{B}(w, \xi; v, \mu) = a(w, v) - b(v, \xi) - b(w, \mu), \quad (6)$$

$$\mathcal{L}(v, \mu) = \ell(v) - g(\mu), \quad (7)$$

A new formulation

Defining on $\mathcal{H} = V \times Q$ the bilinear and linear forms

$$\mathcal{B} : \mathcal{H} \times \mathcal{H} \longrightarrow \mathbb{R} \quad \text{and} \quad \mathcal{L} : \mathcal{H} \longrightarrow \mathbb{R}$$

through

$$\mathcal{B}(w, \xi; v, \mu) = a(w, v) - b(v, \xi) - b(w, \mu), \quad (6)$$

$$\mathcal{L}(v, \mu) = \ell(v) - g(\mu), \quad (7)$$

the variational problem can be reformulated as:

$$\left\{ \begin{array}{l} \text{Find } (u, \lambda) \in V \times \Lambda \text{ such that :} \\ \mathcal{B}(u, \lambda; v, \mu - \lambda) \leq \mathcal{L}(v, \mu - \lambda) \quad \forall (v, \mu) \in V \times \Lambda. \end{array} \right. \quad (8)$$

Continuous stability

For the new formulation we have the following theorem:

Theorem 1 ([2])

If,

☛ $a(\cdot, \cdot)$ is V -elliptic.

Continuous stability

For the new formulation we have the following theorem:

Theorem 1 ([2])

If,

- ☛ $a(\cdot, \cdot)$ is V -elliptic.
- ☛ $b(\cdot, \cdot)$ satisfies the inf-sup condition (5).

Continuous stability

For the new formulation we have the following theorem:

Theorem 1 ([2])

If,

- ☛ $a(\cdot, \cdot)$ is V -elliptic.
- ☛ $b(\cdot, \cdot)$ satisfies the inf-sup condition (5).

Then problem (8) admits a unique solution.

Continuous stability

For the new formulation we have the following theorem:

Theorem 1 ([2])

If,

- $a(\cdot, \cdot)$ is V -elliptic.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5).

Then problem (8) admits a unique solution. Moreover, we have the following stability result:

For every $(v, \mu) \in V \times Q$ there exists $w \in V$ such that

Continuous stability

For the new formulation we have the following theorem:

Theorem 1 ([2])

If,

- $a(\cdot, \cdot)$ is V -elliptic.
- $b(\cdot, \cdot)$ satisfies the inf-sup condition (5).

Then problem (8) admits a unique solution. Moreover, we have the following stability result:

For every $(v, \mu) \in V \times Q$ there exists $w \in V$ such that

$$\mathcal{B}(v, \mu; w, -\mu) \gtrsim |||(v, \mu)|||^2 \quad \text{and} \quad \|w\|_V \lesssim |||(v, \mu)||| \quad (9)$$

where,

$$|||(w, \xi)||| = (\|w\|_V^2 + \|\xi\|_{V'}^2)^{1/2}, \quad (10)$$

Proof. Define $p \in V$, through

$$a(p, q) = b(q, \mu) \quad \forall q \in V \quad (11)$$

Proof. Define $p \in V$, through

$$a(p, q) = b(q, \mu) \quad \forall q \in V \quad (11)$$

Form the continuity of the bilinear form $a(\cdot, \cdot)$ it follows that

$$\frac{b(q, \mu)}{\|q\|_V} = \frac{a(p, q)}{\|q\|_V} \lesssim \|p\|_V \quad \forall q \in V \quad (12)$$

Proof. Define $p \in V$, through

$$a(p, q) = b(q, \mu) \quad \forall q \in V \quad (11)$$

Form the continuity of the bilinear form $a(\cdot, \cdot)$ it follows that

$$\frac{b(q, \mu)}{\|q\|_V} = \frac{a(p, q)}{\|q\|_V} \lesssim \|p\|_V \quad \forall q \in V \quad (12)$$

Since q is arbitrary, we have

$$\|\mu\|_{V'} \lesssim \sup_{q \in V} \frac{b(q, \mu)}{\|q\|_V} \lesssim \|p\|_V. \quad (13)$$

Moreover, the coercivity of the bilinear form $a(\cdot, \cdot)$ gives

$$\|p\|_V^2 \lesssim a(p, p) = b(p, \mu) \leq \|\mu\|_{V'} \|p\|_V \longrightarrow \|p\|_V \lesssim \|\mu\|_{V'} \quad (14)$$

Moreover, the coercivity of the bilinear form $a(\cdot, \cdot)$ gives

$$\|p\|_V^2 \lesssim a(p, p) = b(p, \mu) \leq \|\mu\|_{V'} \|p\|_V \longrightarrow \|p\|_V \lesssim \|\mu\|_{V'} \quad (14)$$

In other words,

$$\|p\|_V \sim \|\mu\|_{V'}$$

Moreover, the coercivity of the bilinear form $a(\cdot, \cdot)$ gives

$$\|p\|_V^2 \lesssim a(p, p) = b(p, \mu) \leq \|\mu\|_{V'} \|p\|_V \longrightarrow \|p\|_V \lesssim \|\mu\|_{V'} \quad (14)$$

In other words,

$$\|p\|_V \sim \|\mu\|_{V'}$$

Choosing $w = v - p$, noting that

$$\begin{aligned} \mathcal{B}(v, \mu; v - p, -\mu) &= a(v, v) - a(p, v) + b(p, \mu) \\ &= a(v, v) - b(v, \mu) + b(p, \mu) \\ &= \frac{1}{2}(a(v, v) + a(p, p) + a(v - p, v - p)) \\ &\quad + a(p, p) \end{aligned}$$

Moreover, the coercivity of the bilinear form $a(\cdot, \cdot)$ gives

$$\|p\|_V^2 \lesssim a(p, p) = b(p, \mu) \leq \|\mu\|_{V'} \|p\|_V \longrightarrow \|p\|_V \lesssim \|\mu\|_{V'} \quad (14)$$

In other words,

$$\|p\|_V \sim \|\mu\|_{V'}$$

Choosing $w = v - p$, noting that

$$\begin{aligned} \mathcal{B}(v, \mu; v - p, -\mu) &= a(v, v) - a(p, v) + b(p, \mu) \\ &= a(v, v) - b(v, \mu) + b(p, \mu) \\ &= \frac{1}{2}(a(v, v) + a(p, p) + a(v - p, v - p)) \\ &\quad + a(p, p) \end{aligned}$$

and applying inequalities (13) and (14) proves the result.

Variationally Consistent Discretization or Stabilized FE

The aim is to perturb "consistently" the bilinear form \mathcal{B} and \mathcal{L} ,

Variationally Consistent Discretization or Stabilized FE

The aim is to perturb "consistently" the bilinear form \mathcal{B} and \mathcal{L} , i.e., find

$$\begin{aligned}\mathcal{B}_h((u_h, \lambda_h); (v, \xi)) &= \mathcal{B}((u_h, \lambda_h); (v, \xi)) - \alpha \mathcal{B}_h((u_h, \lambda_h); (v, \xi)) \\ \mathcal{L}_h(v, \xi) &= \mathcal{L}(v, \xi) - \alpha \mathcal{L}_h(v, \xi)\end{aligned}$$

Variationally Consistent Discretization or Stabilized FE

The aim is to perturb "**consistently**" the bilinear form \mathcal{B} and \mathcal{L} , i.e., find

$$\begin{aligned}\mathcal{B}_h((u_h, \lambda_h); (v, \xi)) &= \mathcal{B}((u_h, \lambda_h); (v, \xi)) - \alpha \mathcal{B}_h((u_h, \lambda_h); (v, \xi)) \\ \mathcal{L}_h(v, \xi) &= \mathcal{L}(v, \xi) - \alpha \mathcal{L}_h(v, \xi)\end{aligned}$$

such that:

$$\mathcal{B}_h((u, \lambda); (v, \xi)) = \mathcal{L}_h(v, \xi), \quad \forall (v, \xi) \in \mathcal{H}$$

For suitable choice of the parameter $\alpha > 0$ and for **simple** choice of the finite dimensional space $V_h \subset V$ and $Q_h \subset Q$, we need to get analogue results as in the continuous level, i.e.,

$$\forall (v_h, \mu_h) \in V_h \times Q_h, \quad \exists w_h \in V_h \text{ such that}$$

$$\mathcal{B}_h(v_h, \mu_h; w_h, -\mu_h) \gtrsim |||(v_h, \mu_h)|||^2 \quad \text{and} \quad \|w_h\|_V \lesssim |||(v_h, \mu_h)|||$$

Second order contact problems

As a first model, we consider the contact problem of a **simplified** Timoshenko clamped beam with a rigid obstacle.

As a first model, we consider the contact problem of a **simplified** Timoshenko clamped beam with a rigid obstacle.




Figure: A timoshenko beam with a rigid obstacle ψ

The minimization problem consists of :

$$\text{Finding } (\theta, w) : \arg \min_{(\eta, \nu) \in \mathcal{K}} J(\eta, \nu) \quad (15)$$

where,

The minimization problem consists of :

$$\text{Finding } (\theta, w) : \arg \min_{(\eta, v) \in \mathcal{K}} J(\eta, v) \quad (15)$$

where,

$$J(\eta, v) := \frac{1}{2} \int_0^L (\eta')^2 dx + \frac{t^{-2}}{2} \int_0^L (v' - \eta)^2 dx - \langle f, v \rangle$$
$$\mathcal{K} := \{ (\eta, v) \in H_0^1(0, L) \times H_0^1(0, L); \text{ and } v \geq \psi \}$$

Then if $f \in H^{-1}(0, L)$, the assumptions of our abstract framework are satisfied.

The minimization problem consists of :

$$\text{Finding } (\theta, w) : \arg \min_{(\eta, v) \in \mathcal{K}} J(\eta, v) \quad (15)$$

where,

$$J(\eta, v) := \frac{1}{2} \int_0^L (\eta')^2 dx + \frac{t^{-2}}{2} \int_0^L (v' - \eta)^2 dx - \langle f, v \rangle$$
$$\mathcal{K} := \{ (\eta, v) \in H_0^1(0, L) \times H_0^1(0, L); \text{ and } v \geq \psi \}$$

The minimization problem consists of :

$$\text{Finding } (\theta, w) : \arg \min_{(\eta, v) \in \mathcal{K}} J(\eta, v) \quad (15)$$

where,

$$J(\eta, v) := \frac{1}{2} \int_0^L (\eta')^2 dx + \frac{t^{-2}}{2} \int_0^L (v' - \eta)^2 dx - \langle f, v \rangle$$
$$\mathcal{K} := \{ (\eta, v) \in H_0^1(0, L) \times H_0^1(0, L); \text{ and } v \geq \psi \}$$

Then if $f \in H^{-1}(0, L)$, the assumptions of our abstract framework are satisfied.

Then we have the following result:

Then we have the following result:

Theorem 2

Problem (15) admits a unique solution.

Then we have the following result:

Theorem 2

Problem (15) admits a unique solution. Moreover, the minimizer (θ, w) of problem (15) satisfies

$$\left\{ \begin{array}{l} \text{Find } (\theta, w) \in \mathcal{K} \text{ such that } \forall (\eta, v) \in \mathcal{K} \\ \int_0^L \theta'(\eta' - \theta') \, dx + t^{-2} \int_0^L (w' - \theta)((v - w)' - (\eta - \theta)) \, dx \\ \qquad \qquad \qquad \geq \langle f, v - w \rangle \end{array} \right.$$

Using suitable choice of test functions we can easily show that the complementarity system reads:

$$\left. \begin{aligned} -\theta'' - t^{-2}(w' - \theta) &= 0 \\ -t^{-2}(w' - \theta)' &\geq f \\ w - \psi &\geq 0 \\ (-t^2(w' - \theta)' - f)(w - \psi) &= 0 \end{aligned} \right\} \quad \text{a.e in } \Omega \quad (16)$$

$$\begin{cases} \theta(0) = w(0) = 0 \\ w(L) = \theta(L) = 0 \end{cases} \quad (17)$$

Theorem 3

If f and g are in $L^2(0, L)$, then $(\theta, w) \in (H^2(0, L))^2$.

Theorem 3

If f and g are in $L^2(0, L)$, then $(\theta, w) \in (H^2(0, L))^2$.

Remark 1

If $g = 0$ (or $g \in H^1(0, L)$), then we can expect that $\theta \in H^3(0, L)$, which mean that θ is more regular then w , which can not be happen in the equality cas. But this is not surprising because w is constrained whereas θ is not. The regularity of w is limited even when f and g are very smooth, it cannot exceed $C^{1,1}$.

Mixed formulation

By introducing:

Mixed formulation

By introducing:

$$\lambda = -t^{-2}(w' - \theta)' - f$$

the complementarity system reads:

$$\left. \begin{aligned} -\theta'' - t^{-2}(w' - \theta) &= 0 \\ -t^{-2}((w' - \theta)' - \lambda) &= f \\ \lambda &\geq 0 \\ \lambda(w - \psi) &= 0 \end{aligned} \right\} \quad \text{a.e in } \Omega \quad (18)$$

$$\begin{cases} \theta(0) = w(0) = 0 \\ \theta(L) = w(L) = 0 \end{cases} \quad (19)$$

We define,

$$V = H_0^1(0, L) \times H_0^1(0, L), \quad Q = H^{-1}(0, L)$$

and let Λ be the space defined by,

$$\Lambda := \{\mu \in Q, \langle \mu, \varphi \rangle \geq 0, \quad \forall \varphi \geq 0, \varphi \in C_0^\infty(0, L)\}$$

and we consider the following mixed variational formulation

We define,

$$V = H_0^1(0, L) \times H_0^1(0, L), \quad Q = H^{-1}(0, L)$$

and let Λ be the space defined by,

$$\Lambda := \{\mu \in Q, \langle \mu, \varphi \rangle \geq 0, \quad \forall \varphi \geq 0, \varphi \in C_0^\infty(0, L)\}$$

and we consider the following mixed variational formulation

$$\left\{ \begin{array}{l} \text{Find } (\theta, w, \lambda) \in V \times \Lambda \\ a((\theta, w), (\eta, v)) + b((\eta, v), \lambda) = F(\eta, v) \quad \forall (\eta, v) \in V \\ b((\theta, w), \mu - \lambda) \leq G(\mu - \lambda), \quad \forall \mu \in \Lambda \end{array} \right. \quad (20)$$

where,

We define,

$$V = H_0^1(0, L) \times H_0^1(0, L), \quad Q = H^{-1}(0, L)$$

and let Λ be the space defined by,

$$\Lambda := \{\mu \in Q, \langle \mu, \varphi \rangle \geq 0, \quad \forall \varphi \geq 0, \varphi \in C_0^\infty(0, L)\}$$

and we consider the following mixed variational formulation

$$\begin{cases} \text{Find } (\theta, w, \lambda) \in V \times \Lambda \\ a((\theta, w), (\eta, v)) + b((\eta, v), \lambda) = F(\eta, v) \quad \forall (\eta, v) \in V \\ b((\theta, w), \mu - \lambda) \leq G(\mu - \lambda), \quad \forall \mu \in \Lambda \end{cases} \quad (20)$$

where,

$$a((\theta, w); (\eta, v)) = \int_0^L \theta' \eta' \, dx + t^{-2} \int_0^L (w' - \theta)(v' - \eta) \, dx, \\ b((\eta, v), \lambda) = -\langle v, \lambda \rangle, \quad F(\eta, v) = \langle f, v \rangle, \quad G(\mu) = -\langle \psi, \mu \rangle$$

Consistent FE Discretization

Let us consider a finite dimensional space $V_h \subset H_0^1(0, L)$, $\eta_h \subset H_0^1(0, L)$ and $Q_h \subset L^2(0, L)$. Moreover, we introduce the closed convex set

$$\Lambda_h := \{\mu_h \in Q_h; \quad \mu_h \geq 0\}$$

Then we introduce the following bilinear and linear forms:

$$\begin{aligned} \mathcal{S}_h((\theta, w, \lambda); (\eta, v, \xi)) = & h^2[(\theta'' + t^{-2}(w' - \theta), \eta'' + t^{-2}(v' - \eta) \\ & + (t^{-2}(w'' - \theta') + \lambda, t^{-2}(v'' - \eta') + \xi)] \end{aligned}$$

$$\mathcal{L}_h(\eta, v, \xi) = h^2(f, t^{-2}(v'' - \eta') + \xi)$$

and for suitable choice of the parameter $\alpha > 0$, we define,

$$\begin{aligned} \mathcal{B}_h((\theta, w, \lambda); (\eta, v, \xi)) = & \mathcal{B}((\theta, w, \lambda); (\eta, v, \xi)) \\ & - \alpha \mathcal{B}_h((\theta, w, \lambda); (\eta, v, \xi)) \end{aligned}$$

$$\mathcal{L}_h(\eta, v, \xi) = \mathcal{L}(\eta, v, \xi) - \alpha \mathcal{L}_h(\eta, v, \xi)$$

Finally, we consider the following problem:

Finally, we consider the following problem:

$$\left\{ \begin{array}{l} \text{Find } (\theta_h, w_h, \lambda_h) \in \eta_h \times V_h \times \Lambda_h \quad \text{such that} \\ \forall (\eta_h, v_h, \mu_h) \in \eta_h \times V_h \times \Lambda_h \\ \mathcal{B}_h((\theta_h, w_h, \lambda_h); (\eta_h, v_h, \mu_h - \lambda_h)) \leq \mathcal{L}_h(\eta_h, v_h, \mu_h - \lambda_h) \end{array} \right. \quad (21)$$

Then we can choose the finite element spaces:

$$\left\{ \begin{array}{l} V_h = \eta_h = \mathbb{P}_{k+2} \\ Q_h = \mathbb{P}_k \end{array} \right| \quad k \geq 0$$

to get the discrete stability:

$$\forall (v_h, \mu_h) \in V_h \times Q_h, \quad \exists w_h \in V_h \text{ such that} \\ \mathcal{B}_h(v_h, \mu_h; w_h, -\mu_h) \gtrsim |||(v_h, \mu_h)|||^2 \quad \text{and} \quad \|w_h\|_V \lesssim |||(v_h, \mu_h)|||$$

The obstacle problem of an elastic membrane consists of

$$\left\{ \begin{array}{l} \text{Finding } u := \arg \min_{v \in \mathcal{K}} J(v) \end{array} \right. \quad (22)$$

where,

$$J(v) := \frac{1}{2} \int_{\Omega} |\nabla v|^2 \, dx - \langle f, v \rangle$$
$$\mathcal{K} := \{v \in H_0^1(\Omega); \quad v \geq \psi \text{ a.e in } \Omega\}$$

Then, the primal problem reads:

$$\left\{ \begin{array}{l} \text{Find } u \in \mathcal{K} \text{ such that} \\ a(u, v - u) \geq \langle f, v - u \rangle, \quad \forall v \in \mathcal{K} \end{array} \right. \quad (23)$$

with,

$$a(u, v) := \int_{\Omega} \nabla u \cdot \nabla v \, dx$$

The strong formulation reads:

$$\begin{aligned} -\Delta u - f &\geq 0, & \text{dans } \Omega \\ u &\geq \psi, & \text{dans } \Omega \\ (\Delta u + f)(u - \psi) &= 0, & \text{dans } \Omega \\ u &= 0, & \text{sur } \Gamma \end{aligned} \tag{24}$$

We introduce the Lagrange multiplier $\lambda = \Delta u + f$, then the problem reads:

$$\begin{aligned} -\Delta u - \lambda &= f, & \text{dans } \Omega \\ u &\geq \psi, & \text{dans } \Omega \\ \lambda &\geq 0, & \text{dans } \Omega \\ \lambda(u - \psi) &= 0, & \text{dans } \Omega \\ u &= 0, & \text{sur } \Gamma \end{aligned} \tag{25}$$

The Lagrange multiplier belongs to the space

$$Q = H^{-1}(\Omega).$$

We introduce, the set:

$$\Lambda = \{\mu \in H^{-1}(\Omega) \mid \langle \mu, v \rangle_{H^{-1}, H_0^1} \geq 0, \forall v \in \mathbf{V}, v \geq 0 \text{ a.e in } \Omega\}$$

The mixed formulation reads:

$$\begin{cases} \text{Trouver } (u, \lambda) \in \mathbf{V} \times \Lambda \text{ such that} \\ a(u, v) + b(v, \lambda) = \ell(v), & \forall v \in \mathbf{V} \\ b(u, \mu - \lambda) \leq g(\mu - \lambda), & \forall \mu \in \Lambda \end{cases} \quad (26)$$

with,

$$b(v, \mu) = -\langle \lambda, v \rangle_{H^{-1}, H_0^1}, \quad G(\mu) = -\langle \psi, \mu \rangle$$

A compact formulation

Defining on $\mathcal{H} = V \times Q$ the bilinear and linear forms

$$\mathcal{B} : \mathcal{H} \times \mathcal{H} \longrightarrow \mathbb{R} \quad \text{and} \quad \mathcal{L} : \mathcal{H} \longrightarrow \mathbb{R}$$

through

A compact formulation

Defining on $\mathcal{H} = V \times Q$ the bilinear and linear forms

$$\mathcal{B} : \mathcal{H} \times \mathcal{H} \longrightarrow \mathbb{R} \quad \text{and} \quad \mathcal{L} : \mathcal{H} \longrightarrow \mathbb{R}$$

through

$$\mathcal{B}(w, \xi; v, \mu) = a(w, v) - b(v, \xi) - b(w, \mu), \quad (27)$$

$$\mathcal{L}(v, \mu) = \ell(v) - g(\mu), \quad (28)$$

A compact formulation

Defining on $\mathcal{H} = V \times Q$ the bilinear and linear forms

$$\mathcal{B} : \mathcal{H} \times \mathcal{H} \longrightarrow \mathbb{R} \quad \text{and} \quad \mathcal{L} : \mathcal{H} \longrightarrow \mathbb{R}$$

through

$$\mathcal{B}(w, \xi; v, \mu) = a(w, v) - b(v, \xi) - b(w, \mu), \quad (27)$$

$$\mathcal{L}(v, \mu) = \ell(v) - g(\mu), \quad (28)$$

the variational problem can be reformulated as:

$$\begin{cases} \text{Find } (u, \lambda) \in V \times \Lambda \text{ such that :} \\ \mathcal{B}(u, \lambda; v, \mu - \lambda) \leq \mathcal{L}(v, \mu - \lambda) \quad \forall (v, \mu) \in V \times \Lambda. \end{cases} \quad (29)$$

$$\mathcal{B}_h((u_h, \lambda_h); (v, \xi)) = \mathcal{B}((u_h, \lambda_h); (v, \xi)) - \alpha \mathcal{B}_h((u_h, \lambda_h); (v, \xi))$$

$$\mathcal{L}_h(v, \xi) = \mathcal{L}(v, \xi) - \alpha \mathcal{L}_h(v, \xi)$$

$$\begin{aligned}\mathcal{B}_h((u_h, \lambda_h); (v, \xi)) &= \mathcal{B}((u_h, \lambda_h); (v, \xi)) - \alpha \mathcal{B}_h((u_h, \lambda_h); (v, \xi)) \\ \mathcal{L}_h(v, \xi) &= \mathcal{L}(v, \xi) - \alpha \mathcal{L}_h(v, \xi)\end{aligned}$$

with

$$\begin{aligned}\mathcal{B}_h((w, \xi); (v, \mu)) &:= \sum_{T \in \mathcal{T}_h} h_T^2 (-\Delta w - \xi, -\Delta v - \mu)_T \\ \mathcal{L}_h(v, \mu) &:= \sum_{T \in \mathcal{T}_h} h_T^2 (f, -\Delta v - \mu)_T\end{aligned}$$


Note that with the assumption $f \in L^2(\Omega)$ it holds that $\Delta u + \lambda \in L^2(\Omega)$ even if $\Delta u \notin L^2(\Omega)$ and $\lambda \notin L^2(\Omega)$. Hence, it holds that:

$$\mathcal{B}_h(u, \lambda; v_h, \mu_h) = \mathcal{L}_h(v_h, \mu_h), \quad \forall (v_h, \mu_h) \in V_h \times \Lambda_h \quad (30)$$

Reissner-Mindlin plate

For a clamped Reissner-Mindlin plate we look for a rotation θ and displacement w in the set \mathcal{K} defined by:

$$\mathcal{K} := \{(\eta, v) \in V := \mathbf{H}_0^1(\Omega) \times H_0^1(\Omega); \quad w \geq \psi\}$$



Reissner-Mindlin plate

The problem consists of

$$\text{Finding } (\boldsymbol{\theta}, w) =: \arg \min_{(\boldsymbol{\eta}, v) \in \mathcal{K}} J(\boldsymbol{\eta}, v) \quad (31)$$

where,

$$J(\boldsymbol{\theta}, w) = \frac{1}{2} \int_{\Omega} \mathbb{C} \boldsymbol{\varepsilon}(\boldsymbol{\theta}) : \boldsymbol{\varepsilon}(\boldsymbol{\theta}) \, dx + \frac{\lambda t^{-2}}{2} \int_{\Omega} |\nabla w - \boldsymbol{\theta}|^2 \, dx - \int_{\Omega} f w \, dx$$

where the matrix \mathbb{C} and the scalar λ depend on plate material, t is the thickness of the plate and f represents the loading. We recall the

$$\boldsymbol{\varepsilon}(\boldsymbol{\theta}) = \begin{pmatrix} \partial_1 \theta_1 & \frac{\partial_1 \theta_2 + \partial_2 \theta_1}{2} \\ \frac{\partial_2 \theta_1 + \partial_1 \theta_2}{2} & \partial_2 \theta_2 \end{pmatrix}$$

Fourth order contact problems

Bernoulli's beam

Now we consider a clamped Bernoulli's beam posed over an obstacle ψ , the equilibrium problem reads :

$$\text{Find } u := \operatorname{argmin}_{v \in \mathcal{K}_B} J(v)$$

where,

$$J(v) := \frac{1}{2} \int_0^L (v'')^2 dx - \langle f, v \rangle$$
$$\mathcal{K}_B := \{v \in V := H_0^2(0, L); v \geq \psi\}$$

Then,

$$a(u, v) := \int_0^L u'' v'' dx, \quad b(v, \xi) = \langle \xi, v \rangle$$
$$\ell(v) := \langle f, v \rangle, \quad g(\mu) = (\psi, \mu)$$

The complementarity system reads:

$$\left. \begin{aligned} w^{(4)} - \lambda &= f \\ \lambda &\geq 0 \\ \lambda(w - \psi) &= 0 \end{aligned} \right\} \quad \text{a.e in } \Omega \quad (32)$$

$$\begin{cases} w(0) = w'(0) = 0 \\ w(L) = w'(L) = 0 \end{cases} \quad (33)$$

Remark 2

Under appropriate smoothness assumptions, the solution to the Bernoulli's problem over a rigid obstacle is in H^3 but it cannot belong to H^4 . The exact solutions given in [5] seem to indicate that the smoothness threshold is $C^{2,1}$ or $H^{7/2-\epsilon}$, $\epsilon > 0$.

Compact form

We define,

$$\mathcal{H} := H_0^2(0, L) \times H^{-2}(0, L)$$

$$\Lambda := \{\mu \in H^{-2}(0, L); \mu \geq 0; \quad \text{a.e in } (0, L)\}$$

and

$$\mathcal{B}(w, \mu; (v, \xi)) = a(w, v) - b(v, \mu) - b(w, \xi)$$

$$\mathcal{L}(v, \xi) = (f, v) - (\psi, \xi)$$

the variational problem can be reformulated as:

$$\begin{cases} \text{Find } (u, \lambda) \in V \times \Lambda \text{ such that :} \\ \mathcal{B}(u, \lambda; v, \mu - \lambda) \leq \mathcal{L}(v, \mu - \lambda) \quad \forall (v, \mu) \in V \times \Lambda. \end{cases} \quad (34)$$

VC Discretization

Let \mathcal{C}_h be a discretization of $[0, L]$, we consider the finite element subspaces

$$V_h \subset H_0^2(0, L), \quad Q_h \subset H^{-2}(0, L) \quad (35)$$

Moreover, we define

$$\Lambda_h = \{\mu_h \in Q_h : \mu_h \geq 0 \text{ in } (0, L)\} \subset \Lambda. \quad (36)$$

Let us introduce bilinear and linear forms \mathcal{B}_h and \mathcal{L}_h by

$$\mathcal{B}_h(w, \xi; v, \mu) = \mathcal{B}(w, \xi; v, \mu) - \alpha \mathcal{S}_h(w, \xi; v, \mu)$$

$$\mathcal{S}_h(w, \xi; v, \mu) = \sum_{I \in \mathcal{C}_h} h_I^4 (w^{(4)} - \xi, v^{(4)} - \mu)_I$$

$$\mathcal{L}_h(v, \mu) = \mathcal{L}(v, \mu) - \alpha \sum_{I \in \mathcal{C}_h} h_I^4 (f, v^{(4)} - \mu)_I, \quad \alpha > 0$$

Discrete problem

$$\left\{ \begin{array}{l} \text{Find } (u_h, \lambda_h) \in V_h \times \Lambda_h \text{ such that :} \\ \mathcal{B}_h(u_h, \lambda_h; v_h, \mu_h - \lambda_h) \leq \mathcal{L}_h(v_h, \mu_h - \lambda_h) \quad \forall (v_h, \mu_h) \in V_h \times \Lambda_h. \end{array} \right.$$

Let us introduce the following norm

$$|||(w_h, \xi_h)|||_h^2 = \|w_h\|_2^2 + \|\xi_h\|_{-2}^2 \quad (37)$$

Theorem 4

Then for all $(v_h, \mu_h) \in V_h \times Q_h$ there exists $w_h \in v_h$ such that

$$\mathcal{B}_h(v_h, \mu_h; w_h, -\mu_h) \gtrsim |||(v_h, \mu_h)|||_h^2 \quad (38)$$

$$|||(w_h, -\mu_h)|||_h \lesssim |||(v_h, \mu_h)|||_h \quad (39)$$

Theorem 5

It holds that

$$\begin{aligned} & |||(u - u_h, \lambda - \lambda_h)||| \\ & \lesssim \inf_{v_h \in V_h, \mu_h \in \Lambda_h} \left(|||(u - v_h, \lambda - \mu_h)||| + \sqrt{\langle u - \psi, \mu_h \rangle} \right) + \text{osc}(f). \end{aligned}$$

(A priori estimate)

Theorem 5

It holds that

$$\begin{aligned} & |||(u - u_h, \lambda - \lambda_h)||| \\ & \lesssim \inf_{v_h \in V_h, \mu_h \in \Lambda_h} \left(|||(u - v_h, \lambda - \mu_h)||| + \sqrt{\langle u - \psi, \mu_h \rangle} \right) + \text{osc}(f). \\ & = \inf_{v_h \in V_h, \mu_h \in \Lambda_h} \left(|||(u - v_h, \lambda - \mu_h)||| + \sqrt{\langle u - \psi, \mu_h - \lambda \rangle} \right) + \text{osc}(f). \\ & \sim h^\alpha, \quad \alpha > 0 \end{aligned}$$

For the Kircchoff plate model, we define:

$$\begin{aligned} K(w) &= -\varepsilon(\nabla w), \\ M(w) &= \frac{t^3}{12} C K(w). \end{aligned}$$

The obstacle problem of a clamped Kircchoff plate reads:

$$\text{Find } u = \arg \min_{v \in \mathcal{K}} \left[\frac{1}{2} a(v, v) - \ell(v) \right], \quad (40)$$

with

$$\begin{aligned} a(w, v) &= \int_{\Omega} M(w) : K(v) dx, \\ \ell(v) &= \int_{\Omega} f v \, dx \\ \mathcal{K} &= \{v \in H_0^2(\Omega) : v \geq \psi \text{ in } \Omega\}. \end{aligned}$$

The strong form is thus : Find u and λ such that

$$\mathcal{A}(u) - \lambda = \ell \quad \text{in } \Omega \quad (41)$$

$$\lambda \geq 0 \quad \text{in } \Omega \quad (42)$$

$$\lambda(u - \psi) = 0 \quad \text{in } \Omega \quad (43)$$

$$u = 0 \quad \text{and} \quad \frac{\partial u}{\partial n} = 0 \quad \text{on } \partial\Omega. \quad (44)$$

with the biharmonic operator $\mathcal{A}(u)$ given by

$$\mathcal{A}(u) := D\Delta^2 u \quad (45)$$

where D stands for the bending stiffness defined through

$$D = \frac{Et^3}{12}(1 - \nu^2) \quad (46)$$

Consistent FE discretization

Let \mathcal{T}_h be a conforming shape regular triangulation of Ω which we assume to be polygonal. The finite element subspaces are

$$V_h \subset V, \quad Q_h \subset Q \quad (47)$$

Moreover, we define

$$\Lambda_h = \{\mu_h \in Q_h : \mu_h \geq 0 \text{ in } \Omega\} \subset \Lambda. \quad (48)$$

Let us introduce bilinear and linear forms \mathcal{B}_h and \mathcal{L}_h by

$$\mathcal{B}_h(w, \xi; v, \mu) = \mathcal{B}(w, \xi; v, \mu) - \alpha \mathcal{S}_h(w, \xi; v, \mu)$$

$$\mathcal{S}_h(w, \xi; v, \mu) = \sum_{T \in \mathcal{T}_h} h_T^4 (\mathcal{A}(w) - \xi, \mathcal{A}(v) - \mu)_T$$

$$\mathcal{L}_h(v, \mu) = \mathcal{L}(v, \mu) - \alpha \sum_{T \in \mathcal{T}_h} h_T^4 (f, \mathcal{A}(v) - \mu)_T, \quad \alpha > 0$$

We then consider the following problem: **Problem 2** Find $(u_h, \lambda_h) \in V_h \times \Lambda_h$ such that

$$\mathcal{B}(u_h, \lambda_h; v_h, \mu_h - \lambda_h) \leq \mathcal{L}(v_h, \mu_h - \lambda_h) \quad \forall (v_h, \mu_h) \in V_h \times \Lambda_h$$

Then for the conforming finite element spaces :

$$V_h = \{v_h \in H_0^2(0, L), \quad v_h|_T \in \mathbb{P}^5(T), \forall T \in \mathcal{T}_h\}$$
$$Q_h = \{\mu_h \in Q; \quad \mu_h|_T \in \mathbb{P}^k(T), \forall T \in \mathcal{T}_h, \quad k \geq 0\}$$

Then we obtain:

- The analogue discrete stability result as in Theorem 4.
- The analogue a priori error estimate as in Theorem 5.

A posteriori error estimate

First we recall the following integration by parts formula, valid in any domain $R \subset \Omega$

$$\begin{aligned} a_R(w, v) = & \int_R \mathcal{A}(w) v dx - \int_{\partial R} Q_n(w) v ds \\ & - \int_{\partial R} \left(M(w) \frac{\partial v}{\partial n} + M_{ns}(w) \frac{\partial v}{\partial s} \right) ds. \end{aligned}$$

where we have used the shorthand notation

$$a_R(w, v) = \int_R M(w) : K(v) dx,$$

A posteriori error estimate

Now we define the normal shear force and the normal and twisting moments through

$$\begin{aligned} Q_n(w) &= Q(w) \cdot n, & M_{nn}(w) &= n \cdot M(w)n, \\ M_{ns}(w) &= M_{sn}(w) = s \cdot M(w)n, \end{aligned}$$

with n and s denoting the normal and tangential directions at R .
integrating by parts on a smooth $S \subset R$ we get

$$\int_S Q_w v ds - \int_S M_{ns}(w) \frac{\partial v}{\partial s} ds = \int_S v_n(w) ds - |_p^q M_{ns}(w) v, \quad (49)$$

where p and q are the endpoints of S and the quantity

$$V_n(w) = Q_n(w) + \frac{\partial M_{ns}(w)}{\partial s} \quad (50)$$

Denote by $\omega_E = T_1 \cup T_2$ the pair of triangles sharing an edge E and define jumps in the normal moment and the shear force over E through

$$\begin{aligned}\llbracket M_{nn}(v) \rrbracket_E &= M_{nn}(v) - M_{n'n'}(v) \\ \llbracket V_n(v) \rrbracket_E &= V_n(v) + V_{n'}(v)\end{aligned}$$

where n and n' stand for the outward normals to T_1 and T_2 , respectively.

To derive a posteriori error bounds, we define the local residual estimators

$$\eta_T^2 = h_T^4 \|\mathcal{A}(u_h) - \lambda_h - f\|_{0,T}^2, \quad (51)$$

$$\eta_E^2 = h_E^3 \| \llbracket V_n(u_h) \rrbracket \|_{0,E}^2 + h_E \| \llbracket M_{nn}(u_h) \rrbracket \|_{0,E}^2, \quad (52)$$

and the corresponding global estimator

$$\eta^2 = \sum_{T \in \mathcal{T}_h} \eta_T^2 + \sum_{E \in \mathcal{E}_h^I} \eta_E^2, \quad (53)$$

where \mathcal{E}_h^I denotes the set of interior edges in the mesh, An additional global estimator S , due to the unknown location of the contact boundary, is defined through

$$S^2 = (u_h - \psi)_+ + \sum_{T \in \mathcal{T}_h} \frac{1}{h_T^4} \|(\psi - u_h)_+\|_{0,T}^2 \quad (54)$$

where $u_+ = \max(u, 0)$ denotes the positive part of u .

The following a posteriori estimate holds:

Theorem 6

$$|||(u - u_h, \lambda - \lambda_h)||| \lesssim \eta + S$$

Remark 3

the upper bound cannot be established as elegantly as for the second order problem, since the positive part function is not in $H^2(\Omega)$.

Theorem 7

$$\eta \lesssim |||(u - u_h, \lambda - \lambda_h)|||. \quad (55)$$

The following a posteriori estimate holds:

Theorem 6

$$|||(u - u_h, \lambda - \lambda_h)||| \lesssim \eta + S$$

Remark 3

the upper bound cannot be established as elegantly as for the second order problem, since the positive part function is not in $H^2(\Omega)$.

Theorem 7

$$\eta \lesssim |||(u - u_h, \lambda - \lambda_h)|||. \quad (55)$$


(55) can be proved with the help of the following **saturation assumption**: There exists $\beta < 1$ such that:

$$|||(u - u_{h/2}, \lambda - \lambda_{h/2})|||_{h/2} \leq \beta |||(u - u_h, \lambda - \lambda_h)|||_h$$

which itself an open problem.

Numerical Tests

Signorini problem



Signorini problem







FIGURE 1 – The domain Ω




(a) The mesh



(b) Isovalues



(c) Displacements



(d) Deformation

Timoshenko's beam

Now we present numerical tests for Timoshenko's beam:

Timoshenko's beam

Now we present numerical tests for Timoshenko's beam:

- 1 For the first test we take $\psi_1 = -0.4x^2 + 0.4x - 0.150$ and $f = -1$.

Timoshenko's beam

Now we present numerical tests for Timoshenko's beam:


- 1 For the first test we take $\psi_1 = -0.4x^2 + 0.4x - 0.150$ and $f = -1$.
- 2 For the second test we take $\psi_2 = 0.05$ and $f = 1$.

Timoshenko's beam


Now we present numerical tests for Timoshenko's beam:

- 1 For the first test we take $\psi_1 = -0.4x^2 + 0.4x - 0.150$ and $f = -1$.
- 2 For the second test we take $\psi_2 = 0.05$ and $f = 1$.

For both tests we use the finite element $P_2 - P_1 - P_0$ and consider very small thickness $t = 0.001$ in order to test the method against the locking phenomena.




(a) with $w \geq \psi_1$




(b) with $w \leq \psi_2$


Kircchoff plate




(a) isovalues



(b) deformed



(c) The obstacle



(d) the constraint

The finite element method leads to stable discrete problems for very simple choice of the finite element subspaces even for very small values of thickness t .

The finite element method leads to stable discrete problems for very simple choice of the finite element subspaces even for very small values of thickness t . Therefore, at least for the considered problem, it is locking-free. It allows us to use different and various approaches to solve a constrained minimization problem as it reformulates the problem as a standard variational inequality.

The finite element method leads to stable discrete problems for very simple choice of the finite element subspaces even for very small values of thickness t . Therefore, at least for the considered problem, it is locking-free. It allows us to use different and various approaches to solve a constrained minimization problem as it reformulates the problem as a standard variational inequality. The only drawback that we have observed is the choice of the parameter α .

The finite element method leads to stable discrete problems for very simple choice of the finite element subspaces even for very small values of thickness t . Therefore, at least for the considered problem, it is locking-free. It allows us to use different and various approaches to solve a constrained minimization problem as it reformulates the problem as a standard variational inequality. **The only drawback that we have observed is the choice of the parameter α .** Theoretically, it belongs to an interval of the form $]0, C[$ where the constant C depends on the domain and the coercivity constant of the corresponding bilinear form, which is not always available.

The finite element method leads to stable discrete problems for very simple choice of the finite element subspaces even for very small values of thickness t . Therefore, at least for the considered problem, it is locking-free. It allows us to use different and various approaches to solve a constrained minimization problem as it reformulates the problem as a standard variational inequality. **The only drawback that we have observed is the choice of the parameter α .** Theoretically, it belongs to an interval of the form $]0, C[$ where the constant C depends on the domain and the coercivity constant of the corresponding bilinear form, which is not always available. However, in practical tests, we have seen that for the considered example, some simple choice of the parameter α leads to the convergent method.



Brezzi, F., Hager, W.W., Raviart, P.A. : Error estimates for the finite element solution of variational inequalities. II.Mixed methods. Numer. Math. 31(1), 1-16 (1978).



T. Gustafsson, R. Stenberg and J. Videman. A stabilised finite element method for the plate obstacle problem. BIT Numerical Mathematics. 59, pages: 97-124 (2019) Springer.



P. Hild and Y. Renard. A stabilized Lagrange multiplier method for the finite element approximation of contact problems in elastostatics. Numer. Math., 115(1):101(129, 2010).



T. Fuhrer. First-order least-squares method for the obstacle problem. Numerische Mathematik (2019).



G. Aleksanyan. Regularity of the free boundary in the biharmonic obstacle problem. Calc. Var. (2019) 58:206.