

L3: Higher-order Functions; Scope of Names

Structure and Interpretation of Computer Programs

Martin Henz

July 7, 2023

- 1 Announcements
- 2 Nested declarations
- 3 Higher-order functions
- 4 Scope of names

Announcements

- Missions: they are the main pieces of homework! Work in the assigned pairs.
- Quests: they are “extra homework”, for practice! Quests are not graded.
- Contest “Beautiful Runes” opens today! Closes on Monday, 10/7. Contests are not graded.
- Exam: On Thursday, 20/7, 10am to 12noon.

Schedule

- Lectures, 10am–12noon: Saturday (8/7), Monday–Saturday (10/7–15/7)
- Labs, 2pm–6pm: Monday–Saturday (10/7–15/7)
- Project work: 17/7–12/7
- Project presentations: Tuesday 25/7

Some Words of Advice

- Read the textbook
- Use the substitution model (and stepper tool, if needed)
- Think, then program
- Less is more

- 1 Announcements
- 2 **Nested declarations**
 - Nested function declarations
 - Nested constant declarations
- 3 Higher-order functions
- 4 Scope of names

Names can refer to intermediate values

Example from SICP JS 1.3.2

$$f(x, y) = x(1 + xy)^2 + y(1 - y) + (1 + xy)(1 - y)$$

Compute $f(2, 3)$

```
function f(x, y) {  
    const a = 1 + x * y;  
    const b = 1 - y;  
    return x * square(a) + y * b + a * b;  
}
```

```
f(2, 3);
```

Can we do this with functions, too?

```
function sum_of_squares(a, b) {  
    return square(a) + square(b);  
}  
function hypotenuse(a, b) {  
    return math_sqrt(sum_of_squares(a, b));  
}
```

“Hiding”

Can we hide the function `sum_of_squares` so that only the body of `hypotenuse` can “see” it?

Yes, we can! (see also SICP JS 1.1.8)

```
function hypotenuse(a, b) {  
    function sum_of_squares(a, b) {  
        return square(a) + square(b);  
    }  
    return math_sqrt(sum_of_squares(a, b));  
}
```

Function nesting

Function declarations can be *nested inside of* other function declarations, and only visible there.

sum_of_squares could use parameters of hypotenuse

```
function hypotenuse(a, b) {  
    function sum_of_squares() {  
        return square(a) + square(b);  
    }  
    return math_sqrt(sum_of_squares());  
}
```

Even simpler version: Using nested const

```
function hypotenuse(a, b) {  
    const sum_of_squares = square(a) + square(b);  
    return math_sqrt(sum_of_squares);  
}
```

Can we avoid tree recursion?

```
function fractal_1(rune, n) {  
    return n === 1  
        ? rune  
        : beside(rune,  
                  stack(fractal_1(rune, n - 1),  
                        fractal_1(rune, n - 1)));  
}
```

Question

Can we implement this function with linear recursion?

Is this a good idea?

```
function fractal_2(rune, n) {  
    const smaller_frac = fractal_2(rune, n - 1);  
    return n === 1  
        ? rune  
        : beside(rune,  
                  stack(smaller_frac, smaller_frac));  
}
```

Can we declare a `const...`

...just for the alternative of the conditional?

Conditional *statements* (see SICP JS 1.3.2)

```
function fractal_3(rune, n) {  
  if (n === 1) {  
    return rune;  
  } else {  
    const f = fractal_3(rune, n - 1);  
    return beside(rune, stack(f, f));  
  }  
}
```

- Each branch of the conditional is a *block*.
- A block can have local names, only visible inside the block.
- Remember to return a result *in each branch*.
(Otherwise undefined is returned.)

1 Announcements

2 Nested declarations

3 Higher-order functions

- Functions as arguments (1.3.1)
- Lambda expressions (1.3.2)
- Functions as returned values (1.3.4)
- Summary of constructs discussed today

4 Scope of names

Passing functions to functions

```
function f(g, x) {  
    return g(x);  
}
```

```
function g(y) {  
    return y + 1;  
}
```

```
f(g, 7);
```


Passing more functions to functions

```
function f(g, x) {  
    return g(g(x));  
}
```

```
function g(y) {  
    return y + 1;  
}
```

```
f(g, 7);
```

Abstraction: Recall `repeat_pattern`

Repeating the pattern n times

```
repeat_pattern(4, make_cross, rcross);
```

Passing a **rune** function

```
function transform_mosaic(p1, p2, p3, p4,  
                          transform) {  
    return transform(mosaic(p1, p2, p3, p4));  
}
```

Look at **this function (1.3.1)**

```
function sum_integers(a, b) {  
    return a > b  
        ? 0  
        : a + sum_integers(a + 1, b);  
}
```

...and this one

```
function cube(x) {  
    return x * x * x;  
}
```

```
function sum_skip_cubes(a, b) {  
    return a > b  
        ? 0  
        : cube(a) + sum_skip_cubes(a + 2, b);  
}
```

Abstraction (1.3.1)

```
function sum(a, b) {  
    return a > b ? 0  
        : ⟨compute value with a⟩  
        +  
        sum(⟨next value from a⟩, b);  
}
```

in Source:

```
function sum(term, a, next, b) {  
    return a > b ? 0  
        : term(a)  
        +  
        sum(term, next(a), next, b);  
}
```

sum_integers using sum

```
function identity(x) {  
    return x;  
}  
function plus_one(x) {  
    return x + 1;  
}  
function sum_integers(a, b) {  
    return sum(identity, a, plus_one, b);  
}
```

sum_skip_cubes using sum

```
function cube(x) {  
    return x * x * x;  
}  
function plus_two(x) {  
    return x + 2;  
}  
function sum_skip_cubes(a, b) {  
    return sum(cube, a, plus_two, b);  
}
```


sum_skip_cubes using sum

```
function cube(x) {  
    return x * x * x;  
}  
function plus_two(x) {  
    return x + 2;  
}  
function sum_cubes(a, b) {  
    return sum(cube, a, plus_two, b);  
}
```

Visibility

Can we “hide” cube and plus_two inside of sum_skip_cubes?

Yes, we can! (see also SICP JS 1.1.8)

```
function sum_skip_cubes(a, b) {  
    function cube(x) {  
        return x * x * x;  
    }  
    function plus_two(x) {  
        return x + 2;  
    }  
    return sum(cube, a, plus_two, b);  
}
```

Another look at such local functions

```
function sum_skip_cubes(a, b) {  
    function cube(x) {  
        return x * x * x;  
    }  
    function plus_two(x) {  
        return x + 2;  
    }  
    return sum(cube, a, plus_two, b);  
}
```

This is still quite verbose

Do we need all these words such as `function`, `return`?

Do we need to even give names to these functions?

No, we don't! Lambda expressions

```
function sum_skip_cubes(a, b) {  
  function cube(x) {  
    return x * x * x;  
  }  
  function plus_two(x) {  
    return x + 2;  
  }  
  return sum(cube, a, plus_two, b);  
}
```

// instead just write:

```
function sum_skip_cubes(a, b) {  
  return sum(x => x * x * x, a, x => x + 2, b);  
}
```

Lambda expressions (1.3.2)

New kinds of expressions

$$(\textit{parameters}) \Rightarrow \textit{expression}$$

If there is only one parameter, you can write

$$\textit{parameter} \Rightarrow \textit{expression}$$

Meaning

The expression evaluates to a function value.

Function has given *parameters* and **return** *expression* ; as body.

An alternative syntax for function declaration

```
function plus4(x) {  
    return x + 4;  
}
```

can be written as

```
const plus4 = x => x + 4;
```

Returning Functions from Functions (1.3.4)

```
function make_adder(x) {  
    function adder(y) {  
        return x + y;  
    }  
    return adder;  
}  
  
const adder_four = make_adder(4);  
adder_four(6);
```

...or with the new lambda expressions

```
function make_adder(x) {  
    return y => x + y;  
}
```

```
const adder_four = make_adder(4);  
adder_four(6);
```


Returning Functions from Functions

```
function make_adder(x) {  
    return y => x + y;  
}
```

```
( make_adder(4) )(6);
```

```
// you can also write:  
//  
// make_adder(4)(6);
```

Returning Functions from Functions

```
function make_adder(x) {  
    return y => x + y;  
}
```

```
const adder_1 = make_adder(1);  
const adder_2 = make_adder(2);
```

```
adder_1(10); // returns 11
```

```
adder_2(20); // returns 22
```

Summary of constructs discussed today

- Nested constant and function declaration statements
- Conditional statements and blocks
- **Lambda expressions**

- 1 Announcements
- 2 Nested declarations
- 3 Higher-order functions
- 4 Scope of names**
 - Examples
 - Overview of scoping rules
 - The details

Scope of names: an example

```
const z = 2;  
function f(g) {  
    const z = 4;  
    return g(z);  
}
```

```
f( y => y + z );
```

Questions about scope

What names are declared by this program?

Which declaration does each name occurrence refer to?

Scope of names: another example

```
const x = 10;  
function square(x) {  
    return x * x;  
}  
function addx(y) {  
    return y + x;  
}  
square(x + 5) * addx(x + 20);
```

Questions about scope

Which declaration does each occurrence of `x` refer to?

Scope of names: yet another example

```
const pi = 3.141592653589793;  
function circle_area_from_radius(r) {  
    const pi = 22 / 7;  
    return pi * square(r);  
}
```

Questions about scope

Which declaration does the occurrence of `pi` refer to?

Scope of names: **hypotenuse** example

```
function square(x) {  
    return x * x;  
}  
  
function hypotenuse(a, b) {  
    function sum_of_squares() {  
        return square(a) + square(b);  
    }  
    return math_sqrt(sum_of_squares());  
}
```

Names can refer to declarations outside of the immediately surrounding function declaration.

Overview of scoping rules

Declarations mandatory

All names in Source must be declared.

Forms of declaration

- 1 Pre-declared names
- 2 Constant declarations
- 3 Parameters of function declarations and lambda expressions
- 4 Function name of function declarations

Scoping rule

A name occurrence refers to the *closest surrounding* declaration.

Forms of Declaration

(1) Pre-declared names

The [Source §1](#) pages tell us what names are pre-declared, e.g. `math_floor`.

We can also import further pre-declared names from modules. For example, from the [rune](#) module:

```
import { heart, quarter_turn_right } from "rune";
```

Forms of Declaration

(2) Constant declarations

The scope of a constant declaration is the closest surrounding pair of `{...}`, or the whole program, if there is none.

Example

```
function f(x, y) {  
    if (x > 0) {  
        const z = x * y;  
        return math_sqrt(z);  
    } else {  
        ...  
    }  
}
```

Forms of Declaration

(3) Parameters

The scope of the parameters of a lambda expression or function declaration is the body of the function.

```
function f(x, y, z) {  
    ... x ... y ... z ...  
}
```

$(v, w, u) \Rightarrow \dots v \dots w \dots u \dots$

Forms of Declaration

(4) Function name

The scope of the function name of a function declaration is as if the function was declared with `const`.

```
function f(x) {  
    ...  
}
```

as if we wrote

```
const f = ...;
```

Lexical scoping

Scoping rule

A name occurrence refers to the *closest surrounding* name declaration.

```
function f(x) {  
    function g(w) {  
        const x = ...;  
        const y = x + 1;  
        return x =>  
            ...x...;  
    }  
    return g(x);  
}
```

Important Ideas

- *Hiding* can be a useful abstraction technique
- *Recursion* is an elegant pattern of problem solving
- Functions can be *passed to* functions
- Functions can be *returned from* functions
- Higher-order functions are *useful* for building abstractions
- With nested functions and conditional statements, we need to understand the *scope* of names

Concluding Chapter 1

- Mental model: substitution model
- Big ideas: iterative/recursive processes, higher-order, scope
- Problem solving technique: recursion (“wishful thinking”)
- Look out for Chapter 2: Building Abstractions with Data, starting with L5 tomorrow