

Calculation of Parameters and Details Discussion of Neural Network Model

Md. Istiak Ahammed

Example: **Feed Forward Neural Network Architecture including**

1. Fully connected layer/Dense layer/Linear layer
2. 1D Batch Normalization layer
3. ReLU activation function layer
4. Dropout layer

Model's Code: Dimensionality increasing custom model

```
class CustomFFNv5(nn.Module):
    def __init__(self, input_dim, hidden_dim, output_dim, l2_lambda):
        super(CustomFFNv5, self).__init__()

        self.fc1 = nn.Linear(input_dim, hidden_dim) # 32
        self.bn1 = nn.BatchNorm1d(hidden_dim) # Apply Batch Normalization
        self.relu1 = nn.ReLU()
        self.dropout1 = nn.Dropout(0.2)

        self.fc2 = nn.Linear(hidden_dim, 2 * hidden_dim) # (32, 64)
        self.bn2 = nn.BatchNorm1d(2 * hidden_dim) # Apply Batch Normalization # 64
        self.relu2 = nn.ReLU()
        self.dropout2 = nn.Dropout(0.2)

        self.fc3 = nn.Linear(2 * hidden_dim, 4 * hidden_dim) # (64, 128)
        self.bn3 = nn.BatchNorm1d(4 * hidden_dim) # Apply Batch Normalization
        self.relu3 = nn.ReLU()
        self.dropout3 = nn.Dropout(0.2)

        self.fc4 = nn.Linear(4 * hidden_dim, 8 * hidden_dim) # (128, 256)
        self.bn4 = nn.BatchNorm1d(8 * hidden_dim) # Apply Batch Normalization
        self.relu4 = nn.ReLU()
        self.dropout4 = nn.Dropout(0.2)

        self.fc5 = nn.Linear(8 * hidden_dim, 16 * hidden_dim) # (256, 512)
        self.bn5 = nn.BatchNorm1d(16 * hidden_dim) # Apply Batch Normalization
```

```

self.relu5 = nn.ReLU()
self.dropout5 = nn.Dropout(0.2)

self.fc6 = nn.Linear(16 * hidden_dim, output_dim) # (512, 2=Two Class)
self.l2_lambda = l2_lambda

def forward(self, x):
    x = self.fc1(x)
    x = self.bn1(x) # Apply Batch Normalization
    x = self.relu1(x)
    x = self.dropout1(x)

    x = self.fc2(x)
    x = self.bn2(x) # Apply Batch Normalization
    x = self.relu2(x)
    x = self.dropout2(x)

    x = self.fc3(x)
    x = self.bn3(x) # Apply Batch Normalization
    x = self.relu3(x)
    x = self.dropout3(x)

    x = self.fc4(x)
    x = self.bn4(x) # Apply Batch Normalization
    x = self.relu4(x)
    x = self.dropout4(x)

    x = self.fc5(x)
    x = self.bn5(x) # Apply Batch Normalization
    x = self.relu5(x)
    x = self.dropout5(x)

    x = self.fc6(x)
    return x

def l2_regularization_loss(self):
    l2_loss = 0.0
    for param in self.parameters():
        l2_loss += torch.sum(torch.square(param))

    return self.l2_lambda * l2_loss

```

Model's Summary:

Layer (type)	Output Shape	Param #
Linear-1	[-1, 32]	6,560
BatchNorm1d-2	[-1, 32]	64
ReLU-3	[-1, 32]	0
Dropout-4	[-1, 32]	0
Linear-5	[-1, 64]	2,112
BatchNorm1d-6	[-1, 64]	128
ReLU-7	[-1, 64]	0
Dropout-8	[-1, 64]	0
Linear-9	[-1, 128]	8,320
BatchNorm1d-10	[-1, 128]	256
ReLU-11	[-1, 128]	0
Dropout-12	[-1, 128]	0
Linear-13	[-1, 256]	33,024
BatchNorm1d-14	[-1, 256]	512
ReLU-15	[-1, 256]	0
Dropout-16	[-1, 256]	0
Linear-17	[-1, 512]	131,584
BatchNorm1d-18	[-1, 512]	1,024
ReLU-19	[-1, 512]	0
Dropout-20	[-1, 512]	0
Linear-21	[-1, 2]	1,026
Total params: 184,610		
Trainable params: 184,610		
Non-trainable params: 0		

Explanation of Parameters calculation in each layer

Linear-1: This is a fully connected layer with an input dimension of `input_dim` (204) and an output dimension of `hidden_dim` (32). The number of parameters in this layer is calculated as $(\text{input_dim} + 1) * \text{hidden_dim} = (204 + 1) * 32 = 6,560$.

BatchNorm1d-1: This is a batch normalization layer for 1-dimensional input with `hidden_dim` (32) features. It has $2 * \text{hidden_dim}$ parameters, consisting of mean and variance for each feature. So the number of parameters in this layer is $2 * \text{hidden_dim} = 2 * 32 = 64$.

Batch Normalization is typically applied after the linear transformation in a neural network layer and before the non-linear activation function. This helps to normalize the inputs to the activation function, stabilizing the training process and improving the network's ability to learn.

ReLU-1: This is the activation function layer and doesn't have any parameters.

Dropout-1: This is the dropout layer with a dropout rate of 0.2. It doesn't have any parameters.

Linear-2: This is a fully connected layer with an input dimension of `hidden_dim` (32) and an output dimension of $2 * \text{hidden_dim}$ (64). The number of parameters in this layer is $(\text{hidden_dim} + 1) * (2 * \text{hidden_dim}) = (32 + 1) * 64 = 2,112$.

BatchNorm1d-2: Batch normalization layer for 1-dimensional input with $2 * \text{hidden_dim}$ (64) features. It has $2 * (2 * \text{hidden_dim}) = 2 * 64 = 128$ parameters.

ReLU-2: Activation function layer.

Dropout-2: Dropout layer with a dropout rate of 0.2.

Linear-3: Fully connected layer with an input dimension of $2 * \text{hidden_dim}$ (64) and an output dimension of $4 * \text{hidden_dim}$ (128). The number of parameters in this layer is $(2 * \text{hidden_dim} + 1) * (4 * \text{hidden_dim}) = (2 * 32 + 1) * 128 = 8,320$.

BatchNorm1d-3: Batch normalization layer for 1-dimensional input with $4 * \text{hidden_dim}$ (128) features. It has $2 * (4 * \text{hidden_dim}) = 2 * 128 = 256$ parameters.

ReLU-3: Activation function layer.

Dropout-3: Dropout layer with a dropout rate of 0.2.

Linear-4: Fully connected layer with an input dimension of $4 * \text{hidden_dim}$ (128) and an output dimension of $8 * \text{hidden_dim}$ (256). The number of parameters in this layer is $(4 * \text{hidden_dim} + 1) * (8 * \text{hidden_dim}) = (4 * 32 + 1) * 256 = 33,024$.

BatchNorm1d-4: Batch normalization layer for 1-dimensional input with $8 * \text{hidden_dim}$ (256) features. It has $2 * (8 * \text{hidden_dim}) = 2 * 256 = 512$ parameters.

ReLU-4: Activation function layer.

Dropout-4: Dropout layer with a dropout rate of 0.2.

Linear-5: Fully connected layer with an input dimension of $8 * \text{hidden_dim}$ (256) and an output dimension of $16 * \text{hidden_dim}$ (512). The number of parameters in this layer is $(8 * \text{hidden_dim} + 1) * (16 * \text{hidden_dim}) = (8 * 32 + 1) * 512 = 131,584$.

BatchNorm1d-5: Batch normalization layer for 1-dimensional input with $16 * \text{hidden_dim}$ (512) features. It has $2 * (16 * \text{hidden_dim}) = 2 * 512 = 1,024$ parameters.

ReLU-5: Activation function layer.

Dropout-5: Dropout layer with a dropout rate of 0.2.

Linear-6: Fully connected layer with an input dimension of $16 * \text{hidden_dim}$ (512) and an output dimension of output_dim (2). The number of parameters in this layer is $(16 * \text{hidden_dim} + 1) * \text{output_dim} = (16 * 32 + 1) * 2 = 1,026$.

To calculate the total number of parameters, you sum up the parameters from all the layers. In this case, you sum up the parameters from all the Linear layers.

Let's calculate the total parameters for your model using $\text{input_dim} = 204$, $\text{hidden_dim} = 32$, and $\text{output_dim} = 2$

$$\begin{aligned}\text{Total parameters} &= 6,560 + 64 + 2,112 + 128 + 8,320 + 256 + 33,024 \\ &+ 512 + 131,584 + 1,024 + 1,026 \\ &= 184,610\end{aligned}$$