LAB REPORT

Submitted by:

Name: Esha Silvia Rozario

ID: 0692220005101004

Batch: CSE 19

Date: 04-12-22

Course: CSE LAB

Course Code: 1202

Submitted to:

A.H.M Saiful Islam
Associate Professor, Chairman

Department of CSE, NDUB

INDEX

LAB 01

INTRODUCTION TO C

NAME OF PROBLEMS: **PAGE**

[1] Write a program with C which display “We are CSE students.” ----------1

[2] Write a program with C which display,” Varsity, CSE, Your name, Code.”----1

[3] Write a program with C which display, F(letter) using # ----------1

[4] Write a program with C which display, A(letter) using # ----------2

[5] Write a program with C which display, C(letter) using # ----------2

[6] Write a program with C which display, multiplication table of 5 for 10 times.----------2

[7] Write a program with C which display, square with {-} & rhombus with {/}.-3

LAB 02

GENERAL PROBLEMS

NAME OF PROBLEMS: **PAGE**

[1] Input two numbers from the keyboard, find out the summation of two numbers. ----------4

[2] Find out the area of a Rectangle shaped Room. ----------4

[3] Find out the area of a Square shaped Room. ----------5

[4] Write down all three programs from P1 to P3 in a single code. ----------5

[5] There were 4687 people in a village in the last year. In this year, 349 people moved in and 280 people moved out of the village. how many people are there in this year?----------6

[6] A butcher sells beef at 700 Taka per kg and mutton at 800 Taka per kg. If we buy 3 kg of beef and 2 kg of mutton, and pay 4000 Taka, how much will be the change? ----------6

[7] Mr. X's monthly salary is P Taka. Every month he spends A Taka for house rent, B Taka for household expenses. He saves the remaining money in a bank. What amount of money does Mr. X save in a year? ----------7

[8] M and R together have X amount of Taka. M has 550 Taka more than R. How much money does M and R each has? You have to input the total amount of money. ----------7

[9] M and R together have 8500 Taka. M has 480 Taka less than R. how much money does M and R each has? ----------8

[10] The sum of ages of a Father and his daughter is 80 years. Father's age is four times the age of the daughter. What are their ages? ----------8

[11] The price of 2 cows and 3 goats together is 98050 Taka. The price of 1 goat is 6800 Taka. what is the price of one cow? ----------9

LAB 03

ARITHMETIC OPERATORS

NAME OF PROBLEMS: **PAGE**

[1] Write a C program to convert a given integer (in seconds) to hours, minutes and seconds.
Sample Input:
Input seconds: 25300
Sample Output: There are:
H:M:S - 7:1:40 ----------10

[2] Write a C program to convert specified days into years, weeks and days. Ignore leap year.
Sample Input:
Number of days: 1329
Sample Output:
Years: 3
Weeks: 33
Days: 3 ----------10

[3] Write a C program to convert a given integer (in days) to years, months and days, assume that all months have 30 days and all years have 365 days.
Sample Input:
Input no. of days: 2535

Sample Output:
6 Year(s)
11 Month(s)
15 Day(s) ----------11

[4] Write a C program to calculate a bike's average consumption from the given total distance (integer value) traveled (in km) and spent fuel (in litres, float number – 2 decimal point).
Sample Input:
Input total distance in km: 350
Input total fuel spent in liters: 5
Sample Output:
Average consumption (km/L) 70.000 ----------12

[5] There are X grams of rice at home. If we eat Y(Y<X) grams of rice every day, when the rice will be finish? ----------13

[6] N pieces of papers are necessary to prepare one book, how many books can be prepared by M(M>N) pieces of papers? ----------13

[7] A company gained profit of 95200 Taka in business and wanted to distribute this money equally to its employees. If 800 taka was given to each employee, how many employees are there in the company? ----------14

[8] Generalize the problem [7]. ----------14

[9] Every 250 products are packed in one cardboard box. In order to pack 43548 products, how many boxes will be necessary? ----------15

[10] Generalize the problem [9]. ----------15

[11] The price of 8 eggs is 72 Taka. If we buy 15 pieces of eggs, how much do we need to pay? ----------16

[12] Generalize the problem [11]. ----------17

[13] If the price of 4 bananas is 80 Taka, how much is the price for 10 bananas? ----------17

[14] Generalize the problem [13] ----------18

[15] Aysha bought 8 pencils at 64 Taka. How much will she pay if she buys 24 pencils?----------19

[16] Generalize the problem [15]. ----------19

[17] Write a program to calculate the sum of the first and the second last digit of a 5 digits number entered from the keyboard. ----------20

LAB 04

CONDITIONAL AND OTHER OPERATORS

NAME OF PROBLEMS: **PAGE**

[1] Write a C program to find the maximum in the given two numbers using the conditional operator. ----------21

[2] Write a C program to find the inputted number is positive or negative using the conditional operator. ----------22

[3] Write a C program to check whether the given number is odd or even using the conditional operator in C. ----------22

[4] Write a C program to find the minimum of two numbers using the conditional operator.----------23

[5] Write a program to enter two numbers. Make a comparison between them with the conditional operator. If the first number is greater than the second, perform a division operation otherwise multiplication operation.--23

[6] Use the conditional operator to produce a code to have the following sample input and output:
Sample Output for the different test-cases: -
Enter the number of items: 1
You have 1 item.
Enter the number of items: 2
You have 2 items.----------24

[7] Find the largest among three numbers using the conditional operator--24

[8] Length and breadth of a rectangle are 5 and 7 respectively. Write a program to calculate the area and perimeter of the rectangle.----------25

[9] Write a program to input the value of the radius of a circle from keyboard and then calculate its perimeter and area.----------25

[10] Write a program to enter a 4 digits number from keyboard. Add 8 to the number and then divide it by 3. Now, the modulus of that number is taken with 5 and then multiply the resultant value by 5. Display the final result.---26

[11] Now, solve the above question, [3] using assignment operators (e.g. +=, -=, *=). ---------- 26

[12] Enter two numbers from keyboard. Write a program to check if the two numbers are equal.----------27

[13] Write a program to enter the values of two variables 'a' and 'b' from keyboard and then check if both the conditions 'a < 50' and 'a < b' are true.27
[14] Now solve the above question [6] to check if at least one of the conditions 'a < 50' and 'a < b' is true.----------28
[15] Write a program to convert Fahrenheit into Celsius.----------29

[16] Write a program to calculate the sum of the digits of a 3 digits number which is entered from keyboard.---------- 29

LAB 05

IF, ELSE IF LADDER

NAME OF PROBLEMS: **PAGE**

[1] Admission to a professional course in subject to the following conditions:
Marks in mathematics >=60
Marks in Physics >=50
Marks in Chemistry >=40
Total in all three subjects >=200
or
Total in mathematics and physics>=150
Given the marks in the three subjects, write a program in C to process the applications to list the eligible candidates.----------31

[2] An electric power distribution company charges its domestic consumers as follows:

Consumption Units	Rate of Charge
0 - 200	BDT 0.50 per unit
201 - 400	BDT 100 plus BDT 0.65 per unit excess of 200
401 - 600	BDT 230 plus BDT 0.80 per unit excess of 400
601 and above	BDT 390 plus BDT 1.00 per unit excess of 600

Write a program to read number of units consumed and print out the amount to be paid by the customer.----------31

[3] The problem is attached in the image:

A computer showroom has announced the following seasonal discounts on purchase of items:

Purchase Amount	*Discount*	
	Pen Drive	*RAM*
0-100	---	5%
101-200	5%	7.5%
201-300	7.5%	10.0%
Above300	10.0%	15.0%

Write a program using switch and if statements to compute the net amount to be paid by a customer.

----------33

[4] Take values of length and breadth of a rectangle from user and check if it is square or not. ----------35

[5] Take two int values from user and print greatest among them.----------36

[6] Write a C program to input amount from user and print minimum number of notes (TK. 1000, 500, 100, 50, 20, 10, 5, 2, 1) required for the amount. ----------37

LAB 06

SWITCH STATEMENT

NAME OF PROBLEMS: **PAGE**

[1] A computer showroom has announced the following seasonal discounts on purchase of items:

Purchase Amount	Discount	
	Pen Drive	RAM
0-100	---	5%
101-200	5%	7.5%
201-300	7.5%	10.0%
Above300	10.0%	15.0%

Write a program using switch and if statements to compute the net amount to be paid by a customer.

[2] Write a C program using a switch case to check whether the number entered by the user is odd or even.

[3] Write a C program to checks whether a character entered by the user is a vowel or not by using the switch case statement.

[4] Write a menu-driven C program to find the area of the circle, area of the triangle and area of the rectangle according to the user's input choice.

The area is given by,

circle = PI*r*r

triangle = 0.5*base*height

rectangle = length*breadth

[5] Write a menu-driven C program to convert a given year into,

Months

Days

Hours

Minutes

Seconds

For simplicity don't include leap year, use

1 Year = 365 days

1 Month = 30 days

[1] A computer showroom has announced the following seasonal discount on purchase of items. Write a program using switch and if statements to computer the net amount to be paid by a customer.----------39

[2] Write a C program using a switch case to check whether the number entered by the user is odd or even.----------42

[3] Write a C program to check whether a character entered by the user is a vowel or not by using the switch case statement. ----------43

[4] Write a menu-driven C program to find the area of the circle, area of the triangle and area of the rectangle according to the user's input choice.
The area is given by,
circle = PI*r*r
triangle = 0.5*base*height
rectangle = length*breadth ----------44

[5] Write a menu-driven C program to convert a given year into,
Months Days Hours Minutes Seconds.
For simplicity don't include leap year.
Use:
1 Year = 365 days
1 Month = 30 days ----------46

LAB 07

NESTED LOOPS

NAME OF PROBLEMS: **PAGE**

[1] Print 1 to 10 using for loop. ----------47

[2] Print even numbers between 1 to 10 using loop. ----------47

[3] Print odd numbers between 1 to 10 using loop. ----------48

[4] Print the number of even numbers between 1 to 10 using loop. ----------48

[5] Print the number of odd numbers between 1 to 10 using loop. ----------49

[6] Summation of 1 to 5 using loop. ----------50

[7] Sum of all even numbers between 1 to 10. ----------50

[8] Sum of all odd numbers between 1 to 10. ----------51

[9] Run all the above 8 codes in one code. ----------51

LAB 08

ARRAY

NAME OF PROBLEMS: **PAGE**

[1] Display the array element. ----------57

[2] Show the square of each array element. ----------57

[3] Display the even number of an array. ----------58

[4] Display the odd number of an array. ----------59

[5] Count the even number of the array. ----------60

[6] Count the odd number of the array. ----------61

[7] Show the summation of the array element. ----------62

[8] Show all above 7 codes in one. ----------63

LAB 01

INTRODUCTION TO C

Code 1:

Source Code:

```
#include <stdio.h>

main()

{

   printf("We are CSE students");

}
```

Code 2:

Source Code:

```
#include <stdio.h>
main()

{
   printf("NDUB\nCSE\nEsha\n04");
}
```

Code 3:

Source Code:

```
#include <stdio.h>

main()

{
   printf("#####\n#\n####\n#\n#");
}
```

Code 4:

Source Code:

```
#include <stdio.h>
```

```
main()
{
   printf("     #     \n");
   printf("    # #     \n");
   printf("   #   #     \n");
   printf("  #######     \n");
   printf(" #       #     \n");
   printf("#         #     \n");
}
```

Code 5:

Source Code:

```
 #include <stdio.h>

main()
{
   printf("      ########   \n");
   printf("     ###      #    \n");
   printf("    ###            \n");
   printf("   ##             \n");
   printf("  ##             \n");
   printf("   ##            \n");
   printf("    ###            \n");
   printf("     ###      #     \n");
   printf("      ########  \n");
}
```

Code 6:

Source Code:

```
#include <stdio.h>
main()
{
   printf("5*1=1 \n");
   printf("5*2=10\n");
   printf("5*3=15\n");
   printf("5*4=20\n");
   printf("5*5=25\n");
   printf("5*6=30\n");
   printf("5*7=35\n");
   printf("5*8=40\n");
   printf("5*9=45\n");
   printf("5*10=50\n");
```

```
}
```

Code 7:

Source Code:

```
#include <stdio.h>
main()
{
  printf("---------------\n");
   printf("|              |\n");
   printf("|              |\n");
   printf("|              |\n");
   printf("---------------\n");
   printf("               \n");
   printf("   ----------\n");
   printf("  /          /\n");
   printf(" /          / \n");
   printf(" ----------  \n");
 }
```

LAB 02

GENERAL PROBLEMS

Code 1:

Source Code:

```
#include <stdio.h>
int main()
{
    int num1, num2, sum;

    printf("Enter two integers: ");
    scanf("%d %d", &num1, &num2);

    sum = num1 + num2;

    printf("Summation of %d and %d is : %d", num1, num2, sum);
    return 0;
}
```

Code 2:

Source Code:

```
#include <stdio.h>
int main()
{
    float length, width, area;
    printf("Enter length of rectangle: ");
    scanf("%f", &length);
    printf("Enter width of rectangle: ");
    scanf("%f", &width);

    area = length * width;

    printf("Area of rectangle = %f sq. units", area);

   return 0;
}
```

Code 3:

Source Code:

```
#include <stdio.h>
int main()
{
    float length, area;
    printf("Enter length of square: ");
    scanf("%f", &length);


    area = length * length;

    printf("Area of square = %f sq. units", area);

    return 0;
}
```

Code 4:

Source Code:

```
#include <stdio.h>
int main()
{
    float length, width, area;
    printf("Enter length of rectangle: ");
    scanf("%f", &length);
    printf("Enter width of rectangle: ");
    scanf("%f", &width);

    area = length * width;

    printf("Area of rectangle = %f sq. units", area);

    float length2, area2;
    printf("Enter length of square: ");
    scanf("%f", &length2);


    area2 = length2 * length2;

    printf("Area of square = %f sq. units", area2);

    int num1, num2, sum;
```

```
    printf("Enter two integers: ");
    scanf("%d %d", &num1, &num2);

    sum = num1 + num2;

    printf("Summation of %d and %d is : %d", num1, num2, sum);


    return 0;
}
```

Code 5:

Source Code:

```
#include <stdio.h>
int main()
{
    int num1, num2, num3, sum;

    printf("Enter number of people in the village last year: ");
    scanf("%d", &num1);
    printf("Enter the number of people moving in: ");
    scanf("%d", &num2);
    printf("Enter the number of people moving out: ");
    scanf("%d", &num3);
    sum = (num1 + num2) - num3;

    printf("Number of people this year is : %d", num1, num2, num3, sum);
    return 0;
}
```

Code 6:

Source Code:

```
#include <stdio.h>
int main()
{
    float paid, beef, mutton, change;

    printf("Amount being paid: ");
    scanf("%f", &paid);

    printf("Kilos of beef getting bought: ");
    scanf("%f", &beef);
```

```
    printf("Kilos of mutton getting bought: ");
    scanf("%f", &mutton);
    change = paid - (beef * 700 + mutton * 800);

    printf("Amount of change is : %f", change);
    return 0;
}
```

Code 7:

Source Code:

```
#include <stdio.h>
int main()
{
    float salary, rent, expenses, savings;

    printf("Mr. Xs monthly salary is: ");
    scanf("%f", &salary);
    printf("house rent: ");
    scanf("%f", &rent);
    printf("household expenses: ");
    scanf("%f", &expenses);
    savings = salary - (rent + expenses);

    printf("Remaining money in the bank = %f", savings);
    return 0;
}
```

Code 8:

Source Code:

```
#include <stdio.h>
int main()
{
    float X, M, R;

    printf("X is: ");
    scanf("%f", &X);

    M = (X + 500)/2;
    R = X - M;

    printf("M and R are = %f, %f", M, R);
    return 0;
```

```
}
```

Code 9:

Source Code:

```
#include <stdio.h>
int main()
{
    float X, M, R;

    printf("X is: ");
    scanf("%f", &X);

    M = (X + 480)/2;
    R = X - M;

    printf("M and R are = %f, %f", M, R);
    return 0;
}
```

Code 10:

Source Code:

```
#include <stdio.h>

 int main()

{

   int x,y;

   printf("Enter the sum of age of Father & his daughter:  ");

   scanf("%d",&x);

   printf("How many times the age of the Father is the age of his daughter:  ");

   scanf("%d",&y);


   x=x/y;

   y=x*y;


   printf("Father's age is: %d\n", y);

   printf("Daughter's age is: %d\n", x);
```

```
   return 0;
}
```

Code 11:

Source Code:

```
#include <stdio.h>
 int main()
{
   float cg, c, g;
   printf("Enter the price of 2 cows and 3 goats together");
   scanf("%f",&cg);
   printf("Enter the price of 1 goat:  ");
   scanf("%f",&g);

   g=3*g;
   c=cg-g;
   c=c/2;

   printf("The price of one cow is %f: \n", c);

   return 0;
}
```

LAB 03

ARITHMETIC OPERATORS

Code 1:

Source Code:

```
#include <stdio.h>
int main()
{
        int sec, h, m, s;
        printf("Input seconds: ");
        scanf("%d", &sec);

        h = (sec/3600);

        m = (sec -(3600*h))/60;

        s = (sec -(3600*h)-(m*60));

        printf("H:M:S - %d:%d:%d\n",h,m,s);

        return 0;
}
```

Code 2:

Source Code:

```
#include <stdio.h>
int main()
{
   int days, years, weeks;
```

```
    printf("Input days: ");
            scanf("%d", &days);

    // Converts days to years, weeks and days
    years = days/365;
    weeks = (days % 365)/7;
    days = days- ((years*365) + (weeks*7));

    printf("Years: %d\n", years);
    printf("Weeks: %d\n", weeks);
    printf("Days: %d \n", days);

    return 0;
}
```

Code 3:

Source Code:

```
#include <stdio.h>
int main()
{
    int days, years, months;

    printf("Input days: ");
            scanf("%d", &days);

    // Converts days to years, months and days
    years = days/365;
    months = (days % 365)/30;
```

```
    days = days- ((years*365) + (months*30));

    printf("%d Years\n", years);
    printf("%d Months\n", months);
    printf("%d Days\n", days);

    return 0;
}
```

Code 4:

Source Code:

```
#include<stdio.h>
int main()
{
    //Program to print the average consumption of bike

    int dist, fuel;
    float avg;
    printf("Input the total distance in km: ");
    scanf("%d", &dist);
    printf("Input total fuel spent in litres: ");
    scanf("%d", &fuel);
    avg = dist / fuel;
    printf("Average consumption (km/lt) = %.2f", avg);
    return 0;
}
```

Code 5:

Source Code:

```
#include <stdio.h>
int main()
{
      int rice, consumption, days;

       printf("Input grams of rice: ");
          scanf("%d", &rice);
          printf("Input grams of rice consumed per day: ");
          scanf("%d", &consumption);

          days = rice/consumption;

          printf("Rice will be finished in: %d days", days);



   return 0;
}
```

Code 6:

Source Code:

```
#include <stdio.h>
int main()
{
         int N1, N2 , Total;

          printf("Input total number of papers: ");
             scanf("%d", &N1);
             printf("Input number of papers used to make one book: ");
             scanf("%d", &N2);
```

```
        Total = N1/N2;

        printf("Amount of books that can be made are: %d", Total);



    return 0;
}
```

Code 7:

Source Code:

```
#include <stdio.h>
int main()
{
    int employees;

   employees = 95200/800;
    printf("Number of employees in the company if the profit is 95200 Taka and each employee was given 800 Taka is: %d", employees);

      return 0;
}
```

Code 8:

Source Code:

```
 #include <stdio.h>
int main()
{
      int profit, given , employees;
```

```
        printf("Input amount of profit: ");
            scanf("%d", &profit);
            printf("Input amount given to each employee: ");
            scanf("%d", &given);

            employees = profit/given;
        printf("Number of employees in the company: %d", employees);

    return 0;
}
```

Code 9:

Source Code:

```
#include <stdio.h>
int main()
{
   int boxes;
   boxes = 43548/250;
    printf("Number of boxes necessary to pack 43548 products if every 250 products are packed in one cardboard box is: %d", boxes);

  return 0;
}
```

Code 10:

Source Code:

```
#include <stdio.h>
int main()
{
   int P1, P2, boxes;
```

```
        printf("Input amount of products: ");
          scanf("%d", &P1);
          printf("Input amount of products in each box: ");
          scanf("%d", &P2);

    boxes = P1/P2;

          printf("Number of boxes necessary to pack everything: %d", boxes);

    return 0;
}
```

Code 11:

Source Code:

```
#include <stdio.h>
int main()
{
   int E1, E2;

          E1 = 72/8;
          E2 = 15*E1;
   printf("Amount needed to pay for 15 eggs if the price of 8 eggs is 72 taka: %d taka", E2);

    return 0;
}
```

Code 12:

Source Code:

```
#include <stdio.h>
int main()
{
   int E1, E2 , E3, E4, pay;

        printf("Input amount of eggs: ");
           scanf("%d", &E1);
           printf("Input price of the given amount of eggs: ");
           scanf("%d", &E2);

           E3 = E2/E1;

           printf("Input amount of eggs being bought: ");
           scanf("%d", &E4);

           pay = E3*E4;

         printf("Amount needed to pay: %d", pay);

      return 0;
}
```

Code 13:

Source Code:

```
#include <stdio.h>
int main()
{
   int E1, E2;
         E1 = 80/4;
```

```
        E2 = 10*E1;

    printf("Amount needed to pay for 10 banans if the price of 4 bananas is 80 taka: %d taka", E2);

     return 0;
}
```

Code 14:

Source Code:

```
#include <stdio.h>
int main()
{
   int E1, E2 , E3, E4, pay;

        printf("Input amount of bananas: ");
          scanf("%d", &E1);
          printf("Input price of the given amount of bananas: ");
          scanf("%d", &E2);

          E3 = E2/E1;

          printf("Input amount of bananas being bought: ");
          scanf("%d", &E4);

        pay = E3*E4;
        printf("Amount needed to pay: %d", pay);

     return 0;
}
```

Code 15:

Source Code:

```
#include <stdio.h>
int main()
{
   int E1, E2;

            E1 = 64/8;
            E2 = 24*E1;

            printf("Amount Ayesha needs to pay for 24 pencils if 8 pencils cost 64 taka is: %d taka",
E2);



   return 0;
}
```

Code 16:

Source Code:

```
#include <stdio.h>
int main()
{
   int E1, E2 , E3, E4, pay;

         printf("Input amount of pencils: ");
            scanf("%d", &E1);
            printf("Input price of the given amount of pencils: ");
            scanf("%d", &E2);
```

```
        E3 = E2/E1;

        printf("Input amount of pencils being bought: ");
        scanf("%d", &E4);

        pay = E3*E4;
      printf("Amount needed to pay: %d", pay);

    return 0;
}
```

Code 17:

Source Code:

```
#include <stdio.h>
int main()
{
   int n, sum=0, firstdigit, lastdigit;
   printf("Enter number to find sum of first and last digit = ");
   scanf("%d", &n);

 // Find last digit of a number
   lastDigit = n % 10;

 //Find the first digit by dividing n by 10 until n greater then 10
   while(n >= 10)
   {
      n = n / 10;
   }
   firstDigit = n;
```

```
  //Calculate sum of first and last digit

    sum = firstdigit + lastdigit;
    printf("Sum of first and last digit = %d", sum);

    return 0;
}
```

LAB 04

CONDITIONAL AND OTHER OPERATORS

Code 1:

Source Code:

```
#include <stdio.h>
int main()
{
   int num1, num2, max;

   printf("Enter two numbers: ");
   scanf("%d%d", &num1, &num2);

   max = (num1 > num2) ? num1 : num2;

   printf("Maximum between %d and %d is %d", num1, num2, max);

   return 0;
}
```

Code 2:

Source Code:

```
void main()
{
        int number;

      printf("Enter a number:\t");
        scanf("%d", &number);
```

```
        (number > 0) ? printf("%d is a positive number\n", number):
        (number < 0) ? printf("%d is a negative number\n", number):
        printf("Number is zero\n");
}
```

Code 3:

Source Code:

```
void main()
{
        int number;

        printf("Enter a number:\t");
        scanf("%d", &number);

        (number%2==0) ? printf("%d is an even number\n", number): printf("%d is an odd number\n", number);

}
```

Code 4:

Source Code:

```
#include <stdio.h>
int main()
{
   int num1, num2, min;

   printf("Enter two numbers: ");
   scanf("%d%d", &num1, &num2);

   min = (num1 < num2) ? num1 : num2;
```

```
    printf("Minimum between %d and %d is %d", num1, num2, min);

    return 0;
}
```

Code 5:

Source Code:

```
#include <stdio.h>
int main()
{
   float a,b,result;
   printf("Enter two number: ");
   scanf("%f %f", &a, &b);
   result = (a>b)? a/b : a*b;
   printf("Result : %2f", result);

 return 0;
}
```

Code 6:

Source Code:

```
#include <stdio.h>
int main()
{
   int num;
   printf("Enter the number of items: ");
   scanf("%d", &num);
   (num==1) ? printf("You have 1 item") : printf("You have %d items", num);
```

```
}
```

Code 7:

Source Code:

```
#include <stdio.h>
int main()
{
    int num1, num2, num3, max;

    printf("Enter three numbers: ");
    scanf("%d%d%d", &num1, &num2, &num3);



    max = (num1 > num2 && num1 > num3) ? num1 :
          (num2 > num3) ? num2 : num3;

      printf("\nMaximum between %d, %d and %d is = %d", num1, num2, num3, max);

    return 0;
}
```

Code 8:

Source Code:

```
#include<stdio.h>
int main()
{
 int perimeter, area;
 perimeter = 2 * (5+7);
```

```
 area = 5*7;

 printf("In the given rectangle, perimeter is %d meter and area is %d square meter",
perimeter,area);
 return 0;
 }
```

Code 9:

Source Code:

```
#include<stdio.h>
int main()
{
 int num, perimeter, area;
 printf("Enter the radius of the circle: ");
 scanf("%d", &num);

 perimeter = 2 * 3.1416 * num;
 area = 3.1416 * (num*num);

 printf("In the given circle, perimeter is %d meter and area is %d square meter", perimeter,area);
 return 0;
}
```

Code 10:

Source Code:

```
#include<stdio.h>
 int main()
{
  int n;
  printf("Enter a 4 digit number\n");
```

```
  scanf("%d", &n);

 float i;
  i = (((n + 8)/3)%5)*5;
  printf("%f\n", i);
}
```

Code 11:

Source Code:

```
#include<stdio.h>
  int main()
{
  int n;

 float i, i2, i3, i4;
  printf("Enter a 4 digit number\n");
  scanf("%d", &n);

 i = n+=8;
  i2 = n/=3;
  i3 = n%=5;
  i4 = n*=5;

  printf("%f\n", i4);
}
```

Code 12:

Source Code:

```
#include <stdio.h>
void main()
{
    int int1, int2;
    printf("Input the values for Number1 and Number2 : ");
    scanf("%d %d", &int1, &int2);

 if (int1 == int2)
        printf("Number1 and Number2 are equal\n");
    else
        printf("Number1 and Number2 are not equal\n");
}
```

Code 13:

Source Code:

```
#include <stdio.h>
#include <stdlib.h>
int main()
{
    int a,b;
    printf("Enter a and b:");
    scanf("%d%d",&a,&b);

 if (a<50 && a<b)
        printf("%d<50 and %d<%d are true",a,a,b);
 else
        printf("%d<50 and %d<%d are false",a,a,b);

    return 0;
```

```
}
```

Code 14:

Source Code:

```
#include <stdio.h>
#include <stdlib.h>
int main()
{
    int a,b;
    printf("Enter a and b:");
    scanf("%d%d",&a,&b);

 if (a<50 || a<b)
        printf("At least one of %d<50 and %d<%d is true",a,a,b);

 else
        printf("%d<50 and %d<%d are false",a,a,b);

    return 0;
}
```

Code 15:

Source Code:

```
#include <stdio.h>
int main()
{
    float celsius, fahrenheit;
```

```
    printf("Enter temperature in Fahrenheit: ");
    scanf("%f", &fahrenheit);

    celsius = (fahrenheit - 32) * 5 / 9;

    printf("%.2f Fahrenheit = %.2f Celsius", fahrenheit, celsius);

    return 0;
}
```

Code 16:

Source Code:

```
#include <stdio.h>
int main()
{
      int n,l,f,m,sum,t1;

      printf("Enter 3-Digit Number: ");
      scanf("%d",&n);

      f=n/100;

      t1=n%100;

      l=t1%10;

      m=t1/10;

      printf("\nFirst Digit  = %d \nMiddle Digit = %d \nLast Digit   = %d\n",f,m,l);
```

```
    sum=l+m+f;
      printf("\nSum of All 3-Digits : %d",sum);

return 0;
}
```

LAB 05

IF, ELSE IF LADDER

Code 1:

Source Code:

```
#include <stdio.h>
int main()
 {
   int sub1, sub2, sub3;

   printf("\nEnter the marks in Mathematics: ");
   scanf("%d", &sub1);
   printf("\nEnter the marks in Physics: ");
   scanf("%d", &sub2);
   printf("Enter the marks in Chemistry: ");
   scanf("%d", &sub3);

   if((sub1>=60 && sub2>=50 && sub3>=40 && sub1+sub2+sub3>=200) || sub1+sub2>=150)
   printf("The candidate is eligible");

   else
   printf("The candidate is not eligible");

   return 0;
}
```

Code 2:

Source Code:

```
#include<stdio.h>
```

```
void main()
{
    float units,bill;
    printf("Enter the number of units consumed: ");
    scanf("%f",&units);

    if(units>=0 && units<=200)
    {
        bill = units * 0.50;
        printf("amount to be paid is: %f", bill);
    }
    else if(units>=201 && units<=400)
    {
        bill = 100 + ((units-200) * 0.65);
        printf("amount to be paid is: %f", bill);
    }
    else if(units>=401 && units<=600)
    {
        bill = 230 + ((units-400) * 0.80);
        printf("amount to be paid is: %f", bill);
    }
    else if(units>=601)
    {
        bill = 390 + ((units-600) * 1.00);
        printf("amount to be paid is: %f", bill);
        return 0;
    }
}
```

Code 3:

Source Code:

```
#include<stdio.h>
 int main()
{
  char ch;

  int amount,price;

  float net,discount,amountToBePaid;

    printf("Enter 1.If it is a pendrive purchase\nEnter 2.If it is a ram purchase\n");
    scanf("%d",&ch);

    printf("\n Enter purchased amount: ");
    scanf("%d",&amount);

    printf("Enter the price per item: ");
    scanf("%d", &price);

    net = amount * price;
    switch(ch)

 {
  case 1:
       if(amount<=100)
       {
       amountToBePaid = net;
       printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
```

```
    }
    else if(amount>=101 && amount<=200)
    {
        discount = (net*5)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }
    else if(amount>=201 && amount<=300)
    {
        discount = (net*7.5)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }
    else if(amount>300)
    {
        discount = (net*10)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }
   break;



case 2:
    if(amount<=100)
    {
        discount = (net*5)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }
```

```
        else if(amount>=101 && amount<=200)
        {
            discount = (net*7.5)/100;
            amountToBePaid = net-discount;
            printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
        }
        else if(amount>=201 && amount<=300)
        {
            discount = (net*10)/100;
            amountToBePaid = net-discount;
            printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
        }
        else if(amount>300)
        {
            discount = (net*15)/100;
            amountToBePaid = net-discount;
            printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
        }
        break;
    }
    getch();
}
```

Code 4:

Source Code:

```
#include<stdio.h>
int main()
{
    int length, breadth;
```

```
    printf("Enter the values of length and breadth:\n");
    scanf("%d%d", &length,&breadth);

    if (length==breadth)
    printf("It is a square");
    else
    printf("It is a rectangle");
    return 0;
}
```

Code 5:

Source Code:

```
#include<stdio.h>
int main()
{
    int N1, N2;

    printf("Enter the two numbers: ");
    scanf("%d%d", &N1,&N2);

    if (N1>N2)
    printf("%d is the larger number among the two", N1);
    else
    printf("%d is the larger number among the two", N2);
}
```

Code 6:

Source Code:

```
#include <stdio.h>
int main()
{
    int amount;
    int note500, note100, note50, note20, note10, note5, note2, note1;



    note500 = note100 = note50 = note20 = note10 = note5 = note2 = note1 = 0;

    printf("Enter amount: ");
    scanf("%d", &amount);

    if(amount >= 500)
    {
        note500 = amount/500;
        amount -= note500 * 500;
    }
    if(amount >= 100)
    {
        note100 = amount/100;
        amount -= note100 * 100;
    }
    if(amount >= 50)
    {
        note50 = amount/50;
        amount -= note50 * 50;
    }
    if(amount >= 20)
    {
```

```
    note20 = amount/20;
    amount -= note20 * 20;
}
if(amount >= 10)
{
    note10 = amount/10;
    amount -= note10 * 10;
}
if(amount >= 5)
{
    note5 = amount/5;
    amount -= note5 * 5;
}
if(amount >= 2)
{
    note2 = amount /2;
    amount -= note2 * 2;
}
if(amount >= 1)
{
    note1 = amount;
}

printf("Total number of notes = \n");
printf("500 = %d\n", note500);
printf("100 = %d\n", note100);
printf("50 = %d\n", note50);
printf("20 = %d\n", note20);
printf("10 = %d\n", note10);
```

```
    printf("5 = %d\n", note5);
    printf("2 = %d\n", note2);
    printf("1 = %d\n", note1);

    return 0;
}
```

LAB 06

SWITCH STATEMENT

Code 1:

Source Code:

```
#include<stdio.h>
 void main()
{
  int amount,price,ch;

  float net,discount,amountToBePaid;

     printf("enter 1.if it is a pendrive purchase\n 2.if it is a ram purchase\n");
     scanf("%d",&ch);

     printf("\n Enter purchased amount: ");
     scanf("%d",&amount);

     printf("Enter the price per item: ");
     scanf("%d", &price);

     net = amount * price;

     switch(ch)

 {
  case 1:
        if(amount<=100)
        {
```

```
 amountToBePaid = net;
 printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
 }

else if(amount>=101 && amount<=200)
{
    discount = (net*5)/100;
    amountToBePaid = net-discount;
    printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
}

else if(amount>=201 && amount<=300)
{
    discount = (net*7.5)/100;
    amountToBePaid = net-discount;
    printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
}

else if(amount>300)
{
    discount = (net*10)/100;
    amountToBePaid = net-discount;
    printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
}

break;

case 2:
    if(amount<=100)
```

```
    {
        discount = (net*5)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }

    else if(amount>=101 && amount<=200)
    {
        discount = (net*7.5)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }

    else if(amount>=201 && amount<=300)
    {
        discount = (net*10)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }

    else if(amount>300)
    {
        discount = (net*15)/100;
        amountToBePaid = net-discount;
        printf("After applying the discount, you have to pay: %0.2f", amountToBePaid);
    }

    break;
}
```

```
    getch();

}
```

Code 2:

Source Code:

```
#include <stdio.h>
int main()
{
    int number;

    printf("Enter a positive integer number: ");
    scanf("%d",&number);

    switch(number%2) //this will return either 0 or 1
    {
        case 0:
            printf("%d is an EVEN number.\n",number);
            break;
        case 1:
            printf("%d is an ODD number.\n",number);
            break;
    }
    return 0;
}
```

Code 3:

Source Code:

```
#include <stdio.h>
int main()
```

```
{
    char ch;
    printf("Enter any alphabet: ");
    scanf("%c", &ch);

    switch(ch)
    {
        case 'a':
            printf("Vowel");
            break;
        case 'e':
            printf("Vowel");
            break;
        case 'i':
            printf("Vowel");
            break;
        case 'o':
            printf("Vowel");
            break;
        case 'u':
            printf("Vowel");
            break;
        case 'A':
            printf("Vowel");
            break;
        case 'E':
            printf("Vowel");
            break;
        case 'I':
```

```
            printf("Vowel");
            break;
        case 'O':
            printf("Vowel");
            break;
        case 'U':
            printf("Vowel");
            break;
        default:
            printf("Consonant");
    }
    return 0;
}
```

Code 4:

Source Code:

```
#include <stdio.h>
void main()
{
    int fig_code;

    float base, length, breadth, height, area, radius;

    printf("-------------------------\n");
    printf(" 1 -->Area of Circle\n");
    printf(" 2 -->Area of Rectangle\n");
    printf(" 3 -->Area of Triangle\n");
    printf("-------------------------\n");
    printf("Enter the Figure code\n");
    scanf("%d", &fig_code);
```

```
    switch(fig_code)
    {
    case 1:
        printf("Enter the radius\n");
        scanf("%f", &radius);
        area = 3.142 * radius * radius;
        printf("Area of a circle = %f\n", area);
        break;
    case 2:
        printf("Enter the breadth and length\n");
        scanf("%f %f", &breadth, &length);
        area = breadth * length;
        printf("Area of a Reactangle = %f\n", area);
        break;
    case 3:
        printf("Enter the base and height\n");
        scanf("%f %f", &base, &height);
        area = 0.5 * base * height;
        printf("Area of a Triangle = %f\n", area);
        break;

    default:
        printf("Error in figure code\n");
        break;
    }
}
```

Code 5:

Source Code:

```
#include<stdio.h>
int main()
{
        int years,months,days,hours,minutes,seconds;

        printf("\n Enter the number of years: ");
        scanf("%d",&years);
       months = 12 * years;

      days = 365 * years;
      hours = 24 * 365 * years;
      minutes = 60 * 24 * 365 * years;
      seconds = 60 * 60 * 24 * 365 * years;
       printf("\n %d Months",months);
       printf("\n %d Days",days);
       printf("\n %d Hours",hours);
       printf("\n %d minutes",minutes);
       printf("\n %d seconds",seconds);
     return 0;
}
```

LAB 07

NESTED LOOPS

Code 1:

Source Code:

```
#include<stdio.h>
 int main()
{
  int i;

  for(i=1;i<=10;i++)
  printf("%d\t", i);

}
```

Code 2:

Source Code:

```
#include<stdio.h>
int main()
{
  int i,even=0;

  printf("\nEven numbers between 1 to 10 are:");

  for(i=1;i<=10;i++)
  {
    if(i%2==0)
    {
      printf("\n%d",i);
```

```
      even++;
    }
  }
  return 0;
}
```

Code 3:

Source Code:

```
#include <stdio.h>
int main()
{
    int i;

     printf("All odd numbers from 1 to 10 are: \n", i);

    for(i=1; i<=10; i++)
    {
        if(i%2!=0)
        {
            printf("%d\n", i);
        }
    }
    return 0;
 }
```

Code 4:

Source Code:

```
#include<stdio.h>
int main()
```

```
{
  int i,even=0;

  for(i=1;i<=10;i++)
  {
    if(i%2==0)
    {
       even++;
    }
  }

  printf("\nTotal even numbers between 1 to 10 :%d",even);

  return 0;
}
```

Code 5:

Source Code:

```
#include<stdio.h>
int main()
{
  int i,odd=0;

  for(i=1;i<=10;i++)
  {
    if(i%2!=0)
    {
       odd++;
    }
```

```
  }

  printf("\nTotal odd numbers between 1 to 10 :%d",odd);

  return 0;
}
```

Code 6:

Source Code:

```
#include <stdio.h>
int main()
{
    int  j, sum = 0;

    for (j = 1; j <= 5; j++)
    {
        sum = sum + j;
    }

    printf("\nThe Summation of 1 to 5  is : %d\n", sum);
}
```

Code 7:

Source Code:

```
#include <stdio.h>
int main()
{
    int i, sum=0;
```

```
    for(i=2; i<=10; i+=2)
    {
        sum += i;
    }

    printf("Sum of all even number between 1 to 10 are = %d",sum);

    return 0;
}
```

Code 8:

Source Code:

```
#include <stdio.h>
int main()
{
    int i, n, sum=0;

    for(i=1; i<=10; i+=2)
    {
        sum += i;
    }

    printf("Sum of odd numbers = %d", sum);
    return 0;
}
```

Code 9:

Source Code:

```
#include<stdio.h>
```

```
int main()
{
    int val;

    printf("1. All numbers between 1 to 10 using loop\n2. Even numbers between 1 to 10\n3. Odd numbers between 1 to 10.\n4. Count of even between 1 to 10\n5. Count of odd between 1 to 10.\n6. Summation of 1 to 5\n7. Summation of even numbers between 1 to 10\n8. Summation of odd numbers between 1 to 10\n");

    printf("\n Press any number from 1 to 8");
    scanf("%d",&val);

    switch (val)
{
 case 1:
 {
  int i;
  for(i=1;i<=10;i++)

  printf("%d\t", i);
}

 break;

 case 2:
 {
  int i,even=0;

  printf("\nEven numbers between 1 to 10 are:");
```

```
  for(i=1;i<=10;i++)
  {
    if(i%2==0)
    {
      printf("\n%d",i);
      even++;
    }
  }
  return 0;
}

 break;

 case 3:
 {
    int i;

     printf("All odd numbers from 1 to 10 are: \n", i);

    for(i=1; i<=10; i++)
    {
        if(i%2!=0)
        {
            printf("%d\n", i);
        }
    }
    return 0;
}
```

```
 break;

 case 4:
 {
  int i,even=0;

  for(i=1;i<=10;i++)
  {
    if(i%2==0)
    {
       even++;
    }
  }

  printf("\nTotal even numbers between 1 to 10 :%d",even);

  return 0;
}

 break;

 case 5:
 {
  int i,odd=0;

  for(i=1;i<=10;i++)
  {
    if(i%2!=0)
    {
```

```
        odd++;
    }
  }

  printf("\nTotal odd numbers between 1 to 10 :%d",odd);

  return 0;
}

 break;

 case 6:
 {
    int  j, sum = 0;

    for (j = 1; j <= 5; j++)
    {
        sum = sum + j;
              }
    printf("\nThe Summation of 1 to 5  is : %d\n", sum);
}

 break;

 case 7:
 {
    int i, sum=0;

    for(i=2; i<=10; i+=2)
```

```
    {
        sum += i;
    }

    printf("Sum of all even number between 1 to 10 are = %d",sum);

    return 0;
}

 break;

 case 8:
 {
    int i, n, sum=0;

    for(i=1; i<=10; i+=2)
    {
        sum += i;
    }
    printf("Sum of odd numbers = %d", sum);

    return 0;
}

 break;
 default:
 printf("input error!!");
}
}
```

LAB 08

ARRAY

Code 1:

Source Code:

```
#include <stdio.h>
int main() {

  int values[5];

  printf("Enter 5 integers: ");

  for(int i = 0; i < 5; ++i)
 {
     scanf("%d", &values[i]);
  }
  printf("Displaying integers: ");

  for(int i = 0; i < 5; ++i){

     printf("%d\n",values[i]);
  }
  return 0;
}
```

Code 2:

Source Code:

```
#include <stdio.h>
```

```
int main()
{
  int values[5];

  printf("Enter 5 integers: ");

  for(int i = 0; i < 5; ++i)
 {
     scanf("%d", &values[i]);
  }

  printf("Displaying the squares of the given values: ");

  for(int i = 0; i < 5; ++i)
{
    values[i] = values[i] * values[i];

     printf("%d\n",values[i]);
  }
  return 0;
}
```

Code 3:

Source Code:

```
#include<stdio.h>
int main()
{
    int arr[10], i;
```

```
    printf("Enter any 10 array elements: ");

    for(i=0; i<10; i++)
    scanf("%d", &arr[i]);
    printf("\nAll Even Array elements are:\n");

    for(i=0; i<10; i++)
    {
        if(arr[i]%2==0)
        {
            printf("%d ", arr[i]);
        }
    }
    return 0;
}
```

Code 4:

Source Code:

```
#include<stdio.h>
int main()
{
    int arr[10], i;

    printf("Enter any 10 array elements: ");

    for(i=0; i<10; i++)
    scanf("%d", &arr[i]);
    printf("\nAll Odd Array elements are:\n");
```

```
    for(i=0; i<10; i++)
    {
        if(arr[i]%2==1)
        {
            printf("%d ", arr[i]);
        }
    }
    return 0;
}
```

Code 5:

Source Code:

```
#include<stdio.h>
int main()
{
    int a[10],i,even=0;

    printf("Enter any 10 Array elements: ");

    for(i=0; i<10; i++)
    {
        scanf("%d", &a[i]);
    }
        for(i=0; i<10; i++)
    {
        if(a[i]%2==0)
        even++;
    }
    printf("Total number of even integers among the given values are: %d", even);
```

```
    return 0;
}
```

Code 6:

Source Code:

```
#include<stdio.h>
int main()
{
    int a[10],i,odd=0;

   printf("Enter any 10 Array elements: ");

    for(i=0; i<10; i++)
      {
        scanf("%d", &a[i]);
     }
        for(i=0; i<10; i++)
    {
        if(a[i]%2==1)
        odd++;
    }
    printf("Total number of odd integers among the given values are: %d", odd);

    return 0;
}
```

Code 7:

Source Code:

```
#include<stdio.h>
 main()
 {
   int a[5],b[5],i,total[5];

   printf("\nEnter elements of first array: ");

   for(i=0;i<5;i++)
   {
   scanf("%d",&a[i]);
   }
   printf("\nEnter elements of second array: ");

   for(i=0;i<5;i++)
   {
   scanf("%d",&b[i]);
   }
   for(i=0;i<5;i++)
   {
   total[i]=a[i]+b[i];
   }
   printf("\nSummation of the elements among the arrays: ");

   for(i=0;i<5;i++)
   {
   printf("\n  \t\t\t %d",total[i]);
   }
 }
```

Code 8:

Source Code:

```
#include<stdio.h>

int main()

{

    int val;


    printf("1. Display array elements\n2. Display the squares of the given values\n3. All even array elements among the given integers.\n4. All odd elements among the given integers.\n5. Total number of even integers among the given values.\n6. Total number of odd integers among the given values\n7. Summation of the elements among the arrays\n");


    printf("\n Press 1 to 7");

    scanf("%d",&val);


    switch (val)

{

    case 1:

     {


  int values[5];


  printf("Enter 5 integers: ");


  for(int i = 0; i < 5; ++i)

 {

     scanf("%d", &values[i]);

  }
```

```
  printf("Displaying integers: ");
  for(int i = 0; i < 5; ++i){

     printf("%d\n",values[i]);
  }
  return 0;
}

 break;

 case 2:
 {

  int values[5];

  printf("Enter 5 integers: ");

  for(int i = 0; i < 5; ++i)
{
     scanf("%d", &values[i]);
  }

  printf("Displaying the squares of the given values: ");

  for(int i = 0; i < 5; ++i)
{
    values[i] = values[i] * values[i];
     printf("%d\n",values[i]);
  }
```

```
  return 0;
}

    break;

    case 3:
    {
    int arr[10], i;

    printf("Enter any 10 array elements: ");

    for(i=0; i<10; i++)
        scanf("%d", &arr[i]);
    printf("\nAll Even Array elements are:\n");

    for(i=0; i<10; i++)
    {
        if(arr[i]%2==0)
        {
            printf("%d ", arr[i]);
        }
    }
    return 0;
}
    break;

    case 4:
    {
    int arr[10], i;
```

```
    printf("Enter any 10 array elements: ");

    for(i=0; i<10; i++)
     scanf("%d", &arr[i]);
    printf("\nAll Odd Array elements are:\n");

    for(i=0; i<10; i++)
    {
        if(arr[i]%2==1)
        {
            printf("%d ", arr[i]);
        }
    }
    return 0;
}
    break;

    case 5:
    {
    int a[10],i,even=0;
    printf("Enter any 10 Array elements: ");

    for(i=0; i<10; i++)
    {
          scanf("%d", &a[i]);
    }
          for(i=0; i<10; i++)
    {
```

```
        if(a[i]%2==0)
        even++;
    }
      printf("Total number of even integers among the given values are: %d", even);

    return 0;
}
    break;

    case 6:
    {
    int a[10],i,odd=0;

    printf("Enter any 10 Array elements: ");

    for(i=0; i<10; i++)
    {
     scanf("%d", &a[i]);
   }
     for(i=0; i<10; i++)
   {
        if(a[i]%2==1)
        odd++;
    }
    printf("Total number of odd integers among the given values are: %d", odd);

    return 0;
}
    break;
```

```
 case 7:
 {
int a[5],b[5],i,total[5];

printf("\nEnter elements of first array: ");

for(i=0;i<5;i++)
{
scanf("%d",&a[i]);
}
printf("\nEnter elements of second array: ");

for(i=0;i<5;i++)
{
scanf("%d",&b[i]);
}
for(i=0;i<5;i++)
{
total[i]=a[i]+b[i];
}
printf("\nSummation of the elements among the arrays: ");

for(i=0;i<5;i++)
{
printf("\n  \t\t\t %d",total[i]);

}
 }
```

```
    break;

}
}
```

----------O----------