

TK Series Electric Ovens

TKA- TKB- TKC & TKD Models



www.ItalforniUSA.com

424.477.2221

Specification

Italforni TK Series Electric Deck Ovens are designed for high volume pizza, baking, roasting and all-purpose operations.

Each oven has one or two decks with separate tilt-up door(s). Ovens may be stacked in any combination up to 4 decks high.

Oven front and doors are stainless steel and are fully insulated for cooler outer temperatures and consistent interior temperatures. Oven interiors are manufactured of high-heat resistant 18-gauge aluminized steel.

Each deck features independent, operator controlled top & bottom, infinite heat for perfectly balanced results and a 200°-840° F (100°- 450° C) thermostat. 5.75" (150mm) interior deck height with 3/4" (19mm) thick hearth stone decks (steel decks optional).
Interior oven lights.

Voltages are available in 208-240 1Ø or 3Ø/50/60Hz. 1 Year limited part and labor warranty standard.

Standard Features

TKA single @ Approx 4.5 KW in 208-240V,
TKB single @ Approx 6.5 KW in 208-240V,
TKC single @ Approx 9.5 KW in 208-240V,
TKD Double @ Approx 13 KW in 208-240V,

- 200°-840° F (100°-450°C) thermostat
- Infinite Top & Bottom heat controls per deck
- Interior oven lights
- 5.75" (150mm) Interior deck heights with hearth stone decks
- Stainless steel front and door
- Aluminized steel interiors
- Balanced door/s with windows
- Fully insulated
- 1 Year limited part and labor warranty

Certification



TK Series Electric Ovens

TKA– TKB– TKC & TKD Models



www.ItalforniUSA.com

424.477.2221

All dimensions nominal– Ovens may be stacked in any combination up to 4 decks

Shipping Information										
Shipping Weight			Carton Dimensions						Crate Size	
Model	lbs	Kg	Inches	mm	Inches	mm	Inches	mm	Cubic Ft	Cubic Meter
TKA—1	268	100	38.6	980	38.6	980	23.7	600	20.4v	0.579
TKA—2	375	140	38.6	980	38.6	980	33.2	840	28.6	0.811
TKB—1	322	120	38.6	980	51.2	1300	23.7	600	27.1	0.768
TKB—2	455	170	38.6	980	51.2	1300	33.2	840	38	1.075
TKC—1	400	150	49.2	1250	51.2	1300	22.5	570	32.8	0.929
TKC—2	805	300	49.2	1250	51.2	1300	39.5	1000	57.6	1.631
TKD—2	535	200	40.2	1020	40.2	1260	39.5	1000	37	1.046

Power Supply			
Model	KW*	V	Ph
TKA—1	4.5	220	1/ 3
TKA—2	9	220	1/ 3
TKB—1	6.5	220	1/ 3
TKB—2	13	220	1/ 3
TKC—1	9.6	220	1/ 3
TKC—2	19	220	1/ 3
TKD—2	13	220	1/ 3

*Maximum Wattage Shown

Shipping Class #85. Each oven sold separately

Specifications												
Deck Size			Deck Height			Overall Dimension						
Model	inch	mm	inch	mm	# Decks	W Inch	W MM	D Inch	D MM	H Inch	H MM	
TKA—1	26 x 26	660 x 660	5.75	150	1	36	910	34	840	17	430	
TKA—2	26 x 26	660 x 660	5.75	150	2	36	910	34	840	28	700	
TKB—1	26 x 39	660 x 990	5.75	150	1	36	910	46	1170	17	430	
TKB—2	26 x 39	660 x 990	5.75	150	2	36	910	46	1170	28	700	
TKC—1	39 x 39	990 x 990	5.75	150	1	49	1250	46	1170	17	430	
TKC—2	39 x 39	990 x 990	5.75	150	2	49	1250	46	1170	34	860	
TKD—2	39 x 26	990 x 660	5.75	150	2	49	1250	37	940	28	700	

Minimum Clearances– 3” sides– 5” Rear

Specification and design are subject to change without notification.