

HYBRID COAXIAL CABLES



SPECIFICATIONS

Conductor:	Rigid wire
Conductor color:	Red, Black
Outer sheath color:	Grey
Marking:	ITALCOND Brand
Impedance:	75 Ohm
Rules:	EN 50117-2-4



EMPLOYMENT

Cables suitable for connecting cameras remotely, consisting of coaxial and red-black wires for power supply.

PHYSICAL CHARACTERISTICS

Code			ITAL1757H5	ITAL1757H75
Class			At	At
coaxial	Inner conductor	type	Cu	Cu
	Nominal conductor diameter	Mm	0.40 ± 0.02	0.40 ± 0.02
	Dielectric	type	Polyethylene foam	Polyethylene foam
	Dielectric diameter	Mm	1.8 ± 0.1	1.8 ± 0.1
	Taping	type	Al/Pet/100%	Al/Pet/100%
	Braided screen	type	At 80%	At 80%
	Coaxial sheath material	type	LSZH	LSZH
Conductors	Coaxial nominal outer diameter	Mm	3.3 ± 0.2	3.3 ± 0.2
	Electrical conductor	mm ²	2x0,50	2x0,75
	Conductor insulation	type	LSZH	LSZH
			Conductor outer diameter	Mm
			1.8 ± 0.2	1.9 ± 0.2
			Outer sheath material	type
			LSZH	LSZH
			Cable Nominal Outer Diameter	Mm
			6.6 x 5.0	6.7 x 5.0
Electrical Characteristics				
			Impedance	Ohm
			75 ± 3	75 ± 3
			Capacity	pF/m
			55 ± 2	55 ± 2
			Propagation speed	%
			83	83
			Conductor resistance Int./Est. at 20°C	Ohms/km
			140/38	140/38
			Maximum electrical conductor current	At
			6	6
			Electrical conductor resistance	Ohms/km
			39	24,7
Various				
			Operating Temperature	°C
			-20/+70	-20/+70
			Min. bending radius	Mm
			25	25
			Cable Rated Weight	kg/km
			42,5	44,5

Shielding Efficiency (SA)		MHZ Freque ncy	Attenuation at 20°C ITAL1757H5 db/100m	Attenuation at 20°C ITAL1757H75 db/100m
Frequency				
		1	1,6	1,5
		3,6	3,1	4,3
Mhz		10	5,0	8,1
30-1000	>85dB	71,5	12,7	12,6
1000-2000	>80dB	88,5	14,1	16,9
2000-3000	>80dB	135	17,5	18,9
		270	24,9	28,5
Cumulative reflection losses (S.R.L.)		360	28,8	30,2
		540	35,5	34,0
Frequency		750	42,0	
Mhz		1000	48,9	
50-470	>30dB	1500	61,5	
470-1000	>20dB	2250	80,0	
1000-2000	>16dB	3000	95,0	

Data and drawings shown in this catalogue are not binding and may be modified following modifications and/or improvements deemed necessary by the manufacturer. Weight and diameter tolerances ± 5%.