


LIY-CY LIH-CH

Cu/PVC/PVC screened



TECHNICAL FEATURES

Operating temperature	-15 °C ÷ +70 °C (-40 °C fixed inst.)
Rated voltage	250 V
Testing voltage	2,0 kV
Current carrying capacity	Acc. to DIN VDE 0295 resp. IEC 60228
Conductor material	Bare copper flexible
Conductor class	Class 5 DIN VDE 0812 resp. IEC 60228
Core insulation	Thermoplastic material based PVC (quality TI2)
Core identification	Acc. to DIN 47100
Separator	Polyester Tape
Screening	Tin copper braid coverage > 80%
Outer sheath material	Thermoplastic material based PVC (quality TM2)
Colour outer sheath	Grey RAL 7001
Printing	To be defined
Max. temp. of short circuit	150 °C (max. 5 sec)
Min. bending radius	DIN VDE 0298 part 3
Other versions	LIHCH Low Smoke Zero Halogen

APPLICATION

Data transmission cable, control and connecting cable mainly for transmission of analog and digital signals in process controlled facilities in measurement and control technology. For fixed laying and flexible applications. Suitable for use in dry and humid rooms.

SPECIAL FEATURES

IEC 60332-1, EN50265 -2-1, IEC 60332-3C, HD 405.3, IEC 70754-1, EN 50267-2-1, IEC 61034, EN 50268-2 LT > 60%

REMARKS

Conform to RoHS
CE acc. to EC Low-Voltage Directive 73/23/EEC and 93/68/EEC

Section mm²	Nom. O.D. mm	Copper weight kg/km	Approx. Cable weight kg/km	Section mm²	Nom. O.D. mm	Copper weight kg/km	Approx. Cable weight kg/km	Section mm²	Nom. O.D. mm	Copper weight kg/km	Approx. Cable weight kg/km
2 x 0,14	3,8	12,1	23	12 x 0,25	7,6	54,3	96	27 x 0,34	11,9	138	239
3 x 0,14	4	14	27	14 x 0,25	8	59	106	28 x 0,34	12,3	146	259
4 x 0,14	4,2	16,4	30	16 x 0,25	8,3	65	118	30 x 0,34	12,5	159	265
5 x 0,14	4,5	18,9	35	18 x 0,25	8,7	83	131	32 x 0,34	13	163	290
6 x 0,14	4,8	22	40	20 x 0,25	9,2	88	142	36 x 0,34	13,6	178	315
7 x 0,14	4,8	22,8	41	21 x 0,25	9,2	93	144	2 x 0,50	5,8	29,0	51
8 x 0,14	5,4	25,6	49	24 x 0,25	10,4	110	171	3 x 0,50	6,1	39,0	61
10 x 0,14	6	30,8	58	25 x 0,25	10,6	114	181	4 x 0,50	6,5	49,0	72
12 x 0,14	6,2	34,1	63	27 x 0,25	10,6	125	185	5 x 0,50	7,0	57,0	85
14 x 0,14	6,6	37,8	73	28 x 0,25	11	127	195	6 x 0,50	7,6	66,0	99
16 x 0,14	6,9	43	80	30 x 0,25	11	132	199	7 x 0,50	7,6	69,0	103
18 x 0,14	7,2	52	88	32 x 0,25	11,3	138	218	8 x 0,50	9,1	82,0	138
20 x 0,14	7,6	55	96	36 x 0,25	11,8	146	238	10 x 0,50	9,6	90,0	147
21 x 0,14	7,6	56	97	2 x 0,34	4,8	21	36	12 x 0,50	9,9	104,0	165
24 x 0,14	8,2	62	108	3 x 0,34	5,1	27	43	14 x 0,50	10,4	122,0	186
25 x 0,14	8,4	63	113	4 x 0,34	5,6	33	54	16 x 0,50	11,1	129,0	214
27 x 0,14	8,4	66	116	5 x 0,34	6,1	36	64	18 x 0,50	11,7	141,0	236
28 x 0,14	8,6	67,7	122	6 x 0,34	6,7	39	76	21 x 0,50	12,5	168,0	268
30 x 0,14	8,6	69	125	7 x 0,34	6,7	46	79	25 x 0,50	13,6	211,0	314
32 x 0,14	9,1	76	141	8 x 0,34	7,3	52	89	2 x 0,75	6,2	43,0	60
36 x 0,14	9,6	82	154	10 x 0,34	8,2	74	107	3 x 0,75	6,5	52,0	77
2 x 0,25	4,4	16,6	31	12 x 0,34	8,5	80	119	4 x 0,75	7,0	61,0	87
3 x 0,25	4,6	21	36	14 x 0,34	8,8	86	133	5 x 0,75	7,7	72,0	106
4 x 0,25	5	24	42	16 x 0,34	9,3	94	148	6 x 0,75	8,3	80,0	124
5 x 0,25	5,5	29	53	18 x 0,34	9,9	103	169	7 x 0,75	8,3	89,0	129
6 x 0,25	5,9	31,3	60	20 x 0,34	10,7	112	188	8 x 0,75	9,9	98,0	172
7 x 0,25	5,9	37	62	21 x 0,34	10,7	116	191	10 x 0,75	10,5	115,0	184
8 x 0,25	6,4	42	69	24 x 0,34	11,7	130	221	12 x 0,75	10,9	138,0	211
10 x 0,25	7,4	46,1	87	25 x 0,34	11,9	135	233				