AIKO

COMET

3N72 Mono-Glass Module

660W-690W



Technical Features:

- Partial Shading Optimisation
- Better Temperature Coefficient
- High Temperature Restriction
- Micro-crack Resistance
- Higher Power
- Lower BOS
- More Aesthetic Values
- Infinite Technology

TIER 1 BloombergNEF

ESG Innovation Award 2023/24 Excellence

inter solar award 2023 WINNER

reddot winner 2023

15 year Product Warranty Extendable to 25years*

30 year Performance Warranty

TÜVRheinland

Warranty partner

Munich RE

Comet 3N72

AIKO-A-MDE72Mw

690W	25.5%	≤1%	≤0.35%
Output	Efficiency	First-year Degradation	Annual Degradation from Year 2-30

30-year Linear Performance Warranty





Tolerance
L: ±2mm
W: ±2mm
Unit: mm

Electrical Characteristics (STC: AM1.5 1000W/m² 25℃ NOCT: AM1.5 800W/m² 20℃ 1m/s)

Power Tolerance:0~ + 3%

Module Type	AIKO-A660-MDE72Mw		AIKO-A665-MDE72Mw		AIKO-A670-MDE72Mw		AIKO-A675-MDE72Mw		AIKO-A680-MDE72Mw		AIKO-A685-MDE72Mw		AIKO-A690-MDE72Mw	
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
P_{max} [W]	660	500	665	504	670	508	675	512	680	515	**685**	**519**	**690**	**523**
V_{oc} [V]	54.20	51.42	54.35	51.56	54.50	51.71	54.65	51.85	54.80	51.99	**55.00**	**52.18**	**55.20**	**52.37**
V_{mp} [V]	45.50	43.17	45.60	43.26	45.70	43.36	45.80	43.45	45.90	43.55	**46.00**	**43.64**	**46.10**	**43.74**
I_{sc} [A]	15.22	12.30	15.28	12.35	15.35	12.40	15.41	12.45	15.47	12.5	**15.53**	**12.55**	**15.59**	**12.6**
I_{mp} [A]	14.51	11.60	14.59	11.66	14.67	11.72	14.74	11.79	14.82	11.85	**14.90**	**11.91**	**14.97**	**11.97**
Module Efficiency	**24.4%**		**24.6%**		**24.8%**		**25.0%**		**25.2%**		**25.4%**		**25.5%**	

Product Specification

Cell Type	N-Type ABC
Glass	3.2mm tempered glass
Backsheet	High weather resistant backsheet
Frame	Anodized aluminum
Cable	4mm²(IEC) 12AWG(UL) +400mm, -200mm/±1400mm or Customized Length
No. of Cells	144(6*24)
Junction Box	IP68, 3 bypass diodes
Connector	MC4 Compatible/Original MC4-EVO2A
Weight	28.2kg±3%
Dimension	2382*1134*30mm
Package Detail	36pcs per pallet / 144pcs per 20'GP / 720pcs per 40'HC

Temperature Ratings (STC)

Temperature Coefficient of I_{sc}	+ 0.05%/ °C
Temperature Coefficient of V_{oc}	- 0.22%/ °C
Temperature Coefficient of P_{max}	- 0.26%/ °C

Installation Guide

Operation Temperature	-40℃ - +85℃
Maximum Series Fuse Rating	25A
Protection Class	Class II
Maximum System Voltage	DC1500V
Maximum Static Loading	Front 5400Pa Back 2400Pa
Hail Test	25 mm diameter hail at 23 m/s
Fire Rating	IEC Class C

www.aikosolar.com
marketing@aikosolar.com

*AIKO reserves right to update the specification without notice

V4.1_202510_DsDr_EN