

Pickle Rick


Description : A Rick and Morty CTF. Help turn Rick back into a human!

So , We will start with scanning the Machine_IP using [Nmap - The Ultimate Cheat Sheet](#)

Command : `nmap -sC -sV -T4 Machine_IP` where,

- `-sC` : Run default, safe NSE scripts.
- `-sV` : Enumerate service versions.
- `-T4` : Use the "aggressive" timing template for speed.

This will give you the following Output :



```
Kali [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
1 2 3 4
root@kali: /home/kali

(root@kali)~[/home/kali]
# nmap -sC -sV -T4 10.201.24.203
Starting Nmap 7.95 ( https://nmap.org ) at 2025-08-11 11:43 IST
Nmap scan report for 10.201.24.203
Host is up (0.40s latency).
Not shown: 998 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.2p1 Ubuntu 4ubuntu0.11 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   3072 63:d3:61:50:7e:e4:c1:4f:4d:97:50:d1:52:ef:dc:6b (RSA)
|   256  c4:93:a3:a8:66:1f:7a:53:cc:8c:b9:4b:7b:10:12:9e (ECDSA)
|_  256  7e:85:b2:45:03:03:81:5a:44:59:e5:45:17:a2:28:04 (ED25519)
80/tcp    open  http     Apache httpd 2.4.41 ((Ubuntu))
|_ http-title: Rick is sup4r cool
|_ http-server-header: Apache/2.4.41 (Ubuntu)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 21.19 seconds
```


Here, we can see that there are 2 ports open.

Port 22 - SSH


Port 80 - HTTP

We also found out that the server is running the Linux OS.

So we will navigate to **Machine_IP** to view the webpage.




Let us check the Source code of the website using **Inspect**.



So we got the Username which is **R1ckRu13s** which can be useful if we get the login page.

Now we can try with robots.txt file.



We got some text. I do not think for now it will work so we will move forward.

Now we will try to use [Gobuster - The Ultimate Cheat Sheet](#) to find out the directories of the website.

The Command which we are going to use is :

`gobuster dir -u https://target.com -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -x php,html` where,

- `dir` : Directory brute force mode.
- `-u` : Target URL.
- `-w` : Wordlist path.
- `-x` : File extensions (comma-separated).

We got the following result.

```
(root@kali)~[/home/kali]
# gobuster dir -u http://10.201.0.212/ -w /usr/share/wordlists/dirbuster/directory-list-lowercase-2.3-small.txt -x php,html -fc 200


Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url: http://10.201.0.212/
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-lowercase-2.3-small.txt
[+] Negative Status codes: 404
[+] Cookies: 200
[+] User Agent: gobuster/3.6
[+] Extensions: php,html
[+] Add Slash: true
[+] Timeout: 10s


Starting gobuster in directory enumeration mode

./php/ (Status: 403) [Size: 277]
./html/ (Status: 403) [Size: 277]
/login.php/ (Status: 200) [Size: 882]
/icons/ (Status: 403) [Size: 277]
/assets/ (Status: 200) [Size: 2191]
/portal.php/ (Status: 302) [Size: 0] [→ /login.php]
```

We can see that we got login.php page. Let's visit the page.



We do have the username from the source code which is R1ckRu13s.
Now we will try the text from robots.txt as password.




Okay. So we got the Username and Password.

Username : R1ckRu13s

Password : Wubbalubbadubdub

Now we will try to execute some commands to check what access we have. Do we will start with **ls -l** to list the files in the current directory.



Command Panel

Commands

Execute

```
total 32
-rwxr-xr-x 1 ubuntu ubuntu 17 Feb 10 2019 Sup3rS3cretPickl3Ingred.txt
drwxrwxr-x 2 ubuntu ubuntu 4096 Feb 10 2019 assets
-rwxr-xr-x 1 ubuntu ubuntu 54 Feb 10 2019 clue.txt
-rwxr-xr-x 1 ubuntu ubuntu 1105 Feb 10 2019 denied.php
-rwxrwxrwx 1 ubuntu ubuntu 1062 Feb 10 2019 index.html
-rwxr-xr-x 1 ubuntu ubuntu 1438 Feb 10 2019 login.php
-rwxr-xr-x 1 ubuntu ubuntu 2044 Feb 10 2019 portal.php
-rwxr-xr-x 1 ubuntu ubuntu 17 Feb 10 2019 robots.txt
```


So we got multiple files in the directory. But we will focus mainly on two files,

1)Sup3rS3cretPickl3Ingred.txt

2)Clue.txt

We will use command Cat to read the files.

So the command is **Cat File_name.txt**



Command Panel

Commands

Execute


Command disabled to make it hard for future PICKLEEEEE RICCKKKK.

SO cat does not work. SO we could try multiple ways to read the file like :

==Grep File_name.txt==

****Tac File_name.txt****


We will try ==Tac Sup3rS3cretPickl3Ingred.txt ==



Command Panel

It gave us our First ingredient which is **mr . meeseek hair**


Now we will use tac clue.txt



Command Panel

Clue says that we should look for other file systems.


So lets first see which directory we are currently in. We will use PWD command to check current working directory.



Command Panel

So we are currently working with `/var/www/html` directory.

So we will try to load the files from root directory first using the command **`ls -l /root`**.




Command Panel

We got the error. The reason we got the error is that when we access the root files as the normal user we should use `sudo`.

We will try the same command using `sudo`.

command : **`sudo ls -l /root`**




Command Panel

Commands

Execute

total 8
-rw-r--r-- 1 root root 29 Feb 10 2019 3rd.txt
drwxr-xr-x 4 root root 4096 Jul 11 2024 snap

Okay so we got our third ingredient in the file 3rd.txt . Now we will read the file using command **sudo tac /root/3rd.txt**



Command Panel


Commands

Execute

3rd ingredients: fleeb juice

We got the **3rd ingredient : fleeb juice**

Now we will try the home directory.
command : ls /home



Command Panel


Execute

```
rick
ubuntu
```

We got two users : **Rick & Ubuntu**

We will check both the directories using command **ls /home/directory_name**.

We will start with Rick.



Command Panel


Execute

```
second ingredients
```

We get the second ingredients file in the rick directory.

Now we need to read the file to get the second ingredient. (Note : since there is space between file name we need to add ' \' in between the name).

Command : **tac /home/rick/second\ ingredients**



Command Panel

```
1 jerry tear
```

We got our last ingredient which is **1 jerry jar**.

This way we solved the entire **Pickle Rick** Lab . In this lab we learned about gobuster, linux commands, and many more things.