Survey on Group Sparsity in Security Applications

Itay Shorian
Advisor: Dr. Nadav Hallak

11 December 2025

Abstract

This survey reviews the application of Group Sparsity in security-oriented systems. We classify applications into four domains: Cyber-Physical Systems, Network Traffic Analysis, Smart Grids, and Biometric Security. For each domain, we present the mathematical formulation, the optimization model, and the algorithmic solution utilized to detect and mitigate threats. Additionally, we discuss emerging applications in detecting algorithmically generated malicious domains.

1 Introduction

Group sparsity has become an important modeling tool in security-oriented systems such as cyber-physical infrastructures, communication networks, and power grids. These systems often exhibit anomalies or attacks that are not isolated to individual measurements but instead affect entire functional subsystems. This motivates the use of structured sparsity models that operate over predefined groups of variables. The objective of this report is to outline the concepts of sparsity and group sparsity and to examine representative uses of these models in security applications.

2 Sparse Optimization

Let $x \in \mathbb{R}^n$. The sparsity of x is defined through the cardinality of its support,

$$\|x\|_0 = |\{\, i : x_i \neq 0 \,\}|.$$

Sparse optimization refers to problems that incorporate such structure, typically of the form

$$\min_x \; f(x) \quad \text{subject to} \quad \|x\|_0 \leq k.$$

Problems of this type arise in high-dimensional inference, compressed sensing, anomaly detection, regression, and inverse problems, as comprehensively reviewed by Bruckstein et al. [BDE09]. However, the ℓ_0 constraint is nonconvex and generally intractable, motivating the use of surrogate formulations.

2.1 Convex Relaxation

A common relaxation replaces ℓ_0 with the convex ℓ_1 norm,

$$\min_x \ f(x) + \lambda \|x\|_1.$$

Under appropriate conditions on the measurement operator (such as the Restricted Isometry Property), solutions to this relaxation recover the same support as those to the original ℓ_0 problem [BDE09]. This principle forms the basis of many modern methods in sparse regression.

2.2 Structured Sparsity

While standard sparsity models encourage solutions with few nonzero entries, many modern applications involve variables that exhibit correlations or belong to meaningful subsets. In such settings, enforcing sparsity at the individual-coordinate level is often suboptimal, as it ignores known structure in the problem. This motivates the concept of *structured sparsity* [BCDH10]. Formally, let the support of a vector $x \in \mathbb{R}^n$ be defined as the set of indices corresponding to nonzero entries:

$$\text{supp}(x) = \{i \in \{1, \dots, n\} : x_i \neq 0\}.$$

In standard k-sparsity, the support is allowed to be any subset of cardinality k. In contrast, structured sparsity restricts the support to belong to a specific family of allowed patterns, denoted by $\mathbb{M}$. A vector x is said to satisfy the structured sparsity model if:

$$\text{supp}(x) \in \mathbb{M}.$$

This generally implies that the nonzero coefficients must appear in specific configurations, effectively constraining x to lie in a union of low-dimensional subspaces defined by $\mathbb{M}$. Let $\mathcal{G} = \{G_1, \dots, G_m\}$ be a collection of groups describing these patterns. Typical examples include:

- **Group sparsity:** The allowed supports are unions of a small number of disjoint groups.
- **Tree-structured sparsity:** Nonzero entries must follow a rooted hierarchy (e.g., if a node is nonzero, its parent must also be nonzero).
- **Graph sparsity:** The support must form a connected subgraph over an underlying topology.

Structured sparsity is typically enforced by replacing the ℓ_1 norm with structured norms (such as the $\ell_{2,1}$ norm) that penalize deviations from the allowed patterns $\mathbb{M}$.

3 Group Sparsity

Consider a partition of the index set $\{1, \dots, n\}$ into m disjoint groups $\mathcal{G} = \{G_1, \dots, G_m\}$, where $G_i \subseteq \{1, \dots, n\}$. A vector x is said to be *group-sparse* if the sub-vectors x_{G_i} are identically zero for the majority of groups (i.e., $x_{G_i} = 0$ for most i). To promote this structure, we utilize the mixed $\ell_{2,1}$-norm (Group-Lasso penalty), defined as the sum of the Euclidean norms of the sub-vectors:

$$\|x\|_{2,1} = \sum_{i=1}^{m} \|x_{G_i}\|_2.$$

The recovery of group-sparse signals is achieved by solving the convex optimization problem:

$$\min_x \; f(x) + \lambda \sum_{i=1}^{m} \|x_{G_i}\|_2,$$

where $f(x)$ represents a convex loss function (such as the squared error) measuring the data fidelity, and λ is a regularization parameter. As discussed in model-based compressive sensing frameworks [BCDH10], the non-differentiability of the term $\|x_{G_i}\|_2$ at zero forces the entire block x_{G_i} to zero simultaneously when its contribution is insignificant, thereby enforcing the group structure.

4 Security Applications of Group Sparsity

Structured sparsity plays an increasingly important role in detecting, characterizing, and mitigating security threats in large-scale engineered systems. We examine several representative applications.

4.1 Cyber-Physical Manufacturing Systems

In multistage manufacturing systems, identifying the source of a fault is challenging because errors propagate downstream. Malicious False Data Injection (FDI) attacks or component failures in one stage affect quality measurements in all subsequent stages. This dependency creates a *grouped* structure in the error vector. The relationship between quality measurements y and the fault sources u is modeled via a Stream of Variation (SoV) state-space model, often reduced to a linear form $y = \Phi u + v$. Kokhahi and Li [KL24] formulate the fault isolation problem as a Group Lasso regression:

$$\min_u \frac{1}{2}\|y - \Phi u\|_2^2 + \lambda \sum_{k=1}^{K} \|u_k\|_2,$$

where u_k represents the fault vector associated with the k-th manufacturing stage. By using the $\ell_{2,1}$ norm, the estimator enforces sparsity at the stage level rather than the sensor level.

Algorithmic Solution: This problem is typically solved using *Block Coordinate Descent (BCD)*. The algorithm iteratively optimizes a single block (stage) u_k while keeping others fixed. *Theoretical Guarantee:* Since the objective function is convex and the non-smooth part is separable across blocks, Block Coordinate Descent is guaranteed to converge to a global optimum of the problem.

4.2 Network Traffic Anomaly Detection

Backbone communication networks generate massive traffic matrices (OD flows). Under normal operation, traffic exhibits high temporal and spatial correlation, resulting in a low-rank matrix. Anomalies (e.g., DDoS attacks, port scans) appear as sparse deviations. To robustly detect these attacks, the traffic matrix is decomposed into a low-rank component representing nominal traffic and a sparse component representing anomalies. Mardani et al. [MMG13] use an elementwise ℓ_1 penalty for the anomaly matrix, not a group-sparsity penalty:

$$\min_{X,A} \frac{1}{2}\|\mathcal{P}_\Omega(Y - X - RA)\|_F^2 + \lambda_*\|X\|_* + \lambda_1\|A\|_1.$$

Here, R maps origin–destination flows to measured links and $\mathcal{P}_\Omega$ retains the available link observations. The nuclear norm promotes a low-rank nominal component, while the ℓ_1 norm promotes isolated sparse flow–time anomalies. Their online Algorithm 2 factors the low-rank component and alternates a Lasso anomaly update with ridge-regression/subspace updates. A group-sparse extension would require replacing or augmenting $\|A\|_1$ with a penalty such as $\sum_g \|A_{G_g}\|_2$, together with attack data whose groups have an externally justified meaning; it is not part of the original paper.

4.3 Sparse Malicious False Data Injection Attacks in Smart Grids

State estimation in smart grids is traditionally performed using Weighted Least Squares (WLS). The linearized measurement model is given by:

$$z = Hx + e,$$

where H is the Jacobian matrix determined by the grid topology. In a False Data Injection Attack (FDIA), an adversary injects a vector $a = Hc$ to bias the state estimate while avoiding detection by standard residual tests. Since physical access to sensors is constrained, the attack vector a is sparse. Moreover, because attackers typically compromise entire substations, the attack exhibits group sparsity. Ozay et al. [OEV+16] formulate the defense mechanism as:

$$(\hat{x}, \hat{a}) = \arg\min_{x,a} \frac{1}{2}\|z - Hx - a\|_2^2 + \lambda\|a\|_{2,1}.$$

The $\ell_{2,1}$ norm promotes block-sparsity, helping to identify and zero out uncompromised sensor groups. **Algorithmic Solution:** This optimization is solved via the *Alternating Direction Method of Multipliers (ADMM). Theoretical Guarantee:* ADMM is particularly suitable

for smart grids as it allows for distributed implementation and is theoretically guaranteed to converge to the global optimum for this convex problem setup.

4.4 Robust Face Recognition with Locality Constraints

In biometric security, standard Sparse Representation Classification (SRC) methods assume that occlusion (noise) is sparse and randomly distributed. However, real-world disguises (e.g., sunglasses, scarves) form contiguous spatial blocks. Furthermore, standard sparse coding does not consider the local manifold structure of face data, leading to unstable representations. To address this, *Locality-constrained Group Sparse Representation (LGSR)*, as proposed by Xu et al. [XZLY14] and Chao et al. [CYC+11], models the error term using group sparsity (matching spatial blocks) while enforcing locality on the dictionary atoms. The problem is formulated as:

$$\min_{x,e} \|y - Ax - e\|_2^2 + \lambda_1 \|d \odot x\|_2^2 + \lambda_2 \|e\|_{2,1},$$

where y is the test sample, A is the training dictionary, and d is a locality adaptor vector. The term $\|e\|_{2,1}$ specifically enforces the error to be concentrated in spatial blocks. **Algorithmic Solution:** The problem is solved using an iterative alternating minimization strategy. *Theoretical Guarantee:* Since the dictionary A is fixed during the recognition phase, the optimization problem is convex with respect to x and e, and the alternating minimization algorithm is guaranteed to converge to a global minimizer of the objective.

4.5 Detection of Algorithmically Generated Malicious Domains

Botnets frequently use Domain Generation Algorithms (DGAs) to maintain resilient communication with their command-and-control (C&C) servers. Instead of relying on a static domain, a DGA produces hundreds of pseudo-random domain names per day. Security systems must identify these algorithmically generated domains hidden among vast volumes of benign DNS traffic. To address this, Yadav et al. [YRRR10] propose identifying *groups* of malicious domains that map to the same IP address or belong to the same connected component in the DNS graph. The method extracts statistical features for each group, such as the Kullback-Leibler (KL) divergence of character distributions and Jaccard index of bigrams. The classification problem is formulated as a supervised learning task using *L1-regularized Linear Regression (Lasso)*. Let y be the vector of labels for groups, and X be the matrix of computed features. The model seeks a sparse weight vector β by solving:

$$\min_{\beta} \sum_i \left(y_i - \beta_0 - \sum_j \beta_j x_{ij} \right)^2 + \lambda \sum_j |\beta_j|.$$

Here, the ℓ_1 regularization term enforces sparsity, selecting only the most discriminative statistical features. **Algorithmic Solution:** The problem is solved using coordinate descent methods (e.g., `glmnet`). *Theoretical Guarantee:* For the convex Lasso objective, coordinate

descent is guaranteed to converge to a minimizer of the objective function. The resulting sparse solution selects a subset of informative statistical features for classification.

5 Discussion

The applications reviewed in this survey demonstrate that Group Sparsity provides a unifying mathematical framework for addressing security challenges in cyber-physical and networked systems. Whether in identifying compromised manufacturing stages, detecting coordinated false data injection in smart grids, or isolating occlusions in biometric recognition, these methods exploit low-dimensional structures to enable scalable detection, localization, and interpretation of adversarial behavior.

Research Gaps. Although structured sparsity has demonstrated substantial potential in security-oriented applications, several gaps remain open in the literature:

- **Limited use of explicit group-sparse models in security:** Many works still rely on unstructured ℓ_1 penalties (Lasso) or heuristic feature selection rather than enforcing structure-aware sparsity (Group Lasso) that aligns with real-world attack patterns, such as those seen in botnet architectures.
- **Mismatch between theoretical models and real-world attack behavior:** Existing formulations often assume idealized group structures (e.g., fixed partitions, non-overlapping groups). However, actual attack surfaces are dynamic; they evolve over time and often exhibit overlapping dependencies that static models fail to capture.
- **Lack of hierarchical or graph-based sparsity models:** Attacks such as coordinated sensor compromise, lateral movement in networks, and multi-stage manufacturing faults naturally follow hierarchical or graph-based patterns. Current optimization models rarely incorporate these complex topological constraints explicitly.
- **Insufficient integration into real-time systems:** While theoretical algorithms (e.g., ADMM, BCD, IALM) offer strong convergence guarantees, few works address the computational constraints of deploying them in real-time, streaming data environments typical of operational security centers (SOCs).
- **Underexplored connections to anomaly families:** Problems such as DGA-based botnet detection exhibit clear group-level statistical behavior. However, structured sparsity methods have not yet been fully leveraged to capture these family-level signatures compared to traditional statistical methods.

Addressing these gaps requires the development of adaptive, graph-aware, and computationally efficient optimization algorithms. Such advancements will enable more accurate and ready-to-deploy detection systems capable of handling the complexity of modern adversarial patterns.

6 Experimental Evaluation and Interpretation

To complement the literature review, we conducted two empirical studies that examine how anomaly-detection models behave under realistic distribution shift and under a controlled transition from linear to nonlinear nominal traffic. The purpose of these experiments is not to replace the theoretical survey, but to test several of its main assumptions: first, that reconstruction-based anomaly detection can identify abnormal traffic from normal-only training data; and second, that low-rank sparse models may become less suitable when the normal component is generated by a nonlinear low-dimensional mechanism.

6.1 Experiment 1: VAE Detection on CICIDS2017

The first experiment evaluates a Variational Autoencoder (VAE) trained only on benign traffic from the CICIDS2017 dataset. The model was trained on the Monday traffic file, which contains only benign flows, and tested on the Friday afternoon DDoS file, which contains both benign and DDoS flows. After removing exact duplicate benign rows, the Monday data contained 459,222 unique normal flows, split into 344,416 training rows and 114,806 validation rows. The Friday test set contained 225,104 retained flows, of which 128,027 were DDoS and 97,077 were benign.

The VAE receives 67 numerical flow features after removing identifiers, IP addresses, timestamps, ports, protocol, and labels. The preprocessing pipeline was fitted only on the training data and included median imputation, signed logarithmic transformation, and standardization. The model architecture was

$$67 \to 128 \to 64 \to 8 \to 64 \to 128 \to 67,$$

where the latent dimension was 8. The anomaly score of a flow was defined as the reconstruction residual

$$s_i = \|x_i - \hat{x}_i\|_2.$$

The detection threshold was calibrated as the 99th percentile of the Monday validation reconstruction scores, corresponding to a target false-positive rate of 1% on the validation distribution.

Table 1: Experiment 1: VAE performance on CICIDS2017 Friday DDoS traffic.

Metric	Mean	Standard deviation
Precision	0.7767	0.0104
Recall	0.8413	0.0104
F1	0.8076	0.0066
False-positive rate	0.3192	0.0201
Average precision	0.6353	0.0117
ROC-AUC	0.7196	0.0150

The results show that the VAE detects a large portion of DDoS flows, with an average recall of 84.13%. However, this comes at the cost of a high false-positive rate on benign Friday traffic: about 31.92% of benign flows are incorrectly flagged as attacks. In operational terms, out of every 1,000 test flows, the model detects roughly 478 attacks, misses 90 attacks, incorrectly flags 138 benign flows, and correctly accepts 294 benign flows.




Figure 1: Summary metrics and average confusion matrix for the VAE on CICIDS2017.

The main explanation for this behavior is distribution shift between the Monday benign traffic used for training and calibration and the Friday benign traffic used during testing. Although the VAE learned the Monday normal distribution well, the benign Friday flows exhibit much larger reconstruction errors. The median anomaly score rises from 0.164 on Monday validation traffic to 0.404 on Friday benign traffic, while the 90th percentile rises from 0.557 to 7.456. Therefore, many benign Friday flows lie far outside the calibrated Monday normal region.




Figure 2: Normalized reconstruction-score distributions and precision-recall behavior. The threshold calibrated on Monday does not transfer cleanly to benign Friday traffic.

Further analysis shows that the false positives are concentrated in traffic subpopulations whose properties changed substantially between Monday and Friday. For example, the proportion of flows with a positive URG flag increases from 6.12% in Monday training to 32.61% in Friday benign traffic. Similarly, high destination ports and source ports 80 or 443 become much more common on Friday. These metadata variables were not used directly as model inputs; rather, they indicate that the Friday benign population contains traffic patterns that are structurally different from those learned during training.




Figure 3: Distribution-shift diagnostics and concentration of false positives in shifted benign subgroups.

A threshold-sensitivity analysis confirms that the problem cannot be solved simply by choosing a more conservative threshold. Raising the threshold reduces the Friday false-positive rate only moderately, while recall drops sharply. For example, moving from a 1% to

a 0.1% target false-positive rate on Monday validation reduces the Friday false-positive rate from 31.92% to 26.22%, but recall falls from 84.13% to 33.93%.




Figure 4: Threshold sensitivity for Experiment 1. More conservative calibration reduces recall much faster than it reduces cross-day false positives.

The conclusion from Experiment 1 is that a normal-only VAE can identify many DDoS flows, but the current calibration procedure is not robust to cross-day benign distribution shift. This result is important for the survey because it shows a practical limitation of reconstruction-based anomaly detection: learning a nonlinear normal model is not sufficient if the definition of "normal" changes between training and deployment. In security systems, this motivates adaptive calibration, context-aware scoring, and structured models that can distinguish attack residuals from benign changes in traffic composition.

6.2 Experiment 2: Paper-Routed Linear Control and Nonlinear Extension

The second experiment replaces the earlier identity-routing pilot with the synthetic network model specified in Section VI-A of Mardani et al. [MMG13]. For each of three fixed seeds, 15 nodes are sampled in the unit square and connected using the paper's distance threshold of 0.35. We retain connected graphs with exactly 52 directed links. The ordered node pairs define 210 origin–destination (OD) flows, and minimum-hop paths define the routing matrix $R \in \{0,1\}^{52\times 210}$.

At the linear endpoint, nominal OD traffic has rank two, attacks are independent sparse signed entries with probability $p = 0.005$, and link noise has standard deviation $\sigma = 0.01$:

$$z_t = Uw_t, \qquad y_t = R(z_t + a_t) + v_t.$$

This matches the published dimensions and distributions but not the authors' unpublished random realization. The main sweep uses static routing and full link observations. It contains

6,000 normal training samples, 2,000 normal validation samples, 2,000 independent normal calibration samples, and 4,000 attacked test samples per seed.

The paper itself assumes a linear low-rank nominal component. Our extension introduces a separate nonlinearity parameter γ while reserving α for the paper's routing-change probability. Independent nonlinear maps produce $G(w_t)$, their routed training energy is matched to the linear endpoint, and

$$z_t(\gamma) = (1-\gamma)Uw_t + \gamma G(w_t), \qquad \gamma \in \{0, .25, .5, .75, 1\}.$$

The topology, latent draws, attacks, and noise are paired across γ within each seed.

Two methods are compared. *VAE+Lasso* trains a two-dimensional VAE only on normal 52-dimensional link measurements. The VAE therefore learns nominal traffic, not attacks. At test time the OD attack estimate is obtained from the unexplained link residual using

$$\hat{a}_t = \arg\min_a \frac{1}{2}\|y_t - \hat{\ell}_t - Ra\|_2^2 + 0.11\|a\|_1.$$

OnlineDA implements the paper's Algorithm 2 with routing matrix R, rank bound 5, ridge parameter 0.36, sparse penalty 0.11, and a normal-prefix SVD initialization. This initialization and the separate normal splits are explicit adaptations needed for a matched comparison with a frozen VAE.

Table 2: Experiment 2: mean attack-time and OD-flow F1 across three seeds.

γ	VAE time F1	OnlineDA time F1	VAE flow F1	OnlineDA flow F1
0.00	0.9995	0.9942	0.1261	0.5539
0.25	0.9965	0.9972	0.1314	0.4107
0.50	0.9962	0.9965	0.1106	0.4031
0.75	0.9966	0.9964	0.1147	0.4154
1.00	0.9976	0.9960	0.1391	0.4163

Both methods detect almost every attacked time point, so time-level F1 is not discriminative in this generator. OD-flow localization gives the important result: OnlineDA has substantially higher F1 for every γ. At $\gamma = 1$, flow average precision is 0.8680 for VAE+Lasso and 0.9295 for OnlineDA, while flow false-positive rates are 0.0585 and 0.0131, respectively.




Figure 5: Detection and OD-flow localization in the paper-routed nonlinear sweep. The VAE preserves attack timing but produces a much denser flow residual.

The nonlinear extension does change the geometry as intended: the mean linear rank required for 99% of nominal-link energy rises from 2 at $\gamma = 0$ to 9.33 at $\gamma = 1$. Nevertheless, the current VAE does not convert that modeling capacity into better attack localization. The inverse problem has only 52 link measurements for 210 OD-flow coefficients, so dense reconstruction error is amplified by sparse decoding. At $\gamma = 1$, relative OD-anomaly recovery error is 0.5860 for VAE+Lasso and 0.4276 for OnlineDA.




Figure 6: The effective linear rank grows with γ, but the configured VAE still has higher OD-anomaly recovery error.

Following the parameter combinations around Figure 4 of the paper, a separate linear-endpoint stress suite uses forgetting factor $\beta = 0.9$, 1,000-sample test streams, time-varying routing, and missing link measurements. The four parameter triples (α, π, σ) are

$$(.01, .8, .01), \quad (.01, .8, 10^{-5}), \quad (.1, .8, 10^{-5}), \quad (.01, 1, 10^{-5}).$$

Table 3: Paper-style tracking stress tests: mean flow F1 / average precision.

(α, π, σ)	VAE+Lasso	OnlineDA
$(.01, .8, .01)$	0.2217 / 0.3793	0.2335 / 0.3810
$(.01, .8, 10^{-5})$	0.2213 / 0.3832	0.2342 / 0.3819
$(.1, .8, 10^{-5})$	0.2790 / 0.3480	0.2748 / 0.3332
$(.01, 1, 10^{-5})$	0.3002 / 0.7560	0.3535 / 0.7977

There is no stable winner under tracking stress: OnlineDA has higher flow F1 in three scenarios, whereas VAE+Lasso is slightly higher under rapid routing changes. Both deteriorate strongly relative to static routing. The VAE models raw link observations and is not conditioned explicitly on R_t or the missing data mask, which limits invariance to topology and observation changes.




Figure 7: Flow localization under the four routing, missing-link, and noise settings adapted from the paper.

Group sparsity is deliberately not inserted into this main comparison. The reference objective uses the elementwise penalty $\|A\|_1$, and its synthetic attacks are drawn independently; it defines neither attack groups nor a Group-Lasso estimator. A defensible group-sparse experiment must first define externally meaningful groups—for example common source, destination, service, subnet, or temporal campaign—and supply attacks structured at that same level. It is a separate extension, not a correction to the paper.

Finally, the article's real Internet2 experiment cannot be reproduced exactly from the publication alone. The authors' traffic files, topology snapshot, observation masks, pseudo-ground-truth output, and random seed are not distributed with the paper. Substituting another Internet2/Abilene archive would be a new experiment and is therefore not presented as a reproduction here.

6.3 Overall Experimental Conclusions

Together, the experiments show that nonlinear representation capacity is only one part of a security detector. Experiment 1 detects many DDoS flows but produces many false positives under benign cross-day distribution shift. Experiment 2 shows that a VAE can learn nonlinear nominal traffic and preserve attack timing, yet still localize OD-flow anomalies worse than the paper's linear sparse method. Calibration, routing, missing observations, and the structure of the residual are therefore as important as the nominal model.

The current results do not justify claiming that VAE+Lasso is superior to Dynamic Anomalography. They identify a concrete bottleneck instead: the VAE residual is too dense for the underdetermined routing inverse problem. A next model should be conditioned on routing and observation masks and should be evaluated on localization, not only event timing.

Group sparsity is a promising but separate continuation. It should be introduced only

after defining meaningful and auditable groups and constructing matched group-structured attacks. The resulting comparison should include the paper's elementwise Lasso as the control, Group Lasso as the structured decoder, and VAE-based nominal models with and without the same structured penalty. This design would isolate the contribution of nonlinearity from the contribution of group structure.

References

[BCDH10] Richard G Baraniuk, Volkan Cevher, Marco F Duarte, and Chinmay Hegde. Model-based compressive sensing. *IEEE Transactions on Information Theory*, 56(4):1982–2001, 2010.

[BDE09] Alfred M Bruckstein, David L Donoho, and Michael Elad. From sparse solutions of systems of equations to sparse modeling of signals and images. *SIAM Review*, 51(1):34–81, 2009.

[CYC+11] Yin-Wen Chao, Yi-Ren Yeh, Yu-Wen Chen, Yuh-Jye Lee, and Yu-Chiang Frank Wang. Locality-constrained group sparse representation for robust face recognition. In *2011 18th IEEE International Conference on Image Processing*, pages 761–764. IEEE, 2011.

[KL24] F Kokhahi and Z Li. Glhad: Group-lasso hybrid attack detector for multistage manufacturing systems. *ASME Journal of Computing and Information Science in Engineering*, 24(3), 2024.

[MMG13] Morteza Mardani, Gonzalo Mateos, and Georgios B Giannakis. Dynamic anomalography: Tracking network anomalies via sparsity and low rank. *IEEE Journal of Selected Topics in Signal Processing*, 7(1):50–66, 2013.

[OEV+16] Mete Ozay, Inaki Esnaola, Fatos T Yarman Vural, Sanjeev R Kulkarni, and H Vincent Poor. Sparse malicious false data injection attacks and defense mechanisms in smart grids. *IEEE Transactions on Smart Grid*, 7(6):2744–2755, 2016.

[XZLY14] Yong Xu, Zhong Zhang, Guangming Lu, and Jian Yang. Approximately locality-constrained group sparse representation for robust face recognition. *Pattern Recognition*, 47(8):2746–2754, 2014.

[YRRR10] Sandeep Yadav, Ashwath KK Reddy, AL Narasimha Reddy, and Supranamaya Ranjan. Detecting algorithmically generated malicious domain names. Technical report, Texas A&M University, 2010. Technical Report.