



Conference Chairman Unit

Conference chairman control embedded software V1.2

TS-0308



Feature:

- * Digital transmission link, connected to the cascade port of the conference server for power supply through the network port to six-pin aviation cable, uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- * The capacitive touch buttons can effectively eliminate the button tapping noise and ensure a good venue environment.
- * Support PC software microphone control and voice control function.
- * The chairman unit has the priority to turn off the speaking delegate unit.
- * Support TCP/IP protocol cluster, support ICMP, HTTP, UDP, TCP, IGMP and other protocols.
- * Support the PING packet function.
- * With an independent web control page, support adjusting parameters such as microphone ID number, microphone sensitivity, and microphone EQ.
- * Support feedback suppression function and voice control function, and the voice control sensitivity is adjustable.
- * Support 5-band EQ adjustment function, adjust sound effects according to voice characteristics of different speakers until the perfect effect is achieved.
- * Support the sign-in function, and stop unit sign-in, control unit sign-in and other functions through PC software
- * Support web page firmware upgrade function.
- * Support the IP address sniffing function; the ID number, IP address, MAC address and other parameters of the unknown unit can be found through the PC tool.

Specification:

Model	TS-0308
Microphone type	Electret condenser microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	680Ω
Sensitivity	-41±1.5dB(0dB=1V/Pa,at1KHz)
Maximum SPL	120dB
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.3%
Maximum power consumption	2W
Network port	2, cascaded network ports
Power supply	Conference server power supply
Color	Gray
Dimension	113×100×36mm (L×W×H) (excluding the length of the microphone pole)
Microphone pole	380mm black
Installation method	Desktop
Weight	0.8kg



Conference Delegate Unit

Hand-in-hand conference delegate control embedded software V1.0
TS-0308A



Feature:

- * Digital transmission link; it is connected to the conference host cascade port for power supply through the network port to the six-pin aviation cable; uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth, perfect sound quality.
- * The microphone unit adopts the capacitive touch button, which can effectively eliminate the key knocking sound and ensure the good environment of the venue.
- * Support PC software microphone control and voice control function.
- * The unit has TCP/IP protocol cluster and supports multiple protocols such as ICMP, HTTP, UDP, TCP, IGMP, etc.
- * The unit supports PING package function.
- * Independent web control page. It supports setting the unit ID number, sensitivity, and EQ through the WEB.
- * With feedback suppression function, voice control function, and adjustable voice control sensitivity.
- * It supports setting up 5-segment EQ adjustment function to adjust different sound effects according to the voice characteristics of the speaker for perfect effect.
- * Support sign-in function. You can also forbid mic unit check-in, manage mic unit check-in and and other functions through the PC software.
- * Support web page firmware upgrade function.
- * Support IP address sniffing, the ID number, IP address and MAC address of unknown units can be found by PC software.

Specification:

Model	TS-0308A
Microphone type	Electret condenser microphone
Microphone directionality	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	68Ω0
Sensitivity	-41±1.5dB(0dB=1V/Pa,at1KHz)
Maximum SPL	120dB
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.3%
Maximum power consumption	2W
Network port	2 cascade networking ports
Power supply	Controller
Color	Graphite grey
Dimension (LxWxH)	113×100×36mm (without microphone rod)
Microphone rod length and color	380mm black
Installation method	Desktop
Weight	0.8kg