

# MAXHUB WT13S

4K Wireless Screen Sharing Dongle


MAXHUB WT13S allowing users to broadcast their audio and 4K video to other devices including MAXHUB UC S15, IFP V6 Series, Commercial display, WB05 etc. With 5-second quick-start features, enjoy a seamless USB type-C plug and play screen sharing experience that doesn't require drivers or other software. Moreover, NFC connect supporting sharing the content from your phone to the Interactive Flat Panel with just one tap.



Exceptional UHD video quality




5s plug and share




Multi-screen sharing




Wi-Fi 6 supported




Share without cables



No need to install software  
on PC(Type-C)



NFC Touch and connect



Supports wireless touchback



| Basic performance            |                                                  |
|------------------------------|--------------------------------------------------|
| Maximum Connection Distance: | 12 M                                             |
| Operating Systems Supported: | Win 10/Win 11/Mac OS 10.12 and above             |
| Maximum Startup Time:        | ≤ 5s                                             |
| Cold Start Time:             | ≤ 12s                                            |
| Maximum Disconnect Time:     | 1 s                                              |
| Transmission Delay:          | ≤ 120ms                                          |
| Maximum Resolution:          | Default: 1920×1080@30 Hz / Up to 3840×2160@30 Hz |
| NFC Connect:                 | Supported                                        |
| Touch Back:                  | Supported                                        |

| Wi-Fi              |                 |
|--------------------|-----------------|
| Version:           | 802.11a/n/ac/ax |
| Working Frequency: | 5 GHz           |
| Working Distance:  | 0~12 m          |

| Interface             |   |
|-----------------------|---|
| USB Type-C:           | 1 |
| USB Type-A (adapter): | 1 |

| Environmental Conditions |           |
|--------------------------|-----------|
| Operation Temperature:   | 0℃~40℃    |
| Operation Humidity:      | 10%~90%RH |
| Storage Temperature:     | -20℃~60℃  |
| Storage Humidity:        | 10%~90%RH |

| Physical Specifications    |                                                                                            |
|----------------------------|--------------------------------------------------------------------------------------------|
| Button:                    | 1                                                                                          |
| Dimension L×H×W:           | 171.3×78.7×19.4 mm (6.74x3.10x0.76 inch)                                                   |
| Dimension (package) L×W×H: | 1pcs: 196×110×28 mm (7.72x4.33x1.1 inch)<br>60pcs: 418×356×340 mm (16.46x14.02x13.39 inch) |
| Net Weight:                | 75g (0.15 lbs)                                                                             |
| Gross Weight:              | 1pcs: 233g (0.51 lbs) / 60pcs: 15.5kg (34.17 lbs)                                          |

| Power               |          |
|---------------------|----------|
| Power Requirements: | 5V@500mA |
| Power Consumption:  | 2.5W     |

| Warranty |  |
|----------|--|
| 2 Year   |  |