

## Use Case: Diabetes Patient Data Analysis

**Objective:** To explore the dataset of diabetes patients, identify trends, and uncover insights such as –

- Demographic distribution of patients.
- Trends in glucose levels across age groups.
- Readmission rates and associated factors.

### Our Schema:

**PatientID:** Unique identifier for each patient.

**Age:** Patient's age group (e.g., "20–30", "30–40").

**Gender:** Male or Female.

**BMI:** Body Mass Index.

**GlucoseLevel:** Fasting glucose level.

**Outcome:** 0 (No diabetes) or 1 (Diabetes diagnosis).

**Readmission:** 1 (Readmitted) or 0 (Not readmitted).

**VisitDate:** Date of hospital visit.

### Dataset:

Download the dataset: *diabetes\_data.csv*, from the below GitHub location:

[https://github.com/ItishaK/codeChallenges/blob/main/diabetes\\_dataset1.csv](https://github.com/ItishaK/codeChallenges/blob/main/diabetes_dataset1.csv)

### Discussion Topics:

- **EDA (Exploratory Data Analysis):** Detailed process of examining Data with an intention to uncover patterns, trends and relationships.
- **Multi-Hop Architecture:** Historical -> Raw\_Table -> Refined\_Table -> Derived/Transformed\_Table

## **Exercise:**

We will implement EDA steps in postgresql to analyze our Healthcare dataset.

**Step 1:** Create table- 'patientDetails\_rw' in postgres as per the schema provided above but we will keep the data types as 'VARCHAR' in order to prevent any loss of data due to data type mismatch.

### **DDL:**

```
CREATE TABLE patientDetails_rw (  
  patientID VARCHAR(10) PRIMARY KEY,  
  age VARCHAR(10),  
  gender VARCHAR(10),  
  bmi VARCHAR(10),  
  glucoseLevel VARCHAR(10),  
  outcome VARCHAR(10),  
  readmission VARCHAR(10),  
  visitDate VARCHAR(10)  
);
```

**Step 2:** Import dataset- 'diabetes\_data.csv' into the table 'patientDetails\_rw'. This table will serve as our raw table which contains the data as it is. We have used this naming convention for maintaining an easy-to-understand code.

### **Script-**

```
COPY patientDetails_rw(patientID, age, gender, bmi, glucoseLevel, outcome, readmission,  
visitDate)  
FROM 'input_path\diabetes_data.csv'  
delimiter ','  
csv header ;
```

Also, maintain a backup of this data (as historical data), let's say: 'patientDetails\_history'.

```
create table patientDetails_history  
as select * from patientDetails_rw;
```

**Step 3:** Cross-check the data import with a simple select statement on the table- 'patientDetails'.

```
select count(*) from patientDetails_rw as TotalRows;
```

```
select count(*) from patientDetails_history as TotalRows;
```

**Step 4:** Perform Basic **Data Quality Checks** to ensure high quality data in our raw tables.

- Check for Overall Row Count.
- Check for NULL value counts for each Column.
- Inspect the NULL values (if any).
- Check for duplicate Primary Key values.
- Check for invalid date formats.
- Check for Outliers like:
  - Out of range BMI values (<10 and >50)
  - Invalid Glucose Level or BMI values
  - Logical Inconsistency in outcome and readmission values
- Check patient counts for distinct age groups and gender.
- Validate distinct values for columns with restricted value range like age group, outcome, readmission etc.

**Step 5: Data Cleaning** – We will clean the data by performing the below checks.

- Cross-check the row-counts and values in the raw table- '*patientDetails\_rw*'.
- Remove or update the records that are not needed (delete only when it is utmost necessary).
- Change date formats into required format (if needed).

**Hints:**

- Add steps for outcome value 0 written as 'o' and '0'.
- Gender values written as 'NA', None, ''.
- Boolean columns having more than 2 values like 'Yes' or 'No'.
- Incorrect date formats or invalid dates.
- Negative value for glucose levels and BMI values.
- Out of range values for BMI.

**Step 6:** In this step we will create a new refined table '*patientDetails\_ref*' with updated data types as per our schema. Maintaining this naming convention plays a significant role in code maintenance.

**Script:**

```
create table patientDetails_ref(  
  patientID VARCHAR(10) PRIMARY KEY,  
  age VARCHAR(10),  
  gender VARCHAR(10),  
  bmi DOUBLE PRECISION,  
  glucoseLevel INTEGER,  
  outcome INTEGER,  
  readmission INTEGER,  
  visitDate DATE  
);
```

Now, using our insertion script, we will cast all values from our raw table before inserting them into our refined table.

**Script:**

```
insert into patientDetails_ref  
select  
  patientID,  
  age,  
  gender,  
  CAST(bmi as DOUBLE PRECISION),  
  CAST(glucoseLevel AS INTEGER),  
  CAST(outcome as INTEGER),  
  CAST(readmission as INTEGER),  
  CAST(visitDate as DATE)  
from patientDetails_rw;
```

**Step 7:** In this step we will add derived columns on top of our refined table. For this, we will create a derived temporary table/view (as per the suitability) - '*patientDetails\_derived\_tbl*' or '*patientDetails\_derived\_vw*'.

- Categorize BMI values into meaningful ranges (like 'Overweight', 'Obese' etc).
- Add a derived column to indicate Patient status using columns 'outcome' and 'readmission'.
- Count of Diabetic vs Non-Diabetic patients by Gender.
- Percentage of Diabetic Patients by Gender.
- Count of Patients (Diabetic/Non-Diabetic) by Gender and BMI Category.