

Data exports and archives

Client handoff edition

A clear, controlled reference for Bridge and PIMASCOR operations, acceptance, and ownership decisions.

Prepared for	Bridge / PIMASCOR
Edition	2026-08-01
Source	DATA-EXPORTS.md
Status	Client-facing; infrastructure and source code excluded

Brand reference: bridge-ph.com/about-us/

Local records exports

Decision

Use the existing private Backblaze B2 S3-compatible storage for completed ZIP archives. Do not place the generated archive on the API server filesystem and do not use a public Bunny CDN URL for it. The API keeps the bucket private and streams a download only after the signed-in Administrator is authorized; the notification email takes the user to the authenticated Accounting Export page, not to a bearer URL.

Backblaze B2 should have bucket-default SSE-B2 (AES-256) enabled before production use. Archive object keys contain only generated IDs, never a client, staff, or shipment name. The production key must be restricted to the configured bucket/prefix and allow only the object operations required by the worker and API.

Archive contents

- `records/* .csv`: UTF-8, comma-separated operational records per module. These include quotations, budgets, releases, expenses, liquidations, billing, collections, allocations, credit memos, audit events, and users without password hashes.
- `attachments/*`: the original uploaded PDF/JPEG/PNG evidence and signed quotations, retained in their original usable formats.
- `README.txt`: archive scope and exclusions.

The archive deliberately excludes password hashes, live sessions, email verification challenges, and storage credentials. It is a portable operational-records copy, not a general-ledger import and not a replacement for a tested disaster-recovery backup.

Controls

- Only an Administrator can request, see, or download an archive.
- The quota is two accepted archive requests per organization per Philippine calendar week. It applies to requests, not download attempts, so a ready archive can be retried during its availability window.
- A single worker processes durable queued requests. It must run as one dedicated replica using `python -m pimascor_api.export_worker`; this is intentionally separate from the API process so a restart does not abandon the work.
- Completion creates an auditable archive, sends the requester an email, and makes it available for exactly one hour. The worker deletes expired objects and records the expiry.
- The API keeps downloads same-origin, authenticated, no-store, and audited. No direct signed URL is mailed or exposed.

Deployment checklist

1. Apply Alembic revision `20260729_0011`.
1. Enable B2 bucket-default SSE-B2 and keep the bucket private.
1. Deploy one `pimascor_api.export_worker` process with the same database, B2, and email secrets as the API, but no inbound public port.
1. Ensure the worker remains up continuously. Its 30-second idle poll performs expiration cleanup; B2 lifecycle policies are only a secondary safety net because their smallest cadence is daily.
1. Have the DPO approve the retention wording, authorized-admin list, and procedure for encrypted removable media before rollout.

Sources

- National Privacy Commission: Data Security (<https://privacy.gov.ph/data-security/>)
- National Privacy Commission: Right to Data Portability (<https://privacy.gov.ph/right-to-data-portability/>)
- Backblaze B2 server-side encryption (<https://www.backblaze.com/docs/cloud-storage-server-side-encryption>)
- OWASP Secure Cloud Architecture Cheat Sheet
(https://cheatsheetseries.owasp.org/cheatsheets/Secure_Cloud_Architecture_Cheat_Sheet.html)