

CS 213 – Software Methodology

Spring 2023

Sesh Venugopal

Apr 5 - Android Programming

ListView/Multiple Activities/Raw
resource/Toolbar/Up Navigation

Example: Rutgers Bus Routes

Project

Make an Android application project called `RU NB Bus Routes` (or whatever).

Choose the `Empty Activity` option when asked to select a template.

(You should have a
`public class MainActivity extends AppCompatActivity`)

Refactor --> Rename `MainActivity` to `Routes`, and `activity_main.xml` to `routes_list.xml`

Part 1:

Showing a List of Route Names

routes_list.xml layout

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    tools:context=".Routes">

    <ListView
        android:id="@+id/routes_list"
        android:layout_width="match_parent"
        android:layout_height="match_parent" />

</LinearLayout>
```



placeholder ListView, the actual list will be populated in the Java code

Routes in `strings.xml` file

```
<resources>
    <string name="app name">RU NB Bus Routes</string>
    <string-array name="routes_array">
        <item>A: College Ave/Busch</item>
        <item>B: Livingston/Busch</item>
        <item>B-HE: Livingston/Busch</item>
        <item>C: Busch Commuter Shuttle</item>
        <item>EE: College Ave/Cook-Douglass</item>
        <item>F: College Ave/Cook-Douglass</item>
        <item>H: College Ave/Busch</item>
        <item>LX: College Ave/Livingston</item>
        <item>REXB: Cook-Douglass/Busch</item>
        <item>REXL: Cook-Douglass/Livingston</item>
    </string-array>
</resources>
```

We will read these names into our `ListView` when the app executes.


See <https://developer.android.com/guide/topics/resources/string-resource.html>

Layout for each `ListView` item

Make a file called `route.xml` in the layout folder, with a top level `TextView` tag, with values for text size, text color (e.g. black), background color (e.g. white), and padding.


`route.xml`

```
<?xml version="1.0" encoding="utf-8"?>
<TextView
    xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:background="#ffffff"
    android:textColor="#000000"
    android:textSize="18sp"
    android:padding="10dp" />
```



`#ffffff` (hex) = White (RGB = 255,255,255)


`#000000` (hex) = Black (RGB = 0,0,0)



Coding the main (launch) activity

When the app is launched, the `onCreate` method in the `Routes` activity will be called. See the Manifest (`app->manifests->AndroidManifest.xml`):

```
...  
<activity android:name=".Routes"  
    android:exported="true">  
    <intent-filter>  
        <action android:name="android.intent.action.MAIN" />  
  
        <category android:name="android.intent.category.LAUNCHER" />  
    </intent-filter>  
</activity>
```



This activity will need to get the list of routes from `strings.xml` and populate the `ListView`

Coding the main (launch) activity

Load the list of routes from `strings.xml` and populate the `ListView`

Routes.java

```
private ListView listView;
private String[] routeNames;

@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.routes_list);

    listView = findViewById(R.id.routes_list);
    routeNames = getResources().getStringArray(R.array.routes_array);
    ArrayAdapter<String> adapter =
        new ArrayAdapter<>(this, R.layout.route, routeNames);
    listView.setAdapter(adapter);
}
```


See <https://developer.android.com/guide/topics/ui/binding> **TRY OUT THE APP!**

Part 2:

Showing Details (Sequence of Stops) for Routes

List Item Selection – Showing Route Stops

When any of the list items (routes) is clicked, we want to show another screen with the details of all the stops on that route:



List Item Selection – Showing Route Stops

This requires us to do the following:

- Get the route details from somewhere (an input file)
- Set up a click listener for the list items
- When a route is clicked, *launch a new detail activity* that has its own layout, and shows the details of the stops on the selected route
- Have the main activity pass to the new activity info on which item/route was clicked (it's *not* passed as a parameter to a method)


Setting up a read-only input file

If a file is read-only, it can be placed in the resource space of the app:

- Set up a folder (directory) called `raw` within the `res` folder
- Place the file (`routes.txt`) in the `raw` folder

See <https://developer.android.com/guide/topics/resources/providing-resources.html>

res/raw/routes.txt



```
College Ave Student Center
The Yard (Scott Hall)
Student Activities Center
Stadium West Lot
Science Buildings (across from ARC)
Busch Student Center
Werblin Recreation Center
College Ave Student Center
*****
Livingston Student Center
Quads
Hill Center
Science Buildings (across from ARC)
Busch Student Center
Livingston Plaza
Livingston Student Center
*****
...
```

Each block of lines up to

is the sequence of stops on a route.

The blocks are in the order of the routes listed in the array resource itemized in `strings.xml`

Reading from read-only input file

The raw resource file can be loaded into the program via `R.raw.routes`

`Routes.java`

```
...
private String[] routeDetails; ← field in Routes class
...

InputStream is = getResources().openRawResource(R.raw.routes);
Scanner sc = new Scanner(new InputStreamReader(is));
routeDetails = new String[routeNames.length];

for (int i = 0; i < routeNames.length; i++) {
    StringBuilder sb = new StringBuilder();
    String line = sc.nextLine();
    while (!line.startsWith("*")) {
        sb.append(line);
        sb.append("\n");
        line = sc.nextLine();
    }
    routeDetails[i] = sb.toString();
}
...
```

Setting up a click listener/event handling code

Routes.java

```
...
listView.setOnItemClickListener(new AdapterView.OnItemClickListener() {

    public void onItemClick(AdapterView<?> parent, View view,
                           int position, long id) {
        showRoute(position);
    }
});
...
```

Or, you can use a lambda since `AdapterView.OnItemClickListener` is a functional interface:

```
...
listView.setOnItemClickListener(
    (p,v,pos,id) -> showRoute(pos));
...
```

Starting route detail activity and passing info to it

Routes.java

```
public static final String ROUTE_NAME = "route_name";
public static final String ROUTE_DETAIL = "route_detail";

private void showRoute(int pos) {
    Bundle bundle = new Bundle();
    bundle.putString(ROUTE_NAME, routeNames[pos]);
    bundle.putString(ROUTE_DETAIL, routeDetails[pos]);
    Intent intent = new Intent(this, ShowRoute.class);
    intent.putExtras(bundle);
    startActivity(intent);
}
```

 Activity to launch for showing route details.

A **Bundle** can be populated with (key -> value) mappings, and can be passed to another activity as info

See <https://developer.android.com/guide/components/activities/parcelables-and-bundles.html>

Implementing activity ShowRoute

File -> New -> Activity -> Empty Activity

Empty Activity

Creates a new empty activity

Activity Name

☒ Generate a Layout File

Layout Name

☐ Launcher Activity

Package name

Source Language

Designing a layout for ShowRoute

route_detail.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    android:orientation="vertical"
    android:layout_width="match_parent"
    android:layout_height="match_parent">

    <TextView
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:id="@+id/route_name"
        android:background="#ff0000"
        android:textColor="#ffffff"
        android:padding="10dp" />

    <TextView
        android:layout_width="match_parent"
        android:layout_height="match_parent"
        android:id="@+id/route_detail"
        android:padding="10dp"
        android:textColor="#ffffff"
        android:background="#000000" />

</LinearLayout>
```

Red bg, →
white text

Need to ID route name and
detail content so they can be
assigned values in the Java code

Black bg, →
white text

Coding activity ShowRoute

```
public class ShowRoute extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.route_detail);

        // get route name and detail from bundle
        Bundle bundle = getIntent().getExtras();
        String routeName = bundle.getString(Routes.ROUTE_NAME);
        String routeDetail = bundle.getString(Routes.ROUTE_DETAIL);

        // get the route name and detail view objects
        TextView routeNameView = findViewById(R.id.route_name);
        TextView routeDetailView = findViewById(R.id.route_detail);

        // set name and detail on the views
        routeNameView.setText(routeName);
        routeDetailView.setText(routeDetail);
    }
}
```


TRY OUT THE APP!

Part 3:


Setting up a Toolbar with Up Navigation

Toolbar + Up Navigation

“Up” navigation (standard for child activities), should be mapped to parent activity in manifest file



Toolbar (used instead of native ActionBar)



Toolbar

Add the following layout code to `routes_list.xml` and `route_detail.xml`

```
<androidx.appcompat.widget.Toolbar  
    android:id="@+id/my_toolbar"  
    android:layout_width="match_parent"  
    android:layout_height="?attr/actionBarSize"  
    android:background="#00ff00"  
    android:elevation="4dp"  
    android:theme="@style/ThemeOverlay.AppCompat.ActionBar"  
    app:popupTheme="@style/ThemeOverlay.AppCompat.Light" />
```

~~android.support.v7.widget.Toolbar~~
(don't use the support.v7 version shown in the documentation, use the appcompat version instead)

`routes_list.xml`

```
<LinearLayout ... >  
  
    <ListView ... />  
  
</LinearLayout>
```

`route_detail.xml`

```
<LinearLayout ... >  
  
    <TextView ... />  
    <TextView ... />  
  
</LinearLayout>
```

<https://developer.android.com/training/appbar/setting-up>


Add Toolbar – Java code

Add the following code to `Routes.java` and `ShowRoute.java`

```
Toolbar myToolbar = (Toolbar) findViewById(R.id.my_toolbar);  
setSupportActionBar(myToolbar);
```

`Routes.java`

```
setContentView(R.layout.route_detail);  
  
listView = findViewById(R.id.routes_list);
```



`ShowRoute.java`

```
setContentView(R.layout.route_detail);  
  
Bundle bundle = getIntent().getExtras();
```

NOTE: The toolbar version to use is `androidx.appcompat.widget.Toolbar`

Enable Up Navigation – Java code

Add the following code to `ShowRoute.java`

```
// Enable the Up button  
getSupportActionBar().setDisplayHomeAsUpEnabled(true);
```

`ShowRoute.java`

```
setSupportActionBar(myToolbar);
```

```
Bundle bundle = getIntent().getExtras();
```



We only add this to `ShowRoute.java` since it is the child activity

<https://developer.android.com/training/appbar/up-action>

Toolbar + Up Navigation – Manifest File

```
<application
  ...
  android:supportRtl="true"
  android:theme="@style/Theme.AppCompat.Light.NoActionBar"
  ...
>
<activity
  android:name=".ShowRoute"
  android:exported="false"
  android:parentActivityName="com.example.runbbusroutes.Routes"/>
...
</application>
```

Replace existing theme with this

Add this so "Up" Nav knows which is the parent activity

<https://developer.android.com/training/appbar/up-action>

<https://developer.android.com/guide/topics/manifest/manifest-intro.html>

DONE!!