

Employee No	Eswaran
Product No	484-0105718-3008
Serial No	17ZY22W12345
Test Type	Continuous Type

Date	02-04-2025
Time	15-59-08
Result	PASS

Description	Limits	Values	Unit	Result
-------------	--------	--------	------	--------

BootCurrentTest_5v	Min : -0.1 A Max : 0.3 A	0.045	A	PASS
(RX_+3.3V)	Min : 3.12 V Max : 3.46 V	3.273	V	PASS
(TX_+15V)	Min : 14.25 V Max : 15.75 V	15.011	V	PASS
(RX_J2.1) MS_5v	Min : 4.75 V Max : 5.25 V	4.978	V	PASS
(RX_J3.2) TX_5v	Min : 4.75 V Max : 5.25 V	4.974	V	PASS
(RX_+2.6V)	Min : 2.47 V Max : 2.75 V	2.603	V	PASS
(D1) - OFF	Min : 3.12 V Max : 3.46 V	3.194	V	PASS
(D2) - OFF	Min : 3.12 V Max : 3.46 V	3.203	V	PASS
(D3) - OFF	Min : 3.12 V Max : 3.46 V	3.198	V	PASS
(D1) - ON	Min : 2.00 V Max : 2.30 V	2.102	V	PASS
SINGLE NOTE	NA	DETECTED	NA	PASS
DOUBLE NOTE	NA	DETECTED	NA	PASS
(D2) - ON	Min : 2.00 V Max : 2.30 V	2.126	V	PASS
(D3) - ON	Min : 2.00 V Max : 2.30 V	2.129	V	PASS
(RX_J1.8) SP-MV LW	Min : 0.00 V Max : 0.50 V	0	V	PASS
(RX_J1.16) RDY HI	Min : 0.00 V Max : 0.50 V	0	V	PASS
(RX_J1.14) TS6-THK HI	Min : 3.12 V Max : 3.46 V	3.283	V	PASS
(RX_J1.12) TS6-BLK HI	Min : 3.12 V Max : 3.46 V	3.284	V	PASS
(RX_J1.10) SP-FST HI	Min : 3.12 V Max : 3.46 V	3.28	V	PASS
(RX_J1.8) SP-MV HI	Min : 3.12 V Max : 3.46 V	3.279	V	PASS
(RX_J1.6) SP-BLK HI	Min : 0.00 V Max : 0.50 V	0	V	PASS
(RX_J1.4) U-DFD HI	Min : 3.12 V Max : 3.46 V	3.285	V	PASS
(RX_J1.2) U-BLK HI	Min : 3.12 V Max : 3.46 V	3.287	V	PASS

(RX_+2.6V)	Min : 2.47 V Max : 2.75 V	2.57	$2.57 - 2.603 = 0.033$
(D1) - OFF	Min : 3.12 V Max : 3.46 V	3.31	diviation $3.31 - 3.19 = 0.12$
(D2) - OFF	Min : 3.12 V Max : 3.46 V	3.31	diviation $3.31 - 3.20 = 0.10$
(D3) - OFF	Min : 3.12 V Max : 3.46 V	3.31	diviation $3.31 - 3.19 = 0.12$
(D1) - ON	Min : 1.87 V Max : 1.96 V	1.93	$2.102 - 1.93 = 0.172$

(D2) - ON	Min : 1.87 V Max : 1.96 V	1.93	$2.126 - 1.93 = 0.196$
(D3) - ON	Min : 1.87 V Max : 1.96 V	1.92	$2.129 - 1.96 = 0.199$

$3.31 - 1.93 = 1.38$
$3.19 - 2.12 = 1.07$

cro
mc