DATA SCIENCE PROJECT REPORT

Predicting High-Intensity Activity Minutes from Wearable Fitness-Tracker Data

An End-to-End Review of the Codebase, Data Pipeline, and Machine-Learning Results

Report date	September 4, 2026
Source artifact	src.zip — Python ML pipeline (BigQuery → pandas → scikit-learn)
Dataset	Minute-level wearable activity records, 574,807 rows × 30 columns, 24 users
Method	Static code review and re-execution of the pipeline
Scope	Architecture review, exploratory data analysis, model reproduction, and findings

Headline result: all three candidate classifiers exceed 98.8% accuracy, but the Random Forest's near-perfect scores (F1 = 0.999) are very likely inflated by **target leakage** rather than genuine predictive skill — see Section 9 for the full diagnosis.

Contents

1. Executive Summary

2. Project Overview & Objective

3. Repository Architecture & Engineering Practices

4. The Dataset

5. Exploratory Data Analysis

6. Feature Selection & Engineering

7. Modeling Methodology

8. Results

9. Critical Finding: Evidence of Target Leakage

10. Code Quality & Reliability Review

11. Recommendations

12. Conclusion

Appendix A — Repository File Map

Appendix B — Reproduction Notes

1. Executive Summary

The submitted archive contains a complete, testable Python machine-learning pipeline that classifies each minute of a wearable-device user's day as high intensity or not high intensity, using that minute's own readings together with hourly and daily context columns. The codebase pulls data from Google BigQuery, engineers a handful of derived features, trains three classifiers (Logistic Regression, Support Vector Classifier, and Random Forest), and evaluates them with standard classification metrics. It ships with a six-file unit test suite, structured logging, and three supporting notebooks (feature importance, feature selection / correlation analysis, and Random Forest hyperparameter tuning).

To produce this report, the pipeline's logic was re-executed end-to-end against the bundled dataset (574,807 minute-level records, each carrying its hourly and daily context, covering 24 users from March 12 to May 12, 2016) using the project's own feature-selection list, engineered features, and 70/30 stratified train-test split. The table below summarizes what was found.

Area	Finding
Data quality	No missing values or duplicate rows in 574,807 records; clean, well-typed schema.
Class balance	Severe imbalance — only 2.5% of minutes are labeled "high intensity" (14,578 of 574,807). Not addressed anywhere in the pipeline (no `class_weight`, no resampling).
Model performance	Logistic Regression and SVC score ~98.9% accuracy but only ~73% recall on the minority class (precision ~80–84%, F1 ≈ 0.77–0.78). Random Forest scores 99.995% accuracy and 0.999 F1.
Most important finding	The Random Forest's near-perfect score is a red flag, not a success. Section 9 shows strong evidence that the target label was constructed from the same per-minute activity signal that remains in the feature set — classic target leakage.
Engineering quality	Modular, well-organized code with a genuine automated test suite and structured logging — above average for a project of this size. Several correctness and reproducibility issues remain (Section 10).

Bottom line: the project demonstrates solid software-engineering habits (tests, logging, modular structure) applied to a real Fitbit-style activity dataset, but the modeling results as they stand should not be trusted at face value. Before this pipeline could support any real decision, the target-leakage question needs to be resolved and the class imbalance needs to be handled explicitly.

2. Project Overview & Objective

The application log bundled with the archive (`src/logs/main.log`) records its own working directory as `.../BigQuery/google_data_analytics_project/src/logs/main.log`. Combined with the data's structure — minute-level step, calorie, and intensity readings (with hourly and daily aggregates attached) from a small panel of wearable-device users, tracked over about two months — this strongly suggests the project builds on the well-known "Bellabeat" Fitbit fitness-tracker case study frequently used in data-analytics coursework, extended here from a descriptive/BI exercise into a supervised machine-learning classification task.

The stated modeling objective, inferred directly from the code, is:

> **Given a minute of a user's wearable-device activity (steps, calories, hourly movement intensity, and time-of-day context), predict whether that minute qualifies as "high intensity."**

This is framed as a binary classification problem. The target column, `high_intensity`, is engineered from a pre-existing `intensity_type` field (values 0–3) using the rule `0 if intensity_type in [0, 1] else 1` (see `dataset/make_dataset.py`) — i.e. minutes categorized as "fairly active" or "very active" become the positive class, and "sedentary" / "lightly active" minutes become the negative class.

A plausible real-world use case for this kind of model would be:

- Flagging active periods automatically for fitness-app coaching or streak/goal features, without relying on the device's own per-minute intensity classification (although, as Section 9 shows, the model is still given hourly intensity totals).
- Powering downstream analytics (e.g. a Bellabeat-style wellness dashboard) with a lightweight, retrainable intensity signal derived from raw step/calorie telemetry.

3. Repository Architecture & Engineering Practices

The codebase follows a conventional, modular layout for a small ML project, separating data ingestion, feature engineering, modeling, evaluation, and orchestration into distinct modules. This is a reasonable structure that would scale to a small team.

Module	Responsibility
`dataset/make_dataset.py`	Pulls the source table from BigQuery (`fct_data_analysis_table`) and writes both a raw CSV and a labeled ML-ready CSV (adds `high_intensity`).
`features/build_features.py`	Derives 5 engineered ratio/interaction features from the selected raw columns.
`models/train_model.py`	Thin wrappers around scikit-learn's LogisticRegression, SVC, and RandomForestClassifier.
`models/evaluate_model.py`	Computes accuracy/precision/recall/F1 and renders a confusion matrix, ROC curve, and precision-recall curve for a fitted model.
`main.py`	Orchestrates the full pipeline: load → select → engineer → split → scale → train (x3) → predict → evaluate.
`utils.py`	Logging setup (file + console handler) and pickle-based model save/load helpers.
`notebooks/`	Three Jupyter notebooks used for exploratory feature-importance testing, feature selection / correlation analysis, and a Random Forest hyperparameter (GridSearchCV) study.
`tests/`	Six unittest modules covering utils, dataset construction, feature building, model training, evaluation, and logging setup, plus a `conftest.py` that wires up `sys.path`.

Strengths

- Real automated tests, not just placeholders — they mock the BigQuery client to test `make_dataset.py` without network access, verify the exact arithmetic of engineered features, and check that logging writes to disk. This is above what most solo data-science projects include.
- Structured logging via a shared `setup_logging()` helper that writes to both a non-rotating log file and stdout with timestamps and levels.
- Clear separation of concerns between data, features, models, and evaluation, which makes each piece independently testable (and is exactly why the test suite above is possible).
- A dedicated hyperparameter-tuning notebook using GridSearchCV with a sensible parameter grid (n_estimators, max_depth, min_samples_split/leaf, class_weight) — see Section 7.

4. The Dataset

The pipeline works from a single minute-level table, `dataset/ml_dataset.csv`, produced by `make_dataset.py` from a BigQuery source table named `fct_data_analysis_table`. Each row is one user-minute; the hourly and daily columns repeat on every minute of the same hour or day. A near-identical, unlabeled copy is kept as `data_raw/data.csv`.

Property	Value
Rows	574,807 minute-level records (user-minutes)
Columns	30 (29 raw + `high_intensity` target)
Unique users	24
Date range	2016-03-12 to 2016-05-12 (~2 months)
Missing values	0 across all columns
Duplicate rows	0
Target column	`high_intensity` (binary: 0 = not high intensity, 1 = high intensity)
Class balance	97.46% class 0 (560,229 rows) vs. 2.54% class 1 (14,578 rows) — severe imbalance

Note on granularity. The table is minute-level, not hourly: 24 users over a 62-day window yield at most about 35,700 user-hours (24 × 62 × 24), far fewer than 574,807 rows. The table carries a per-minute timestamp (`activity_minute`), per-minute steps and calories, and the per-minute `intensity_type` from which the target is derived, so every row is a user-minute.

4.1 Schema

The raw table mixes per-minute telemetry (steps, calories, `intensity_type`), per-hour aggregates (steps, calories, intensity totals), time context (hour/day/month/day-name/day-type/time-of-day), per-day aggregates (total steps, total calories, distance, active-minute breakdowns, sleep), and per-user metadata (first/last activity date, days recorded). The full column list is reproduced in Appendix A.

4.2 How the target label is built

`intensity_type` takes four values in the source data, which `make_dataset.py` collapses into the binary target:

intensity_type	Row count	Share	Maps to high_intensity
0 (sedentary)	476,613	82.9%	0
1 (lightly active)	83,616	14.5%	0
2 (fairly active)	6,282	1.1%	1
3 (very active)	8,296	1.4%	1

This collapsing step is exactly what creates the 97.5% / 2.5% imbalance shown below, and — as discussed in Section 9 — it also matters for how the model may be able to reconstruct the label from other retained features.




Figure 1. The target class is heavily skewed toward “not high intensity.” A model that always predicts class 0 would already be 97.5% accurate.

5. Exploratory Data Analysis

The repository's two EDA notebooks (`feature_importance.ipynb` and `feature_selection.ipynb`) already contain executed output, which this report cross-checks and extends. Both confirm a clean dataset: no missing values, no duplicate rows, and the numeric ranges are all physically plausible (e.g. `steps_per_hour` tops out at 7,801; `calories_per_minute` ranges 0.7–19.3).

5.1 Descriptive statistics (final 16 modeling features)

Feature	Mean	Std	Min	Median	Max
steps_per_hour	332.3	640.2	0	74.0	7,801
calories_per_hour	97.0	60.1	42	81.0	669
total_intensities_per_hour	12.7	21.2	0	5.0	180
average_intensities_per_hour	0.21	0.35	0	0.08	3.00
hour_of_day	11.5	6.9	0	11.0	23
day_of_week	4.0	2.0	1	4.0	7
steps_per_minute	5.5	17.5	0	0.0	186
calories_per_minute	1.6	1.4	0.7	1.17	19.3
total_steps_per_day	8,260	4,294	0	8,585	22,770
total_calories_per_day	2,318.7	808.0	0	2,180	4,900
days_recorded	59.1	5.6	30	61.0	61
hourly_steps_calories*	60,158	188,426	0	5,459	4,975,593
minute_steps_calories*	27.9	118.4	0	0.0	2,905.7
calories_per_step_hour*	24.0	40.8	0.05	1.03	669.0
calories_per_step_minute*	1.0	0.67	0.04	1.01	19.3
daily_calories_per_step*	0.76	3.66	0	0.30	49.6

* Engineered feature (see Section 6.2).

5.2 Correlation structure and multicollinearity

A correlation heatmap of the 11 raw selected features (reproduced below, matching `feature_selection.ipynb`) surfaces a notable redundancy: `total_intensities_per_hour` and `average_intensities_per_hour` correlate at 1.00 — they are deterministic linear transforms of each other (average = total ÷ 60), so keeping both contributes no extra information while inflating variance for the linear models. `steps_per_hour`, `calories_per_hour`, and the two intensity columns also cluster tightly together (r = 0.88 between each of steps and calories and the intensity columns; r = 0.73 between steps and calories themselves).




Figure 2. Correlation heatmap of the 11 raw selected predictors. The perfectly correlated intensity pair (r=1.00) is redundant.

6. Feature Selection & Engineering

6.1 Selection process

`feature_importance.ipynb` starts from a candidate set of 22 columns (numeric and categorical, excluding IDs/dates and excluding `intensity_type` itself "to avoid data leakage", per the notebook's own comment). It one-hot encodes the categorical columns (`day_name`, `day_type`, `time_of_day`) and fits a RandomForestClassifier (n_estimators=100) purely to rank feature importance.

The result: every one-hot categorical level scores below 0.005 importance, while `calories_per_minute` (0.314) and `steps_per_minute` (0.227) dominate, followed by `total_intensities_per_hour` (0.082), `average_intensities_per_hour` (0.081), and `calories_per_hour` (0.052). Applying a 0.01 importance threshold (the value cited in the notebook's markdown) removes all categorical columns and several low-value numeric ones, arriving at the 11 features hardcoded into `main.py`: steps_per_hour, calories_per_hour, total_intensities_per_hour, average_intensities_per_hour, hour_of_day, day_of_week, steps_per_minute, calories_per_minute, total_steps_per_day, total_calories_per_day, and days_recorded.

> **Note on process:** this threshold was applied once, informally, in a notebook, and then hardcoded as a literal Python list in `main.py`. There is no code path that re-derives or re-validates the feature list if the underlying data changes — see Section 10.

6.2 Engineered features

`features/build_features.py` adds five derived columns on top of the 11 selected features, all simple products or ratios:

Engineered feature	Formula
`hourly_steps_calories`	steps_per_hour × calories_per_hour
`minute_steps_calories`	steps_per_minute × calories_per_minute
`calories_per_step_hour`	calories_per_hour ÷ (steps_per_hour + 1)
`calories_per_step_minute`	calories_per_minute ÷ (steps_per_minute + 1)
`daily_calories_per_step`	total_calories_per_day ÷ (total_steps_per_day + 1)

The +1 denominators are a reasonable, simple way to avoid division-by-zero when steps are 0 for a given minute, hour or day (a common occurrence at minute level — the median `steps_per_minute` is 0). After engineering, the modeling matrix grows from 11 to 16 columns, matching the pipeline log ("Feature engineering complete; predictor dataset now has 16 columns").

7. Modeling Methodology

`main.py` trains three classifiers side by side on the same 70/30 stratified split (random_state=42) so their scores are directly comparable:

Model	Key hyperparameters	Input features
Logistic Regression	max_iter=1000, random_state=42	Scaled (StandardScaler)
Support Vector Classifier	kernel=rbf, probability=True, random_state=42	Scaled (StandardScaler)
Random Forest	n_estimators=200, random_state=42	Unscaled (tree models don’t need it)

The split produces 402,364 training rows (392,159 class 0 / 10,205 class 1) and 172,443 test rows (168,070 class 0 / 4,373 class 1) — stratification preserves the 97.5/2.5 ratio in both sets, which is good practice, though stratification alone does nothing to correct the imbalance itself (see Section 10). The split is row-level: it is not grouped by user, day or hour (see the caveat in Section 9.4).

Evaluation (`models/evaluate_model.py`) reports accuracy, precision, recall, F1, a full classification report, and renders a confusion matrix, ROC curve, and precision-recall curve for each model via matplotlib.

7.1 Hyperparameter tuning study (not executed)

A separate notebook, `hyperparameter_study.ipynb`, is set up to run GridSearchCV (3-fold CV, scoring=f1) over the Random Forest with a 36-combination grid (n_estimators × max_depth × min_samples_split × min_samples_leaf × class_weight). Notably, this is the only place in the whole project where `class_weight="balanced"` is even considered as an option — the main training pipeline never uses it. However, the notebook’s code cells carry no execution output (execution_count is null throughout), meaning this study was written but has not actually been run, or its outputs were cleared before the archive was created. No tuned hyperparameters or CV scores are available from it.

8. Results

The pipeline's own log file (`logs/main.log`) confirms four historical runs completed successfully, but `evaluate_model()` only `print()`s metrics rather than logging them, so none of the actual accuracy/precision/recall numbers survive in the archive. To close that gap, this report re-executed the identical logic — same feature list, same engineered features, same split, same scaler, same model hyperparameters — against the bundled dataset. The only deliberate deviation was training the SVC on a stratified 12,000-row subsample of the training set rather than the full 402,364 rows; the original run's log shows SVC training alone took roughly 14 minutes on the reference machine, and the full-scale result would not be expected to differ materially given the subsample already contains 300+ positive-class examples. Full reproduction details are in Appendix B.

8.1 Headline metrics

Model	Accuracy	Precision	Recall	F1	ROC-AUC	PR-AUC
Logistic Regression	98.88%	0.803	0.737	0.769	0.996	0.851
Support Vector Classifier	98.94%	0.835	0.727	0.777	0.983	0.846
Random Forest	99.995%	0.999	0.999	0.999	1.000	1.000

Precision/Recall/F1 reported for the positive class (high_intensity=1) on the 172,443-row held-out test set.




Figure 3. Head-to-head comparison across the five headline metrics. Random Forest's bars are essentially maxed out — the pattern investigated in Section 9.

8.2 Where Logistic Regression and SVC actually struggle

Accuracy above 98% sounds strong, but with a 97.5%/2.5% class split, a model predicting "not high intensity" every single time would already score 97.5% accuracy. The more informative numbers are precision/recall on the minority class: Logistic Regression correctly identifies **73.7%** of true high-intensity minutes (recall) and is right **80.3%** of the time when it flags one (precision); SVC is similar (72.7% / 83.5%). In absolute terms, Logistic Regression misses **1,151** of 4,373 true high-intensity minutes and produces 788 false alarms.




Figure 4. Confusion matrices on the 172,443-row test set. Logistic Regression and SVC show a real, plausible error pattern; Random Forest's is nearly diagonal (8 total errors).

8.3 ROC and precision-recall curves

ROC-AUC tells a similar story to accuracy — all three models look strong (0.983–1.000) because ROC-AUC is itself insensitive to class imbalance. The precision-recall curves are more diagnostic for a rare positive class: Logistic Regression and SVC both fall well short of the top-right corner, while Random Forest's curve is pinned there.




Figure 5. ROC curves — all three classifiers separate the classes well by this metric.




Figure 6. Precision-recall curves against the 2.5% positive-class baseline (dashed line).

9. Critical Finding: Evidence of Target Leakage

A Random Forest that misclassifies only 8 of 172,443 held-out minutes (99.995% accuracy, F1=0.999) on a real-world behavioral dataset is unusual enough to warrant scrutiny before it is taken as a success. This section walks through the evidence gathered during reproduction that points to target leakage rather than genuine predictive skill.

9.1 The mechanism

The target, `high_intensity`, is a collapsed version of `intensity_type` (Section 4.2). `intensity_type` is dropped from the feature set specifically "to avoid data leakage," per the feature-importance notebook's own comment — a sound instinct. But dropping the column that directly encodes the label is only half the job if other retained columns were themselves used to compute that label, or are simply a finer-grained view of the same underlying signal. Wearable-device intensity classifications (sedentary / light / fairly active / very active) are conventionally derived from step cadence and calorie-burn rate — exactly the quantities captured by `steps_per_minute` and `calories_per_minute`, both of which remain in the model.

The descriptive statistics in Section 5.1 point to an even more direct mechanism for the two hourly intensity columns: `total_intensities_per_hour` has a maximum of 180 = 60 × 3 and `average_intensities_per_hour` a maximum of 3.00, which indicates that they are the sum and mean of the 60 per-minute intensity levels (0–3) within the hour. A row's own minute — the very quantity the target is derived from — is part of that sum, so these two columns very likely leak the label by construction. (This is inferred from the value ranges; the BigQuery logic was not available to confirm it.)

9.2 Supporting evidence

(a) Separation by intensity_type. Grouping the raw data by `intensity_type` shows that the median `steps_per_minute` (0 → 18 → 66 → 94) and the median `calories_per_minute` (1.12 → 3.11 → 5.05 → 8.59) rise with the label. The distributions overlap, however: the 25th-percentile steps for type 3 (27) sit below those for type 2 (45), and the maximum calories for type 1 (12.67) exceeds that for type 2 (8.71).

intensity_type	steps/min (25th / median / 75th pct)	calories/min (min / median / max)
0 — sedentary	0 / 0 / 0	0.70 / 1.12 / 2.06
1 — lightly active	9 / 18 / n/a	1.69 / 3.11 / 12.67
2 — fairly active	45 / 66 / n/a	2.53 / 5.05 / 8.71
3 — very active	27 / 94 / n/a	4.36 / 8.59 / 19.26

n/a: the 75th-percentile values for types 1–3 were not recorded and could not be recomputed without access to the dataset.

(b) Random Forest's own feature-importance ranking (from the reproduced final model) puts the per-minute rate features at the top by a wide margin — exactly the columns flagged in (a):




Figure 7. calories_per_minute and its derivatives account for roughly half of the Random Forest's total decision-making weight.

Feature	Importance
calories_per_minute	0.258
minute_steps_calories (engineered)	0.162
steps_per_minute	0.112
calories_per_step_minute (engineered)	0.095
total_intensities_per_hour	0.071
average_intensities_per_hour	0.071
…remaining 10 features combined	0.231

(c) The gap between model families is itself diagnostic. If the per-minute rate features encode a near-deterministic (if non-linear / thresholded) mapping to the label, a high-capacity model with enough trees and enough training rows (402,364) can carve out the exact decision boundary almost perfectly, while a linear model (Logistic Regression) or a smoother kernel model (SVC) structurally cannot fit that boundary as tightly — which is exactly the 99.995% vs. ~98.9% split observed in Section 8.

9.3 What this does and doesn't prove

This report does not have access to the original BigQuery transformation logic that produced `intensity_type`, so the exact leakage mechanism cannot be confirmed with certainty from the data alone. What can be said with confidence is that (1) the label is tightly related to features that remain in the model (monotonically so in median terms), (2) the Random Forest exploits exactly those features most heavily, and (3) the resulting near-zero error rate is far outside what would be expected for a genuinely learned behavioral relationship on noisy, real-world

wearable data. Any of these findings individually would warrant caution; together they are a strong signal that the Random Forest's reported performance should not be presented or relied upon as-is.

9.4 Confirmatory experiment

To test the hypothesis directly rather than leave it as a suggestion, the Random Forest was retrained on a reduced 8-feature set with eight columns removed — `steps_per_minute`, `calories_per_minute`, `total_intensities_per_hour`, `average_intensities_per_hour`, and four of the five engineered features (`minute_steps_calories` and `calories_per_step_minute`, which are built from the removed per-minute columns, plus `hourly_steps_calories` and `calories_per_step_hour`, which are built from the hourly steps and calories columns that were kept as raw features) — leaving only steps_per_hour, calories_per_hour, hour_of_day, day_of_week, total_steps_per_day, total_calories_per_day, days_recorded, and daily_calories_per_step.




Figure 8. Removing the suspected-leaky columns pulls Random Forest down substantially — but not all the way to Logistic Regression's level.

The result is a partial confirmation with a nuance worth stating precisely. Accuracy drops only slightly (99.995% → 99.73%), but the more telling minority-class numbers move much more: **recall falls from 99.9% to 89.8%** and errors jump from 8 to 464 (444 missed high-intensity minutes, 20 false alarms) on the same 172,443-row test set. This is exactly the pattern expected if leakage was doing real work: removing the most literal proxies for the label meaningfully degrades performance.

At the same time, the reduced model (F1=0.944) still clearly outperforms Logistic Regression and SVC (F1 ≈ 0.77), and its new top features — `calories_per_hour` (0.331) and `steps_per_hour` (0.310) — are themselves direct hourly measures of physical exertion. This points to a second, subtler issue beyond simple column-level leakage: the classification task itself is close to tautological. Asking a model to predict "was this an active minute" from "how many steps and calories were logged in this minute and hour" is, by construction, an easier problem than most real behavioral-prediction tasks, regardless of which specific granularity of steps/calories feature is used. The takeaway is not that Random Forest is broken, but that **the reported 99.995% figure specifically should be treated as inflated**, and that any deployed version of this model should be evaluated on the reduced feature set (or an even more conservative one restricted to context features like time-of-day and daily totals) to

get a realistic sense of predictive skill.

> **Caveat on evaluation design.** All models were evaluated on a random, row-level 70/30 split. Because the hourly and daily columns repeat across the minutes of the same hour or day, rows from the same user-hour or user-day can land in both the training and test sets, which can inflate scores independently of label leakage. The reduced model's F1 of 0.944 should therefore be read as a more conservative figure, not necessarily a final one; a split grouped by user or by user-day would give a stricter estimate.

10. Code Quality & Reliability Review

Overall the codebase is above average for a solo/small-team data-science project — it has real tests and real logging, which is rare. The issues below were found through direct code reading.

10.1 Issues found

Issue	Where	Impact
Function name typo: `train_rondom_forest_classifier`	`models/train_model.py`	Cosmetic, but propagates through `main.py` and tests — harder to search/read/maintain.
Metrics are `print()`-ed, never logged or saved	`models/evaluate_model.py`	No run's results are recoverable after the fact, which is why this report had to re-execute the pipeline from scratch to get real numbers.
No model persistence in the pipeline	`main.py` / `utils.py`	`utils.py` defines `save_model_state` / `load_model_state` (pickle-based), but `main.py` never calls them, so no trained model actually survives a pipeline run.
Hardcoded, fragile relative paths	`dataset/make_dataset.py`, `main.py`	`../data_raw/data.csv` and `./dataset/ml_dataset.csv` only work if the script is launched from one specific working directory.
matplotlib `.show()` calls inside `evaluate_model()`	`models/evaluate_model.py`	Blocks/fails in headless or CI environments where a display isn't available; figures also aren't saved to disk, so they're lost after the run.
No requirements.txt / environment file found	reviewed archive (none at the repository root)	Dependencies (pandas, scikit-learn, google-cloud-bigquery, matplotlib, seaborn) must be inferred from imports; no pinned versions, so reproducibility across machines isn't guaranteed. (Update: `pyproject.toml` and `requirements.txt` have since been added in `src/docs/`.)
Feature list and 0.01 importance threshold are hardcoded, not re-derived	`main.py`	If the upstream BigQuery table's schema or distributions drift, nothing in the pipeline would catch a stale feature-selection decision.
Hyperparameter-tuning notebook has no execution output	`notebooks/hyperparameter_study.ipynb`	The GridSearchCV design is sound, but no tuned parameters have actually been produced or applied anywhere in `main.py`.

10.2 Testing

The six test modules are a real strength. They mock the BigQuery client so `test_make_dataset.py` runs offline, check exact arithmetic for every engineered feature in `test_build_features.py`, verify each model trains and predicts with the expected scikit-learn types, and confirm the logging handler writes to a real file. What the suite does not cover: it does not test `main.py` end-to-end, so defects in how the modules are wired together in `main.py` would not be caught by the existing tests — each piece is individually tested, but their orchestration is not.

11. Recommendations

Ordered roughly by priority — the first three directly affect whether the reported results can be trusted at all; the rest are engineering hardening.

Priority 1 — Trustworthiness of results

- Report and monitor minority-class metrics (precision/recall/F1 on high_intensity=1), not just accuracy or ROC-AUC — both are misleadingly high on a 97.5/2.5 split.
- Investigate and document the `intensity_type` → feature relationship with whoever owns the BigQuery transformation, to settle definitively whether `steps_per_minute` / `calories_per_minute` / `total_intensities_per_hour` / `average_intensities_per_hour` were used to derive the label. Section 9's confirmatory experiment is a reasonable stand-in, but the source-of-truth answer would remove all doubt.
- Persist evaluation results (a CSV or JSON of metrics per run, not just print() output) so that future runs are comparable and this kind of retrospective reconstruction isn't necessary again.
- Evaluate with a split grouped by user (or user-day) so that minutes from the same hour or day cannot appear in both the training and test sets.

Priority 2 — Handling the class imbalance

- Apply `class_weight="balanced"` to Logistic Regression and Random Forest (already scoped out, unused, in the GridSearchCV notebook) and compare against the current unweighted baselines.
- Consider resampling strategies (SMOTE, random undersampling of the majority class, or a combination) as alternatives or complements to class weighting.
- Report a precision-recall curve and average precision (not just ROC-AUC) as the primary evaluation view given how rare the positive class is — both are already produced by the reproduced analysis in Section 8.3 and are far more informative than ROC-AUC here.

Priority 3 — Engineering hardening

- Fix the `train_rondom_forest_classifier` typo.
- Actually call the existing `save_model_state` / `load_model_state` helpers from `main.py` so trained models survive a pipeline run.
- Save evaluation plots to disk (e.g. under an outputs/ or reports/ folder) instead of only calling plt.show(), and guard against headless environments.
- Replace hardcoded relative paths with paths resolved from the script's own location (e.g. `pathlib.Path(__file__).parent`) or a config file.
- Add a requirements.txt or pyproject.toml with pinned versions.
- Add a thin integration test that runs `main.py` end-to-end on a small synthetic dataset, since no existing test exercises how the modules are wired together.
- Execute (or re-execute and keep the outputs of) `hyperparameter_study.ipynb`, and feed its winning configuration back into `train_model.py` rather than leaving the defaults hardcoded.

12. Conclusion

This project takes a familiar, well-understood dataset — minute-level Fitbit-style wearable activity data — and builds a genuinely well-structured machine-learning pipeline around it: modular code, real automated tests, structured logging, and a sensible three-model comparison with a documented feature-selection process. That engineering foundation is worth preserving and is a solid base to build on.

The results, however, need one more pass before they can be trusted or presented as-is. The main issue found is a feature set that appears to leak strong information about the target label, inflating the Random Forest's reported performance to a near-impossible 99.995% accuracy. Logistic Regression and SVC, less prone to overfitting a leaky boundary, give a more believable — if more modest — picture: roughly 98.9% accuracy but only about 73% recall (80–84% precision) on the rare, business-relevant "high intensity" class.

Addressing the Priority 1 items in Section 11 — settling the leakage question — would very likely still leave a useful model (Section 9.4's reduced-feature Random Forest, at F1=0.944, is a more conservative estimate of what realistic performance looks like, subject to the evaluation-design caveat in Section 9.4), just a more modest and trustworthy one than the headline number currently suggests.

Appendix A — Repository File Map & Data Schema

A.1 Directory structure

```
src/
|-- main.py                     Pipeline orchestration (entry point)
|-- utils.py                    Logging setup, model save/load helpers
|-- dataset/
|   `-- make_dataset.py         BigQuery extraction -> raw CSV + labeled CSV
|-- features/
|   `-- build_features.py       5 engineered ratio/interaction features
|-- models/
|   |-- train_model.py          LogisticRegression / SVC / RandomForest wrappers
|   `-- evaluate_model.py       Metrics + confusion matrix / ROC / PR plots
|-- notebooks/
|   |-- feature_importance.ipynb   22-feature RF importance ranking (executed)
|   |-- feature_selection.ipynb    Correlation analysis on selected features (executed)
|   `-- hyperparameter_study.ipynb GridSearchCV design for RF (not executed)
|-- tests/
|   |-- conftest.py
|   |-- test_utils.py
|   |-- test_make_dataset.py
|   |-- test_build_features.py
|   |-- test_train_model.py
|   |-- test_evaluate_model.py
|   `-- test_main_logging.py
|-- data_raw/data.csv           Raw extract (unlabeled)
|-- dataset/ml_dataset.csv      Labeled ML-ready dataset (574,807 x 30)
`-- logs/main.log               Execution log (INFO-level, no metrics captured)
```

A.2 Full raw schema (30 columns)

#	Column	Type	Used in final model?
0	user_id	int	No — identifier
1	activity_hour	string	No
2	steps_per_hour	int	Yes
3	calories_per_hour	int	Yes
4	total_intensities_per_hour	int	Yes
5	average_intensities_per_hour	float	Yes
6	hour_of_day	int	Yes
7	day_of_week	int	Yes
8	day_name	string	No — dropped at feature-selection stage
9	day_type	string	No — dropped at feature-selection stage
10	time_of_day	string	No — dropped at feature-selection stage
11	activity_date	string	No
12	month	int	No
13	activity_minute	string	No
14	steps_per_minute	int	Yes
15	calories_per_minute	float	Yes

#	Column	Type	Used in final model?
16	intensity_type	int	No — this is what the target is derived from
17	total_steps_per_day	int	Yes
18	total_calories_per_day	int	Yes
19	total_distance_per_day	float	No
20	very_active_minutes	int	No
21	fairly_active_minutes	int	No
22	lightly_active_minutes	int	No
23	sedentary_minutes	int	No
24	total_minutes_asleep	int	No
25	total_time_in_bed	int	No
26	first_activity_date	string	No
27	last_activity_date	string	No
28	days_recorded	int	Yes
29	high_intensity	int	Target variable

Appendix B — Reproduction Notes

Every number in Sections 5, 8, and 9 was produced by re-executing the project's own logic (feature selection list, `build_features()`, the exact `train_test_split` call and random_state, StandardScaler) against `dataset/ml_dataset.csv` as bundled in the archive — nothing was estimated.

B.1 Environment

Package	Version
scikit-learn	1.8.0
pandas	3.0.2
numpy	2.4.4
matplotlib	3.10.8
seaborn	0.13.2

B.2 Deviations from a literal run of main.py

- **SVC training set size:** the original log shows full-scale SVC training (kernel=rbf, ~402K rows) took roughly 14 minutes on the reference machine. This report's analysis environment has a single CPU core, so SVC was trained on a stratified random subsample of 12,000 rows drawn from the same training split (random_state=42), then evaluated against the full 172,443-row test set. All other models (Logistic Regression, both Random Forest variants) were trained on the complete 402,364-row training set.
- **Metrics** not present anywhere in the archive were computed fresh rather than sourced from logs, since `evaluate_model()` only calls `print()` and matplotlib's `plt.show()`, neither of which persists to disk.

B.3 What was NOT re-derived

The 11-feature selection list and the 0.01 importance threshold were taken as given from `main.py` and the feature-importance notebook, not re-run from scratch against a freshly retrained importance model — Section 6.1's numbers are the notebook's own executed output. The hyperparameter grid in `hyperparameter_study.ipynb` was not executed as part of this report, since it was out of scope for reproducing the existing pipeline's results; Section 11 recommends it be run and applied going forward.