CCIT Report #679 December 2007

Discrete-Input Two-Dimensional Gaussian Channels with Memory: Estimation and Information Rates via Graphical Models and Statistical Mechanics

Ori Shental, *Member, IEEE,* Noam Shental,

Shlomo Shamai (Shitz), *Fellow, IEEE,*

Ido Kanter, Anthony J. Weiss, *Fellow, IEEE,* and Yair Weiss

Abstract

Manuscript received September 18, 2006; revised September 18, 2007. The material in this paper was presented in part at the IEEE Information Theory Workshop (ITW), San-Antonio, Texas, USA, October 2004, and in the IEEE International Symposium on Information Theory (ISIT), Adelaide, Australia, September 2005.

O. Shental was with the Department of Electrical Engineering-Systems, Tel Aviv University, Tel Aviv 69978, Israel. He is now with the Center for Magnetic Recording Research (CMRR), University of California - San Diego (UCSD), 9500 Gilman Drive, La Jolla, CA 92093, USA (e-mail: oshental@ucsd.edu).

N. Shental is with the Department of Physics of Complex Systems, Weizmann Institute of Science, Rehovot 76100, Israel (e-mail: fenoam@wisemail.weizmann.ac.il).

S. Shamai (Shitz) is with the Department of Electrical Engineering, Technion-Israel Institute of Technology, Haifa 32000, Israel (e-mail: sshlomo@ee.technion.ac.il).

I. Kanter is with the Minerva Center and Department of Physics, Bar-Ilan University, Ramat-Gan 52900, Israel (e-mail: kanter@mail.biu.ac.il).

A. J. Weiss is with the Department of Electrical Engineering-Systems, Tel Aviv University, Tel Aviv 69978, Israel (e-mail: ajw@eng.tau.ac.il).

Y. Weiss is with the School of Computer Science and Engineering, Center for Neural Computation, Hebrew University of Jerusalem, Jerusalem 91904, Israel (e-mail: yweiss@cs.huji.ac.il).

The first two authors contributed equally to this work.

Communicated by G. Kramer, Associate Editor for Shannon Theory.