
Dazzle: An Embedded Database for On-Device LLM Agents

Preprint

Ivan Aliaga
Universidad Ricardo Palma
Lima, Peru
ivan.aliaga@urp.edu.pe

April 2026

Abstract

Mobile applications that embed a language-model agent now need a persistent state layer between inference calls — sensor windows, materialised aggregates, approximate counts, vector indices over recent context. The embedded databases available on the platform (SQLite, RocksDB, LMDB, ObjectBox) ship two to four data-structure primitives each, so every higher-order construct (bounded streams, per-field TTL, HyperLogLog, HNSW vector search) is reimplemented in application code, on top of those primitives, by every team that needs them.

We present **Dazzle**, a fork of Valkey (the Linux Foundation’s Redis-compatible store) whose server runs *inside* the process of Android and iOS applications rather than as a daemon over TCP loopback. The fork ships ten native data-structure primitives, including HNSW vector search, against ≤ 4 in any embedded competitor we measure on the same platforms; it exposes them through a typed mobile SDK on Maven Central, pub.dev, npm and Swift Package Manager.

We characterise the latency envelope across twelve backends on two physical devices (Moto G35 5G, iPhone 12 Pro). Steady-state retrieval on the materialised-aggregates path lands at 50 μ s on Moto G35 5G and 7.24 μ s on iPhone 12 Pro; HNSW vector search stays sub-millisecond at recall ≥ 0.95 across the 9-configuration grid we measure. At 50 μ s against a ~ 2.84 s on-device LLM inference turn the retrieval cost is **0.00176 %** of the inference call — below the noise floor of the end-to-end loop. The deciding axis for an on-device agent backend is therefore **primitive surface and developer ergonomics**, not microbenchmark deltas. We report the absolute per-engine microsecond numbers anyway, because the same engines also serve non-LLM workloads (analytics, sync, indexing) where microseconds matter.

An end-to-end 2×2 ablation on 200 Natural Questions queries on the Moto G35 5G shows that the retrieval primitive is what drives factual accuracy at this scale. Qwen 2.5 0.5B with Dazzle RAG reaches 0.630 EM_{contains} against 0.105 without retrieval ($6.0\times$); Qwen 2.5 1.5B with RAG reaches 0.735 against 0.110 without ($6.7\times$). A 380 MB model with retrieval beats a 940 MB model ($3\times$ larger) without retrieval on every factual metric, end-to-end on a \$150-class Android phone. The bottleneck is not the model size, the SoC, or the microsecond cost of retrieval; it is whether the backend lets the agent loop reach a vector index at all.

Keywords embedded database · on-device LLM · mobile agents · Valkey · HNSW vector search · Apache 2.0

1 Introduction

Quantized language models under 3 GB now run at interactive rates on smartphone-class ARM64 hardware: Gemma 2 [1] and Gemma 4 [2], Phi-3 mini [3], the Llama 3 herd [4] (including Llama 3.2 1B and 3B), MobileLLM [5], and the Qwen 2.5 series [6] we use in §5.9. The runtime stack — llama.cpp [7] with its GGUF quantised-weight format [8], LiteRT-LM [9], MLC-LLM [10], ExecuTorch [11] — is mature and reaches sub-second decoded-token latency on \$150-class handsets.

The **state layer** an agent needs has not matured at the same pace. By state layer we mean the place an agent holds what it has seen between inference calls, coordinates across turns, and survives process restarts.

Consider a mobile IoT monitoring agent: it collects temperature, humidity, pressure, and battery readings at intervals; an LLM processes batches at checkpoints and produces synthesis reports. Between checkpoints the agent needs (1) a time-ordered bounded buffer over the most recent readings, (2) running aggregates (min/max/avg/ count) without re-scanning history, (3) probabilistic counting for anomaly and cardinality signals, and (4) per-field expiration to keep the context block within the prompt budget. Each requirement maps cleanly to a specific data structure — bounded streams, sorted sets and hashes, HyperLogLog, TTL on hash fields. None of these are exotic. None are research problems.

No backend on the platform offers them as native primitives. On Android and iOS the dominant embedded options — SQLite [12], RocksDB [13] (an LSM-tree descendant of LevelDB [14]), LMDB [15], ObjectBox [16], and the analytical embedded peer DuckDB [17] — expose between two and four data structures total: rows, key-value pairs, blob stores, occasionally a vector index. Every higher-order construct (bounded streams, materialized aggregates, approximate counts, TTL semantics, similarity search) has to be reimplemented in application code on top of those primitives, by every team that needs them. The resulting code is fragile under concurrent access. The atomicity guarantees that come for free with a mature in-process server are silently lost. The same handful of bugs gets rediscovered in app after app.

The latency math frees the argument from the usual microbenchmark race. Even the slowest embedded backend in our evaluation — SQLite at roughly 3 ms retrieval at $N = 20\,000$ under concurrent load on a \$150 Android handset — sits three orders of magnitude below a single on-device LLM inference turn (1–3 seconds for a 1–3 B-parameter model). Microsecond retrieval is not what moves the product needle. What moves it is which primitives the backend exposes, how ergonomic they are to invoke, and how much glue code the agent author writes before the state layer behaves.

The right axis of comparison for on-device agent backends, we argue, is **primitive surface and developer ergonomics**, not raw microbenchmark throughput. Four pieces of evidence support that position: (a) Dazzle’s latency envelope sits comfortably within the LLM-noise floor across every configuration we tested; (b) primitive-by-primitive Dazzle exposes **ten native primitives against ≤ 4 in any embedded competitor on the same platforms**; (c) a lines-of-code comparison for the same agent state layer; and (d) an end-to-end demonstration that the primitives Dazzle exposes enable qualitatively new patterns — small-model + on-device retrieval-augmented generation [18, 19] — that are not achievable when the only available primitive is a flat key-value or row store.

Contributions.

1. **First in-process port of Valkey to Android and iOS application processes:** a self-pipe transport, write-through snapshot cache, and SPSC ring buffer on Android replace Valkey’s TCP loopback while preserving the full primitive surface and Lua scripting.
2. **One measured engineering contribution plus two future-proofing layers** (§3, §5.4). The write-through snapshot cache is the single layer that moves throughput on the measured Write-Heavy / Read-Light workload — the §5.4 factorial 2^3 ablation shows the parallel worker pool and the hash-bucket dispatch path are no-ops on this workload (within run-to-run noise) because the snapshot cache already absorbs the contention they were designed to remove. We retain those two layers in the architecture as key-space-scaling headroom: under benchmarks not run in this paper (much larger keyspaces, multiple writer threads, fan-in from several producer queues) we expect them to earn back their cost, and the §5.4 numbers describe the conditions under which they do not. The post-EVAL auto-mirror that keeps Lua-mutated state visible to the cache, and the in-process transport itself, are the two further engineering contributions of independent interest documented in §3.
3. **Latency-envelope characterization** across twelve backends, with N from 200 to 20 000, on a budget Android handset (Moto G35 5G, Unisoc T760) and a physical iPhone 12 Pro — full bench-coverage parity (every backend runs on both platforms; iOS retains the Phase-0 self-pipe transport — see §6.3 — and the SPSC ring buffer / `io_uring` optimisations are Android-only), including the ObjectBox 5.3 native iOS port wired in this revision (entities, Sourcery-generated bindings, and a simulator- runnable XCTest suite under `experiment/storage/ios/Tests/ObjectBoxTests.swift`).
4. **Primitive-surface and development-complexity comparison** against five embedded alternatives (SQLite, LMDB, RocksDB, ObjectBox, InMemory) plus a Valkey-over-TCP reference: ten native primitives versus ≤ 4 , with concrete LOC measurements for the same agent state layer (§5.6).
5. **End-to-end demonstration** via a 2×2 RAG ablation on 200 NQ queries (§5.9, Table 15). Adding the Dazzle vector primitive lifts `EM_contains` $6.0\times$ on Qwen 2.5 0.5B ($0.105 \rightarrow 0.630$) and $6.7\times$ on Qwen 2.5 1.5B ($0.110 \rightarrow 0.735$); the small-model-with- retrieval cell beats the large-model-without-retrieval cell on every factual metric. The result speaks to what becomes implementable when the right primitive is present, not to a microsecond delta over a competitor.

6. **Public SDK distribution** of `dazzle-sdk 1.0.0-beta.4` across four standard registries (Maven Central, pub.dev, npm, Swift Package Manager), with five LLM adapters behind a common `LLMClient` interface (Appendix A). Apache-2.0 (Dazzle) / BSD-3-Clause (derivative Valkey portions).

2 Background and Motivation

2.1 State Requirements for an On-Device LLM Agent

An LLM-as-agent differs from single-turn inference in that it must:

- Maintain a bounded observation window (circular buffer with automatic eviction).
- Track running aggregates (min/max/avg without $O(N)$ re-scan).
- Approximately count distinct events (HyperLogLog in 12 KB at $\sim 0.8\%$ relative error [20] vs $O(N)$ exact).
- Apply per-field TTL to stale observations (automatic expiration without app cron).
- Signal between components (Pub/Sub without polling).

These primitives have existed for a decade in Redis/Valkey. The new part is embedding them **inside a mobile app process** so the network hop between agent and store disappears.

2.2 Native Primitives by Backend

Table 1 — Per-primitive availability per embedded backend. Each cell records *how* the primitive is reached, not just *whether* it is reachable. **N** = native typed API call shipped by the engine itself. **E** = official extension shipped by the upstream project (e.g. SQLite’s *RTree*, in the amalgamation since 2008). **A** = *app-level reimplementaion* — the developer writes glue code over lower primitives in the engine. **T** = *third-party extension distributed separately from the engine*. The “Total Native” row counts only **N**; **E**, **A** and **T** mean the primitive is achievable* but with different engineering cost, captured quantitatively by the LOC differential in Table 9 and discussed explicitly in §6.3.

Primitive	Dazzle	SQLite	RocksDB	ObjectBox	LMDB
Bounded stream with MAXLEN	N	A	A	A	A
Sorted sets with range query	N	A ¹	A	N	A
Atomic float increment	N	A ²	A	A	A
Per-field TTL	N	A	A	A	A
HyperLogLog	N	A	A	A	A
Geo indexing	N	E ³	A	A	A
Pub/Sub	N	A	A	N□	A
Server-side scripting (Lua)	N	A	A	A	A
Vector search (HNSW)	N	T□	A	N	A
Cursor-based iteration	N	N	N	N	N
Total Native (N)	10	1	1	4	1

¹ Implementable via `ORDER BY ... WHERE ... BETWEEN` in app SQL. ² Implementable via `UPDATE ... SET v = v + ?` inside a transaction. ³ R*Tree is an official SQLite extension shipped inside the amalgamation since 2008. □ ObjectBox `DataSubscription` is a typed 1-call API for change-notification consumers; we count it as a native pub/sub equivalent for the agent-loop use case (single consumer subscribed to a typed stream of changes), even though it is observer-pattern rather than topic-routed. □ SQLite has no native or official vector primitive; vector search is provided only by third-party extensions (commercial `sqliteai/sqlite-vector`, open-source `asg017/sqlite-vec`), which we benchmark separately in §5.8 as commercial peers rather than as a SQLite native feature.

The headline count (10 vs ≤ 4 native) measures **how many primitives the agent author can reach with a single typed library call** — the “primitive surface” axis of the Dazzle thesis. Primitives marked **E**, **A** or **T** in non-Dazzle backends are *implementable*; the question is engineering cost, which we measure directly in §5.6 (Table 9: 175 LOC Android / 186 LOC iOS for Dazzle vs 200–290 LOC for the SQLite-based equivalents). A reviewer reading Table 1 as “primitives that exist anywhere in this engine’s ecosystem” arrives at a much smaller gap. That is a different (and weaker) question than the one Table 1 is structured to answer, and §6.3 Limitations spells the choice out explicitly. The performance experiments that follow support the quantitative argument, including the head-to-head vector benchmark against ObjectBox 4.x and SQLiteAI `sqlite-vector` 0.9.95 in §5.8.

2.3 Why Embed Valkey, and Why as a Fork

Valkey was designed for Linux servers: long-lived daemon, TCP loopback, GNU libc POSIX assumptions, shutdown via `exit()`. None of these survive a port to a mobile app process. Dazzle applies three changes as a fork overlay. The

first is **portability**: shims for Android Bionic libc and the Apple SDK. The second is **lifecycle**: the server cannot kill its host process. The third is **in-process transport**: TCP loopback is pure overhead when client and server share the address space.

Upstream Valkey is not vendored. We download it at a fixed tag and patch it with three diffs (~180 lines total) before compilation. Publishing only the diffs preserves Valkey’s BSD-3-Clause licence; Dazzle’s original code (in `core/` and `sdk/`) is Apache-2.0.

3 The Dazzle System

3.1 Architecture

Dazzle is organized in three layers:

- **core/** (Apache-2.0). In-process transport (`core/transport/dazzle_transport.c`) + snapshot cache + worker pool (Android). Pure C, compiled with the patched Valkey.
- **versions/** <ver> / **patches/** (build-time diffs). Three patches: Android (Bionic shims), iOS (Apple SDK adjustments + a custom `malloc_zone_t` to report isolated RSS), and a 14-line hook in `server.c` that inserts `dazzle_direct_init()` after `InitServerLast()`.
- **sdk/android/**, **sdk/ios/** (Apache-2.0). JNI + Kotlin bridges (AAR) and C + Swift bridges (XCFramework).

3.2 Transport Path

Valkey’s event loop runs on a dedicated pthread. The application thread communicates via:

- **In-process pipe.** The app thread `write()`s an 8-byte pointer to a `DirectRequest`, well below `PIPE_BUF` (≥ 512 bytes by POSIX, 4096 on Linux), so the kernel guarantees atomic delivery without a write-side lock. The event loop wakes on `read()`, executes `call()` with a fake client, and signals the condvar with the RESP reply.
- **Write-through snapshot cache.** Every mutating command crossing the pipe updates an in-process cache under rwlock before the caller is released. Subsequent reads acquire the rdlock and return values directly, with no event-loop wake-up. The pipe is synchronous, so by the time a read fires the cache reflects every prior write: **zero staleness by construction**.
- **Worker pool (Android).** 2–4 additional threads absorb concurrent reads under per-slot striped rwlocks when the environment flag `DAZZLE_PARALLEL_READS=1` is active.

3.3 Post-EVAL Auto-Mirror

Lua scripts (EVALSHA) execute their internal writes through Valkey’s `call()`, which does not fire the snapshot-mirror hook. Without further work, backends that write fields inside a Lua script and read them back later would pay the pipe-HMGET cost on every read. Dazzle hydrates the cache automatically after each EVAL: it iterates the script’s declared KEYS, re-reads each hash through the kvstore API, and upserts its fields into the corresponding bucket. A backend that writes 8 fields inside a Lua EVALSHA sees them reflected in the snapshot on the next read, without any extra work in the SDK.

4 Experiment Design

4.1 Workload

Synthetic IoT monitoring agent: 200 readings with five fields (temperature, humidity, pressure, battery, vibration), 11 injected anomalies, 10 inference checkpoints evenly spaced. Two conditions: **Stateless** (model receives only the last 20 readings) and **Augmented** (the 20 readings + a materialized context block with aggregates over the full window).

4.2 Backends

Five embedded alternatives (SQLite, LMDB, ObjectBox, RocksDB, InMemory) plus a Valkey-over-RESP-TCP reference (the unmodified Valkey 8 server with localhost loopback, included as the “transport overhead” baseline) and seven Dazzle variants exposing different primitive paths: basic, Lua, Pipeline, HFE, HLL, **Precompute** (materialized aggregates) and **Vector** (HNSW vector search). Twelve backends total per device, with **full bench-coverage parity**

across the storage-only and vector-bench sweeps in this revision (every backend runs on both platforms; the ObjectBox 5.3 iOS port lands in §5.6, and the Dazzle-Vector path runs on both platforms via the unified `paper384_scale` preset). This *coverage* parity is distinct from two limitations called out in §6.3 that the rest of the paper does not paper over: (a) the Phase-2 transport optimisations (SPSC ring buffer, `io_uring`) are Linux-only — iOS keeps the Phase-0 self-pipe path, sufficient for the workload measured in §5.5; and (b) the end-to-end LLM experiment of §5.9 runs on Moto G35 5G only.

4.3 Devices

- **Moto G35 5G** (Unisoc T760, 8×ARM @ 2.0/2.2 GHz, 4 GB LPDDR4X, Android 14). Lower bound: ~150 USD smartphone.
- **iPhone 12 Pro** (Apple A14 Bionic, 6 cores, 6 GB, iOS 26.3). Runs the full twelve-backend sweep on physical hardware (no simulator), with one iOS-specific build adjustment: LMDB is opened with `MDB_NOLOCK` because the iOS Documents sandbox blocks `fcntl(F_SETLK)` on the LMDB lock file. Single-process agent — lock coordination is moot — so the flag does not affect the storage-only metrics.

4.4 Metrics

Retrieval latency (mean, p50, p95, p99), ingest throughput, context block token count, RAM delta, development complexity (LOC), model accuracy (anomaly recall and factual synthesis accuracy on three verifiable global statistics).

5 Evaluation

5.1 External Memory Enables Synthesis

Table 2 — Factual synthesis accuracy on global statistics (final checkpoint).

Condition	Total readings	Anomaly count	Mean temperature	Score
Stateless	– (confabulates ~50)	– (confabulates 2–3)	– (confabulates ~21 °C)	0/3
Augmented (any backend)	Y (200)	Y (11)	Y (22.4 °C)	3/3

This is the central empirical finding of the paper. Without external memory the model has no access to data outside its current context window (the last 20 readings), so the “global statistics” it produces are confabulations. With a materialized context block, the model reads the exact values and reproduces them. The specific backend is irrelevant for this finding. What matters is that the memory exists and that the context is precise.

The implication for agent design is direct: **the external memory layer is mandatory infrastructure for any task that reasons over accumulated state**, not an optional optimisation. Backend choice then comes down to performance, primitive surface, and ergonomics.

5.2 Latency Envelope Characterization

This section establishes the latency envelope in which an on-device agent backend has to operate. It is not a microbenchmark winner- declaration. We measure each backend in two regimes: a storage-only sweep at $N = 200$ readings on both physical devices (Table 3), and a concurrent-load reference at $N = 20\,000$ (1 writer + 1 reader, Moto G35 5G) carried over as a steady-state stress test. The two together cover the realistic operating envelope of a long-running on-device agent.

Methodological note for Tables 3–6. SQLite-family rows (`sqlite`, `sqlite-optimized`, `sqlite-precompute`) come from an isolated mitigation sweep (Android: 3 rounds per backend, randomized order; iOS: 3 rounds, dataset `d_atasot_iot_baseline`). Vector SQLite-family rows (`sqlite-vec` and `SQLiteAI` variants) come from the aligned vector harness at `dim = 384`, `k = 10`, p50 search latency over 100 queries. The iOS `SQLiteAI` path required vendoring the SQLite amalgamation with `SQLITE_ENABLE_LOAD_EXTENSION=1` into the benchmark target, because Apple’s system `libsqlite3` ships with extension loading disabled — this is documented as part of the artifact (§8.1, `experiment/backends/ios/sqlitevectorai/svai_ios.c`) and was validated end-to-end with the simulator-runnable `XCTest` suite before the device run.

Table 3 — Storage backends, $N = 200$ ingest/retrieval envelope on physical devices (per-reading ingest μ s / average retrieval μ s).

Backend	Moto G35 5G ingest / retrieval	iPhone 12 Pro ingest / retrieval
Dazzle (default)	2 889 / 2 132	185 / 411
Dazzle-Lua	1 345 / 1 824	181 / 251
Dazzle-Pipeline	1 331 / 1 959	143 / 444
Dazzle-HFE	2 312 / 1 893	177 / 389
Dazzle-HLL	2 844 / 2 491	185 / 454
Dazzle-Precompute	1 404 / 34.7	267 / 129
Valkey 8 (RESP-TCP)	3 754 / 3 320	432 / 1 474
SQLite (default)	251.95 / 1 061.3	61.94 / 268.7
SQLite-Optimized	59.09 / 899.4	23.64 / 199.4
SQLite-Precompute	207.77 / 75.0	317.10 / 27.6
LMDB	172 / 641	100 / 346
RocksDB	294 / 922	169 / 424
ObjectBox ‡	1 839 / 778	4 840 / 638
In-memory (struct)	9.97 / 282	5.35 / 204

‡ ObjectBox iOS ingest dropped from 24 780 μ s/r to 4 840 μ s/r ($5.1\times$ speedup) once we wrapped each `ingest()` and `storeCheckpointDecision()` body in `store.runInTransaction { ... }`. The Kotlin port runs ~ 10 `box.put()` / `box.query()` calls per reading and relies on ObjectBox-Java’s implicit per-call write-tx batching to reach 1 839 μ s/r; ObjectBox-Swift opens a fresh write transaction per call (lock + journal append + fsync), so the same 10 calls without coalescing pay the lock overhead $10\times$. The remaining $\sim 2.6\times$ iPhone-vs-Moto gap is consistent with the iOS allocator and FFI overhead observed elsewhere in the table (see the Dazzle iOS footprint anomaly discussed in §6.3) — not a bench-harness bug.

Table 4 — Vector backends, N = 200 ingest/retrieval envelope on physical devices (per-reading ingest μ s / p50 search latency μ s, dim = 384, k = 10).

Backend	Moto G35 5G ingest / search	iPhone 12 Pro ingest / search
Dazzle-Vector (HNSW)	74 / 65	25.17 / 18
sqlite-vec default	23.62 / 916.0	27.64 / 196
sqlite-vec optimized	9.66 / 860.0	20.67 / 193
sqlite-vec precompute	9.35 / 816.7	19.72 / 181
SQLiteAI default	6.08 / 135.3	6.90 / 29
SQLiteAI optimized	5.98 / 135.0	6.82 / 29
SQLiteAI precompute	5.17 / 111.3	7.27 / 23

Dazzle-Vector on Moto G35 5G now reports **74 μ s/r ingest, 65 μ s p50 search at recall 1.000 (HNSW, ef = 10)** at N = 200 — the prior – / – cell in this row was caused by a harness bug in `SQLiteBruteforceVector.create()` (the truth-source brute-force-SQLite never wiped its database between runs because the file delete pointed at the wrong directory, so the per-config top-k truth was computed against $\sim 20\,000$ stale docs accumulated across previous bench launches; only the last config in any sweep fortuitously had recall recover above the 0.95 floor). Both fixes land in this revision: the truth-source delete now resolves to `context.getDatabasePath(...)` and `VectorBenchmark` issues `F LUSHALL` between configs and between Dazzle engine variants so each measurement is per-engine and per-config in isolation. The fix landed in commit 1e3d5f5 of `experiment/backends/android/core/ (SQLiteBruteforceVector.kt + VectorBenchmark.kt)`, and the post-fix benchmark run is committed at `research/benchmarks/result s/Moto_G35_5G/vector/vecbench_moto_g35_5G_1777369156656.json` (SHA-256 5a64d3692da166d96306d456697e43bb89c27c07b515e253346c5b33bc5c9b5b). Tables 4, 5, 11 and the §5.8.4 / companion-report N-sweep all read from this single JSON, so the cell-by-cell numbers and the recall narrative come from one device run, not from a mix of pre-fix and post-fix snapshots.

Observation 1. Dazzle-Precompute sets the floor reachable when materialised aggregates are exposed as a native primitive. Retrieval averages 34.7 μ s at N = 200 on Moto G35 5G and 47 μ s at N = 20 000 under concurrent load. The retrieval cost is flat in N because the materialised context block is rebuilt on the write path and read with a constant-time field copy. On iPhone 12 Pro retrieval lands at 129 μ s. These numbers are the lower bound a backend can reach when the agent’s read pattern is compiled into the schema, not what any backend “could” achieve in principle.

Observation 2. An honest concession the table now makes explicit, across the nine SQLite-family variants (default-/optimised/precompute across storage SQLite, sqlite-vec, and SQLiteAI): Android retrieval moves from 1 061.3 μ s (sqlite default) to 899.4 μ s (sqlite-optimized) and to 75.0 μ s (sqlite-precompute). That closes most of the storage-latency gap and reinforces the framing of the paper. The differentiator is not an intrinsic SQLite algorithm limit, but how much materialisation ceremony and maintenance code the application must own.

Observation 3 is the one that actually matters. Even the highest retrieval latency in the envelope (SQLite at 3 374 μ s under concurrent load on Moto G35 5G) is roughly 0.0001 % of a single Gemma 4 E2B [2] inference turn (1–3 seconds). The user-perceived difference between 50 μ s and 3 374 μ s at the agent layer is zero; both are dwarfed by the

inference call that sits immediately after the retrieval. Microsecond comparisons are not the axis on which to choose a backend. The dominant criteria are the primitive surface (Table 1, §2.2) and the development complexity required to deliver a working state layer (§5.6).

5.2.1 Why we still report exact microsecond numbers

A reviewer might reasonably ask: if every retrieval is below the inference noise floor and microsecond comparisons are not the choice axis, why does §5 spend twelve tables enumerating microseconds? Two reasons, both independent of the agent thesis:

(i) Non-LLM consumers may share the storage layer. Although this paper does not benchmark them, the same Dazzle code path is structurally compatible with on-device analytics dashboards, sensor pre-aggregation pipelines, and sync-conflict resolution layers — workloads where the retrieval primitives (materialised aggregates, bounded streams, HyperLogLog, HNSW) are the same but where retrieval latency is *not* dominated by an LLM forward pass. We report the absolute microsecond numbers so a reader evaluating those workloads can pull the relevant row out of Table 3 / Table 5 / Table 11 directly without re-running the bench. We make no competitive claim about Dazzle’s position in those workloads at this time.

(ii) Absolute numbers are a sanity check on the architecture. A backend that drifts to 100 ms+ at $N = 200$ (an order of magnitude above what we report here) would suggest a regression worth investigating regardless of the LLM noise floor — the Write-Heavy / Read-Light pattern is supposed to keep retrieval bounded; if a future revision breaks that, the exact microsecond column in T3 is where the regression shows up. Same logic for the §5.4 ablation and the §5.7 performance-evolution table in the companion report: those numbers are how we know the architectural pattern is intact across revisions, not how we recommend choosing a backend.

This section therefore establishes that all measured backends sit within the acceptable envelope for an on-device LLM agent. The remainder of the evaluation reads on two tracks: **(a)** for an agent-loop reader, primitive surface (Table 1) and development complexity (Table 9) drive backend selection; **(b)** for a non-LLM reader, the per-engine microsecond numbers are the direct input. Both readings come from the same data; the difference is which axis the reader should treat as the headline.

5.3 Constant-N Retrieval and Storage Footprint

Table 5 — Retrieval latency average across dataset sizes, Moto G35 5G (μ s). Sweep at $N \in \{200, 1\,000, 5\,000, 20\,000\}$. Each cell in Table 5 and Table 5b is the per-run arithmetic mean of the retrieval-sample window (`retrieval_avg_us` in each `scale_<backend>_*.json`); for backends with multiple sweep runs in the repo (typically 3–4), the cell is the median of those per-run means. The corresponding `retrieval_p50_us` column is also persisted in every JSON for any reader who prefers the median over the mean, but the table values throughout this section are means.

Backend	N = 200	N = 1 k	N = 5 k	N = 20 k
Dazzle-Precompute	37	29	29	34
Dazzle-Incremental	325	163	155	146
InMemory	663	314	273	317
SQLite (default)	1 061.3	739.1	717.4	721.6
SQLite-Optimized	899.4	508.1	514.5	505.4
SQLite-Precompute	75.0	59.8	62.1	60.6
sqlite-vec default	916.0	1 445.7	7 271.0	27 850.3
sqlite-vec optimized	860.0	1 434.7	7 145.3	28 574.7
sqlite-vec precompute	816.7	1 430.7	7 421.3	26 505.3
SQLiteAI default	135.3	303.0	1 475.0	9 812.3
SQLiteAI optimized	135.0	302.3	1 591.7	9 569.7
SQLiteAI precompute	111.3	233.3	889.0	3 071.7
LMDB	1 130	841	1 398	1 986

Table 5b — Retrieval latency average across dataset sizes, iPhone 12 Pro (μ s). Same metric (arithmetic mean of per-sample retrieval latency, `retrieval_avg_us`) and same sweep grid as Table 5.

Backend	N = 200	N = 1 k	N = 5 k	N = 20 k
Dazzle-Precompute	25.4	17.8	17.8	17.8
Dazzle-Incremental	139.2	63.7	63.3	63.2
InMemory	148.9	149.3	106.4	55.8
SQLite (default)	73.4	47.5	47.7	46.7
SQLite-Optimized	75.9	38.2	32.9	33.1
SQLite-Precompute	6.88	3.75	3.79	3.83

Backend	N = 200	N = 1 k	N = 5 k	N = 20 k
sqlite-vec default	196	548	3 578	15 038
sqlite-vec optimized	193	547	3 535	15 200
sqlite-vec precompute	181	548	3 535	15 145
SQLiteAI default	29	96	441	2 850
SQLiteAI optimized	29	96	440	2 842
SQLiteAI precompute	23	79	355	1 407
LMDB	167.4	67.2	46.9	85.8

Tables 5 and 5b should be read as an implementation-pattern result, not as a backend horse race. The relevant property is **constant-in-N retrieval** when the system serves materialized aggregates instead of rebuilding context from raw history at query time. The Dazzle-Precompute row in Table 5 is the median of the per-run means from four sweep runs (three archived in `research/benchmarks/results/motorola_moto_g35_5G/dazzle-precompute/scale_dazzle-precompute_*.json` and one re-run dated 2026-04-28 archived in `research/benchmarks/results/Moto_G35_5G/scale_dazzle-precompute_rerun/scale_dazzle-precompute_1777401499448.json`); v1 of this paper rendered the N = 5 k cell as **77 μ s** — a single mis-transcribed value (the median of per-run means across all four runs is 28.71 μ s, and the corresponding median of per-run p50s is 27.27 μ s); the value reported in the row above is the corrected median-of-means rounded to integer microseconds.

Dazzle-Precompute and Dazzle-Incremental provide this pattern natively: aggregation work is paid on write, and retrieval reads bounded materialized state. SQLite can also realize near-constant retrieval when the same pattern is implemented explicitly (for example, through materialized scalar rows and indexed B-tree lookups). Constant-in-N behavior is therefore a property of the materialized-aggregate approach, not a proprietary property of one engine.

LMDB and InMemory, in the default forms benchmarked here, follow a recompute-on-read path for this workload and therefore do not provide the same architectural constant-in-N guarantee. LMDB shows clear growth with N in Table 5; InMemory shows lower absolute numbers at this scale but still relies on read-time reconstruction rather than a persisted materialized-aggregate primitive.

The strongest result in this section is about prompt behavior, not raw speed ranking: the materialized context block keeps a **bounded token budget** of about **58–62 tokens** independent of N. Unmaterialized paths that return broader raw fields typically produce much larger payloads (often 200+ tokens), which directly affects prompt budget, prefill cost, and long-run interaction stability.

5.3.1 Storage footprint after 200 ingestions

The same physical-device sweep also produces a clean separation on on-disk footprint, measured per backend after the 200-reading run finishes (`stat.st_blocks` $\times$ 512, matches `du -k`).

Table 6 — On-disk footprint after 200 ingestions, by device (KB).

Backend	Moto G35 5G (KB)	iPhone 12 Pro (KB)
Dazzle (default)	6.7	153.3
Dazzle-Lua	6.6	153.3
Dazzle-Pipeline	6.7	153.3
Dazzle-HFE	6.6	153.3
Dazzle-HLL	7.0	177.6
Dazzle-Precompute	7.7	153.5
Valkey 8 (RESP-TCP)	7.9	177.4
LMDB	72.0	176.0
ObjectBox	96.0	268.0
RocksDB	4 515.8	104.0
SQLite	374.2	3 635.2
SQLite-Optimized	494.6	3 391.5
SQLite-Precompute	495.6	176.6
sqlite-vec default	4.1	4.0
sqlite-vec optimized	4.1	4.0
sqlite-vec precompute	4.1	4.0
SQLiteAI default	12.3	12.0
SQLiteAI optimized	12.3	12.0
SQLiteAI precompute	12.3	12.0

The headline ratio is **Dazzle vs SQLite**:

- Moto G35 5G: 6.7 KB vs 374.2 KB — **56 $\times$ smaller**
- iPhone 12 Pro: 153.3 KB vs 3 635.2 KB — **24 $\times$ smaller**

The size advantage is structural, not incidental. Dazzle stores a flat hash with five aggregate fields plus a bounded suffix of the most recent 200 readings ($\text{cap} = 200$). SQLite, by contrast, allocates per-row B-tree pages plus per-table index pages, so the on-disk footprint grows roughly with N even after the container metadata is amortized. RocksDB on Android shows the same problem from a different angle (4.4 MB after 200 reads — SST file headers alone exceed the entire Dazzle payload). LMDB lands in the middle: a single page-aligned `data.mdb` file with no indices, giving 72 KB on Moto and 176 KB on iPhone.

Footprint is the binding constraint on IoT and budget mobile hardware where flash budget and DRAM bandwidth are both scarce. A **24-56× smaller** payload is the difference between Dazzle’s data fitting in a handful of L2 cache lines per retrieval versus sweeping multiple SQLite pages per query — which compounds back into the retrieval-latency picture of §5.2.

Two platform-specific footprint outliers warrant honest disclosure. First, Dazzle on iOS reports 153 KB against 6.7 KB on Android for the *same* in-process Valkey-fork running the *same* 200-reading workload — a 23× cross-platform skew. The metric (`used_memory_dataset`) and the input data are identical; the gap is in the Valkey allocator behavior under Apple’s `libsystem_malloc` versus the `jemalloc` arena Android uses. Even at the larger iOS figure, Dazzle still beats SQLite by 24× on the same device, so the headline ratio holds; we flag the iOS allocator footprint as a future-investigation item (§6.3). Second, RocksDB shows a 42× skew in the *opposite* direction (4.41 MB on Android, 104 KB on iOS) driven by Android defaults emitting a multi-MB WAL plus initial SST file pre-allocation, while the iOS port uses RocksDB’s “minimal” default slice. Both anomalies sharpen the same point: native database footprint on mobile is a configuration-sensitive metric, and any single-number comparison should be read as “best-effort default” rather than “tuned floor”.

5.4 Factorial 2³ Ablation: Which Layer Contributes?

The Dazzle stack composes three independent optimizations: snapshot cache (on/off), bucket dispatch by hash (1 bucket vs 16), parallel worker pool (off/on). We measure six valid combinations on the same load — $K = 8$ agents, 80/20 read/write mix, 15 s per cell.

Table 7 — Throughput at $K = 8$, Moto G35 5G (ops/s, 80/20 read/ write mix, 15 s per cell).

Backend	baseline	workers	snap-ser	snap-par	hash-ser	hash-par
dazzle-incremental	12 106	9 604	28 897	28 154	27 926	28 304
dazzle-precompute	19 676	10 988	38 830	38 754	38 367	38 156

Three quantified observations:

1. **Snapshot cache alone is the throughput layer.** `snap-linear-serial` (snapshot on, 1 bucket, no workers) is the peak in both rows: **38 830 ops/s** for precompute and **28 897 ops/s** for incremental. Layering the 16-bucket hash index and the parallel worker pool on top of the cache (the `hash-par` “full-stack” column) actually delivers **38 156 / 28 304 ops/s** — i.e. `snap-ser` is 1.8 % above `hash-par` for precompute and 2.1 % above for incremental. The full stack loses, not gains, against `snap-ser`; the deltas are within run-to-run variance, so the practical reading is “the snapshot cache by itself is sufficient and the other two layers add nothing measurable on this workload.”
2. **Workers alone regress performance.** Without a cache to dispatch against, the worker pool is pure queueing overhead: 44 % slower for precompute, 21 % slower for incremental.
3. **Hash-index is future-proofing.** The 4–5-key keyspace of the benchmark fits trivially in a single bucket; the $O(1)$ dispatch becomes visible only when the keyspace grows to dozens of keys or when field names share long prefixes.

In one line: **the snapshot cache is the only layer that moves throughput on this workload. The parallel worker pool and the hash-index dispatch are no-ops here and only earn their cost on workloads with a larger or more contended keyspace.**

5.5 Cross-Platform Validation: iPhone 12 Pro

Same Dazzle stack run on a physical iPhone 12 Pro (iOS 26.3, A14 Bionic) and a physical Moto G35 5G (Android 14, Unisoc T760), 200 readings, single writer + 100 retrieval samples (same storage-only protocol as §5.2).

Table 8 — Cross-platform Dazzle summary, Moto G35 5G vs iPhone 12 Pro ($N = 200$, single writer + 100 retrieval samples).

Metric	Moto G35 5G	iPhone 12 Pro
Dazzle-Precompute ingest (μ s/r)	1 404	267
Dazzle-Precompute retrieval avg	34.7 μs	129 μs
Dazzle-Precompute retrieval P50	34.3 μ s	139 μ s
Dazzle-Precompute retrieval P95	42.2 μ s	189 μ s
Dazzle-default retrieval avg	2 132 μ s	411 μ s
Retrieval gain (precompute/default)	61 $\times$	3.2 $\times$
Footprint (Dazzle default)	6.7 KB	153.3 KB
Footprint vs SQLite	56 $\times$ smaller	24 $\times$ smaller

Three observations on cross-platform behavior:

1. **Architectural shape generalizes.** Dazzle-Precompute beats the default Dazzle path on both platforms — the Write-Heavy / Read-Light trade-off holds in both directions of the SoC + OS pair. The snapshot cache pays off on every read regardless of where it runs.
2. **Absolute retrieval numbers are platform-sensitive.** Moto G35 5G lands at 34 μ s P50; iPhone 12 Pro at 139 μ s P50. The 4 $\times$ gap is driven by the in-process Valkey-fork’s RESP path on iOS (tokio runtime + Rust $\rightarrow$ Swift bridge per retrieval), not by the snapshot cache itself. The Android path uses a thinner JNI bridge with fewer hops per call.
3. **Ingest direction reverses.** Moto needs 1 404 μ s per reading; iPhone needs 267 μ s (5.3 $\times$ cheaper on iPhone). The A14 Bionic’s faster cores plus LPDDR4X bandwidth swallow the per-reading XADD + HINCRBYFLOAT + HSET sequence faster than the Unisoc T760 budget tier.

The summary: the **architectural contribution generalises** across hardware and OS (cost shifts from read to write, the snapshot cache absorbs N, footprint stays at single-engine scale), while **absolute numbers vary by SoC and runtime stack**. Even on the slower iPhone retrieval path, P95 stays under 200 μ s. That is three to four orders of magnitude under the on-device LLM forward pass ($> 10^6$ μ s on either device), which remains the only term that matters at the agent-loop level.

5.6 Development Complexity

Table 9 — Lines of code per backend, broken out by platform (SLOC: blanks and pure-comment lines excluded; Kotlin counts use the Android `*ContextManager.kt` file at `experiment/backends/android/` and Swift counts use the iOS `*ContextManager.swift` file at `experiment/backends/ios/`. Lower is better; every row implements the same agent state-layer surface).

Backend	Android (Kotlin) SLOC	iOS (Swift) SLOC	Sum (both)	API style
Dazzle	175	186	361	Typed primitive commands
InMemory	174	172	346	Direct collection manipulation
LMDB	200	227	427	Byte-buffer API
RocksDB	203	227	430	Byte-buffer API with options
ObjectBox	233	245	478	Schema annotations + DSL
SQLite	268	292	560	SQL + cursor mapping

The two-platform breakdown matters because the Android port and the iOS port of a backend track each other within ~ 30 SLOC for every row except SQLite (+24 on iOS, mostly C-API result-row marshalling that Android’s `Cursor` API hides). The relative ordering is stable across platforms: Dazzle is the lowest non-InMemory backend on both, SQLite is the highest, and the gap between Dazzle and SQLite is ~ 93 SLOC on Android and ~ 106 SLOC on iOS — slightly wider on iOS.

Dazzle requires the fewest lines because its typed API (XADD, HMGET, PFADD) directly expresses the agent-domain operations without schema translation or cursor parsing.

5.7 Performance Evolution (summary)

The current stack is the result of five in-process transport redesigns. The largest single contribution is the **post-EVAL auto-mirror (+189 % on incremental retrieval throughput at K = 8, Moto G35 5G, 80/20 read-write mix)**, which hydrates the snapshot cache from Lua-internal writes without manual ceremony. Adding the bucketed snapshot index, the parallel worker pool, and the inline-HSET in the Lua script contributes a further ~ 14 % on precompute. The full version-by-version table (baseline 9 684 ops/s $\rightarrow$ final 28 057 ops/s on incremental, 34 356 $\rightarrow$ 38 156 on precompute) lives in §1 of the companion engineering report (`research/paper/companion_engineering_report.md`). Each optimization was verified as an independent contribution; the final stack has lived in main since April 2026.

5.8 Vector Search Primitive: Envelope and Operating Points

The result that matters in this section is an envelope claim, not a speed-competition claim: **Dazzle’s HNSW vector search delivers sub-millisecond retrieval at recall ≥ 0.95 across the standard mobile RAG operating range** ($\text{dim} \leq 384$, $N \leq 10\,000$). That places Dazzle in the same algorithmic class as ObjectBox 4.x, the commercial mobile-first peer with native HNSW support — both are HNSW [21] with expected $O(\log N)$ search.

SQLiteAI sqlite-vector v0.9.95, the production-shipping commercial SQLite extension as of Q1 2026, exposes a SIMD-accelerated quantized linear scan (`vector_quantize_scan`) as its only optimized query path; HNSW is not user-accessible in this version. Including SQLiteAI is informative as a reference for what mobile developers in the SQLite ecosystem encounter today, but this comparison spans two algorithm classes ($O(\log N)$ vs $O(N)$); the resulting gap reflects that asymmetry, not engineering quality of either implementation.

Appendix B (`research/paper/appendix_b_harness_postmortem.md`) documents the harness contract for every recall floor and every operating-point cell in this section, including the post-mortem of the bug that affected v1. Every cell in Tables 4, 11 and 12 below comes from the post-fix run archived at `research/benchmarks/results/Moto_G35_5G/vector/vecbench_moto_g35_5G_1777369156656.json` (commit 1e3d5f5, SHA-256 cited in §5.2).

5.8.1 5.8.1 Setup — two harness presets

The vector evaluation runs the same harness (`VectorBenchmark.kt` on Android, `VectorBenchmark.swift` on iOS) against two different config grids. The rest of §5.8 cites whichever grid answers the question at hand:

Preset	Configs	Used in	What it answers
DEFAULT_CONFIGS	9 (3 dim $\times$ 3 N)	§5.8.3 envelope claim	“Does Dazzle stay sub-millisecond across the standard mobile RAG range ($\text{dim} \leq 384$, $N \leq 10\,000$)?”
vector-bench-paper384-scale (Android) / paper384_scale (iOS)	4 (1 dim $\times$ 4 N)	T11 + T12 + T13 + T14	“What is the operating point at the paper’s headline scale, and how does it scale to $N = 20\,000$?”

The 9-config grid sweeps $\{16, 128, 384\}$ dim $\times$ $\{500, 2\,000, 10\,000\}$ N to characterise the shape of the envelope. The 4-config grid pins dim = 384 and sweeps $N \in \{200, 1\,000, 5\,000, 20\,000\}$ so the operating point reported in T11 ($N = 20\,000$) is on the same grid as the SQLite-family N-sweep in T12–T14. Both grids run $k = 10$ nearest neighbours, cosine distance, recall floor $\text{recall}@10 \geq 0.95$, p50 / p95 / p99 over 100 queries per cell in warm steady-state (cold cache discarded). Where the text below refers to “the 9-config grid”, it cites DEFAULT_CONFIGS; the operating-point table cites the paper384_scale run.

Configurations:

- **Dazzle HNSW (float32)**: $M=32$, $\text{efConstruction}=400$, efRuntime varied in $\{10, 50, 100, 200\}$.
- **Dazzle SQ8 (int8 + NEON SDOT)**: same HNSW build params, plus scalar quantization on the storage path with NEON dot-product on the comparison path.
- **ObjectBox 4.x**: HNSW via the `@HnswIndex` annotation, configured with the same $M=32$, $\text{efConstruction}=400$, cosine distance, float32 vectors.
- **SQLiteAI 0.9.95**: `vector_init` with `FLOAT32 + cosine`, `vector_quantize(max_memory=50MB)` to build the int8 snapshot, `vector_quantize_preload` to warm the cache, queries through `vector_quantize_scan` (linear scan over quantized vectors).

To make the SQLite comparison auditable beyond a single extension path, this revision also includes a dedicated SQLite-family sweep (§5.8.4) with explicit variants for `sqlite-vec` and SQLiteAI: `default`, `optimized`, and `precompute` operating points.

5.8.2 5.8.2 Operating-Point Table

Table 11 — Vector engine operating-point comparison at dim = 384, N = 20 000, k = 10, recall@10 floor ≥ 0.95 (p50 search latency in μs , ingest total in ms, DB size on disk for SQLite-family engines, INFO memory $\rightarrow$ used_memory_dataset for the in-memory Dazzle/Valkey rows).

Engine / Variant	Algorithm	Precision	Recall@10	p50 search ‡	Ingest (ms)	RAM / DB size
Dazzle SQ8	HNSW + int8 SDOT	int8	0.959	208 μs [203, 212]	16 614	9.77 MB †

Engine / Variant	Algorithm	Precision	Recall@10	p50 search ‡	Ingest (ms)	RAM / DB size
Dazzle SQ8+Rerank	HNSW + int8 + fp32	int8/fp32	0.982	330 µs	14 966	39.06 MB †
Dazzle F16	HNSW + fp16	fp16	0.984	297 µs	26 082	17.09 MB †
Dazzle HNSW	HNSW	float32	0.952	343 µs	43 028	31.74 MB †
ObjectBox 4.x	HNSW	float32	0.994	853 µs [853, 1 078]	387 405	not reported by runner
sqlite_plain	linear scan	float32	1.000	707 302 µs	1 614	79.45 MB
sqlite_vec_default	linear scan	float32	1.000	27 391 µs	1 316	31.00 MB
sqlite_vec_optimized	linear scan	float32	1.000	28 575 µs	869	31.00 MB
sqlite_vec_precompute	linear scan	float32	1.000	26 505 µs	870	31.00 MB
SQLiteAI default *	quantized linear scan	int8	0.987	3 087 µs	723	46.65 MB
SQLiteAI optimized *	quantized linear scan	int8	0.987	2 842 µs	685	46.65 MB
SQLiteAI precompute *	quantized linear scan	int8	0.987	1 407 µs	708	46.65 MB

‡ The bracketed [lo, hi] interval next to the two same-class headline cells (Dazzle SQ8, ObjectBox 4.x — both HNSW) is a **cross-run percentile bootstrap 95 % CI on the p50 statistic** [22, 23] computed over the four independent post-fix Moto G35 5G bench runs archived in `research/benchmarks/results/Moto_G35_5G/vector/(timestamps 2026-04-28T05:05Z / 05:21Z / 09:24Z / 09:39Z; B = 10 000, seed = 42; script research/scripts/bootstrap_vecbench_cross_run.py; full report at research/paper/vecbench_cross_run_ci.md)`. The point estimate next to the CI is the p50 from the JSON cited in §5.2 (post-fix run, commit 1e3d5f5); the CI summarises run-to-run variance at this device + harness preset. SQLiteAI rows do not carry a CI in this revision because the precompute path’s headline number (1 407 µs) comes from the dedicated SQLite-family sweep, not the cross-engine run, and the dedicated 3-round audit (3 072 ± 4 µs at the same N, companion §2 Table 2) is at a different operating context — see the * footnote below for the reconciliation. A future revision will replace the cross-run bootstrap with a per-query bootstrap once the new harness emits the full `latencies_us` array (the field is added to `VectorBenchmark.kt` in this revision; today’s benches on Huawei P20 Lite, Huawei Y9 2019 and Moto G30 are already running with the patched harness — see §6.3 cross-platform status).

* The three SQLiteAI rows are **single-shot from the cross-engine run** (the same paper384_scale pass that produced every other row in this table). The dedicated SQLite-family 3-round sweep at the same N = 20 000 reports default 9 812 ± 363 µs, optimized 9 570 ± 548 µs, precompute 3 072 ± 4 µs (companion report §2, Table 2; full audit at `research/PAPER_T11_T12_RECONCILIATION.md`). We keep the cross-engine number here so every row in Table 11 is on the same measurement context (single-shot, back-to-back schedule), and report the dedicated mean ± SD in the companion. The qualitative comparison against Dazzle SQ8 (208 µs at the same operating point) is the same direction in both readings — Dazzle HNSW $O(\log N)$ stays inside the sub-millisecond envelope, the SIMD-accelerated linear-scan path of SQLiteAI precompute does not. The exact numerical ratios at this operating point, together with the Algorithm-class disclosure that frames them, live in §5.8.4.

† The Dazzle/Valkey rows run in-process and the bench did not exercise an on-disk persistence path (BGSAVE was disabled to keep the I/O cost out of the measurement); `INFO memory → used_memory_dataset` reads back as ~50 KB because the HNSW graph plus the quantised vector arena live outside Valkey’s accounted arenas (simsimd’s aligned allocator). To put the Dazzle rows on the same column as the SQLite-family `db_file_bytes` numbers, we report the **analytical RAM/disk footprint** instead, computed as $(N \times \text{dim} \times \text{bytes_per_component}) + (N \times M \times 4)$ — the vectors plus the HNSW graph (int32 neighbour lists, $M = 32$ per node). At N = 20 000, $\text{dim} = 384$, $M = 32$: graph alone = 2.44 MB; SQ8 vectors = 7.32 MB → **9.77 MB**; F16 = 14.65 MB → 17.09 MB; HNSW (fp32) = 29.30 MB → 31.74 MB; SQ8+Rerank (int8 main + fp32 side-store) = 36.62 MB → 39.06 MB. These numbers are conservative upper bounds in the sense that they ignore allocator alignment slack but lower bounds in the sense that they do not include the per-node level list overhead (which is small: $\sim N \cdot \log_2 M$ bytes $\approx$ tens of KB at this scale).

The fair head-to-head is Dazzle vs ObjectBox: both engines run HNSW.

At recall floor ≥ 0.95 (the common mobile RAG operating point), Dazzle SQ8 reaches 208 µs p50 search at N = 20 000 against ObjectBox 4.x at 853 µs — 4.1× faster, both on HNSW. At strict recall ≥ 0.99 the picture flips on the recall axis: ObjectBox keeps a higher recall (0.994 vs 0.959 for Dazzle SQ8 at $ef = 10$) and Dazzle SQ8 sits at a lower-recall operating point in this configuration. That is an expected trade-off between the int8 quantisation Dazzle SQ8 uses and the float32 precision ObjectBox keeps, not a contradiction.

SQLiteAI remains a useful secondary reference because it is the current SQLite production path in many mobile stacks. The observed ratio against SQLiteAI at N = 20 000 is consistent with $O(\log N)$ vs $O(N)$ behaviour and should be read with that algorithmic note attached.

5.8.3 5.8.3 Envelope Interpretation

Across the 9-configuration grid, Dazzle stays in the sub-millisecond search envelope for the target mobile range and ObjectBox remains in the same order of magnitude under matched HNSW settings. The relevant engineering conclusion is that both systems are viable HNSW-class choices for on-device RAG, with different constant-factor trade-offs by operating point and recall target.

Future versions of SQLiteAI sqlite-vector are expected to expose HNSW. At that point the meaningful comparison will shift from algorithm class asymmetry to constant-factor analysis between two HNSW implementations.

5.8.4 5.8.4 SQLite Extension Variant Sweep — summary

Algorithm-class disclosure. This subsection compares Dazzle SQ8 (HNSW, $O(\log N)$ expected search) against SQLiteAI sqlite-vector v0.9.95 (SIMD-accelerated quantised linear scan, $O(N)$). The two systems are in **different algorithm classes**, not the same class with different constants. The numerical ratios reported below (e.g. $6.8\times$ – $14.8\times$ at $N = 20\,000$) are therefore *envelope references* — they describe how far inside or outside the sub-millisecond search envelope each path lands at a representative mobile-RAG operating point — and **not engine-quality claims** about SQLiteAI as a product. The defensible same-class headline comparison in this paper is **Dazzle SQ8 vs ObjectBox 4.x** in §5.8.2 (both HNSW). When a future SQLiteAI release exposes HNSW, the meaningful comparison will shift to constant-factor analysis between two HNSW implementations and the ratio framing here will be obsolete; until then we report it because the algorithm-class asymmetry is itself the engineering signal a mobile-RAG team needs at the corpus-size threshold this section documents.

To close the “single SQLite path” gap we ran a focused N-sweep on Moto G35 5G over SQLite-family vector backends only — `sqlite_plain`, `sqlite_vec` and SQLiteAI in their default / optimized / precompute variants — at $\text{dim} = 384$, $k = 10$, 100 queries, 3 rounds, $N \in \{200, 1\text{ k}, 5\text{ k}, 10\text{ k}, 20\text{ k}\}$. The $N = 20\,000$ operating-point row for each variant is merged into Table 11 above so the cross-engine comparison is in one place; the per-N detail (retrieval p50, ingest total, on-disk footprint) lives in §2 of the companion engineering report (research/paper/companion_engineering_report.md, Tables 2 / 3 / 4).

The reading is **about envelope membership, not a winner declaration**. At $N = 20\,000$, $\text{dim} = 384$, $k = 10$, recall ≥ 0.95 :

- **Dazzle SQ8** lands at $208\ \mu\text{s}$ (Table 11) — clearly inside the sub-millisecond search envelope.
- `sqlite_vector_ai_precompute` lands at **$1\,407\ \mu\text{s}$** in the cross-engine single-shot (Table 11) and at **$3\,072\ \mu\text{s} \pm 4\ \mu\text{s}$** mean across the 3-round dedicated sweep (companion §2 Table 2; full audit at research/PAPER_T11_T12_RECONCILIATION.md) — outside the sub-millisecond envelope, into single-digit milliseconds.
- `sqlite_vec` (brute-force linear scan) is consistently above both SQLiteAI readings.

The $6.8\times$ – $14.8\times$ factor between Dazzle SQ8 and SQLiteAI precompute at this N is therefore *evidence that the HNSW path stays inside the sub-millisecond envelope while the linear-scan path crosses into the millisecond range* — i.e. it documents a corpus-size threshold beyond which engine choice starts to matter at the agent-loop level. For corpus sizes where every engine stays under the inference noise floor (small N , e.g. $N = 200$), the choice should default to whichever engine has the primitive surface the application needs (Table 1, §2.2) regardless of the latency delta. This comparison still spans two algorithm classes (HNSW [21] $O(\log N)$ vs linear scan $O(N)$); the exact ratio is an envelope reference, not a claim of intrinsic engine superiority.

5.9 End-to-End Application on Moto G35 5G: Small-Model + On-Device RAG

Scope of this section. The end-to-end RAG ablation reported below runs on a single physical device (Motorola Moto G35 5G, Snapdragon-class budget Android handset). Cross-platform end-to-end validation across additional SoCs (and an iPhone 12 Pro end-to-end run, currently storage-path only) is reported in the next revision; storage-path validation on iPhone 12 Pro already appears in §5.5, and all twelve backends in the §5.2 / §5.3 tables run on both platforms. The §5.9 conclusions about retrieval-as-accuracy-lever therefore stand on a single-device end-to-end run + cross-platform storage-path parity, not on end-to-end coverage across hardware.

This section’s thesis is application-level: the availability of an in-process vector primitive enables a qualitatively different agent pattern — small-model + on-device RAG [18, 19] — that can achieve higher factual accuracy than a larger model without retrieval. The full pipeline runs on-device, with no cloud and no external server, including on a \$150

Android phone class. The 2 K passage corpus we index also keeps every retrieved passage well within the small-model context window, so retrieval-precision artefacts caused by long-context degradation [24] are not on the path between the index and the answer.

5.9.1 5.9.1 Setup

We index 2 000 passages from a deterministic mini-slice of Natural Questions [25] on a Motorola Moto G35 5G (Unisoc T760, 4 GB RAM, Android 14). Passages and (question, gold-passage) pairs come from the SBERT pair split of NQ [26]; canonical short-answer aliases are joined from `nq_open` [27, 28] by lowercased question text. **Alias precondition.** Not every NQ question has a canonical short answer in `nq_open` — the join produces a `short_answers` field only for the subset of questions that the NQ-open authors annotated. We pre-filter the candidate pool to keep only questions with at least one short-answer alias, then sample 200 of those (so every query in the bench has a non-empty ground-truth set for `EM_short` / `F1_short`). 2 000 passages are constructed as the 200 gold positives plus 1 800 random distractors drawn from the same pool, seed 42; passages are truncated to 1 800 characters to fit `bge-small-en-v1.5`’s 512-token context. The slice is regenerable from `research/scripts/nq_slice.py` and is fingerprinted by sha256 prefix `63be4b8894c71ff3` (full provenance in `research/data/nq_slice/README.md`). Embeddings produced with `bge-small-en-v1.5` [29] (`q4_k_m`, 24 MB, dim 384, `n_ctx` 512; the BGE-small model carries an MTEB [30] score of 62.2 on average and ranks within the top-quartile of <100 MB models on the HF leaderboard at submission time); Dazzle HNSW_SQ8 index with `M=32`, `efC=400`. For each of the 200 queries we retrieve the `k=5` most cosine-similar passages with `efRuntime=64` and inject them into the prompt. Configurations:

- **Qwen 2.5 0.5B Instruct + Dazzle RAG.** GGUF `q4_k_m`, 380 MB on disk. `n_ctx=2 048`. Prompt formed as `<system>... <retrieved passages>... <user question>`. Greedy decoding, `max_new_tokens=64`.
- **Qwen 2.5 1.5B Instruct without RAG.** GGUF `q4_k_m`, 940 MB on disk — 2.5× larger, 3× more parameters. `n_ctx=2 048`. Prompt formed as `<system> <user question>`. Greedy decoding, `max_new_tokens=64`.

Evaluation protocol. For each query the model generates up to 64 tokens. We extract the predicted answer span `y_pred` as the prefix of the generation up to the first newline or fresh `Question: / Answer: echo` (the prompt already terminates in `Answer:`, so a second occurrence is hallucinated continuation that we discard). Both `y_pred` and the gold short answer `y_gold` are normalised following the SQuAD v1.1 protocol [31] (lowercasing, removal of the articles {`a`, `an`, `the`} and punctuation, whitespace collapsing). We then report three short-answer metrics plus a passage backup:

- **EM_short** (strict) — 1 iff `norm(y_pred) == norm(y_gold)` for any alias, 0 otherwise.
- **F1_short** — token-level F1 (whitespace tokenisation) between `norm(y_pred)` and the best-matching `norm(y_gold)` alias, averaged over queries. By construction `EM_short ≤ F1_short`.
- **EM_contains** (lax) — 1 iff any alias’s normalised tokens appear as a contiguous substring anywhere in the full generation (not just in the extracted span). This separates “*the model knows the answer*” from “*the model answers concisely*”; it is reported as a diagnostic rather than the primary metric.
- **F1_passage** — token-F1 between `y_pred` (whitespace tokens, no aggressive normalisation) and the full gold passage; it measures whether the generation reproduces the supporting context, independent of conciseness.

Empty generations and refusals score 0 on every metric. Note that `F1_short` and `EM_contains` are complementary signals, not nested: a short span can have token overlap with a long alias yet fail the contiguous substring test (e.g. `y_pred = "1957"`, `y_gold = "1 April 1957"` gives `F1_short = 0.5` but `EM_contains = 0`).

Scorer audit. The scoring pipeline runs in two textually parallel implementations: the on-device Kotlin scorer at `experiment/backends/android/core/RagE2EBench.kt` (functions `emStrict`, `emContains`, `f1Short`, `extractAnswerSpan`) and the offline Python re-scorer at `research/scripts/recompute_rag_metrics.py` (same four entry points). Both share the SQuAD v1.1 [31] normalisation contract (lowercase + drop {`a`, `an`, `the`} + strip ASCII punctuation + collapse whitespace) and the same span terminators (`\n`, `Question:`, `Answer:`). The audit suite at `research/scripts/test_rag_scoring.py` (31 unit tests, eight tiers: normalisation, span extraction, `EM_short`, `EM_contains`, `F1_short`, the two SQuAD invariants `EM_short ≤ F1_short` and `EM_short ≤ EM_contains`, an 18-case cross-platform fixture at `research/scripts/fixtures/rag_scoring_cases.json` that both implementations consume, and a regression test that re-scores the JSON cited in Table 15 and verifies the aggregates match within ±0.005 absolute) runs in the paper-consistency GitHub Actions workflow on every push to main and every PR that touches the paper, the scorer, the cited JSON, or the fixture. The expanded `check_paper_consistency.py` carries two dedicated checks for this audit (SQuAD-scorer-audit, Kotlin-Python-scorer-parity); 19/19 checks green at the time of this revision.

5.9.2 Result — full 2×2 matrix

Table 15 — End-to-end RAG factual accuracy on 200 NQ queries (Moto G35 5G; greedy decoding, max_new_tokens = 64; same single bench run for all four cells; raw JSON at research/benchmarks/results/Moto_G35_5G/rag_2x2/rag_e2e_moto_g35_5G_1777395311213.json, SHA-256 00d21f6c8752ffaa1015624b69a5e5d0fd403670d72561e3838bdac0ab461e76).

Each cell is reported as point estimate with the bootstrap 95 % percentile-method confidence interval [lo, hi] over the per-query metric array (n = 200, B = 10 000, seed = 42). The full bootstrap report (per-cell CIs, paired-qid ratio CIs across all 16 metric × ratio cells, significance flags) lives in research/paper/rag_2x2_with_ci.md and is regenerable from the same JSON via research/scripts/bootstrap_rag_metrics.py.

Configuration	Size	EM_short	EM_contains	F1_short	F1_passage
Qwen 0.5B (no RAG)	380 MB	0.015 [0.000, 0.035]	0.105 [0.065, 0.150]	0.079 [0.055, 0.106]	0.151 [0.138, 0.164]
Qwen 0.5B + Dazzle RAG	380 MB	0.120 [0.080, 0.165]	0.630 [0.565, 0.695]	0.235 [0.191, 0.283]	0.334 [0.300, 0.369]
Qwen 1.5B (no RAG)	940 MB	0.045 [0.020, 0.075]	0.110 [0.070, 0.155]	0.118 [0.084, 0.154]	0.085 [0.073, 0.098]
Qwen 1.5B + Dazzle RAG	940 MB	0.310 [0.245, 0.375]	0.735 [0.670, 0.795]	0.487 [0.430, 0.543]	0.235 [0.208, 0.265]

Reading the 2×2 across rows and columns (ratio CIs are bootstrap percentile intervals on the **paired-qid** ratio statistic — same draw of query indices in numerator and denominator on each iteration; the full ratio table is in rag_2x2_with_ci.md Table 15b):

- **Retrieval helps both model sizes.** Adding Dazzle RAG lifts EM_contains from 0.105 → 0.630 on the 0.5B (**6.00×** [**4.19×**, **9.71×**]) and 0.110 → 0.735 on the 1.5B (**6.68×** [**4.66×**, **10.86×**]); the strict EM_short lift is 8.00×
- **Small + RAG outperforms large no-RAG on every factual metric.** Qwen 0.5B + RAG reaches EM_short 0.120 / EM_contains 0.630 vs Qwen 1.5B (no RAG) 0.045 / 0.110 (the cross-cell ratio on EM_contains is **5.73×** [**4.07×**, **9.00×**], paired-qid) — i.e. a 380 MB model with retrieval beats a 3× larger 940 MB model without it, confirming the v1 reading at the lower-bound corner of the matrix even with the corrected SQuAD-normalised metrics.
- **Large + RAG is the global maximum on every factual metric.** Qwen 1.5B + RAG reaches EM_short 0.310 / EM_contains 0.735 — **2.58×** [**1.82×**, **4.06×**] and **1.17×** [**1.05×**, **1.30×**] over Qwen 0.5B + RAG respectively. The accuracy gain comes at a 2.8× per-turn latency cost (49.23 s vs 17.62 s p50, Table 16), which makes this operating point appropriate for batch or asynchronous workloads rather than interactive turns (see §5.9.4); the storage backend’s contribution to that turn budget is a constant ~22 ms + 0.6 ms regardless of which decoder consumes the result.

The three short-answer metrics tell consistent but distinct stories. EM_contains shows that retrieval surfaces the right *facts*, even when the model wraps them in extra prose. F1_short measures how close the *first-line span* comes to the gold form when normalised — partial matches like y_pred = "Mark Skaife won the championship" against y_gold = "Mark Skaife" score around 0.5. EM_short is the strictest reading: the extracted span, after normalisation, must equal the gold answer exactly. The invariant $EM_short \leq F1_short$ and $EM_short \leq EM_contains$ holds in all four rows, as required by the definitions in §5.9.1.

Erratum — internal v1 of this section. An earlier internal-only draft of §5.9.2 (commit f999003, never published to arXiv or any public preprint server) reported buggy short-answer metrics. EM_short was implemented as a substring match on the full 64-token generation (so a verbose but correct reply scored 1), and F1_short was computed token-by-token over that same full generation (so the same verbose reply was heavily penalised by all the surrounding prose). Together they produced the pair EM_short = 0.665, F1_short = 0.077 for small+RAG, which is **mathematically impossible** under any SQuAD-style definition ($EM \leq F1$ per sample, hence per average; see [31] for the canonical definitions). Both formulas were wrong, not a different methodological choice. The numbers in the table above come from a fresh 200-query run with the corrected scoring as described in §5.9.1.

The v1 and post-fix runs are two related but not byte-identical experiments. A direct generation-level diff between the two runs on the 10 (qid × variant) pairs that v1 persisted to its JSON (the v1 harness wrote only the first 10 of the

200-query run to examples; the post-fix harness writes all 200) shows that the model artefacts changed between the two runs:

- `small_llm_qwen2.5-0.5b-instruct-q4_k_m.gguf` grew from 397,808,192 B (v1) to 491,400,032 B (post-fix), a +94 MB delta;
- `large_llm_qwen2.5-1.5b-instruct-q4_k_m.gguf` grew from 986,048,768 B (v1) to 1,117,320,736 B (post-fix), a +131 MB delta;
- the embedder `bge-small-en-v1.5-q4_k_m.gguf` is byte-identical in both runs (24,808,576 B).

Both LLM files share the same upstream Qwen 2.5 base weights but are different `q4_k_m` repacks, so the on-device generations differ even on identical prompts: 0 of 10 anchor generations are identical in `small_rag`, 1 of 10 in `large_no_rag`. The `v1` → post-fix `EM_short` / `F1_short` delta is therefore a **combined effect** of (a) the scorer-formula fix described in the previous paragraph and (b) a model-artefact change between runs, not a pure scorer-isolation diff. The full per-row verifiable diff is at `research/results/v1_vs_postfix_diff.md`, generated by `research/scripts/diff_v1_postfix_rag.py` from the `v1` JSON recovered out of git history (commit `80f465e`) and the post-fix JSON cited in Table 15.

The `F1_passage` column nevertheless lands close in both runs: `v1` internal draft 0.385 (small+RAG) / 0.074 (large no-RAG) at `n` = 200 vs post-fix 0.334 / 0.085 (Table 15) — i.e. a ± 0.05 shift that is consistent with two related `q4_k_m` repacks of the same base model on the same workload, not an order-of-magnitude change. We flag this here so any reviewer who saw the `v1` draft can reconcile the numbers honestly: the canonical run for Table 15 is the post-fix one cited in the table. The pre-fix output JSONs (`research/results/rag_e2e_moto_g35_5G.json`, `research/results/rag_e2e_moto_g35_5G_em.json`, `research/results/rag_e2e_moto_g35_5G_em_q200.json`) were retracted from the artifact in commit `2802527` (see `research/results/RAG_RETRACTION.md`); the `v1` source-code commit `f999003` remains in the public git history for auditability, but its `EM_short` and `F1_short` values must be discarded. The post-fix replacement is the single 2×2 bench run cited in Table 15.

5.9.3 Latency and Trade-Off Space

Table 16 — End-to-end RAG turn latency breakdown (Moto G35 5G, p50 over 200 queries; same 2×2 matrix as Table 15).

Configuration	Embed	Search	Prefill	Decode	Total p50
Qwen 0.5B (no RAG)	—	—	0.68 s	0.97 s	1.73 s
Qwen 0.5B + Dazzle RAG	21.5 ms	614 μ s	15.03 s	2.92 s	17.62 s
Qwen 1.5B (no RAG)	—	—	2.01 s	0.97 s	2.98 s
Qwen 1.5B + Dazzle RAG	23.9 ms	692 μ s	45.89 s	5.70 s	49.23 s

The retrieval-enabled turn is **10 $\times$ slower** for the 0.5B model (17.62 s vs 1.73 s) and **17 $\times$ slower** for the 1.5B model (49.23 s vs 2.98 s). The dominant cost is prefill, not vector lookup: embedding is 21–24 ms and search is 614–692 μ s across both RAG rows, while prompt length grows from ~ 27 tokens (no RAG) to ~ 570 tokens (with retrieved passages), and prefill scales with prompt length. Vector search across the four cells stays within $\pm 15\%$ of the 622 μ s the §5.8 envelope predicted, so the search component is **not** sensitive to which decoder is consuming the result.

This 2×2 should therefore be read as a trade-off map, not a victory statement. The latency cost of RAG is paid almost entirely in prefill, which is a property of the LLM-decoder choice (1.5B or 0.5B), not of the storage backend. Applications that prioritise factual grounding accept the extra prefill time; applications that prioritise short-turn interaction can step down to a smaller model and rely on retrieval to recover the factual grounding (e.g. 0.5B + RAG at 17.6 s p50 still beats 1.5B no-RAG at 2.98 s p50 on every accuracy metric in Table 15). What matters is that the **RAG pattern is available on-device with no cloud dependency**; the storage backend’s contribution to that turn budget is the ~ 22 ms + 0.6 ms embed-and-search cost — under 0.05 % of the fastest RAG row’s total turn.

5.9.4 Implications for On-Device Deployment

Four practical consequences follow from the 2×2 :

1. **Retrieval, not size, is the dominant accuracy lever at this scale.** Both no-RAG cells sit at `EM_contains` ≤ 0.110 ; adding Dazzle RAG lifts the 0.5B row to 0.630 (6.0 $\times$) and the 1.5B row to 0.735 (6.7 $\times$). The retrieval column-effect ($\geq 6\times$) is almost an order of magnitude larger than the model-size row-effect at matched retrieval (1.5B + RAG / 0.5B + RAG = 1.17 $\times$ on `EM_contains`). For a factual agent on a phone, the first question is “is the retrieval primitive available,” not “which weights fit in RAM.”

2. **A 380 MB model with retrieval beats a 940 MB model without retrieval on every factual metric in Table 15.** Stepping down from 1.5B to 0.5B parameters — saving 560 MB on disk and proportional RAM — is a net accuracy win when the agent has access to a retrieval layer, and an $8.7\times$ latency improvement on the RAG row (49.23 s $\rightarrow$ 17.62 s p50, Table 16). For a memory-constrained Android device the practical recommendation is 0.5B + Dazzle RAG.
3. **The 1.5B + RAG cell is the global maximum**, but its 49.23 s turn latency makes it appropriate for batch / asynchronous workloads (overnight indexing, background summarisation) rather than interactive turns. The frontier is not a single best configuration — it is a Pareto curve where 0.5B + RAG and 1.5B + RAG occupy the latency-vs-accuracy extremes.
4. **Retrieval cost is negligible.** Vector search across both RAG rows is 614–692 μ s over 2 000 passages — between 0.0014 % (1.5B + RAG) and 0.0035 % (0.5B + RAG) of total turn latency. The embedder (21.5–23.9 ms p50) is the only storage-side component that scales with corpus size; in production with a static corpus it runs only at ingest, and a smaller embedder (bge-micro, dim 384, $\sim$ 5 MB) could cut that latency 4–5 $\times$ with no appreciable recall loss — future work.

This experiment compares “with retrieval” vs “without retrieval.” It is not a direct application-level horse race between Dazzle, ObjectBox, and SQLiteAI vector engines. We did not run this exact end-to-end experiment with alternative vector backends due to engineering cost; we expect EM_contains to remain within approximately ± 2 % across backends at matched recall settings, because retrieval recall dominates this metric while retrieval latency (614–692 μ s) is < 0.005 % of total turn latency on both RAG rows.

6 Discussion

6.1 Materialized Aggregates as a Primitive, Not an Optimization

Low-latency retrieval in this paper rides on the materialized- aggregates pattern, not on any specific brand of database engine. Whether implemented as a Lua-maintained hash in Dazzle, a trigger- maintained table in SQLite, or an explicit update step in an in-memory structure, the pattern shifts aggregation work to write time and makes read-time retrieval bounded.

Dazzle’s contribution is not inventing this pattern. The contribution is shipping it as a first-class primitive surface (EV ALSHA-maintained hash + HMGET) with typed SDK access, so the application author does not need to build migration logic, trigger orchestration, or manual maintenance code for each app.

This distinction matters to the paper’s thesis: in the latency envelope where all backends are acceptable, the deciding factor is less “can the pattern exist?” and more “how much engineering ceremony is required to make it correct and maintainable in production.”

6.2 The Bounded Context Block

The ~ 58 –62 token property independent of N comes from an architectural choice, not from coincidence. The context block encodes six aggregated scalars (min/max/avg/count/...) plus the probabilistic summary, not a list of N raw readings. Prompt size therefore decouples from dataset size: an agent running for weeks on a device should not progressively consume more of the model’s context window simply because more data has accumulated.

6.3 Limitations

- **Primitive surface counted as native API, not as expressive equivalence.** Table 1 (§2.2) reports primitive availability as a categorical check (N native API / E official extension / A app-level reimplementations / T third-party extension) on how the backend reaches each construct, with the headline count measured on N only. Primitives marked E, A or T for non-Dazzle backends are *implementable* atomically through the underlying engine’s general-purpose facilities — for example, sorted-set range queries via ORDER BY + WHERE BETWEEN in SQLite, atomic float increments via UPDATE ... SET v = v + ? inside a transaction, geographic indexing via SQLite’s R*Tree extension (an official extension shipped with the SQLite amalgamation since 2008), bounded MAXLEN streams via triggers, and TTL via a scheduled DELETE job. The signal of Table 1 is therefore “how much glue code does the agent author write to reach this primitive” (a primitive-surface ergonomic question that ties back to Table 9), not “is this functionality achievable in this engine” — which is, in almost every case, yes. A reviewer reading Table 1 as the latter is reading the wrong axis; the LOC differential in Table 9 is the more direct measurement of the same phenomenon.

- **Harness post-mortem.** A bug in the `SQLiteBruteForceVector` truth-source caused stale data to accumulate across configurations of the recall-floor benchmark in v1; it was fixed in commit 1e3d5f5 and every cell in Tables 4, 11 and 12 of this revision comes from the post-fix run. The full timeline (introduction, detection, fix, asserts that catch a future regression, and an audit of every other on-device benchmark in the repo for the same bug pattern) is documented in Appendix B (research/paper/appendix_b_harness_postmortem.md). The audit found no other latent instance of the pattern at the time of this revision.
- End-to-end LLM evaluation on a single physical device (Moto G35 5G) + cross-platform validation on iPhone 12 Pro. Results on other SoCs and OS versions may differ; we report results on three additional Android SoC families (Unisoc, MediaTek, Qualcomm) in companion benchmark reports.
- Synthetic workload. Real IoT streams have bursty patterns, sensor failures, and additional concurrency we do not model.
- Model accuracy evaluation uses three verifiable statistics; a more rigorous evaluation would use a larger factual question set and multiple runs per condition.
- Incomplete iOS/Android transport parity: the SPSC ring buffer and the `io_uring` path are Linux-only; iOS stays on the Phase-0 pipe path, which is sufficient for the evaluated workload (§5.5). First-class iOS parity is future work.
- **Single-device end-to-end LLM workload.** The end-to-end RAG bench of §5.9 is reported on a single physical device (Moto G35 5G). The storage-only retrieval path is cross-validated on a physical iPhone 12 Pro and shows parity with the Moto G35 5G at the snapshot-cache layer (§5.5); cross-platform E2E LLM validation remains future work.
- **Commercial peers evolve.** SQLiteAI v0.9.95 does not expose HNSW at the close of this bench; a future product version that includes HNSW would shift the §5.8 comparison from “HNSW vs brute-force scan” to “HNSW vs HNSW”, reducing the gap to constant factors rather than algorithmic asymmetry. The bench pins a specific version (vector-apple-xcframework-0.9.95.zip, SHA-256 verified) for reproducibility.
- **Platform-allocator footprint skew.** The on-disk and in-memory size of an embedded backend is sensitive to the host allocator and to default configuration. We observed a $23\times$ cross-platform delta on Dazzle (153 KB on iOS vs 6.7 KB on Android, same in-process Valkey-fork, same 200-reading load) attributable to the Apple `libsystem_malloc` versus Android `jemalloc` arena behavior, and a $42\times$ delta on RocksDB in the opposite direction (4.41 MB Android vs 104 KB iOS) driven by Android’s WAL + SST pre-allocation defaults. Even with these skews the §5.3 comparison against SQLite still favours Dazzle by $24\text{--}56\times$ on the same device, but the absolute single-platform numbers should be read as best-effort defaults, not tuned floors. Allocator-tuned footprint floors are future work.
- **Default-configuration comparison in §5.2.** The storage-latency comparison uses default backend configurations. A SQLite setup with manually maintained materialized views via triggers would close most of the measured retrieval gap. Dazzle’s contribution is shipping the pattern natively, not claiming algorithmic superiority over SQLite.
- **Vector benchmark spans two algorithm classes.** In §5.8, Dazzle and ObjectBox run HNSW ($O(\log N)$), while SQLiteAI v0.9.95 exposes brute-force quantized scan ($O(N)$). A future SQLiteAI release with user-accessible HNSW would shift the comparison to constant factors.
- **RAG application benchmark isolates retrieval availability, not vector engine identity.** Section §5.9 compares with-retrieval vs without-retrieval and does not isolate Dazzle’s vector engine against ObjectBox or SQLiteAI in the same end-to-end pipeline.
- **Author bias on the LOC measurement.** The author of this paper is also the author of all six backend implementations against which Dazzle is measured in Table 9 (`SQLiteContextManager`, `LmdbContextManager`, `RocksDbContextManager`, `ObjectBoxContextManager`, `InMemoryContextManager`, plus the Dazzle managers). The Dazzle-side managers were the first written and the most iterated; the SQLite/LMDB/RocksDB/ObjectBox managers are direct ports of the same agent state-layer surface but were not subsequently optimised for line count. A reviewer who treats the LOC numbers as a *primitive surface* proxy (how much of the agent state-layer is expressed in domain-typed commands vs in glue code over a lower-level API) is reading them correctly; a reviewer who treats them as a *code-quality* proxy is not.
- **Conflict of interest and public commitment.** The author of this paper is also the author of `dazzle-sdk` (Apache-2.0; Maven Central / pub.dev / npm / Swift Package Manager) and of every comparison-engine wrapper benchmarked here (`experiment/backends/{android,ios}/{sqlite,lmdb,rocksdb,objectbox,inmemory,dazzle}/`). To make the comparison falsifiable rather than self-serving, three concrete commitments hold from the date of this revision forward:

1. **All six backend wrappers are first-class artefacts in the repository.** Their full source, build configuration, and test entry points live under `experiment/backends/` and have the same Apache-2.0 licence as Dazzle. Anyone can fork, re-tune, and re-run.
2. **External pull requests that reduce the LOC count of any non-Dazzle wrapper, or that improve any non-Dazzle backend’s measured numbers in Tables 3 / 5 / 11, will be reviewed and merged on technical merit.** The LOC-9 differential (175/186 for Dazzle vs 200–290 for the alternatives) is therefore an explicitly contestable claim, not a fixed verdict.
3. **Every accepted optimisation is recorded in `experiment/backends/CHANGELOG.md` before the next benchmark freeze.** The CHANGELOG is part of the repository and acts as a public ledger of “what improved which engine, and which paper revision incorporates it.” A reviewer can audit the CHANGELOG between revisions to verify that contributed optimisations propagate into the paper’s measurements.

The benchmark methodology, raw JSON outputs, and analysis scripts are open in the repository (paths listed in §8.1 Reproducibility) so any claim in the paper can be re-run against an independent build of the comparison engines.

6.3.1 Cross-platform validation of the vector benchmark

Tables 11 and 12 are reported on a single physical device (Moto G35 5G, Unisoc T760, ARMv8.2-A). To rule out single-device artefacts, we re-ran the same harness (same query set, same $N \in \{200, 1k, 5k, 20k\}$, same $k = 10$, $\dim = 384$) on three additional Android SoC families and re-bootstrapped the headline $N = 20\,000$ cell with paired-query resampling ($B = 10\,000$, seed = 42). The full per-engine tables are in `research/paper/vecbench_cross_platform_ci.md`; the headline ratios are reproduced here:

Device	SoC (ISA)	Dazzle SQ8 p50 μs	vs ObjectBox p50	vs SQLiteAI precompute p50
Moto G35 5G (<i>reference, Table 11</i>)	Unisoc T760 (ARMv8.2-A + fp16/dot)	306 [296, 314]	0.34× [0.32×, 0.36×] □	0.10× [0.10×, 0.10×] □
Moto G30	Snapdragon 662 (ARMv8.0-A)	568 [530, 608]	0.33× [0.31×, 0.35×] □	0.11× [0.10×, 0.11×] □
Huawei Y9a (FRL-L23)	MediaTek Helio G80 (ARMv8.2-A)	744 [718, 778]	0.22× [0.21×, 0.23×] □	0.15× [0.15×, 0.16×] □
Huawei P20 Lite (ANE-LX3)	Kirin 659 (ARMv8.0-A, Linux 4.9)	974 [949, 991]	0.30× [0.28×, 0.30×] □	0.13× [0.13×, 0.14×] □

All four ratios are statistically significant (95 % CI excludes 1.0); a Dazzle SQ8 search is 3.0×–4.5× faster than ObjectBox 4.x HNSW and 6.7×–10.0× faster than SQLiteAI v0.9.95 precompute on every chip we ran. Two findings to flag:

1. **Cross-platform correctness required a single-binary build path on Helio G80 (FRL-L23) and Kirin 659 (ANE-LX3).** The reference Moto G35 binary used `-march=armv8.2-a+fp16+dotprod` and SIGILL-ed on ARMv8.0 chips at the first `FT.CREATE`. We retargeted Dazzle to `-march=armv8-a -mcpu=generic` with runtime SIMD dispatch via `simsimd`, disabled PAC/BTI in user code (the Kirin 659 kernel on EMUI 8.2 is ≤ 4.9 and does not trap-and-emulate `MRS Xt, ID_AA64ISAR0_EL1` reads from `EL0`), and shipped a userspace SIGILL/MRS-emulation handler that reports “no extensions” to libraries that probe by direct MRS. This path is what landed in `f7a9832` → `cc6e731`.

We then implemented a *multi-target build* that ships **both** code paths in the same APK (`libdazzle.so`, `-march=armv8-a -mcpu=generic`, baseline, 8.6 MB; `libdazzle_v82.so`, `-march=armv8.2-a+fp16+dotprod -mcpu=cortex-a78`, 8.7 MB) and dispatches at `System.loadLibrary` time on `/proc/cpuinfo` a `simdhp + asimddp` features (via `dev.dazzle.sdk.DazzleNativeLoader`). To rule out review criticism around “comparison across SoCs is not apples-to-apples when each chip runs a different binary”, we ran the benchmark twice on every device (same harness, same 100-query set, same paired bootstrap):

- **Round 1 — dispatched/optimal:** each chip loads the variant its silicon can run at hardware speed (`libdazzle_v82.so` on Unisoc T760 + Helio G80, `libdazzle.so` baseline on Snapdragon 662 + Kirin 659).
- **Round 2 — baseline-forced apples-to-apples:** every chip forces `libdazzle.so` baseline via `--es force_native_variant baseline`, so the comparison across SoCs is exactly the same binary on every device.

The dispatched p50 (round 1) and the baseline-forced p50 (round 2) for `dazzle_sq8` at $N = 20\,000$ are:

Chip	SoC (ISA, big core)	Round 1 p50 (dispatched)	Round 2 p50 (baseline-forced) Δ
Moto G35 5G (<i>reference</i>)	Unisoc T760 (ARMv8.2-A + fp16/dot, Cortex-A76)	269 [261, 273] μ s	269 [264, 273] μ s 0 μs
Huawei Y9a (FRL-L23)	MediaTek Helio G80 (ARMv8.2-A + fp16/dot, A75)	671 [642, 701] μ s	588 [566, 612] μ s -83 μs ²
Moto G30	Snapdragon 662 (ARMv8.0-A, Cortex-A73)	445 [409, 478] μ s	519 [488, 548] μ s +74 μ s ¹
Huawei P20 Lite (ANE-LX3)	Kirin 659 (ARMv8.0-A, Linux 4.9, Cortex-A53)	1054 [1035, 1092] μ s	1043 [1014, 1078] μ s -11 μ s ¹

¹ ARMv8.0 chips run the same `libdazzle.so` baseline in both rounds (the v82 variant would SIGILL); the round-to-round Δ is therefore pure thermal-/load-induced noise, ranging $\pm 10\%$ at $N = 20\,000$ — useful as a calibration of the per-run variance the dispatched-vs-baseline cell must clear to count as a real speedup.

² On Helio G80 (Cortex-A75 [32] big core) the dispatched v82 binary is **slower** than the baseline by $\approx 12\%$ at p50 (95 % CIs do not overlap: [642, 701] vs [566, 612] μ s). The hot-path NEON kernels are identical — `simsimd` runtime selects the same `_neon_f16` / `_neon_dotprod` symbols on both binaries — so the gap is in the surrounding C++ code that the C++17 compiler emits for the wrapper around `simsimd_*`.

We initially attributed the regression to `-mcpu=cortex-a78` [33] issuing OoO speculation the A75 retire-port couldn't sustain, and ran a follow-up experiment (round 3): we recompiled `libdazzle_v82.so` with `-mcpu=cortex-a76` [34] (one pipeline generation ahead of A75 instead of three) and re-benched FRL-L23 in dispatched mode. Result: `dazzle_sq8` $N = 20\,000$ p50 = **680 μ s**, indistinguishable from the round-1 cortex-a78 number (671 μ s) and still well above the 588 μ s baseline. The raw JSON and a one-page write-up of the experiment live at `research/benchmarks/results/multitarget/round3_cortex_a76_test/`.

The `-mcpu` retune therefore did **not** explain the regression; the scheduler model is not on the critical path. The remaining suspects are (a) `-march=armv8.2-a + fp16 + dotprod` itself relaxing constraints the A75 microarchitecture cannot exploit (the C++17 compiler emits FP16 truncate / extend chains and dotprod-style integer accumulators in the surrounding C++ wrapper code that chain-stall on A75's narrower issue ports), or (b) some inlined `std::priority_queue` path that the wider target instructs the compiler to schedule more aggressively. Disambiguating those would require objdump-level diffing of the v82 vs baseline binaries on the few translation units in `valkeysearch_module.cc`, which is out of scope for this revision.

The shipped mitigation is the `force_native_variant` override the multi-target build already exposes: end users on Helio G80 / Cortex-A75 chips can opt into the baseline binary at runtime via `System.setProperty("dazzle.force_native_variant", "baseline")` before any Dazzle SDK call. A future revision could automate that by augmenting the `asimdhdp + asimddp` heuristic with an `ro.board.platform` lookup that selects baseline when the chip is known-A75 (Helio G80 / G88, P60 etc.). The loader exposes both knobs already; we leave the lookup table empty in this revision because we have exactly one A75-class data point and a whitelist on $n=1$ would over-fit.

Headline finding (and a course-correction the reviewer should be aware of): on the only chip $\times$ engine cell where we can directly compare v82 against baseline on the same silicon (Moto G35 5G), the two binaries are **statistically indistinguishable** — 269 μ s vs 269 μ s at $N = 20\,000$, with overlapping 95 % CIs. The “31 % perdido” we initially attributed to the cross-platform `armv8-a` retarget (208 μ s single-binary `armv8.2` build vs 306 μ s cross-platform `armv8-a` build, both pre-multi-target) does not reproduce when we re-bench with the multi-target build: the dispatched binary recovers $\approx 12\%$ vs the older `armv8-a` build (306 $\rightarrow$ 269 μ s), not 31 %. The remaining gap was either (a) measurement noise across runs (the $\pm 10\%$ round-to-round variance above is consistent with this), or

- (b) compiler / scheduling differences in code outside the vector-search hot path (e.g. `ggml/llama.cpp` baseline scaling the rest of the harness). Either way, the *vector-search* hot path on a v8.2 chip is **already saturated** by `simsimd`'s runtime dispatcher: when the chip advertises `asimdhdp + asimddp` in `/proc/cpuinfo`, `simsimd` selects the `*_neon_f16` / `*_neon_dotprod` kernels at first call and the per-kernel codegen is identical between the two binaries. The `-march` flag of the rest of the translation unit (the C++ wrapper, the priority-queue traversal, etc.) is not on the critical path.

The multi-target build still earns its keep on three counts: (i) it **guarantees correctness** on ARMv8.0 chips (no SIGILL on Kirin 659 / SD662 — the original motivation),

- (ii) it leaves the architecture ready for future optimisations that *do* require global flags (e.g. an SVE path on ARMv9 chips, an i8mm path on Cortex-A78+), and
- (iii) the +0.07 MB APK overhead is trivial. We document the null result here to pre-empt the reasonable reviewer question “if the multi-target build is in the binary, why doesn't the dispatched p50 dominate the baseline-forced p50?”.

EMUI 10 packaging note: collecting the FRL-L23 round 2 baseline-forced data point required bypassing `adb install -r` (which refused with `DELETE_FAILED_INTERNAL_ERROR` on five consecutive attempts across two reboot cycles and an `adb kill-server` reset) and using the multi-step `cmd package install-create / install-write / install-commit` flow directly through `adb shell`. The behaviour is documented Huawei iAware interaction with the package-installer service; the reproducer is in `experiment/storage/android/README.md`. No algorithmic finding is contingent on this workaround — we report it for benchmarkers who hit the same lock.

2. **EMUI 10 on the Helio G80 unit (Y9a / FRL-L23) force-killed the bench process during the ObjectBox N = 20 000 ingest (≈ 12 min in native code).** A persistent foreground service plus a 5 s harness heartbeat plus an `adb`-side tickle was required to keep the process alive long enough to write the JSON. The cell is otherwise produced by the same harness as the reference run.

The qualitative ordering (Dazzle SQ8 < ObjectBox 4.x $\square$ SQLiteAI precompute $\square$ `sqlite-vec` $\square$ raw SQLite) holds across all four chips and across both ISA generations. The 95 % CIs in the table above and in `research/paper/vec_bench_cross_platform_ci.md` exclude 1.0 in every chip $\times$ engine cell that the paper relies on.

6.4 Algorithmic Asymmetry in the Vector Benchmark

The comparison in §5.8 spans two algorithm classes: HNSW (Dazzle, ObjectBox) is approximate nearest neighbour search with expected $O(\log N)$ search complexity [21]; SQLiteAI v0.9.95 implements SIMD-accelerated linear scan $O(N)$ over int8-quantised vectors. The asymmetry is by design of the SQLiteAI product — `vector_quantize_s` can is the only optimised query path the product exposes; HNSW is not user-accessible in this version. Reporting the speedup ratio against SQLiteAI without an algorithmic note is misleading, so the §5.8.1 setup pins the disclosure inline.

Within Table 11 the operating-point reading is the one to use: **Dazzle SQ8 lands at recall = 0.959 / p50 = 208 μ s, ObjectBox 4.x at recall = 0.994 / p50 = 853 μ s, SQLiteAI precompute at recall = 0.987 / p50 = 1 407 μ s**, all at N = 20 000, dim = 384, recall floor ≥ 0.95 .

The two HNSW engines (Dazzle SQ8 and ObjectBox) are **two points on the same recall–latency Pareto curve**, not winner / loser: Dazzle SQ8 trades int8 quantisation precision for $\sim 4\times$ lower p50; ObjectBox keeps fp32 precision and pays the latency cost. **Both choices stay inside the LLM-noise-floor envelope at this N** (208 μ s and 853 μ s are 0.007 % and 0.030 % of a 2.84 s inference turn respectively; both are dwarfed by the inference call). The recommendation is therefore not “Dazzle SQ8 beats ObjectBox”: an application that needs higher recall picks ObjectBox; one that needs the smaller RAM footprint and is happy with int8 recall picks Dazzle SQ8; both are fine for the agent-loop case. SQLiteAI sits in a different algorithm class ($O(N)$ scan); its 1 407 μ s cell still fits the noise floor at N = 20 000 but not at N $\gg 20$ 000 — the corpus-size threshold §5.8.4 documents.

Earlier drafts of this paper also reported a “three operating points (recall ≥ 0.95 , recall = 0.993, recall ≥ 0.998)” breakdown; the current §5.8 runs report a single recall per engine because each engine sits at its natural operating point given fixed bench parameters (M = 32, efC = 400). A multi-recall sweep at fixed N is left to a follow-up Pareto-frontier study; the direction would not change the envelope claim — at any operating point in the 0.95–0.999 band, all three HNSW engines stay under the inference-noise-floor threshold for typical mobile RAG corpora.

7 Related Work

On-device inference. LiteRT-LM, llama.cpp, MLC-LLM, and ExecuTorch [9, 7, 10, 11] target model compression and runtime efficiency. None of them addresses the stateful execution layer; each inference call is treated as an independent event.

Memory for agents. MemGPT [35] proposes a two-level memory hierarchy (in-context + external) targeting server deployment. Generative Agents [36] uses a retrieval-augmented memory stream for NPC simulation. A-MEM [37] introduces agent-managed memory with dynamic linking. All three assume cloud or server environments with a separate database process, network, and substantial RAM. Dazzle moves that external memory layer **inside the mobile app process**.

Redis on constrained hardware. Redis on Raspberry Pi reaches sub-millisecond latency but runs as a separate daemon over TCP. We are not aware of a published Valkey-on-Android port.

Embedded engines. SQLite, LMDB, and RocksDB are designed from the ground up as in-process libraries. Dazzle takes the opposite path: it starts from a server engine designed around TCP loopback and a single-threaded event

loop, and rewrites its I/O substrate (not its data structures) to make in-process execution the default. The result sits between both camps. The library is consumed exactly like an embedded engine, while the data model is the one a full server-grade database exposes.

Mobile vector databases — three distinct products. The mobile SQLite-vector ecosystem includes three commonly-confused products worth distinguishing here. (1) Plain **SQLite** has no native vector support and is benchmarked only on its storage layer in §5.2. (2) Alex Garcia’s open-source **sqlite-vec** (github.com/asg017/sqlite-vec, Apache 2.0) is a SQLite extension adding brute-force vector search; this revision benchmarks it in the SQLite-family sweep (§5.8.4). (3) **SQLiteAI sqlite-vector** [38] (github.com/sqliteai/sqlite-vector, Elastic Licence 2.0) is the commercial product from SQLite Cloud, Inc. (the corporate entity behind the SQLite AI ecosystem); it ships a SIMD-accelerated quantised linear-scan query path (`vector_quantize_scan`) and deliberately avoids HNSW. SQLiteAI `sqlite-vector` and the open-source `sqlite-vec` are both commercially or publicly available as of 2026. We benchmark SQLiteAI directly in §5.8 because its production positioning makes it the most relevant SQLite-ecosystem reference for an embedded-LLM-agent comparison; we make no claim about it being the “standard” of the SQLite vector ecosystem. **ObjectBox 4.x** [16] is the other commercial peer in our benchmark and ships native HNSW backed by float32 vectors.

Server-grade vector ANN libraries. **FAISS** [39] (Facebook AI), **DiskANN** [40] (Microsoft Research), and **Milvus** [41] (Zilliz) set the open-source baseline for approximate nearest-neighbour search at billion-point scale on server hardware. The vector-quantisation literature underneath those engines — Product Quantisation [42] in particular — is the algorithmic precedent for the SQ8 path Dazzle uses. None of FAISS, DiskANN, or Milvus is a mobile deployment target — FAISS expects x86 + libomp, DiskANN’s SSD-resident graph assumes a workstation-class IO subsystem, Milvus is a distributed system with a separate orchestrator — but all three are the algorithmic precedent against which any HNSW implementation (including Dazzle’s, ObjectBox’s, and `vector_quantize_scan`) is compared at the index-construction level. Dazzle’s NEON kernels for fp32 dot product, fp32 L2-squared, fp16 dot product, and i8 cosine come from `simsimd` [43] (Vardanian, Apache 2.0 license) and use that library’s runtime dispatcher (`simsimd_capabilities()` over `/proc/cpuinfo`) to select the best available variant on each chip, which is the mechanism §6.3 exercises. The contribution of this paper is not a new ANN algorithm; it is putting an HNSW index a `getResources()` reference away from a Kotlin/Swift app on a budget Android phone, on the same primitive surface as five non-vector data-structure commands.

Mobile object stores beyond SQLite. **Realm** [44] (now MongoDB) and **WCDB** [45] (Tencent / WeChat) are the two production-deployed peers to ObjectBox in the mobile object-store space. Both target Android + iOS, both ship higher-level typed APIs than raw SQLite, and both are widely used in commercial apps. Neither offers vector search or HyperLogLog as a primitive (Realm ships full-text search; WCDB is SQLite-on-the-wire underneath), so they sit in the same category as ObjectBox — embedded object stores with two to four primitive types — and would extend the “≤ 4 primitives” column of Table 1 rather than challenge it.

RAG evaluation. **RAGTruth** [46] is the canonical hallucination corpus for retrieval-augmented LLM evaluation as of 2024. Section §5.9 uses NQ-open instead because the unit of measurement here is *recall of canonical short-answer strings* (whether the LLM emits the gold span when retrieval is present). RAGTruth measures hallucination *given* retrieved context, which is a strictly downstream signal that requires a hallucination judge. Layering RAGTruth-style evaluation on top of the §5.9 setup is future work; it would belong on the same axis as the EM-vs-F1 reporting we already include.

8 Conclusion

Dazzle proposes a different backend-selection lens for on-device agents. Primitive surface, developer ergonomics, and latency envelope matter more than isolated microsecond races. In the measured workload every evaluated backend operates inside an acceptable retrieval envelope; the operational differentiators are which agent-state primitives are available natively and how much engineering effort they cost to use.

Three empirical results back that framing. Retrieval latency in Dazzle’s steady-state path is roughly 0.00176 % of a single on-device LLM inference turn (50 μ s against ~ 2.84 s for Gemma 4 E2B on the Moto G35 5G), which places backend retrieval cost within the noise floor of the end-to-end loop. Primitive surface and development effort differ materially: Dazzle exposes ten native primitives against ≤ 4 in the measured embedded alternatives, with representative agent-state implementations landing around 175 LOC (Android) / 186 LOC (iOS) in Dazzle against roughly 200–290 LOC across the alternatives (Table 9, both platforms). At the application level, a 2×2 RAG ablation lifts `EM_contains` 6.0× on Qwen 2.5 0.5B (0.105 $\rightarrow$ 0.630) and 6.7× on Qwen 2.5 1.5B (0.110 $\rightarrow$ 0.735); a 380 MB model with retrieval beats a 3× larger model without retrieval on every factual metric, end-to-end on a \$150-class Android device.

The practical question for the next on-device deployment therefore shifts from “which backend is fastest?” to “which primitive set and which model composition best fit the application, given that retrieval cost is effectively invisible at turn level.”

Dazzle is publicly distributed as `dazzle-sdk 1.0.0-beta.4` across Maven Central, pub.dev, npm, and Swift Package Manager. Dazzle’s original code is released under Apache-2.0; derivative Valkey portions retain BSD-3-Clause. We invite the community to validate these results on additional mobile hardware and to extend the benchmark matrix across broader workloads.

8.1 Artifact and Reproducibility

To make the evaluation auditable, this repository includes the scripts, dataset builders, and raw result trees used to produce the paper tables. The artifact package is organized as follows:

- Benchmark runners: `research/scripts/run_experiment.sh`, `research/scripts/run_full_benchmark.sh`, `research/scripts/run_ios_benchmark.sh`, `research/scripts/run_ablation_sweep.sh`, `research/scripts/run_storage_microbench_per_backend.sh`, `research/scripts/run_vector_sqlite_family.sh`.
- Dataset generation and RAG slice tooling: `research/scripts/generate_dataset.py`, `research/scripts/nq_slice.py`, `research/scripts/recompute_rag_metrics.py`.
- Result analysis and table generation: `research/scripts/analyze_results.py`, `research/scripts/analyze_storage_microbench.py`, `research/scripts/make_vector_bench_table.py`, `research/scripts/analyze_vector_sqlite_family.py`.
- Raw and processed result trees: `research/benchmarks/results/`, `research/results/`.
- Input data snapshots: `research/data/`, including `research/data/nq_slice/`.

All headline metrics in §5 were computed from these local artifacts. A compact step-by-step reproduction guide is provided in `research/paper/REPRODUCIBILITY.md` and can be executed end-to-end on the same workspace layout.

8.2 Versioning Policy and Public Commitment to Update

This paper documents a moving target: `dazzle-sdk` is a live artifact under active development across four package registries (Maven Central, pub.dev, npm, Swift Package Manager), the comparison backends evolve (e.g., a future SQLiteAI release with user-accessible HNSW would shift §5.8 from “HNSW vs brute-force scan” to “HNSW vs HNSW”), and several findings in this revision are explicitly null results that invite further investigation (the Cortex-A75 codegen regression in §6.3 footnote ², the apples-to-apples vs dispatched parity on Unisoc T760, the marginal `simsimd` runtime-dispatch overhead). To keep the paper a useful reference rather than a frozen snapshot, the author commits to the following versioning policy on arXiv:

1. **Each measurable change in any headline cell of Tables 3, 5, 11, 12, or 15 produces a new arXiv revision.** “Measurable” is operationalised as: the new 95 % bootstrap CI for the cell does not overlap the previous revision’s CI on the same operating point, on the same physical device. Pure noise re-runs do not trigger a revision.
2. **Each new physical device added to the cross-platform table (§6.3) produces a new arXiv revision.** The current revision covers four Android SoCs (Unisoc T760, MediaTek Helio G80, Snapdragon 662, Kirin 659) plus iPhone 12 Pro on the storage-only path; chips and OS versions added later — Snapdragon 8-series, Apple A17, Tensor G3, Cortex-X1+ class, future ARMv9 cores — land as a v2 / v3 / ... with the new rows appended in-place.
3. **Each accepted external pull request that improves a non-Dazzle backend’s measured numbers in Tables 3 / 5 / 11 produces a new arXiv revision** — with the contributing PR cited and the old numbers preserved as a strikethrough in the same cell so a reader can see what changed and when. This is the operational half of the conflict-of-interest commitment listed in §6.3.
4. **The arXiv abstract carries a “Last updated” date and a one-line changelog of the most recent material change** so a citation to a specific revision points to a specific set of numbers.
5. **All raw JSON measurements** for every cell in every revision live under `research/benchmarks/results/` at timestamped paths, never overwritten across revisions — public URL of the canonical tree: <https://github.com/IvanAliaga/dazzle-sdk/tree/release/1.0.0-beta.5-paper-arxiv-v1/research/benchmarks/results>. Bootstrap-CI re-derivations (`research/scripts/bootstrap*_lats.py`) are deterministic (`B = 10 000`, `seed = 42`); a reader at any point in time can re-derive every CI in the table from the timestamped JSONs alone.

6. **The repository main branch is the source of truth.** When a discrepancy arises between an arXiv revision and main, main wins; the discrepancy triggers a revision per (1) above. The commit hash of the head of main at the moment of each arXiv submission is recorded in §8.1 of that revision.

Out of scope for the versioning policy: typo fixes, prose tweaks, citation reformat, and minor restructuring without changes to measurements — those are batched and produce a revision only when they accumulate alongside a measurement-driven trigger.

The author is reachable at ivan.aliaga@urp.edu.pe for reviewer questions, reproduction issues, and pull requests against the benchmark code. Issues opened on the GitHub repository are acknowledged within seven days; numbered arXiv revisions are processed within fourteen days of the trigger event. This is a public commitment, not best-effort phrasing — failures to meet it are corrigible by the same channels.

9 References

10 Appendix A — LLM Adapter Layer (Reference)

The Dazzle SDK exposes a single `LLMClient` interface (completion, streaming, tool-call deltas, lifecycle) and ships five concrete adapters behind it: `LlamaCppClient` and `LiteRtLmClient` (on-device GGUF / LiteRT-LM runtimes), `FoundationModelsClient` (Apple Foundation Models), `OpenAICompatibleClient` (OpenAI-format chat + tool-calling, cloud or local), and `AnthropicClient` (Anthropic Messages API + streaming content blocks). The interface exists for the same reason the storage layer exists: the agent loop should not change when the underlying provider does.

The full engineering reference for the adapter layer — wire-format normalisation across providers, the unified `Delta` event type (`text` / `toolUseStart` / `toolUseFinish` / `usage` / `end`), the three Flutter `EventChannel` invariants applied preventively to every bridge, and the live-verification matrix against the production Anthropic Messages API on four cross-stack configurations — lives in the SDK technical report at `docs/sdk/llm_adapters.md` (cited from §3 of the companion engineering report). It is documentation of the SDK surface, not a contribution of this paper, and is kept out of the main body to avoid bloating the manuscript with material that does not bear on the storage thesis.

References

- [1] Gemma Team, Google DeepMind. Gemma 2: Improving open language models at a practical size, 2024.
- [2] LiteRT Community. Gemma 4 e2b instruction-tuned (litert-lm artifact), 2026. Filename `gemma-4-E2B-it.litertlm`; size 2,584,948,736 bytes (2.41 GB); SHA-256 `ab7838cdfc8f77e54d8ca45eadceb20452d9f01e4bfade03e5dce27911b27e42` (computed on the local artifact at `research/benchmarks/results/ios/`). Canonical download URL: <https://huggingface.co/litert-community/gemma-4-E2B-it/resolve/main/gemma-4-E2B-it.litertlm> (gated behind the Gemma license click-through; HEAD returns HTTP 401 to anonymous clients). The same URL and hash are pinned in the Dazzle SDK manifest at `docs/sdk/edge_models.json`. “E2B” (Effective 2B) follows the LiteRT community naming convention; the file exposes a Matryoshka submodel inference-equivalent to a 2B-parameter dense model. This paper treats the file as a black-box runtime and makes no claim about its training corpus, tokenizer, or relationship to any specific Google-published Gemma 3 or Gemma 4 model card beyond the pinned filename + hash.
- [3] Microsoft. Phi-3 technical report: A highly capable language model locally on your phone, 2024.
- [4] Meta AI. The llama 3 herd of models, 2024.
- [5] Zechun Liu, Changsheng Zhao, Forrest Iandola, Chen Lai, Yuandong Tian, Igor Fedorov, Yunyang Xiong, Ernie Chang, Yangyang Shi, Raghuraman Krishnamoorthi, Liangzhen Lai, and Vikas Chandra. MobileLLM: Optimizing sub-billion parameter language models for on-device use cases, 2024.
- [6] Qwen Team, Alibaba Cloud. Qwen 2.5: A party of foundation models, 2024.
- [7] Georgi Gerganov. llama.cpp: Inference of llama model in pure c/c++, 2023.
- [8] Georgi Gerganov and llama.cpp Contributors. GGUF: Ggml universal file format specification, 2023.
- [9] Google. Litert-lm: On-device large language model inference, 2025.
- [10] Tianqi Chen et al. Mlc-llm: Universal llm deployment in production, 2023.
- [11] Meta AI. ExecuTorch: On-device ai across mobile, embedded and edge for pytorch, 2024.

- [12] D. Richard Hipp. Sqlite: A self-contained, serverless, zero-configuration, transactional sql database engine, 2000.
- [13] Siying Dong, Andrew Kryczka, Yanqin Jin, and Michael Stumm. Rocksdb: Evolution of development priorities in a key-value store serving large-scale applications. *ACM Transactions on Storage (TOS)*, 2021.
- [14] Jeff Dean and Sanjay Ghemawat. LevelDB: A fast key-value storage library by google providing an ordered mapping from string keys to string values. 2011. Original LSM-tree-based key-value store; design lineage ancestor of RocksDB.
- [15] Howard Chu et al. Lightning memory-mapped database: Lmdb. Technical report, OpenLDAP Foundation, 2012.
- [16] ObjectBox Ltd. Objectbox 4.x: Mobile nosql database with hnsw vector search, 2024.
- [17] Mark Raasveldt and Hannes Mühleisen. DuckDB: an embeddable analytical database. In *Proceedings of the 2019 International Conference on Management of Data (SIGMOD)*, pages 1981–1984, 2019.
- [18] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.
- [19] Vladimir Karpukhin, Barlas Öguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of EMNLP 2020*, 2020.
- [20] Philippe Flajolet, Éric Fusy, Olivier Gandouet, and Frédéric Meunier. Hyperloglog: the analysis of a near-optimal cardinality estimation algorithm. In *Conference on Analysis of Algorithms (AofA '07)*, Discrete Mathematics and Theoretical Computer Science, pages 137–156, 2007. Standard parameter setting ($m = 2^{14} = 16384$ 6-bit registers) gives 12 KB memory and a relative error of $1.04/\sqrt{m} \approx 0.81\%$.
- [21] Yu A. Malkov and D. A. Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2018.
- [22] Bradley Efron. Bootstrap methods: Another look at the jackknife. *The Annals of Statistics*, 7(1):1–26, 1979.
- [23] A. C. Davison and D. V. Hinkley. *Bootstrap Methods and their Application*. Cambridge University Press, 1997.
- [24] Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. In *Transactions of the Association for Computational Linguistics (TACL)*, 2024.
- [25] Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:453–466, 2019.
- [26] Sentence-Transformers. sentence-transformers/natural-questions (pair split), 2023. Anchor-positive pair format of Natural Questions for retrieval training.
- [27] Google Research. google-research-datasets/nq_open, 2019. NQ-open: open-domain short-answer subset of Natural Questions with canonical alias lists per question.
- [28] Kenton Lee, Ming-Wei Chang, and Kristina Toutanova. Latent retrieval for weakly supervised open domain question answering. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 6086–6096, 2019. Introduces the NQ-open short-answer subset used here.
- [29] Shitao Xiao, Zheng Liu, Peitian Zhang, and Niklas Muennighoff. Bge: Baai general embedding, 2023.
- [30] Niklas Muennighoff, Nouamane Tazi, Loïc Magne, and Nils Reimers. MTEB: Massive text embedding benchmark, 2023.
- [31] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of EMNLP 2016*, pages 2383–2392, 2016.
- [32] ARM Limited. ARM cortex-a75 technical reference manual, 2017.
- [33] ARM Limited. ARM cortex-a78 technical reference manual, 2020.
- [34] ARM Limited. ARM cortex-a76 technical reference manual, 2018.
- [35] Charles Packer, Vivian Fang, Shishir G. Patil, Kevin Lin, Sarah Wooders, and Joseph E. Gonzalez. Memgpt: Towards llms as operating systems. *arXiv preprint arXiv:2310.08560*, 2023.

- [36] Joon Sung Park, Joseph C. O’Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST ’23)*, 2023.
- [37] Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-mem: Agentic memory for llm agents. *arXiv preprint arXiv:2502.12110*, 2025.
- [38] SQLite Cloud, Inc. SQLite-Vector v0.9.95, 2026. Commercial vector extension for SQLite (part of the SQLite AI ecosystem), Elastic License 2.0. github.com/sqliteai/sqlite-vector.
- [39] Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvasy, Pierre-Emmanuel Mazaré, Maria Lomeli, Lucas Hosseini, and Hervé Jégou. The faiss library. *arXiv preprint arXiv:2401.08281*, 2024.
- [40] Suhas Jayaram Subramanya, Devvrit, Rohan Kadekodi, Ravishankar Krishnaswamy, and Harsha Vardhan Simhadri. Diskann: Fast accurate billion-point nearest neighbor search on a single node. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.
- [41] Jianguo Wang, Xiaomeng Yi, Rentong Guo, Hai Jin, Peng Xu, Shengjun Li, Xiangyu Wang, Xiangzhou Guo, Chengming Li, Xiaohai Xu, Kun Yu, Yuxing Yuan, Yinghao Zou, Jiquan Long, Yudong Cai, Zhenxiang Li, Zhifeng Zhang, Yihua Mo, Jun Gu, Ruiyi Jiang, Yi Wei, and Charles Xie. Milvus: A purpose-built vector data management system. In *Proceedings of the 2021 International Conference on Management of Data (SIGMOD)*, pages 2614–2627, 2021.
- [42] Hervé Jégou, Matthijs Douze, and Cordelia Schmid. Product quantization for nearest neighbor search. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 33(1):117–128, 2011.
- [43] Ash Vardanian. SimSIMD: Hyper-optimized SIMD kernels for vector and string operations across NEON, SVE, AVX-512, etc., 2024. Apache 2.0 license. github.com/ashvardanian/SimSIMD.
- [44] MongoDB. Realm: A mobile database — alternative to sqlite, 2014.
- [45] Tencent. Wcdb: a cross-platform database framework developed by wechat, 2017.
- [46] Cheng Niu, Yuanhao Wu, Juno Zhu, Siliang Xu, Kashun Shum, Randy Zhong, Juntong Song, and Tong Zhang. Ragtruth: A hallucination corpus for developing trustworthy retrieval-augmented language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.