GMF AeroAsia
GARUDA INDONESIA GROUP

GARUDA MAINTENANCE FACILITY
ENGINE MAINTENANCE SERVICES

APU CONDITION TEST SHEET

APU TYPE	: GTCP 85 - 129H/J/K	TSN / TSO	: 26363	REPORT No.	: 212025
SERIAL No.	: P.100035	Job. No.	: 420113189	RUNNING TIME	: 220 MINUTES
OWNER	: GMF	TYPE OF TEST	: PERFORM	DATE	: 14-SEP-2012
Reference	: HONEYWELL, CMM	49 - 25 - 45., Doc No: 19318		FUEL USED	: 350 liter
TEST RESULT	: ACC				

DESCRIPTION	UNIT	LIMIT	PERFORMANCE 1125 F	PERFORMANCE 115 0 F	PERFORMANCE 1175 F	PERFORMANCE 1200 F
BAROMETRIC PRESSURE	mBar	obs	1011.50	1011.63	1011.71	1011.83
AIR INLET TEMPERATURE	F	130 max	93	93	92	90
OIL TEMPERATURE	F	270 max	116	117	116	113
FUEL INLET TEMPERATURE	F	110 max	103	104	104	103
FUEL INLET PRESSURE	PSIG	38 ±2	36	36	36	36
FUEL DISCH.PRESSURE	PSIG	obs	413	419	426	438
OIL DISCH.PRESSURE	PSIG	95 ±5	94	94	94	94
FUEL FLOW	PPH	obs	-	-	-	-
EGT (TEST CELL)	F	1200	1125	1150	1176	1200
EGT ENGINE / ETC	F	±30	1102	1127	1157	1185
VIBRATION GEARCASE	mils	0.6	0.1	0.1	0.1	0.1
VIBRATION TURBINE	mils	0.4	0.1	0.1	0.1	0.1
BEARING CAVITY PRESSURE	INHG	0 to -25	-16.9	-16.8	-16.7	-16.5
GEAR CASE PRESSURE	INHG	-3 to -10	-3.8	-3.9	-3.8	-3.87
BLEED AIR TOTAL PRESSURE	INHG	obs	71.3	70.8	69.9	70.0
BLEED AIR ORIF. PRESSURE	INHG	obs	70.9	70.3	69.5	69.7
BLEED AIR DIFF. PRESSURE	INHG	obs	1.2	1.3	1.4	1.5
AIR PRESS. REGULATOR	INHG	37.6 to 39.7	38	38.1	38	38.1
BLEED AIR TEMPERATURE	F	obs	452	450	450	451
BLEED ORIF. TEMPERATURE	F	obs	433	433	433	430
SPEED	RPM	40400-41700	41512	41530	41544	41560
GENERATOR LOADING	KW	18	18	18	18	18
WB STANDARD	Lb/min		90.01	93.52	96.31	99.09
PB STANDARD	INHG		100	100	99	99
TB STANDARD	F		459	458	458.13	461.151
WF STANDARD	PPH		-	-	-	-
SHAFT OUTPUT	SHP		30	30	30	30

OPERATOR:	OBSERVER:
AB HARTONO	EFI SASMITA