GMF AeroAsia
GARUDA INDONESIA GROUP

GARUDA MAINTENANCE FACILIY
ENGINE MAINTENANCE SEVICES

APU CONDITION TEST SHEET

APU TYPE	: GTCP 85 - 129H/J/K	TSN / TSO	: 36856	REPORT No.	: 210020
SERIAL No.	: P- 100575	Job. No.	: 4200886 19	RUNNING TIME	: 123 Min.
OWNER	: G.A	TYPE OF TEST	: PERFORM	DATE	: 2 AUG '20
TEST RESULT	:	Ref: 49 - 25 - 45., Doc No: 19318		FUEL USED	: 200 LTR

DESCRIPTION	UNIT	LIMIT	RUN IN IDLE	ZERO LOAD	CONTROLING	PERFORMANCE
BAROMETRIC PRESSURE	mBar	obs	1008.7	1007.90	1007.8	1008.7
AIR INLET TEMPERATURE	F	130 max	89	92	93	97
OIL TEMPERATURE	F	270 max	158	195	199	210
FUEL INLET TEMPERATURE	F	110 max	90	101	101	107
FUEL INLET PRESSURE	PSIG	38 ±2	36	36	36	36
FUEL DISCH.PRESSURE	PSIG	obs	367	369	390	425
OIL DISCH.PRESSURE	PSIG	95 ±5	98	96	95	95
FUEL FLOW	PPH	obs	-	-	-	-
EGT (TEST CELL)	F	1200	730	749	1045	1200
EGT ENGINE / ETC	F	±30	708	732	1075	1220
VIBRATION GEARCASE	mils	0.6	0.1	0.1	0.1	0.1
VIBRATION TURBINE	mils	0.4	0.1	0.1	0.1	0.1
BEARING CAVITY PRESSURE	INHG	0 to -25	-17.8	-19.9	-19.7	-20.4
GEAR CASE PRESSURE	INHG	-3 to -10	-3.5	-3	-3.0	-3.5
BLEED AIR TOTAL PRESSURE	INHG	obs	Z	Z	3.9	66.5
BLEED AIR ORIF. PRESSURE	INHG	obs	Z	Z	3.8	66.1
BLEED AIR DIFF. PRESSURE	INHG	obs	Z	Z	4"Hg	2"Hg ≈ 27.2
AIR PRESS. REGULATOR	INHG	37.6 to 39.7	39.7	38.0	36.1	38.1
BLEED AIR TEMPERATURE	F	obs	Z	Z	423	432
BLEED ORIF. TEMPERATURE	F	obs	Z	Z	395	412
SPEED	RPM	41600 ±100	41601	41514	41157	41000
GENERATOR LOADING	KW	18				18
WB STANDARD	Lb/min					118 ≈ 122%
PB STANDARD	INHG					96.3
TB STANDARD	F					405
WF STANDARD	PPH					-
SHAFT OUTPUT	SHP					30

OPERATOR:	OBSERVER:
AB HARTONO	EFI SASMITA

GMF AeroAsia

APU TEST REPORT

ENGINE/APU TYPE	: GTCP85-129H/J/K	PD Sheet No.	: B3PE490021
SERIAL No.	:P 100575	TEST No.	: 210020
OWNER	:G.A	Work Order	: 420088619
TSN / TSO	:36856	DATE	: 3 August 2010
TYPE OF TEST	:PERFORMANCE	RUNNING TIME	: 123 MINUTES
		REFERENCE	: Honeywell, CMM 49-25-45, Rev No.5, 23 August , 2006 (Doc.No.:19318)

CONDITIONAL TEST

DESCRIPTION	LIMIT	ACTUAL	UNIT	DESCRIPTION	LIMIT	ACTUAL	UNIT
Barometer Pressure	Obs	1008.7	mbar	Vib. Gearcase 110 Hz	0.6 max	0.1	mills
Comp. Inlet Temp.	130 max	97	deg.F	Vib. Turbine 110 Hz	0.4 max	0.1	mills
Oil Inlet Temp.	270 max	210	deg.F	**Heavy repair**			
Main Oil Pressure	95 ±5	95	psig	T Bearing Cavity Press.	0 to -25	-20.4	inHg
Fuel Temp.	130 max	107	deg.F	Gearcase Pressure	-3 to -10	-3.5	inHg
Fuel Inlet Pressure	38 ±2	36	psig	**Light/Medium Repair**			
Fuel manifold Press.	Obs	425	psig	T Bearing Cavity Press.	+4 to -25		inHg
Fuel Flow	333 (Max)		lbs/hr	Gearcase Pressure	0 to -10		inHg
EGT Test Cell	1200 max	1200	deg.F	Bleed Air Tot. press.	Obs	66.5	inHg
EGT Engine / ETC	± 30	1220	deg.F	Bleed Air Orif. Press.	Obs	66.1	inHg
				Bleed Air Dif. Press	Obs	27.2	WgD
Air Pressure Reg.	37.6-39.7	38.1	inHg	Bleed Air Orif. Temp	Obs	412	deg. F
				Bleed Air Temp.	Obs	432	deg. F
				Speed (Loading)	40400-41700	41157	rpm

ACCEPTANCE TEST REPORT

PERFORMANCE RECORD

☑ Heavy Repair ☐ Light / Medium Repair

	Medium Repair	Heavy repair	ACTUAL	UNIT
Bleed Air Flow	96.8	103.1	118	Lb / min
Bleed Air Pressure	90.4	93.2	96.3	inHgA
Bleed AIR Temp	403-473	403-473	405	deg.F
Shaft Output	30	30	30	Shp

TB DISCHARGE AT LOAD ATM CONDITION

	LIMIT	ACTUAL	UNIT
Auto. Start Test	Obs	3X	N/A
Over Speed Ctrl. Test	Obs	3X	N/A
EGT Test Cell	1200 max	1045	deg. F
EGT Engine	± 30	1075	deg. F

PRESERVATION

☑ **Yes for** 6 **Months** ☐ **No**

TEST RESULT

☑ **Accepted** ☐ **Rejected**

Performance result has been corrected based on a compressor inlet temperature of 100 Deg.F and an Ambient air pressure of 29.92 inHg.Abs.

TEST CELL PERFORMER	SUPERVISOR	QC INSPECTOR
SIGN	SIGN	SIGN
NAME A.B. Hartono	NAME Rey. P	NAME A HARYANTO
SW No. : 5315		
DATE : 3 AUG '10	DATE : 3. Agust. '10	DATE : 03 AUG 2010