SUMMARY:

This Lab covers fundamental IAM functions, AWS Orgs, SCP's, and Cloud Trail logging

Contents

1.	Simple Identity Permissions in AWS	1
	Groups in IAM	
	AWS Organization Creation:	
	Create Service Control Policy for the ORG	
	Cloud Trail – implementing and ORG trail	
٥.	Cloud Trail – implementing and ONG trail	. 10

1. Simple Identity Permissions in AWS


CFN Template to use for default user with password change policy:

```
AWSTemplateFormatVersion: "2010-09-09"
Description: >
  This template implements an IAM user 'Sally'
  An S3 bucket for cat pictues
  An S3 bucket for dog pictures
  An S3 bucket for other animals
  And permissions appropriate for Sally.
Parameters:
  sallypassword:
    NoEcho: true
    Description: IAM User Sallys Password
    Type: String
Resources:
  catpics:
    Type: AWS::S3::Bucket
  animalpics:
    Type: AWS::S3::Bucket
  sally:
    Type: AWS::IAM::User
    Properties:
      ManagedPolicyArns:
        - arn:aws:iam::aws:policy/IAMUserChangePassword
      LoginProfile:
        Password: !Ref sallypassword
        PasswordResetRequired: "true"
  policy:
    Type: AWS::IAM::ManagedPolicy
    Properties:
      Description: Allow access to all S3 buckets, except catpics
      ManagedPolicyName: AllowAllS3ExceptCats
      PolicyDocument:
        Version: 2012-10-17
        Statement:
          - Effect: Allow
            Action: 's3:*'
```


```
Resource: '*'
- Effect: Deny
Action: 's3:*'
Resource: [ !GetAtt catpics.Arn, !Join ['', [!GetAtt catpics.Arn, '/*']]]

Outputs:
catpicsbucketname:
Description: Bucketname for catpictures (the best animal!)
Value: !Ref catpics
animalpicsbucketname:
Description: Bucketname for animalpics (the almost best animals!)
Value: !Ref animalpics
sallyusername:
Description: IAM Username for Sally
Value: !Ref sally
```

CFN Resources completed:




Confirm and Login as Sally user:





CFN to add to sally user – as an in-line policy:


Add a managed policy to Sally user:




2. Groups in IAM

Create "developers" group > remove sally managed permissions, and switch over to group:

Add users to developers




Clean up account when finished, delete CFN IAM stack:




3. AWS Organization Creation:

- The GENERAL account will become the MASTER account for the organisation
- We will invite the PRODUCTION account as a MEMBER account and create the DEVELOPMENT account as a MEMBER account.
- Finally we will create an OrganizationAccountAccessRole in the production account, and use this role to switch between accounts.


Create main Organization from General account:




Add Production account to new ORG:




Be sure to accept invite, via email on Production account:



Prod account added:




Add the newly added production account to Switch Roles on General acc Console:




Switch Role


Allows management of resources across Amazon Web Services accounts using a single user ID and password. You can switch roles after an Amazon Web Services administrator has configured a role and given you the account and role details. Learn more.



Can now seamlessly switch account from General account:




Create Development account in Organization, and add to switch role to have 3 total accounts in the ORG:



4. Create Service Control Policy for the ORG

Create OU structure for accounts in ORG:



Enable SCP in AWS ORG:


Service control policies

Service control policies (SCPs) enable central administration over the permissions available within the accounts in your organization. This helps ensure that your accounts stay within your organization's access control guidelines. Learn more 🔀

Enable service control policies

JSON for Policy (denies access to S3):

SCP is created:



Assign to PROD account, and test with S3:



You don't have permissions to list buckets

After you or your AWS administrator have updated your permissions to allow the s3:ListAllMyBuckets action, refresh this page. Learn more about Identity and access management in Amazon S3 🖸


SCP kicks in and denies access ^

5. Cloud Trail – implementing and ORG trail


- In this [DEMO] lesson we will implement a Organizational CloudTrail for the Animals4life organisation.
- This CloudTrail will be configured for all regions and set to log global services events.
- We will set the trail to log to an S3 bucket and then enhance it to inject data into CloudWatch Logs.
- CloudTrail Pricing: https://aws.amazon.com/cloudtrail/pricing/
- CloudWatch Logs Pricing: https://aws.amazon.com/cloudwatch/pricing/

Feel free to disable the trail after completion if you are concerned about small S3 costs ... (there is a \$0.01 per 2000 requests and cloudtrail can be pretty noisy)


Setup cloudwatch logs:



Create Trail:



Can locate Trail log in S3 bucket:




Log in JSON:

```
JSON
        Raw Data
                   Headers
▼ Records:
  - Ø:
      eventVersion:
                                  "1.05"
    ▼ userIdentity:
                                  "IAMUser"
        type:
                                  "AIDAX5K53LLHXAEDUWFRW"
        principalId:
        arn:
                                  "arn:aws:iam::544047061711:user/iamadmin"
        accountId:
                                  "544047061711"
        accessKeyId:
                                  "ASIAX5K53LLHYM3F7KVZ"
                                  "iamadmin"
        userName:
       ▼ sessionContext:
           sessionIssuer:
                                  {}
           webIdFederationData:
                                 {}
         w attributes:
             mfaAuthenticated:
                                  "true"
             creationDate:
                                  "2020-08-19T20:56:50Z"
      eventTime:
                                  "2020-08-19T22:25:05Z"
                                  "health.amazonaws.com"
      eventSource:
      eventName:
                                  "DescribeEventAggregates"
      awsRegion:
                                  "us-east-1"
      sourceIPAddress:
                                  "119.18.34.73"
      userAgent:
                                  "console.amazonaws.com"
    requestParameters:
        aggregateField:
                                  "eventTypeCategory"
      - filter:
         ventStatusCodes:
             0:
                                  "open"
             1:
                                  "upcoming"

▼ startTimes:
           - Ø:
                from:
                                  "Aug 12, 2020 10:25:04 PM"
      responseElements:
                                  null
      requestID:
                                  "d17f8424-7db5-4f1c-ab27-b21e376b9192"
      eventID:
                                  "af127628-86ed-4ddf-afad-13d8ead90c97"
      eventType:
                                  "AwsApiCall"
      recipientAccountId:
                                  "544047061711"
```

Logging also being done in CloudWatch Logs:



```
Policy for Trail:
 "Version": "2012-10-17",
 "Statement": [
  {
   "Sid": "AWSCloudTrailCreateLogStream2014110",
   "Effect": "Allow",
   "Action": [
    "logs:CreateLogStream"
   ],
   "Resource": [
    arn:aws:logs:us-east-1:361618461803:log-group:aws-cloudtrail-logs-361618461803-cde4e7f7:log-stream:361618461803_CloudTrail_us-east-"
1*"
    "arn:aws:logs:us-east-1:361618461803:log-group:aws-cloudtrail-logs-361618461803-cde4e7f7:log-stream:o-xgka3j67fk *"
   ]
  },
   "Sid": "AWSCloudTrailPutLogEvents20141101",
   "Effect": "Allow",
   "Action": [
    "logs:PutLogEvents"
   ],
   "Resource": [
```

```
"arn:aws:logs:us-east-1:361618461803:log-group:aws-cloudtrail-logs-361618461803-cde4e7f7:log-stream:361618461803_CloudTrail_us-east-1*",

"arn:aws:logs:us-east-1:361618461803:log-group:aws-cloudtrail-logs-361618461803-cde4e7f7:log-stream:o-xgka3j67fk_*"

]
}
]
}
```