	laaS solution, server autoscaling, use case is general workloads					
	predefined or custom machines types Compute, Storage, Networking	— Compute Engine				
metadata and scripts for boot, run, maintenance, shudown						
move an instance to a new zone: between regions is manual process, within = automatic	— common compute engine actions					
Snapshots: backup critical data, migrate data between zones, transfer to SSD to improve performance						
resize persistent disk: you can grow size but never shrink	J					
	> Linux: SSH, requires firewall rule to allow top: 22				Broad network access	> access resources over internet from anywhere
Availability policy	> Win: RDP , requires firewall rule to allow tcp: 3389				Rapid elasticity —	> resources are elastic/flexible, can scale up or down based on load
> automatic restart: auto VM restart due to crash or maintenance event > on host maintenance: determines whether		2015		Cloud Computing Characteristics	Resource pooling —	> CSP allocates resources from shared pool, economies of scale = cheaper service
host is live-migrated or terminated due to a maintenance event		— VM access & lifecycle			On-demand self service	> provision and terminate resources using UI/CLI, without human interaction
> live migration: during maintenance event,VM is migrated to different hardware without interruption					Measured service SaaS	> pay for what you use, reserve as you go
OS patch management: > Patch compliance reporting > Patch deployment	Lifecycle: provisioning > staging > running > stopping	J			Jado	> responsible for data > bind code to libraries that provide access to
Charges for stopped/terminated VMs: > Attached Disks					- PaaS	the infra the app needs > responsible for runtime, data, and app
> Reserved IP addresses >>can't change image of stopped VM				Service Models		> pay for what you use
families: > General-purpose: E2, N2, N2D, N1, Tau T2D > Compute-optimized: C2, C2D				Service Fibries	laaS –	> provides compute, storage, networking > responsible for OS, container, runtime, data,
Compute-optimized: C2, C2DMemory-optimized: M1, M2Accelerator-optimized: A2	Machine type structure: family >> series >> type	— Compute options				and app > pay for what you allocate
Custom machine types: cost slightly more than predefined					Serverless = managed infra	> Cloud Functions: manages event-driven code as pay-as-you-go service
	per-second billing with Imin minimum resource based pricing				Serveness – managed inita	> Cloud Run: deploy containerized microservices based app in a fully-managed environment
	discounts: sustained use, committed use, premptible VM instances	— Compute pricing —	4 VMs		5 Geolocations > NA, SA, EU, AS, AU	
notifies of underutilized instances	Recommendation Engine			GCP Network	Divided in to Regions >> Zones	Currently 37 regions and 112 zones
lower price for interruptible serviceVM might be terminated at any timeno live migrate or auto restart	— preemptible VMs				Google data centers were first to achieve ISO	Can do multi-region hosting
> latest version of preemptible VMs > share same pricing model as preemp			① GCP Overview	Environmental Impact	carbon neutral, renewable energy by 2030 carbon free	
 no min or max runtime Spot VMs are finite Compute Engine resources, so they might not always be 	— spot VMas					> custom hardware design and provenance
available > no live migrate or auto restart		— Special compute configs			Hardware infra layer	> secure boot stack > physical security
> secure boot	sole-tenant nodes physically isolate workloads				Service deployment layer User identity layer	
secure bootvTPM - virtual trusted platform moduleintegrity monitoring	— Shielded VMs offer verifiable integrity			Security	Storage services layer	Service Service Service Service
encrypts data while being processed	Confidential VMs allow you to encrypt data in use	J			Internet comm layer —	> Google Front End (GFE) > DoS protection
	Boot loader, OS, File system structure, Software, Customizations	<u>)</u>				> intrusion detection
Public: Goog, 3P vendors, community, premium > Linux and Win	> public base images				Ops security layer	> reducing insider risk > employee universal second factor (U2F) use
Custom: create new image from VM, import from on-prem, workstation, or another cloud	> custom images	- Images			Google publishes key elements of tech using	> software dev practices
most ideal for disk backups as well as instance cloning replication	— machine image	J		Open source ecosystems	open source licenses to create ecosystems that provide customers with options other than GCP	
	every VM comes with a single root persistent disk; image is loaded onto root disk during			open source ecosystems	great interoperability with different CSPs	
attached to vm through network interface	first boot				per-second billing Compute Engine offeres Sustained-use	
network storage appearing as block device						
disk resizing, even running and attached				Pricing and Billing	discounts Online Pricing Calculator	
disk resizing, even running and attached zonal or regional: pd-standard, pd-ssd, pd- balanced, pd-extreme (zonal only)	Persistent disks	Disk options		Pricing and Billing	7	Budgets, Alerts, Reports, Quotas
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate	Persistent disks	— Disk options	Essential GCP Infra: Foundation	Pricing and Billing	Online Pricing Calculator GCP Tools	> policies can be defined at the project,
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied		— Disk options		Pricing and Billing	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed	
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer	Persistent disks local SSD: physically attached to a VM	— Disk options	Infra: Foundation	Pricing and Billing	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop		Disk options	Infra: Foundation	Pricing and Billing	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory	local SSD: physically attached to a VM		Infra: Foundation	Resource hierarchy	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary	A secure, individual, private cloud-	Infra: Foundation		Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and	A secure, individual, private cloud- computing model hosted within a public	Infra: Foundation		Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP	 > policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud	A secure, individual, private cloud-computing model hosted within a public cloud. A VPC is hosted remotely by public	Infra: Foundation		Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles:	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to	A secure, individual, private cloud-computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to	Infra: Foundation		Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator	 > policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to	A secure, individual, private cloud-computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to	Infra: Foundation		Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles:	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation		Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation	Resource hierarchy	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation	Resource hierarchy	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation 2023 Ivan Vlad S.	Resource hierarchy	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16	Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation	Resource hierarchy	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation,	Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation 2023 Ivan Vlad S.	Resource hierarchy	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation,	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have	Infra: Foundation 2023 Ivan Vlad S.	Resource hierarchy IAM	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral),	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP	local SSD: physically attached to a VM RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on same network to communicate, destination is in CIDR, traffic is	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on same network to communicate, destination is in CIDR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access FOM CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on sme network to communicate, destination is in CIDR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed firewall, firewall rules are applied to the network as a whole, connections are allowed or denied at the instance level, firewall rules	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and apps hosted in GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API Client libraries Start, stop, and use SSH to connect into
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on same network to communicate, destination is in CIDR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed firewall, firewall rules are applied to the network as a whole, connections are allowed	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range VMs Routes Firewalls	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and apps hosted in GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API Client libraries
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (I5 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /I6 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on sam ne network tance communicate, destination san etwork to communicate, destination san etwork to communicate, destination is in CIDR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed firewall, firewall rules are applied to the network as a whole, connections are allowed or denied at the instance level, firewall fules are stateful, implied deny all ingress and	Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range VMs Routes	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and apps hosted in GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API Client libraries Start, stop, and use SSH to connect into Compute Engine instances, and see logs Stop and start Cloud SQL instances Administer apps deployed on App Engine
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (I5 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /I6 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on sam ne network tance communicate, destination san etwork to communicate, destination san etwork to communicate, destination is in CIDR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed firewall, firewall rules are applied to the network as a whole, connections are allowed or denied at the instance level, firewall fules are stateful, implied deny all ingress and	Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range VMs Firewalls increased availability with multiple zones globalization with multiple regions Contraction with multiple regions Contraction architecture internal and supplementations.	A secure, individual, private cloud- computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and apps hosted in GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API Client libraries Start, stop, and use SSH to connect into Compute Engine instances
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (I5 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default firewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /I6 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), BYOIP, VM doesn't know external IP; it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on sam ne network tance communicate, destination san etwork to communicate, destination san etwork to communicate, destination is in CIDR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed firewall, firewall rules are applied to the network as a whole, connections are allowed or denied at the instance level, firewall fules are stateful, implied deny all ingress and	RAM disk Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range VMs Routes Firewalls increased availability with multiple zones globalization with multiple regions Best practice - only assign internal IP to VM instances whenever possible Cloud NAT = GCP managed network address translation services	A secure, individual, private cloud-computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and apps hosted in GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API Client libraries Start, stop, and use SSH to connect into Compute Engine instances, and see logs Stop and start Cloud SQL instances Administer apps deployed on App Engine
zonal or regional: pd-standard, pd-ssd, pd-balanced, pd-extreme (zonal only) durable storage - can survive VM terminate encryption keys: google managed, customer managed, customer supplied more IOPS, lower latency, higher throughput than persistent faster than local disk, slower than memory very volatile, erase on start or stop consider using a persistent to back up RAM disk data associates objects and services with billing contains networks (15 max) that can be shared/peered has no IP address range global and spans all available regions Default = every project, one subnet per region, default friewalls auto mode = default network, one subnet per region, regional IP allocation, fixed /20 subnet per region, expandable to /16 custom = no default subnets created, full control of IP ranges, regional IP allocation, expandable to IP ranges you specify each VM can have 2 IPs assigned: internal + external internal: allocated from subnet range to VMs by DHCP, lease renewed every 24hrs, VM name + IP is registered with network-scoped DNS external: assigned from pool (ephemeral), reserved (static), ByOIP, VM dopen't know external IP, it is mapped to the internal IP Apply traffic egressing a VM, fwd traffic to most specific route, created when subnet is created, enable VMs on same network to communicate, destination is in CIDIR, traffic is delivered only if it matches a firewall fule VPC network functions as a distributed firewall, firewall rules are stateful, implied deny all ingress and allow all egress	Run code, store data, host websites, and anything else that can be done in an ordinary private cloud segmenting networks using firewall rules to restrict access to instances creating static routes to forward traffic to specific destinations Projects Networks: Default, auto mode, custom mode Subnetworks Regions Zones IP Addresses: internal, external, range VMs Firewalls increased availability with multiple zones globalization with multiple regions Best practice - only assign internal IP to VM instances whenever possible Cloud NAT = GCP managed network address	A secure, individual, private cloud-computing model hosted within a public cloud. A VPC is hosted remotely by public cloud provider VPC networks connect GCP resources to each other and to the internet GCP VPC networks are global and can have subnets in any GCP region worldwide	Infra: Foundation 2023 Ivan Vlad S. ② Resources & Access	Resource hierarchy IAM Service Accounts Cloud Identity	Online Pricing Calculator GCP Tools Order from bottom up: Resources > Project > Folder > Organization directly relates to how policies are managed and applied in GCP Projects are the basis for enabling GCP services Folders let you assign policies to resources at a level of granularity you choose At org node: can assign 2 special roles: > org policy admin and project creator Admins can apply policies that define WHO can do WHAT on WHICH resources IAM role = collection of permissions Accounts for machines/services, NOT humands > named with an email address > use cryptographic keys instead of password can define policies and manage users and groups using the Google Admin console Cloud console SDK: set of tools to manage resources and apps hosted in GCP	> policies can be defined at the project, folder, and org levels > some policies can be assigned at the resource level > policies are applied downward each resource belongs to exactly one project can have different owners and users because they're billed and managed separately 3 identifying attributes: ID, name, number > ID = globally unique identifier that CANT be changed after creation, immutable Resource Manager Tool - manage projects Use folders to group projects under an organization in a hierarchy > goog workspace customer = projects will automatically belong to your org node > non-goog workspace customer = use Cloud Identity to create an org node 3 types: basic, predefined, custom Basic = broad in scope > owner, editor, viewer, billing admind Predefine = google defined roles > some for each service, e.g., Instance Admin Role Custom = user defined > need to manage the permissions that define the custom role you create > can only be applied to either project or org level, not folder level need to be managed, can have IAM roles attached to it log in and manage resources using the same creds used in existing AD or LDAP systems Goog admin console can be used to disable user accounts and remove them from groups when they leave available in free and premium editions already available to goog workspace customers in goog admin console web-based GUI, can connect to resources via SSH in the browser gcloud - main CLI for products and services gsutil - storage access from CLI bq - BigQuery CLI Cloud shell = access SDK CLI from browser Google APIs Explorer - shows what APIs are available Google provides Cloud Client and Google API Client libraries Start, stop, and use SSH to connect into Compute Engine instances, and see logs Stop and start Cloud SQL instances Administer apps deployed on App Engine