Data Structures and Algorithm

Xiaoqing Zheng zhengxq@fudan.edu.cn





What is data structure?


A data structure is a way to store and organize data in order to facilitate access and modifications.


Elementary data structures


- □ Stacks
- Queues
- □ Linked lists
- □ Trees






















```
top[S] = 6
                     PUSH 8
              12
                     PUSH 12
                     PUSH 3
```





STACK-EMPTY(*S***)**


- 1. **if** top[S] = 0
- 2. then return TRUE
- 3. else return FALSE


PUSH(S, x)


- 1. $top[S] \leftarrow top[S] + 1$
- 2. $S[top[S]] \leftarrow x$


POP(S)

- 1. **if** STACK-EMPTY(S)
- 2. **then error** "underflow"
- 2. **else** $top[S] \leftarrow top[S] 1$
- 4. **return** S[top[S] + 1]













```
tail[Q] = 8
         3 4 5 6
                             10
         9
head[Q] = 1
           ENQUEUE 6
           ENQUEUE 1
           ENQUEUE 8
           ENQUEUE 2
```






```
tail[Q] = 1
         3 4 5 6
                            10
          head[Q] = 5
           ENQUEUE 9
           ENQUEUE 3
           ENQUEUE 5
```





Empty Full
$$head[Q] = tail[Q]$$
 $head[Q] = tail[Q] + 1$



Underflow

When the queue is empty, an attempt to dequeue and element.

$$head[Q] = tail[Q]$$

Overflow

When the queue is full, an attempt to dequeue and element


$$head[Q] = tail[Q] + 1$$


ENQUEUE(Q, x)

- 1. $Q[tail[Q]] \leftarrow x$
- 2. **if** tail[Q] = length[Q]
- 3. then $tail[Q] \leftarrow 1$
- 4. **else** $tail[Q] \leftarrow tail[Q] + 1$


DEQUEUE(Q, x)

- $1. x \leftarrow Q[head[Q]]$
- 2. **if** head[Q] = length[Q]
- 3. then $head[Q] \leftarrow 1$
- 4. **else** $head[Q] \leftarrow head[Q] + 1$
- 5. return x







LIST-INSERT 25




LIST-DELETE 4



LIST-DELETE 4




LIST-DELETE 4




LIST-SEARCH(L, k)

- $1. x \leftarrow head[L]$
- 2. While $x \neq \text{NIL}$ and $key[x] \neq k$
- 3. **do** $x \leftarrow next[x]$
- 4. return *x*



LIST-INSERT(L, x)


- 1. $next[x] \leftarrow head[L]$
- 2. **if** $head[L] \neq NIL$
- 3. **then** $prev[head[L]] \leftarrow x$
- 4. $head[L] \leftarrow x$
- 5. prev[x] ← NIL




LIST-DELETE(L, x)

- 1. if $prev[x] \neq NIL$
- 2. **then** $next[prev[x]] \leftarrow next[x]$
- 3. **else** $head[L] \leftarrow next[x]$
- 4. **if** $next[x] \neq NIL$
- 5. **then** $prev[next[x]] \leftarrow prev[x]$

Rooted trees



Rooted trees



Postfix

Infix


$$9+3*7+(4*5+6)*2$$


Postfix (reverse Polish notation)


Infix

$$9+3*7+(4*5+6)*2$$

Input








Infix

$$9+3*7+(4*5+6)*2$$

Input




Infix

$$9+3*7+(4*5+6)*2$$

Input

3 and 7 are popped and 3 * 7 = 21 is pushed




Infix

$$9+3*7+(4*5+6)*2$$

Input

3 and 7 are popped and 3 * 7 = 21 is pushed



Infix

$$9+3*7+(4*5+6)*2$$

Input

9 and 21 are popped and 21 + 9 = 30 is pushed

Infix

$$9+3*7+(4*5+6)*2$$

Input

9 and 21 are popped and 21 + 9 = 30 is pushed


30

Infix

$$9+3*7+(4*5+6)*2$$

Input


30



Infix

$$9+3*7+(4*5+6)*2$$

Input



Infix

$$9+3*7+(4*5+6)*2$$

Input

4 and 5 are popped and 4 * 5 = 20 is pushed


Infix

$$9+3*7+(4*5+6)*2$$

Input

4 and 5 are popped and 4 * 5 = 20 is pushed


20 30



Infix

$$9+3*7+(4*5+6)*2$$

Input



Infix

$$9+3*7+(4*5+6)*2$$

Input

6 and 20 are popped and 6 + 20 = 26 is pushed

Infix

$$9+3*7+(4*5+6)*2$$

Input

6 and 20 are popped and 6 + 20 = 26 is pushed

26 30




Infix

$$9+3*7+(4*5+6)*2$$

Input

Stack

26



Infix

$$9+3*7+(4*5+6)*2$$

Input

2 and 26 are popped and 2 * 26 = 52 is pushed

Infix

$$9+3*7+(4*5+6)*2$$

Input

2 and 26 are popped and 2 * 26 = 52 is pushed

52 30

Infix

$$9+3*7+(4*5+6)*2$$

Input

52 and 30 are popped and 52 + 30 = 82 is pushed

52 30

Infix

$$9+3*7+(4*5+6)*2$$

Input

82

Stack

52 and 30 are popped and 52 + 30 = 82 is pushed

Infix

done

$$9+3*7+(4*5+6)*2$$

Input

82

82 are popped and we get the answer

Conversion rules

- □ Operands are immediately placed onto the output and operators are placed onto the stack.
- When the operator on the top of the stack that has higher priority than the input operator, it is popped.
- □ If we see a right parenthesis, then we pop the stack, writing symbols until we encounter a left parenthesis.
- □ If we read the end of input, we pop the stack until it is empty.

Input

$$9+3*7+(4*5+6)*2$$


Output

Input

$$9+3*7+(4*5+6)*2$$

Output

9




Input


$$9+3*7+(4*5+6)*2$$


Output

93

+







Pop the other +

Input

Output


+


Push the input + onto stack


Input


Output


+











Push the input + onto stack

Input

Output



Push the input + onto stack

Input


Output


Input

Pop the stack until we encounter left parenthesis

Output

Stack





Pop the stack until it is empty

Input

Output

done

Any question?

Xiaoqing Zheng Fundan University