



Not So Tiny Task №7 (2 points)

Implement a hierarchy of classes for symbolic differentiation of expressions.

- **Base class**: Expression;
- **Derived classes**: Binary, Unary, Add, Sub, Mult, Div, Exponent, Var, Val;
- **Base class** expression should contain pure virtual function `Expression* diff(std::string var)`; (its implementations should return differentiation result for the expression by the given variable);
- Tests should be prepared as usual.

Not So Tiny Task №7 (2 points)



Example:

```
Expression* e = new Add(new Var("x"),  
                        new Mult(new Val(10), new Var("y")));
```

```
// e = x + 10*y
```

```
Expression* res1 = e->diff("x");  
// res1 = 1 + (0*y + 10*0) (it is ok to have non-simplified exprs)
```


```
Expression* res2 = e->diff("y");  
// res2 = 0 + (0*y + 10*1) (it is ok to have non-simplified exprs)
```

System Programming with C++

Inheritance and virtual calls



Inheritance



Inheritance

```
class Person {  
    const char* name;  
    size_t age;  
public:  
    Person(): name("John Doe"), age(33) {}  
    Person(const char* n, int a): name(n), age(a) {}  
  
    const char* getName() const { return name; }  
    size_t getAge() const { return age; }  
    ...  
};
```

Inheritance

```
class Person {  
    const char* name;  
    size_t age;  
public:  
    Person(): name("John Doe"), age(33) {}  
    Person(const char* n, int a): name(n), age(a) {}  
  
    const char* getName() const { return name; }  
    size_t getAge() const { return age; }  
    ...  
};
```



```
Person:  
    const char* name  
    size_t age
```

Imagine we have one more class

Person:

```
const char* name  
size_t age
```

Student:

```
const char* name  
size_t age  
-----  
size_t group  
size_t id
```

Imagine we have one more class



Similar fields and methods => code duplication!

Imagine we have one more class



Similar fields and methods => code duplication!

How can we solve that?



Imagine we have one more class

```
Student:  
  const char* name  
  size_t age  
-----  
  size_t group  
  size_t id
```



```
Student:  
  Person base  
-----  
  size_t group  
  size_t id
```

Imagine we have one more class

```
Student:  
  const char* name  
  size_t age  
-----  
  size_t group  
  size_t id
```



```
Student:  
  Person base  
-----  
  size_t group  
  size_t id
```

This is called **composition**.

Imagine we have one more class

```
Student:  
  const char* name  
  size_t age  
-----  
  size_t group  
  size_t id
```




```
Student:  
  Person base  
-----  
  size_t group  
  size_t id
```

This is called **composition**.

There are some benefits of such approach, but it just doesn't look logical here (why Person should be a part of Student?)

Imagine we have one more class




This is called **composition**.

There are some benefits of such approach, but it just doesn't look logical here (why Person should be a part of Student?)

Also: how can I get a name from Student?

Imagine we have one more class



This is called **composition**.

There are some benefits of such approach, but it just doesn't look logical here (why Person should be a part of Student?)

Also: how can I get a name from Student? Some forwarding method to base => **boilerplate code**! Something we want to get rid of.

```
Person:  
    const char* name  
    size_t age
```

```
Person:  
    const char* name  
    size_t age
```

```
Student:  
    size_t group  
    size_t id
```





```
Person:  
  const char* name  
  size_t age
```




```
Student:  
  size_t group  
  size_t id
```

Inheritance relationship









Derived class **extends** base: «Student — is a Person, who also has some group and id». It specifies the **particular case** of base class, **narrows** set of objects.


Inheritance




Inheritance



Inheritance




Inheritance




Inheritance

inheritance defines
relationship: "is-a"



Inheritance

inheritance defines
relationship: "is-a"



Talk is cheap.

Show me the **code**! (c)

Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
};
```

Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
};
```

```
struct Student: Person {  
    size_t group;  
    size_t id;  
};
```

Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
};
```



```
struct Student: Person {  
    size_t group;  
    size_t id;  
};
```

base class



Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
};
```

```
struct Student: Person {  
    size_t group;  
    size_t id;  
};
```

base class



```
Person p;  
p.name = "Bob"; p.age = 30;
```

```
Student s;  
s.name = "Alice"; s.age = 18;  
s.group = 22126; s.id = 1234;
```

Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
};
```

```
struct Student: Person {  
    size_t group;  
    size_t id;  
};
```


base class




```
Person p;  
p.name = "Bob"; p.age = 30;
```

```
Student s;  
s.name = "Alice"; s.age = 18;  
s.group = 22126; s.id = 1234;
```

"Bob"



"Alice"




Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
};
```

```
struct Student: Person {  
    size_t group;  
    size_t id;  
};
```

base class

```
Person p;  
p.name = "Bob"; p.age = 30;  
  
Student s;  
s.name = "Alice"; s.age = 18;  
s.group = 22126; s.id = 1234;
```




Inheritance (structs)

```
struct Person {  
    const char* name;  
    size_t age;  
  
    Person(const char* name, int age): name(name), age(age) {}  
};
```

```
Person p("Bob", 30);
```

Inheritance (structs)

```
struct Student: Person {  
    size_t group;  
    size_t id;  
  
    Student(const char* name, size_t age, size_t group, size_t id):  
        Person(name, age), group(group), id(id) {}  
};
```




Initialize **base** part with help of corresponding constructor.

Inheritance (structs)

```
struct Student: Person {  
    size_t group;  
    size_t id;
```

```
    Student(const char* name, size_t age, size_t group, size_t id):  
        Person(name, age), group(group), id(id) {}  
};
```




Initialize **base** part with help of corresponding constructor.

Don't confuse with **delegating constructor**, this one works fine with the rest of member initialization list.

Inheritance (structs)

```
struct Student: Person {  
    size_t group;  
    size_t id;
```

```
    Student(const char* name, size_t age, size_t group, size_t id):  
        Person(name, age), group(group), id(id) {}  
};
```



Initialize base part with help of corresponding constructor.

```
Student s("Alice", 18, 22126, 1234);
```

What about methods?

```

struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age): name(name), age(age){}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age << std::endl;
    }
};

Person p("Bob", 30);
p.print(); // Person Bob; age = 30

```

```

struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age): name(name), age(age){}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age << std::endl;
    }
};

```

```

Person p("Bob", 30);
p.print(); // Person Bob; age = 30
Student s("Alice", 18, 22126, 1234);
s.print(); // Person Alice; age = 18

```

Student also inherits method
print from its base.


```

struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

struct Student: Person {
    size_t group;
    size_t id;

    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}
};

```

```

Person p("Bob", 30);
p.print(); // Person Bob; age = 30
Student s("Alice", 18, 22126, 1234);
s.print(); // Person Alice; age = 18

```

```

struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

struct Student: Person {
    size_t group;
    size_t id;

    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

```

```

Person p("Bob", 30);
p.print(); // Person Bob; age = 30
Student s("Alice", 18, 22126, 1234);
s.print(); // Student Alice from group 22126

```

```

struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

Person p("Bob", 30);
p.print(); // Person Bob; age = 30
Student s("Alice", 18, 22126, 1234);
s.print(); // Student Alice from group 22126

```


```

struct Student: Person {
    size_t group;
    size_t id;

    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

```



Method print was **overridden** in Student with some custom implementation.

```
struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age):
        name(name), age(age) {}


    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};
```

```
Person p("Bob", 30);
p.print(); // Person Bob; age = 30
Student s("Alice", 18, 22126, 1234);
s.print(); // Student Alice from group 22126
s.Person::print(); // Person Alice; age = 18
```

```
struct Student: Person {
    size_t group;
    size_t id;

    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};
```



Method print was **overridden**
in Student with some custom
implementation.

What about encapsulation?

```

struct Person {
    const char* name;
    size_t age;

    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

struct Student: Person {
    size_t group;
    size_t id;

    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

```

```

struct Person {
private:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

struct Student: Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

```

Is everything is still ok here?

```

struct Person {
private:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```


```

struct Student: Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

```

Compilation **error**: private field name
is inaccessible out of the struct



Inheritance (structs)

It was quite straightforward previously:
code was split into "internal" and
"external"

Inheritance (structs)

It was quite straightforward previously:
code was split into "internal" and
"external"

But the question is: are fields and
methods of the base class are internal or
external for the derived class?



Inheritance (structs)

It was quite straightforward previously:
code was split into "internal" and
"external"

But the question is: are fields and
methods of the base class are internal or
external for the derived class?

Solution: new access modifier `protected`.
Such fields and methods are accessible* in
code of the class `itself` and `derived` one.

```

struct Person {
private:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```


```

struct Student: Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

```

Compilation **error**: private field name
is inaccessible out of the class



```

struct Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};


```


```

struct Student: Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}


    void print() const {
        std::cout << "Student " << name ✓
                    << " from group " << group
                    << std::endl;
    }
};

```






Should **protected** fields/methods of **Person** be accessible in **Contractor**?



Should **protected** fields/methods of **Person** be accessible in **Contractor**?

Should **public** fields/methods of **Person** be accessible through instances of **Student** or **Contractor**?



Should **protected** fields/methods of **Person** be accessible in **Contractor**?

Should **public** fields/methods of **Person** be accessible through instances of **Student** or **Contractor**?

In C++ you can control it!

```
struct Foo {  
  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
struct Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
Bar bar;
```

```
std::cout << bar.c; ✓
```

```
struct Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
struct Baz:  
    protected Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        protected  
};
```

Baz baz;

std::cout << baz.c; ❌

```
struct Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
struct Baz:  
    protected Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        protected  
};
```

```
struct Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
struct Baz:  
    protected Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        protected  
};
```

```
struct Qux:  
    private Foo {  
  
    no access  
  
    accessed as  
        private  
  
    accessed as  
        private  
};
```

By default



```
struct Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
struct Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
struct Baz:  
    protected Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        protected  
};
```

```
struct Qux:  
    private Foo {  
  
    no access  
  
    accessed as  
        private  
  
    accessed as  
        private  
};
```



```
class Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
class Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
class Baz:  
    protected Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        protected  
};
```

```
class Qux:  
    private Foo {  
  
    no access  
  
    accessed as  
        private  
  
    accessed as  
        private  
};
```

By default



```
class Foo {  
    private:  
        int a;  
  
    protected:  
        int b;  
  
    public:  
        int c;  
};
```

```
class Bar:  
    public Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        public  
};
```

```
class Baz:  
    protected Foo {  
  
    no access  
  
    accessed as  
        protected  
  
    accessed as  
        protected  
};
```

```
class Qux:  
    private Foo {  
  
    no access  
  
    accessed as  
        private  
  
    accessed as  
        private  
};
```

```

struct Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

struct Student: Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name ✓
                  << " from group " << group
                  << std::endl;
    }
};

```

```

class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

class Student: public Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name ✓
                    << " from group " << group
                    << std::endl;
    }
};

```

```

class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

class Student: public Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name ✓
                    << " from group " << group
                    << std::endl;
    }
};

```

Usually you need `public` inheritance in C++.

```

class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

class Student: public Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name ✓
                  << " from group " << group
                  << std::endl;
    }
};

```

Usually you need `public` inheritance in C++.

Scenarios for `non-public` inheritance: when you want to remove something from public API that you've gotten from the base class.

```

class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

class Student: public Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name ✓
                    << " from group " << group
                    << std::endl;
    }
};

```


Usually you need `public` inheritance in C++.

Scenarios for `non-public` inheritance: when you want to remove something from public API that you've gotten from the base class. Details later.

About building hierarchies


About building hierarchies

Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.




About building hierarchies

Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.




What should we do? Make Square a base class and Rectangle a derived? Or vice versa?



Derived class **extends** base: «Student — is a Person, who also has some group and id». It specifies the **particular case** of base class, **narrows** set of objects.

About building hierarchies


Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.



Approach #1: Every square is a rectangle.

About building hierarchies

Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.



Approach #1: Every square is a rectangle. So, square - is a particular case of rectangle. So, Rectangle should be **base class**, but square - a **derived class**.

```
struct Rectangle {  
protected:  
    double w, h;  
public:  
    Rectangle(double w, double h): w(w), h(h) {}  
};
```

```
struct Square: Rectangle {  
    Square(double length): Rectangle(length, length) {}  
};
```

```
struct Rectangle {  
protected:  
    double w, h;  
public:  
    Rectangle(double w, double h): w(w), h(h) {}  
};
```

```
// invariant of the class: w == h  
struct Square: Rectangle {  
    Square(double length): Rectangle(length, length) {}  
};
```

```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}
};

```



```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}
};

Square s{10};
s.stretchOnlyWidth(); // ---> breaks invariants of Square!

```

```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}

    void stretchOnlyWidth(double c) {
        w *= c;
        h *= c;
    }
};

```

```

Square s{10};
s.stretchOnlyWidth(); // ok, but...

```

```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}

    void stretchOnlyWidth(double c) {
        w *= c;
        h *= c;
    }
};

```

```

Square s{10};
s.stretchOnlyWidth(); // ok, but...

```

ok, but obviously **violates** the contract of stretchOnlyWidth!

```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}

    void stretchOnlyWidth(double c) {
        w *= c;
        h *= c;
    }
};

```

```

Square s{10};
s.stretchOnlyWidth(); // ok, but...


```

ok, but obviously **violates** the contract of stretchOnlyWidth!

Another argument against such approach: we have two fields where we could have only one.

About building hierarchies


Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.



~~**Approach #1:** Every square is a rectangle. So, square - is a particular case of rectangle. So, Rectangle should be **base class**, but square - a **derived class**.~~

About building hierarchies

Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.



Approach #2: Rectangle is an **extension** of Square (it could have some additional fields). So, why not to make Square a base class?

```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
};  
  
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```

Something is already so **wrong** here, it is obvious that not every Rectangle is a Square...

```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
};
```

```
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```



```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
};
```

```
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```

Something is already so **wrong** here, it is obvious that not every Rectangle is a Square... and that field length in Rectangle, so awkward

```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
};
```

```
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```

Something is already so **wrong** here, it is obvious that not every Rectangle is a Square... and that field length in Rectangle, so awkward.

How to break it even more?

```
struct Square {
private:
    double length;
public:
    Square(double length): length(length) {}

    double getInscribedCircleSquare() {
        return M_PI * (length / 2) * (length / 2);
    }
};

struct Rectangle: Square {
    double height;
public:
    Rectangle(double width, double height): Square(width), height(height) {}
};
```


```
struct Square {
private:
    double length;
public:
    Square(double length): length(length) {}

    double getInscribedCircleSquare() {
        return M_PI * (length / 2) * (length / 2);
    }
};

struct Rectangle: Square {
    double height;
public:
    Rectangle(double width, double height): Square(width), height(height) {}
};


Rectangle rect(42);
double d = rect.getInscribedCircleSquare();

// what it can even mean?
```



About building hierarchies


Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.




~~**Approach #2:** Rectangle is an **extension** of Square (it could have some additional fields). So, why not to make Square a base class?~~

About building hierarchies


Task: define a **hierarchy** (?) of classes to work with both **squares** and **rectangles**.



So, both approaches failed us. Why?



Derived class **extends** base: «Student — is a Person, who also has some group and id». It specifies the **particular case** of base class, **narrows** set of objects.



Derived class **extends** base: «Student — is a Person, who also has some group and id».
It specifies the **particular case** of base class, **narrows** set of objects.

Both should
be true!

About building hierarchies

So, both approaches failed us. Why?

About building hierarchies

So, both approaches failed us. Why?

Because when you build hierarchies with
"is-a" relationship, you should check that:

About building hierarchies

So, both approaches failed us. Why?

Because when you build hierarchies with "is-a" relationship, you should check that:

If some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

About building hierarchies

If some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

This is called Liskov substitution principle (LSP).



```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

```



Predicate: "after calling stretchOnlyWidth(c), w is multiplied by c and h is unchanged" is **true** for any instance of Rectangle.

```

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}

    void stretchOnlyWidth(double c) {
        w *= c;
        h *= c;
    }
};

```

```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

```



Predicate: "after calling stretchOnlyWidth(c), w is multiplied by c and h is unchanged" is **true** for any instance of Rectangle.

```

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}

    void stretchOnlyWidth(double c) {
        w *= c;
        h *= c;
    }
};

```

But it is **not true** for instances of Square.

```

struct Rectangle {
protected:
    double w, h;
public:
    Rectangle(double w, double h): w(w), h(h) {}

    // w -> w*c
    // h is unchanged
    void stretchOnlyWidth(double c) {
        w *= c;
    }
};

// invariant of the class: w == h
struct Square: Rectangle {
    Square(double length): Rectangle(length, length) {}

    void stretchOnlyWidth(double c) {
        w *= c;
        h *= c;
    }
};

```

Predicate: "after calling stretchOnlyWidth(c), w is multiplied by c and h is unchanged" is **true** for any instance of Rectangle.

But it is **not true** for instances of Square.

So, LSP is violated, "is-a" relationship is wrong here.

```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
  
    double getInscribedCircleSquare() {  
        return M_PI * (length / 2) * (length / 2);  
    }  
};  
  
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```



```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
  
    double getInscribedCircleSquare() { ←  
        return M_PI * (length / 2) * (length / 2);  
    }  
};
```

Predicate: "calling
getInscribedCircleSquare,
will give you a square of
inscribed circle" is true
for any instance of Square.

```
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```

```
struct Square {  
private:  
    double length;  
public:  
    Square(double length): length(length) {}  
  
    double getInscribedCircleSquare() {  
        return M_PI * (length / 2) * (length / 2);  
    }  
};
```

Predicate: "calling
getInscribedCircleSquare,
will give you a square of
inscribed circle" is true
for any instance of Square.

```
struct Rectangle: Square {  
    double height;  
public:  
    Rectangle(double width, double height): Square(width), height(height) {}  
};
```

And of course that's **not true** for instances of Rectangle.
So, LSP is violated again.

About building hierarchies

If some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

This is called Liskov substitution principle (LSP).



About building hierarchies

If some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

This is called Liskov substitution principle (LSP).

Practical consequence: you can write your code in terms of **basic classes** and be sure that it will work with **derived classes** as well.



About building hierarchies

If some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

This is called Liskov substitution principle (LSP).


Practical consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

Talk is cheap.

Show me the **code**! (c)

Subtyping polymorphism


inheritance defines
relationship: "is-a"



Subtyping polymorphism

inheritance defines
relationship: "is-a"


So, instances of all
these classes are
actually Persons.



Subtyping polymorphism

inheritance defines
relationship: "is-a"

So, instances of all
these classes are
actually Persons.



Subtyping polymorphism

```
class Employee: public Person {
private:
    const char* dep;
    size_t salary;
public:
    Employee(const char* name, size_t age,
             const char* dep, size_t salary):
        Person(name, age), dep(dep), salary(salary) {}


    void print() const {
        std::cout << "Employee " << name
                    << " from dep " << dep
                    << std::endl;
    }
};
```

Subtyping polymorphism

inheritance defines
relationship: "is-a"

And all of them
have `print` method
(at least one)

So, instances of all
these classes are
actually Persons.



Subtyping polymorphism

Task: handle the whole hierarchy of these classes with a single **generic** algorithm

Subtyping polymorphism

Task: handle the whole hierarchy of these classes with a single **generic** algorithm

For example: iterate over collection of objects and just print them, using print method.

Subtyping polymorphism

LSP consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

Subtyping polymorphism

LSP consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

Implementation of this principle in C++:

A pointer (a reference) to the **derived class** can be substituted instead of a pointer (a reference) to the **base class**.

Subtyping polymorphism

LSP consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

Implementation of this principle in C++:

A pointer (a reference) to the **derived class** can be substituted instead of a pointer (a reference) to the **base class**.

The opposite is not true!

Subtyping polymorphism

Semantics guarantees!

LSP consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

Implementation of this principle in C++:

A pointer (a reference) to the **derived class** can be substituted instead of a pointer (a reference) to the **base class**.

The opposite it not true!

Subtyping polymorphism

Semantics guarantees!

LSP consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

Implementation of this principle in C++:

A pointer (a reference) to the **derived class** can be substituted instead of a pointer (a reference) to the **base class**.

The opposite is not true!

Syntax guarantees by C++!

Subtyping polymorphism

```
Person* p = new Person("Bob", 30);
```

```
Person* s = new Student("Alice", 18, 22126, 1234);
```

Subtyping polymorphism

```
Person* p = new Person("Bob", 30);
```

```
✓ Person* s = new Student("Alice", 18, 22126, 1234);
```

Quite logical, because every student is still a person.

Subtyping polymorphism

```
Person* p = new Person("Bob", 30);
```

```
✓ Person* s = new Student("Alice", 18, 22126, 1234);
```

```
✓ Person* e = new Employee("John", 25, "MMF", 5000);
```

```
✗ Student* k = new Person("Tom", 42);
```

But not every person is a student.


Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class



```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

- ✓ print_info(p);
- ✓ print_info(s);
- ✓ print_info(e);

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

LSP guarantees us that no semantic invariants will be ruined here.

- ✓ print_info(p);
- ✓ print_info(s);
- ✓ print_info(e);

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

LSP guarantees us that no semantic invariants will be ruined here.

But what will be printed?

- ✓ print_info(p);
- ✓ print_info(s);
- ✓ print_info(e);

Subtyping polymorphism

```
class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};
```

```
class Student: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};
```

```
class Employee: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Employee " << name
                    << " from dep " << dep
                    << std::endl;
    }
};
```

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

But what will be printed?

- ✓ print_info(p);
- ✓ print_info(s);
- ✓ print_info(e);

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

But what will be printed?

- ✓ print_info(p); // Person Bob; age = 30
- ✓ print_info(s); // Person Alice; age = 18
- ✓ print_info(e); // Person John; age = 25

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

But what will be printed?

- ✓ print_info(p); // Person Bob; age = 30
- ✓ print_info(s); // Person Alice; age = 18
- ✓ print_info(e); // Person John; age = 25




is it what you expected?

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class



```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

- ✓ `print_info(p);` // Person Bob; age = 30
- ✓ `print_info(s);` // Person Alice; age = 18
- ✓ `print_info(e);` // Person John; age = 25

By default we will call the method `print` from type that is actually (**statically**) specified in the code.

Subtyping polymorphism

```
class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};
```

```
class Student: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};
```

```
class Employee: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Employee " << name
                    << " from dep " << dep
                    << std::endl;
    }
};
```

Subtyping polymorphism

```
class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    virtual void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};
```

Virtual modifier changes this behavior.

```
class Student: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};

class Employee: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Employee " << name
                    << " from dep " << dep
                    << std::endl;
    }
};
```


Subtyping polymorphism

```
class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    virtual void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};
```

Virtual modifier changes this behavior: the closest method to the **real** type of the instance will be called.

```
class Student: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Student " << name
                    << " from group " << group
                    << std::endl;
    }
};
```

```
class Employee: public Person {
    ...
public:
    ...

    void print() const {
        std::cout << "Employee " << name
                    << " from dep " << dep
                    << std::endl;
    }
};
```

Subtyping polymorphism

In C++ values can have static and dynamic type.

```
void print_info(Person& k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

- ✓ `print_info(p);` // Person Bob; age = 30
- ✓ `print_info(s);` // Person Alice; age = 18
- ✓ `print_info(e);` // Person John; age = 25

By default we will call the method `print` from type that is actually (statically) specified in the code.

Subtyping polymorphism

In C++ values can have static and dynamic type.

```
void print_info(Person& k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
Employee e("John", 25, "MMF", 5000);
```

- ✓ `print_info(p);` // Person Bob; age = 30
- ✓ `print_info(s);` // Student Alice from group 22126
- ✓ `print_info(e);` // Employee John from dep MMF


But if `print` is `virtual` method: the closest print to real derived class (that was passed here) will be called.

Subtyping polymorphism

inheritance defines
relationship: "is-a"

And all of them
have `print` method
(at least one)

So, instances of all
these classes are
actually Persons.



Subtyping polymorphism

In C++ values can have static and dynamic type.

```
void print_info(Person& k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);  
PartTime pe("John", 25, "MMF", 5000, {Date{10, 12,}});
```

- ✓ `print_info(p);` // Person Bob; age = 30
- ✓ `print_info(s);` // Student Alice from group 22126
- ✓ `print_info(pe);` // Employee John from dep MMF


But if `print` is `virtual` method: the closest print to real derived class (that was passed here) will be called.

Subtyping polymorphism

inheritance defines
relationship: "is-a"

And all of them
have `print` method
(at least one)

So, instances of all
these classes are
actually Persons.



Subtyping polymorphism

- Based on Liskov substitution principle

Subtyping polymorphism

- Based on `Liskov substitution principle`
- Allows you to write `generic` algorithms that will work with any class from hierarchy

Subtyping polymorphism

- Based on **Liskov substitution principle**
- Allows you to write **generic** algorithms that will work with any class from hierarchy
- I can know nothing about the implementation of **derived classes**
- **Derived classes** can know nothing about how they will be used

Subtyping polymorphism

- Based on `Liskov substitution principle`
- Allows you to write `generic` algorithms that will work with any class from hierarchy
- I can know nothing about the implementation of `derived classes`
- `Derived classes` can know nothing about how they will be used
- But generic code `will still work!`

Subtyping polymorphism

```
void print_info(Person& k) {  
    k.print();  
}
```

k can be a reference to some **Person** instance, but can be also a reference to instance of any **Derived** class

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);
```

But what will be printed?

```
✓ print_info(p);  
✓ print_info(s);
```

Subtyping polymorphism

```
void print_info(Person k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);
```

But what will be printed?

✓ print_info(p);
✓ print_info(s);

Subtyping polymorphism

```
void print_info(Person k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);
```

But what will be printed?

```
✓ print_info(p);  
✓ print_info(s);
```

Subtyping polymorphism

```
void print_info(Person k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);
```

But what will be printed?

```
✓ print_info(p); // Person Bob; age = 30  
✓ print_info(s); // Person Alice; age = 18
```

Why? What happened?




Subtyping polymorphism

```
void print_info(Person k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);
```

```
print_info(p); // Person Bob; age = 30
```

```
→ print_info(s); // Person Alice; age = 18
```




Subtyping polymorphism

```
void print_info(Person k) {  
    k.print();  
}
```

```
Person p("Bob", 30);  
Student s("Alice", 18, 22126, 1);
```

```
print_info(p); // Person Bob; age = 30  
→ print_info(s); // Person Alice; age = 18
```



*layout is actually a bit different, we will discuss it soon

Subtyping polymorphism

Another example of how `subtyping polymorphism` doesn't work with values (only pointers and refs):

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

```
Person p[10];
```

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

```
Person p[10]; // ???
```

In such case it contains only persons, no students (if you will try to assign a student it will be just copied to person).

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

```
Person* p[10];
```

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

```
Person* p[10];  
p[0] = new Student(...);  
p[1] = new Employee(...);
```

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

```
Person* p[10];  
p[0] = new Student(...);  
p[1] = new Employee(...);
```

This is possible, pointer to **derived** is used instead of pointer to the **base**.

Subtyping polymorphism

Another example of how **subtyping polymorphism** doesn't work with values (only pointers and refs).

Imagine you want to have an array of different instances from the **hierarchy** (Persons, Students, Employees, etc). What type will it have?

```
Person* p[10];
```

```
for (size_t i = 0; i < 10; i++) {  
    p->print();  
}
```

Virtual methods mechanism
will work as well!


```

class Person {
protected:
    const char* name;
    size_t age;
public:
    Person(const char* name, size_t age):
        name(name), age(age) {}

    void print() const {
        std::cout << "Person " << name
                    << "; age = " << age
                    << std::endl;
    }
};

```

```

class Student: public Person {
private:
    size_t group;
    size_t id;
public:
    Student(const char* name, size_t age,
            size_t group, size_t id):
        Person(name, age),
        group(group), id(id) {}

    void print() const {
        std::cout << "Student " << name ✓
                    << " from group " << group
                    << std::endl;
    }
};

```

Usually you need `public` inheritance in C++.

Scenarios for `non-public` inheritance: when you want to remove something from public API that you've gotten from the base class. Details later.

About building hierarchies

LSP: if some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

Practical consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

About building hierarchies

LSP: if some predicate is true about all **Base** class instances, it should also be true for all **Derived** class instances.

Practical consequence: you can write your code in terms of **basic classes** and instances of **derived classes** can be **substituted** there.

How is LSP connected with different types of inheritance in C++?

```
class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};
```

```
class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};
```

```
class Stack: public LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};
```

```
class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};
```

```
class Stack: public LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};
```

What do you think about such hierarchy?

```
class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};
```

```
class Stack: public LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};
```

What do you think about such hierarchy? Is **awful**:

1. Stack has some unneeded public methods getHead and etc,

```

class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};

```

```

class Stack: public LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};

```

What do you think about such hierarchy? Is **awful**:

1. Stack has some unneeded public methods getHead and etc,
2. Logic is **ruined** here: Stack is NOT necessary a LinkedList!


```
class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};
```

```
class Stack: public LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};
```

What do you think about such hierarchy? Is **awful**:

1. Stack has some unneeded public methods getHead and etc,
2. Logic is **ruined** here: Stack is NOT necessary a LinkedList!
3. LSP?

```
class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};
```

```
class Stack: public LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};
```

What do you think about such hierarchy? Is **awful**:

1. Stack has some unneeded public methods getHead and etc,
2. Logic is **ruined** here: Stack is NOT necessary a LinkedList!
3. LSP? Violated as hell (LinkedList invariants can be broken)

```

class LinkedList {
    Node* head;
public:

    Node* getHead() {
        return head;
    }

    bool isEmpty() {
        return head == nullptr;
    }

    void addToHead(int value) {
        ...
    }
};

```

```

class Stack: /* private */ LinkedList {
public:
    void push(int value) {
        addToHead(value);
    }
    ...
};

Stack s;
s.getHead(); // compilation error

```

But what if inheritance would be private?

1. No more unneeded public methods getHead and etc,

<pre> class LinkedList { Node* head; public: Node* getHead() { return head; } bool isEmpty() { return head == nullptr; } void addToHead(int value) { ... } }; </pre>	<pre> class Stack: /* private */ LinkedList { public: void push(int value) { addToHead(value); } ... }; LinkedList* l1 = new Stack(); // compilation error!!! </pre>
---	---

But what if inheritance would be private?

1. No more unneeded public methods getHead and etc,
2. Logic is different here Stack is **not** a LinkedList indeed,
3. LSP is **violated**, but it is ok, it is just not "**is-a**" relationship

<pre> class LinkedList { Node* head; public: Node* getHead() { return head; } bool isEmpty() { return head == nullptr; } void addToHead(int value) { ... } }; </pre>	<pre> class Stack: /* private */ LinkedList { public: void push(int value) { addToHead(value); } ... }; LinkedList* l1 = new Stack(); // compilation error!!! </pre> <p>What relationship do we have here?</p>
---	---

But what if inheritance would be private?


1. No more unneeded public methods getHead and etc,
2. Logic is different here Stack is **not** a LinkedList indeed,
3. LSP is **violated**, but it is ok, it is just not "**is-a**" relationship

<pre> class LinkedList { Node* head; public: Node* getHead() { return head; } bool isEmpty() { return head == nullptr; } void addToHead(int value) { ... } }; </pre>	<pre> class Stack: /* private */ LinkedList { public: void push(int value) { addToHead(value); } ... }; LinkedList* l1 = new Stack(); // compilation error!!! </pre> <p>What relationship do we have here? LinkedList is part of Stack.</p>
---	--

But what if inheritance would be private?

1. No more unneeded public methods getHead and etc,
2. Logic is different here Stack is **not** a LinkedList indeed,
3. LSP is **violated**, but it is ok, it is just not "**is-a**" relationship

Imagine we have one more class



This is called **composition**.

There are some benefits of such approach, but it just doesn't look logical here (why `Person` should be a **part** of `Student`?)

Also: how can I get a name from `Student`? Some forwarding method to base => **boilerplate code**! Something we want to get rid of.

<pre> class LinkedList { Node* head; public: Node* getHead() { return head; } bool isEmpty() { return head == nullptr; } void addToHead(int value) { ... } }; </pre>	<pre> class Stack: /* private */ LinkedList { public: void push(int value) { addToHead(value); } ... }; LinkedList* l1 = new Stack(); // compilation error!!! </pre> <p>What relationship do we have here? Linked List is part of Stack. This is composition!!!</p>
---	--

But what if inheritance would be private?

1. No more unneeded public methods getHead and etc,
2. Logic is different here Stack is **not** a LinkedList indeed,
3. LSP is **violated**, but it is ok, it is just not "**is-a**" relationship

About building hierarchies

- 1) Use `public` inheritance where LSP works.

About building hierarchies

- 1) Use `public` inheritance where LSP works.
- 2) Use `private` inheritance where you want to have composition, but still want to have direct access to private parts of Base without getters.

About building hierarchies

- 1) Use `public` inheritance where LSP works.
- 2) Use `private` inheritance where you want to have composition, but still want to have direct access to private parts of Base without getters.
- 3) Use protected inheritance when you want to `seal` the hierarchy in some reason.

Abstract classes

Abstract classes

```
class Figure {  
public:  
    virtual double area() {  
        throw "error!";  
    }  
};
```

```
class Square: public Figure {  
    double length;  
public:  
    Square(double l): length(l) {}  
    double area() {  
        return length * length;  
    }  
};
```

Abstract classes

```
class Figure {  
public:  
    virtual double area() {  
        throw "error!";  
    }  
};
```



Why do we need
instances of such
classes?

```
class Square: public Figure {  
    double length;  
public:  
    Square(double l): length(l) {}  
    double area() {  
        return length * length;  
    }  
};
```

Abstract classes

```
class Figure {  
public:  
    virtual double area() = 0;  
};
```

```
class Square: public Figure {  
    double length;  
public:  
    Square(double l): length(l) {}  
    double area() {  
        return length * length;  
    }  
};
```

Abstract classes

```
class Figure {  
public:  
    virtual double area() = 0;  
};
```

Pure virtual function

Abstract class

```
class Square: public Figure {  
    double length;  
public:  
    Square(double l): length(l) {}  
    double area() {  
        return length * length;  
    }  
};
```


Abstract classes

```
class Figure {  
public:  
    virtual double area() = 0;  
};
```

Pure virtual function

Abstract class

```
class Square: public Figure {  
    double length;  
public:  
    Square(double l): length(l) {}  
    double area() {  
        return length * length;  
    }  
};
```

If class either defines or inherits **pure virtual** function it becomes **abstract**

Abstract classes

```
class Figure {  
public:  
    virtual double area() = 0;  
};
```

Pure virtual function

Abstract class

You can't instantiate such classes.
But you can have pointers or references to them.

```
class Square: public Figure {  
    double length;  
public:  
    Square(double l): length(l) {}  
    double area() {  
        return length * length;  
    }  
};
```

✗ `Figure f();`
✗ `Figure arr[10];`
✓ `Figure* p = new Square(3.14);`

Abstract classes

- We need abstract classes to form the **correct hierarchies** (they are usually roots or their direct successors)
- You **can't** create instances of such classes
- If **pure virtual function** is not overridden in the derived class it also becomes **abstract**.

Virtual destructors

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```


Expression:
simplify()

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};  
  
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

Expression:
simplify()

Binary:
left
right
~Binary()


A black arrow points from the Binary class box to the Expression class box, indicating that Binary inherits from Expression.

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```




Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```




Do you see any problems here?

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```



Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);
```

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);  
exp->simplify();  
// what will be called?
```

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);  
exp->simplify();  
// Add:simplify will be called
```

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);  
exp->simplify();  
// Add:simplify will be called  
  
delete exp;  
// what will be called?
```

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);  
exp->simplify();  
// Add:simplify will be called
```

```
delete exp;  
// Expression::~~Expression  
// Memory leak!
```

How to fix?

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
};
```

```
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};
```

```
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);  
exp->simplify();  
// Add:simplify will be called
```

```
delete exp;  
// Expression::~~Expression  
// Memory leak!
```

How to fix? We need to have a virtual destructor in Expression.

Virtual destructors

```
class Expression {  
public:  
    virtual Expression* simplify() = 0;  
    virtual ~Expression() {};  
};  
  
class Binary: public Expression {  
    Expression* left;  
    Expression* right;  
public:  
    ~Binary() {  
        delete left;  
        delete right;  
    }  
};  
  
class Add: public Binary { ... };  
class Sub: public Binary { ... };
```

```
Expression* exp = new Add(...);  
exp->simplify();  
// Add:simplify will be called  
  
delete exp;  
// Binary::~~Binary() will be called  
// No more memory leak 😊
```




Not So Tiny Task №7 (2 points)

Implement a hierarchy of classes for symbolic differentiation of expressions.

- **Base class**: `Expression`;
- **Derived classes**: `Binary`, `Unary`, `Add`, `Sub`, `Mult`, `Div`, `Exponent`, `Var`, `Val`;
- **Base class** expression should contain pure virtual function `Expression* diff(std::string var)`; (its implementations should return differentiation result for the expression by the given variable);
- Tests should be prepared as usual.

Not So Tiny Task №7 (2 points)



Example:

```
Expression* e = new Add(new Var("x"),  
                        new Mult(new Val(10), new Var("y")));
```

```
// e = x + 10*y
```

```
Expression* res1 = e->diff("x");  
// res1 = 1 + (0*y + 10*0) (it is ok to have non-simplified exprs)
```

```
Expression* res2 = e->diff("y");  
// res2 = 0 + (0*y + 10*1) (it is ok to have non-simplified exprs)
```

Takeaways

- Inheritance in subtyping polymorphism in C++
- LSP as its theoretical base (please don't be too serious about it)
- Virtual functions in C++ and virtual destructors
- Pure virtual functions, abstract classes

How virtual functions actually work?

