

1 Basic linux commands

Here will be briefly explained some basic linux commands. For information about more commands, feel free to consult with the internet.

1.1 Getting around

Command	Explanation
<code>ls</code>	list contents of current directory
<code>ls <i>dirname</i></code>	list contents of directory named <i>dirname</i>
<code>cd <i>dirname</i></code>	change current directory to <i>dirname</i>
<code>cd ~</code>	go to home directory (default directory)
<code>cd ..</code>	go one directory up
<code>pwd</code>	print name of current directory
<code>mkdir <i>dirname</i></code>	make a new directory named <i>dirname</i>
<code>man <i>command</i></code>	show manual for <i>command</i>

1.2 File manipulation

Command	Explanation
<code>cp <i>filename1 filename2</i></code>	copy file
<code>cp -r <i>dirname1 dirname2</i></code>	copy directory
<code>mv <i>name1 name2</i></code>	move file or directory (can be used for renaming)
<code>rm <i>filename</i></code>	remove file (you won't be able to recover removed file)
<code>rm -r <i>dirname</i></code>	remove directory and its contents
<code>more <i>filename</i></code>	command for paging through text file one screenful at a time
<code>less <i>filename</i></code>	similar as more. Better for viewing large text files
<code>cat <i>filename1 filename2 filenameN</i></code>	concatenate text files in print output to terminal window
<code>head <i>filename</i></code>	print first 10 lines of a text file to terminal window
<code>head -n 20 <i>filename</i></code>	print first 20 lines of a text file to terminal window
<code>tail</code>	opposite of <code>head</code>
<code>wc <i>filename</i></code>	show the number of lines, words and characters in a text file
<code>cut -f 2 <i>tabDelimitedFilename</i></code>	extract 2nd column from a tab delimited file
<code>cut -f 3 -d , <i>comaSeperatedFilename</i></code>	extract 3rd column from a coma seperated file
<code>nano <i>filename</i></code>	open <i>filename</i> in text editor <code>nano</code>

1.3 Archiving and unarchiving of files

Note that for the `tar` utility, option `c` stands for compress, `x` - for uncompress or extract, `z` - for dealing with `tar.gz`, and `j` - for dealing with `tar.bz2`

1.3.1 Compressing

Command	Explanation
<code>tar -cvf filename.tar filename</code>	compress file to .tar format
<code>tar -zcvf filename.tar.gz filename</code>	compress file to .tar.gz format
<code>tar -jcvf filename.tar.bz2 filename</code>	compress file to .tar.bz2 format
<code>zip filename.zip filename</code>	compress file to .zip format
<code>gzip filename</code>	compress file to .gz format

1.3.2 Uncompressing

Command	Explanation
<code>tar -xvf filename.tar</code>	uncompress from .tar format
<code>tar -zxvf filename.tar.gz</code>	uncompress from .tar.gz format
<code>tar -jxvf filename.tar.bz2</code>	uncompress from .tar.bz2 format
<code>unzip filename.zip</code>	uncompress from .zip format
<code>gzip -d file.gz</code>	uncompress from .gz format

1.4 Input/Output redirection

Command	Explanation
<code>command > filename</code>	Output of <i>command</i> is saved to <i>filename</i> , overwriting it
<code>command >> filename</code>	Output of <i>command</i> is appended at the end of <i>filename</i>
<code>command < filename</code>	<i>command</i> reads input from <i>filename</i>
<code>command1 command2</code>	<i>command2</i> takes the output of <i>command1</i> and produces result

1.5 Filters

Command	Explanation
<code>grep text filename</code>	Prints every line in <i>filename</i> containing <i>text</i>
<code>sed 's/red/green/' filename</code>	Prints every line in <i>filename</i> substituting word <i>red</i> with word <i>green</i>

1.6 Pattern matching

Pattern	Explanation
<code>*</code>	matches zero or more characters
<code>?</code>	matches one character

1.7 Miscellaneous

Command	Explanation
<code>echo text</code>	display a line of text
<code>history</code>	view your command line history
<code>wget someWebAddress</code>	download contents of <i>someWebAddress</i> to current directory
<code>make</code>	tool that is used to compile source code creating executables
<code>export name=value</code>	sets <i>value</i> to <i>name</i> . Type <code>echo \$name</code> to view <i>value</i>

2 Setup of the working environment

Since we do not have the administrator's rights on this server, we can't install software on the system. However, we can still install software locally in our home directories. We will create a special directory where all our executables will be stored. Let's create this directory and name it **binaries**. In linux terminal type:

```
mkdir binaries
```

Let's make this directory special - every executable file we put there, we will be able to easily execute, just by typing the executable's file name from anywhere in the system. To achieve this, we will be adding `~/binaries` folder to the `$PATH` system's environment variable by editing a text file named `.bashrc` using text editor **nano**. In linux terminal type:

```
nano ~/.bashrc
```

Text editor will open the file and you can edit it. Navigate to the bottom of the text file using arrows and type in following text:

```
export PATH=$PATH:~/binaries
```

Hit **Ctrl o** and **Enter** to save file and **Ctrl x** to exit. Reload `.bashrc`:

```
source .bashrc
```

`$PATH` variable contains a list of directories that the system will look in, when we are entering a command. To view contents of `$PATH`, type in terminal:

```
echo $PATH
```

To install software we will simply have to copy executable to our special directory **binaries**.

Many of the open source tools are deposited in the <https://github.com> repository. To download software from <https://github.com> easily, we will use a tool called **git**. **git** is already preinstalled on our servers, however, on your own Ubuntu servers you can install it by typing:

```
sudo apt-get install git
```

3 *De-novo* assembly of sequenced reads

3.1 Installation of *de-novo* assembler

For *de-novo* assembly we will use mira assembler. You can download it from <http://sourceforge.net/projects/mira-assembler/>. Click on Files → MIRA → stable. Rightclick on `mira_4.0.2_linux-gnu_x86_64_static.tar.bz2` and Copy link address. To download it on our linux server, we will be using command `wget`. In linux terminal type:

```
cd ~/programs
wget -O mira.tar.bz2
```

paste the copied location and hit **Enter**. The program will be downloaded in our `~/programs` directory. The downloaded software is archived in `.tar.bz2` format, therefore we need to extract it from archive. To extract it from archive, type in terminal:

```
tar -jxvf mira.tar.bz2
```

A new folder named `mira_4.0.2_linux-gnu_x86_64_static` will appear. This is our extracted software. MIRA is already precompiled for us, so we just need to find the compiled binary files in the folder and copy them to appropriate directory:

```
cd mira_4.0.2_linux-gnu_x86_64_static
cd bin
cp mira ~/binaries
cd ~
```

Let's create a separate directory for our *de-novo* assembly project and copy the reads in it:

```
cd ngs_work
mkdir denovo
cd denovo
cp ~/data/readsfordenovo.fastq .
```

MIRA needs a manifest file for performing *de-novo* assembly. We will create a basic manifest file. Our manifest file will consist of 5 entries. From MIRA's manual, these entries are:

- **project** - name of our assemblies project. The project name will be used by MIRA in project's directory naming
- **job** - tells the assembler whether

1. we want to perform *de-novo* assembly or map reads against reference genome
 2. genomic DNA or transcripts were sequenced
 3. we want accurate (slow) or draft (fast) assembly
- **readgroup** - tells assembler which reads can be pooled together when assembling reads from multiple sequencing technologies
 - **data** - tells the assembler where are our reads
 - **technology** - tells the assembler what sequencing technology was used for generating reads

To create manifest file, we will use text editor **nano**. To start the text editor, type

```
nano
```

and the editor will open. Now, to create the manifest file, in the text editor type:

```
project=readsfordenovo_Assembly
job=denovo,genome,draft
readgroup
data=readsfordenovo.fastq
technology=iontor
```

To save the text file hit **Ctrl o**, enter the name of the file (e.g. **readsfordenovo.mnfst**), hit **Enter** to save and **Ctrl x** to quit **nano**. To launch MIRA, type:

```
~/binaries/mira readsfordenovo.mnfst
```

If you wish to gain finer control of some aspects of the assembling process, then, please, do refer to the MIRA's manual.

4 Building variant calling pipeline

We have *IonTorrent* targeted resequencing data from human chromosomes 1., 2. and 19. Our task is to find all nonsynonymous and stop mutations present in the data and to automatize this process by building data analysis pipeline. To accomplish this task we can divide our work in following subtasks:

- Installation of relevant tools
- Obtaining of reference sequences
- Read mapping against reference genome
- Variant calling

- Variant annotation
- Filtering of nonsynonymous and stop mutation variants
- Pipeline building

4.1 Tool installation

4.1.1 Installation of *IonTorrent* mapping software

To detect variants present in the data we need to map sequencing reads against reference sequence. For reads generated with *IonTorrent* sequencing platform we will use program `tmap`.

`tmap` and its compilation instructions can be found at <https://github.com/iontorrent/TS/tree/master/Analysis/TMAP>. Installation instructions:

```
cd ~/programs
git clone git://github.com/iontorrent/TMAP.git
cd TMAP
git submodule init
git submodule update
sh autogen.sh
./configure
make
```

Lets test the program to confirm that it was compiled successfully:

```
./tmap
```

If you see the programs interface, the program was installed successfully. Move the compiled binary file to our `binaries` folder:

```
cp tmap ~/binaries
```

We will also need two tools named `samtools` and `bcftools` which are used for manipulation of mapped reads and variation calling. You can obtain these tools from <http://sourceforge.net/projects/samtools/>. Click on Files → `samtools` → 1.2 Rightclick on `samtools-1.2.tar.bz2` and choose Copy link address. We will download these tools in directory `programs`:

```
cd ~/programs
wget -O samtools.tar.bz2
paste the copied location and hit Enter.
```

Now, repeat this process for `bcftools`:

```
wget -O bcftools.tar.bz2
paste the copied location and hit Enter.
```

The tools are compressed in `.tar.bz2` format, so we need to extract them:

```
tar -jxvf samtools.tar.bz2
tar -jxvf bcftools.tar.bz2
```

Note that if we had a lot more files to extract and it would be too time consuming to manually extract them, we could use a `for` loop and pattern matching to extract archives automatically:

```
for archive in *.tar.bz2; do
    tar -jxvf $archive
done
```

We have downloaded and extracted source code of the tools, but to make these tools usable, we need to compile the source code. Source code compiling is performed with command `make`:

```
cd samtools-1.2
make
```

If (hopefully) no errors were encountered, then `samtools` was compiled correctly. type:

```
./samtools
```

to test the tool. If you see the program's interface, then the program was compiled successfully. Move compiled binary file to a directory where we will store our compiled software:

```
cp samtools ~/binaries
```

Repeat the same process for `bcftools` (go to `bcftools` source code directory, compile it and copy resulting binary file to `~/binaries`)

4.2 Obtaining reference sequences

We will download reference sequences in a separate directory to avoid file cluttering. Let's make a new directory in our `ngs_work` directory named `reseq`, and there we will create a separate folder `ref` for our reference sequences:

```
cd ~
cd ngs_work
mkdir reseq
```

```
cd reseq
mkdir ref
cd ref
```

Our reference sequences can be accessed from a database made by University of California, Santa Cruz. The web address of the database is <http://genome.ucsc.edu/>. To find the necessary references sequences for chromosomes 1., 2. and 19. click on **Downloads** → **human** → **Data set by chromosome**. Right click on **chr1.fa.gz** and choose **Copy link location**. In terminal type

```
wget
```

paste the copied location and hit **Enter**. The reference sequence is compressed in **.gz** format, so we need to extract it:

```
gzip -d chr1.fa.gz
```

File **chr1.fa** will appear in our folder.

Repeat the process for chromosomes 2. and 19.

After we have obtained and extracted our reference sequences, we need to concatenate them. To accomplish this task we will use command **cat**:

```
cat chr1.fa chr2.fa chr19.fa > chr_merged.fa
```