

Java



IT Learning &
Outsourcing Center

www.pragmatic.bg

Lector: Milen Penchev


Skype: donald8605

E-mail: milen.penchev@gmail.com

Facebook: <http://www.facebook.com/milen.penchev.39>


Copyright © Pragmatic LLC

2013 – 2016



Recap

- Скоростта на интернета в залата





Recap





Recap

1995





Recap

James Gosling



Recap



IT Learning &
Outsourcing Center



Recap

- Object-Oriented



Recap

- Object-Oriented
- Compiles .java into .class



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)
- Class name rules



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)
- Class name rules
- Instance, class and local variables; arguments



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)
- Class name rules
- Instance, class and local variables; arguments
- Primitives



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)
- Class name rules
- Instance, class and local variables; arguments
- Primitives
- Arithmetic, Unary, Equality, Conditional Operators



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)
- Class name rules
- Instance, class and local variables; arguments
- Primitives
- Arithmetic, Unary, Equality, Conditional Operators
- AND, OR, NOT



Recap

- Object-Oriented
- Compiles .java into .class
- Runs in JVM
- How to install Java / Eclipse
- First program (Hello from the other side)
- Class name rules
- Instance, class and local variables; arguments
- Primitives
- Arithmetic, Unary, Equality, Conditional Operators
- AND, OR, NOT
- If-Else



Lecture 2 - Overall

- Loops
- while
- for
- do-while
- Switch
- Keywords - break and continue



Problem to solve

- Print all the numbers
 - From 1 to 5
 - From 1 to 1000
 - From 1 to n
 - From n to m





What is loop?

- A loop is a structure that allows sequence of statement to be executed more times in a row
- Loops have a boolean condition and a block of code for execution. While the condition is true, the block is being executed.
- A loop that never ends is called an infinite loop



While loop

- While the condition is true, the block is being executed.





While loop

- While loop example:

Counter
initialization

Boolean condition.
If $i > 100$, the block will
NOT be executed

Block of code for
repeatable
execution

```
int i = 1;
while (i <= 100) {
    System.out.println(i);
    i++;
}
```


- WhileExample.java , WhileExample2.java, WhileExample3.java, Example.java in code examples
- Numbers.java – nested while loop in code examples



do-while

- Gets executed at least once
- Condition is after the execution

Flow Diagram of do .. while LOOP





Example of do-while

- An example of a do-while loop:

The code block that
gets executed


```
do {  
    System.out.println(i);  
    i++;  
} while (i <= 1000)
```

if $i \leq 1000$ (TRUE),
execute the block once
again



For loop

- FOR loop:
 - Initialization
 - Condition
 - Increment
 - Body





Example of for loop

An example of for loop:

```
for (int i = 0; i < 100; i++) {  
    System.out.println(i);  
}
```

- Initialization: `int i = 0;`
- Condition: `i < 100;`
- Increment: `i++`
- Body: {
 `System.out.println(i);`
}

**ForExample.java, ForExample1.java,
Fibonacci.java, Factorial.java, Sum.java in
code examples**



Problem

- Try to quit a for-loop during the execution of the repeatable block
- One possible to solution is to set the counter to a value which will make the boolean condition quit the loop.... but there is a much more proper way



Break

- Break is a keyword
- A statement by itself
- It doesn't require anything else
- It stops the execution of the loop
- **BreakExample.java** in code examples

```
for (int i = 0; i < 50; i++) {  
    if (i == 7) {  
        break;  
    }  
}
```

The loop will quit when i
= 7



Problem

- Try to omit specific block of code in the body – for example sum all numbers between 1 and 100 but omit all numbers between 51 and 74
- Encapsulating the code in if-else statements may be used. Although for more complicated structures should be used for more complicated cases



Continue

- Continue is a keyword
- A statement by itself
- It doesn't require anything else
- It stops the current iteration of the loop, but doesn't stop the loop
- **ContinueExample.java** in code examples

if it is between 51 and 71,
it will skip everything that
is after continue



Switch statement

- Unlike *if-then* and *if-then-else* statements, the *switch* statement can have a number of possible execution paths
- A switch works with the byte, short, char, and int primitive data types. It also works with String class, and a few special classes that wrap certain primitive types: Character, Byte, Short, and Integer



Switch example (part 1)

- The body of a switch statement is known as a *switch block*. A statement in the switch block can be labeled with one or more case or default label. The switch statement evaluates its expression, then executes all statements that follow the matching case label.



Switch example (part 2)

```
public static void main(String[] args) {  
  
    int user = 18;  
  
    switch ( user ) {  
        case 18:  
            System.out.println("You're 18");  
            break;  
        case 19:  
            System.out.println("You're 19");  
            break;  
        case 20:  
            System.out.println("You're 20");  
            break;  
        default:  
            System.out.println("You're not 18, 19 or 20");  
    }  
  
}
```

- SwitchDemo.java in the code examples



Switch – break & default

- Another point of interest is the **break** statement. Each **break** statement terminates the enclosing switch statement. Control flow continues with the first statement following the switch block. The **break** statements are necessary because without them, statements in switch blocks *fall through*: All statements after the matching case label are executed in sequence, regardless of the expression of subsequent case labels, until a **break** statement is encountered.
- The **default** section handles all values that are not explicitly handled by one of the case sections.
- **SwitchDemoFallThrough.java** in the code examples



How to 'for each' in Java

- You'll get to know in the lecture related to Arrays and collections

Cheers! 😊



Summary

- Why do we use loops?
- What does a loop consist of?
- Difference between *while* and *do-while*?
- How to use *for – loop*?
- How to terminate a loop?
- How to stop the current iteration?