

# SOAP and REST Web Services

## Software Testing

Lector: Aleksandar Karamfilov

Skype: sanders\_kar

Email: alex@pragmatic.bg

Facebook: facebook.com/a.karamfilov

Copyright © Pragmatic LLC



[www.pragmatic.bg](http://www.pragmatic.bg)



# Content

- Different Types of Web Services
- SOAP Services – Theory
  - SOAP (Simple Object Access Protocol)
  - WSDL (Web Service Description Language)
  - UDDI (Universal Description Discovery and Integration)
- RESTful Services – Theory
  - Resource
  - Representation
  - Actions
- SOAP vs. REST



# Web Service Types

Person A



Hi, how are you?



Person B



Fine.



- Two important things
  - Media / Transport (Phone)
  - Message Format (English grammar)



# Web Service Types

- Based on messaging format and transport we can distinguish two types of Web Services
  - SOAP
  - REST



# SOAP Services

- Message Format
  - XML
  - SOAP strictly defines message format in SOAP protocol
- Transport
  - HTTP, FTP, UDP



# REST Services

- Message Format
  - XML, JSON, YAML, HTML, plain text
  - Message can be anything we can transfer over the network
  - Data is send as it is (not enveloped)
- Transport
  - HTTP



# What is SOAP?

- SOAP Services are based on SOAP protocol
- SOAP stands for Simple Object Access Protocol
- SOAP is
  - A communication protocol
  - A format for sending messages
  - Based on XML
  - Platform independent
  - Language independent
  - Simple and extensible
  - Will be developed as a W<sub>3</sub>C standard



# SOAP Services

- In order to access the server client should know two things
  - Location of the service (where the service is)
  - Description of the service (what this service provides and how it works)
    - Description is XML file know as WSDL
    - WSDL stands for “Web Services Description Language”





# SOAP Services

- How client locate the server
  - Server knows the client and send him WSDL
  - UDDI
    - Place where service providers register their services
    - UDDI stands for “Universal Description, Discovery and Integration”




# SOAP Services

- UDDI communication workflow
  - Client search UDDI
  - UDDI returns all services providing searched service
  - Client chooses a service and get its WSDL



# SOAP Services


- SOAP Services communication in picture






# What is WSDL?

- WSDL is an XML-based language
- WSDL document is actually XML document
- WSDL is used to describe Web services
- WSDL is also used to locate Web services
- WSDL is W3C recommendation





# WSDL Structure



- Abstract Section
  - What messages service use
  - What operations service can perform
- Concrete Section
  - Where service is located
  - How we can access the service



# WSDL Abstract Section

- Types
  - Defines the data type definitions for messages that will be exchanged by the web service.
- Message
  - Defines the set of actual messages that will be exchanged.
- PortType
  - Defines the operations provided/available and involved messages.
  - Operation refers to the messages involved in the transaction.

# WSDL Abstract Section



## ■ Types

```
<!-- Type definitions -->
<types>
  <xsd:schema targetNamespace="http://www.skatestown.com/ns/availability"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <xsd:complexType name="availabilityType">
      <xsd:sequence>
        <xsd:element name="sku" type="xsd:string"/>
        <xsd:element name="price" type="xsd:double"/>
        <xsd:element name="quantityAvailable" type="xsd:integer"/>
      </xsd:sequence>
    </xsd:complexType>
  </xsd:schema>
</types>
```

# WSDL Abstract Section



## ■ Message

```
<!-- Message definitions -->
<!-- A PriceCheckRequest is simply an item code (sku) -->
<message name="PriceCheckRequest">
  <part name="sku" type="xsd:string"/>
</message>

<!-- A PriceCheckResponse consists of an availability structure,
<!-- defined above.
<message name="PriceCheckResponse">
  <part name="result" type="avail:availabilityType"/>
</message>
```



# WSDL Abstract Section



## ■ PortType

```
<!-- Port type definitions -->
<portType name="PriceCheckPortType">
  <operation name="checkPrice">
    <input message="pc:PriceCheckRequest"/>
    <output message="pc:PriceCheckResponse"/>
  </operation>
</portType>
```

# WSDL Concrete Section



- Bindings
  - Defines transport protocol
  - Defines the message format for operations defined by the portType.
  
- Service
  - Defines the endpoint where the web service will be exposed

# WSDL Concrete Section



## ■ Bindings

```
<!-- Binding definitions -->
<binding name="PriceCheckSOAPBinding" type="pc:PriceCheckPortType">
  <soap:binding style="rpc"
    transport="http://schemas.xmlsoap.org/soap/http"/>
  <operation name="checkPrice">
    <soap:operation soapAction=""/>
    <input>
      <soap:body use="encoded"
        namespace=
          "http://www.skatestown.com/services/PriceCheck"
        encodingStyle=
          "http://schemas.xmlsoap.org/soap/encoding/" />
    </input>
    <output>
      <soap:body use="encoded"
        namespace=
          "http://www.skatestown.com/services/PriceCheck"
        encodingStyle=
          "http://schemas.xmlsoap.org/soap/encoding/" />
    </output>
  </operation>
</binding>
```

# WSDL Concrete Section



## ■ Service

```
<!-- Service definition -->
<service name="PriceCheckService">
  <port name="PriceCheck" binding="pc:PriceCheckSOAPBinding">
    <soap:address
      location=
        "http://localhost:8080/axis/services/PriceCheck" />
  </port>
</service>
```




# WSDL Example

- Examples
  - [Example 1](#)
  - [Example 2](#)

# SOAP Messages

- Client and server communicate with SOAP messages





# SOAP Messages

- Plain SOAP Message Diagram





# SOAP Messages

- SOAP Message contains following main elements:
  - Envelope (mandatory)
  - Header (optional)
  - Body (mandatory)
- Both SOAP Requests and Responses use Envelope







# SOAP Message

```
<soap:Envelope
```

```
  xmlns:soap="http://www.w3.org/2001/12/soap-envelope"
```

```
  soap:encodingStyle="http://www.w3.org/2001/12/soap-encoding">
```

```
    <soap:Header>
```

[Here's where extraneous information, like password data, resides]

```
    </soap:Header>
```

```
    <soap:Body>
```

[Here's where the actual message content resides]

```
      <soap:Fault>
```

[Here are instructions to the server about how to handle errors]

```
      </soap:Fault>
```

```
    </soap:Body>
```

```
</soap:Envelope>
```



# SOAP Message

- Example
  - Simple request message with out headers

```
<?xml version="1.0"?>

<soap:Envelope
xmlns:soap="http://www.w3.org/2003/05/soap-envelope/"
soap:encodingStyle="http://www.w3.org/2003/05/soap-encoding">

<soap:Body>
  <m:GetPrice xmlns:m="https://www.w3schools.com/prices">
    <m:Item>Apples</m:Item>
  </m:GetPrice>
</soap:Body>

</soap:Envelope>
```



# SOAP Message

- Example
  - Simple response message

```
<?xml version="1.0"?>

<soap:Envelope
xmlns:soap="http://www.w3.org/2003/05/soap-envelope/"
soap:encodingStyle="http://www.w3.org/2003/05/soap-encoding">

<soap:Body>
  <m:GetPriceResponse xmlns:m="https://www.w3schools.com/prices">
    <m:Price>1.90</m:Price>
  </m:GetPriceResponse>
</soap:Body>

</soap:Envelope>
```



# SOAP Envelope

- SOAP Envelope encapsulates the entire message
- SOAP Envelope is the root element of a SOAP message
- This element defines the XML document as a SOAP message.
- SOAP Envelope contains two child elements, an optional **<Header>** and a mandatory **<Body>**



# SOAP Header

- SOAP Header is optional
- Must be the first child element of the Envelope
- Header elements can occur multiple times
- Header includes information that might be needed by the receiver but isn't strictly part of the message content, like
  - login and password information
  - digital signatures
  - maximum time the SOAP request may take to process
  - state



# SOAP Header Attributes

- Attributes appear in Header elements
- Determine how a recipient processes a message
- The SOAP 1.1 specification defines two attributes that can appear in SOAP Header Element:
  - actor
  - mustUnderstand
- The SOAP 1.2 specification defines three attributes:
  - role (a new name for actor)
  - mustUnderstand
  - relay



# Role/Actor Attribute

- Header blocks (elements) can be targeted at nodes acting in specific roles
- Example:
  - If a header block is targeted for nodes acting in the "ultimateReceiver" role, then only nodes acting as ultimate receivers must process that header block. All other nodes should leave it unprocessed.

# mustUnderstand Attribute



- Indicate whether a header entry is mandatory or optional
- Has two valid values
  - True
    - Means that any node (computer) processing the SOAP message must understand the given header block
    - If intermediate node does not understand the header block (element) containing the mustUnderstand attribute, it should not process the header and must return a SOAP fault.
  - False
    - Means that node might not understand given header block





# Relay Attribute

- Determines if a header block is allowed to be relayed if not processed
- Has two valid values
  - True
    - Header element can be forwarded even if not processed
  - False (Default)
    - Header element should be removed if the message is forwarded



# SOAP Body

- The SOAP Body element is **mandatory**
- The SOAP Body element **contains the actual SOAP message**
- Sample request:

```
<soap:Body>  
  <m:GetPrice xmlns:m="http://www.w3schools.com/prices">  
    <m:Item>Apples</m:Item>  
  </m:GetPrice>  
</soap:Body>
```

- Sample response:

```
<soap:Body>  
  <m:GetPriceResponse xmlns:m="http://www.w3schools.com/prices">  
    <m:Price>1.90</m:Price>  
  </m:GetPriceResponse>  
</soap:Body>
```



# SOAP Fault

- SOAP Fault element is optional
- Must appear as a child element of the Body element
- Fault element can only appear once in a SOAP
- Holds errors and status information for a SOAP message



# SOAP Fault

- SOAP Fault element has the following sub elements

## **<faultcode>**

A code for identifying the fault

## **<faultstring>**

A human readable explanation of the fault

## **<faultactor>**

Information about who caused the fault to happen

## **<detail>**

Holds application specific error information related to the Body element



# SOAP Faultcode Values

- SOAP Fault code values

## **<VersionMismatch>**

Found an invalid namespace for the SOAP Envelope element

## **<MustUnderstand>**

Child element of the Header element, with the mustUnderstand attribute set to "1", was not understood

## **<Client>**

The message was incorrectly formed or contained incorrect information

## **<Server>**

There was a problem with the server so the message could not proceed



# SOAP Example

- Examples
  - [Example Request](#)
  - [Example Response](#)



# What is REST?

- REST stands for “Representational State Transfer”
- Definition
  - Representational State Transfer (REST) is a software architecture style consisting of guidelines and best practices for creating scalable web services.
- REST is not a standard!



# REST Concepts

- A RESTful system should be
  - Client-server
  - Stateless
    - Each request should be independent of others
  - Cacheable
    - Clients are able to cache responses
    - Responses must therefore, implicitly or explicitly, define themselves as cacheable, or not
  - Uniformly accessible
    - Each resource must have a unique address and a valid point of access




# A RESTful System

## Main Actors



- Resources, Representations and Actions






# Resources

- A **resources** is "everything" the service can provide
- State and functions of a remote application are also considered as resources
- A resource must have a unique address over the Web

- Example of resources:
  - Title of a movie from IMDb
  - YouTube video
  - Images from Flickr
  - Order info from eBay





# Representations

- The **representations of resources** is what is sent back and forth clients and servers
- We never send or receive resources, only their representations



# Representation Formats

- Different clients are able to consume **different representations** of the same resource
- A representation can take various forms, but its resource has to be available through the **same URI**
- The format of the representations is determined by the **content-type**
  - Content type is a reusable collection of settings that you want to apply to a certain category of content

```
Accept: application/json, text/javascript, */*  
Content-Type: application/json; charset=utf-8  
Accept-Encoding: gzip, deflate
```



# XML Format

- **XML** is markup-language for encoding documents in machine-readable form
  - Text-based format
  - Consists of tags, attributes and content
  - Provide data and meta-data in the same time

```
<?xml version="1.0"?>
<library>
  <book><title>HTML 5</title><author>Bay Ivan</author></book>
  <book><title>WPF 4</title><author>Microsoft</author></book>
  <book><title>WCF 4</title><author>Kaka Mara</author></book>
  <book><title>UML 2.0</title><author>Bay Ali</author></book>
</library>
```



# JSON Format

- **JSON** (JavaScript Object Notation)
  - Standard for representing simple data structures and associative arrays
  - Lightweight text-based open standard
  - Derived from the JavaScript language

```
{
  "firstName": "John", "lastName": "Smith", "age": 25,
  "phoneNumber": [{ "type": "home", "number": "212 555-1234"},
    { "type": "fax", "number": "646 555-4567" }]
},
{
  "firstName": "Bay", "lastName": "Ivan", "age": 79
}
```



# JSON vs. XML

## XML

```
<employees>
  <employee>
    <firstName>John</firstName> <lastName>Doe</lastName>
  </employee>
  <employee>
    <firstName>Anna</firstName> <lastName>Smith</lastName>
  </employee>
  <employee>
    <firstName>Peter</firstName> <lastName>Jones</lastName>
  </employee>
</employees>
```

## JSON

```
{"employees":[
  {"firstName":"John", "lastName":"Doe"},
  {"firstName":"Anna", "lastName":"Smith"},
  {"firstName":"Peter", "lastName":"Jones"}
]}
```



# Actions

- Actions are used to operate on resources
- For example they can be used for
  - Getting info about a movie
  - Adding photo to Flickr
  - Deleting a post from Facebook
  - Updating Facebook status





# HTTP Based Actions

- Under HTTP, actions are standard HTTP request

Method	Description
GET	Retrieve / load a resource
POST	Create / store a resource
PUT	Update a resource
DELETE	Delete (remove) a resource
PATCH	Update resource partially
HEAD	Retrieve the resource's headers



# HTTP Status Codes

Status Code	Action	Description
<b>200</b>	OK	Successfully retrieved resource
<b>201</b>	Created	A new resource was created
<b>204</b>	No Content	Request has nothing to return
<b>301 / 302</b>	Moved	Moved to another location (redirect)
<b>400</b>	Bad Request	Invalid request / syntax error
<b>401 / 403</b>	Unauthorized	Authentication failed / Access denied
<b>404</b>	Not Found	Invalid resource
<b>409</b>	Conflict	Conflict was detected, e.g. duplicated email
<b>500 / 503</b>	Server Error	Internal server error / Service unavailable



# SOAP vs REST

## ■ REST

- Exposes RESOURCES which represent DATA
- Use HTTP Verbs (GET/POST/PUT/DELETE)
- Supports multiple data formats

## ■ SOAP

- Exposes OPERATIONS which represent LOGIC
- Use HTTP POST
- Supports only XML (and attachments)




# SOAP vs REST

Consider "Martin Lawrence" as your data

## SOAP



## REST




# SOAP vs REST

PRAGMATIC

IT Learning &  
Outsourcing Center

HTTP



REST



Rides directly on HTTP. Plain and simple. In reality, this is all you need to send data from point A to point B and get the required response. Catch: Until something that represents a service contract is put in place, it's kinda "anything goes".

SOAP



The coach is your SOAP envelope: it wraps your data. Main strength is the presence of a contract: the WSDL. Gives you the "comfort" of easily generating artifacts. Catch: look at the complexity and added weight.



# Who Use REST?



flickr

amazon.com.

Google™



WIKIPEDIA



You Tube™

ebay

YAHOO!®



# Who Prefer SOAP?

- Big old companies
- Mission critical software systems



# Additional Resources

- SOAP Specification

- <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

- REST Articles

- [http://en.wikipedia.org/wiki/Representational\\_state\\_transfer](http://en.wikipedia.org/wiki/Representational_state_transfer)
- <http://www.ibm.com/developerworks/library/ws-restful/>



# Questions

