

1.  
Kraft's ineq:  $\sum_{i=1}^{|X|} r^{-l_i} \leq 1$

$$\sum r^{-l_i} = 4^{-1} \times 2 + 4^{-2} \times 7 = 0.9375 \leq 1 \quad \checkmark$$

To construct such a code we should make sure that any code is not a prefix of any other codeword in the code. We have

$\{0, 1, 20, 21, 22, 30, 31, 32, 33\}$  instantaneous code

$\{0.15, 0.15, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1\}$  prob

Expected length:

$$E(l) = \sum P(l_i) l_i = 1 \times 0.15 \times 2 + 2 \times 0.1 \times 7$$

2.

To check a codebook we first verify Kraft's ineq:

if it satisfies  $\rightarrow$  there exists an instantaneous code.

if a code is instantaneous

(no codeword is a prefix of others)

$\downarrow$   
uniquely decodable

(its extension must be non-singular)

$\downarrow$   
non-singular ( $x_1 \neq x_2 \Rightarrow C(x_1) \neq C(x_2)$ )

2.

a)  $\{1, 01, 000, 001\}$

Kraft's ineq:

$$2^{-1} + 2^{-2} + 2^{-3} \times 2 \leq 1$$

inst.  $\rightarrow$  uniquely decodable  $\rightarrow$  non-singular

b)  $\{0, 10, 000, 100\}$

nonsingular (no codewords equal) ?  $\checkmark$

uniquely decodable (no ambiguity / different interpretation) ?  $\times$

instantaneous (decode without ref. to future?)  $\times$

c)  $\{01, 01, 110, 100\}$

$$\sum r^{-l_i} = 2^{-2} \times 2 + 2^{-3} \times 2 < 1$$

two codewords equal  $\Rightarrow$  not nonsingular

$\downarrow$

not u.d.

$\downarrow$

not inst.

d)  $\{0, 01, 011, 0111\}$

$$z^{-1} + z^{-2} + z^{-3} + z^{-4} < 1$$

non-singular  $\checkmark$

u.d.  $\checkmark$  (only one possible string.  $C^+$  is non-singular)

inst.  $\times$  (0 is prefix of the others)


e)  $\{10, 01, 0010, 0111\}$

non-singular  $\checkmark$

u.d.  $\checkmark$

inst.  $\times$  (01 is prefix of 0111)


3.



$$m(D-1) + 1$$

$m$ : integer

$D$ : number of leaves at each node



every time remove one leaf.

add  $D$  leaves

+


initial leaf = 1

$$1 + m(D-1)$$


4.

a)  $P = \{0.25, 0.2, 0.15, 0.1, 0.1, 0.1, 0.1\}$

$D=3 \Rightarrow m(D-1)+1 = 2m+1$



c)  $D=5 \Rightarrow m(D-1)+1 = 4m+1$



5.


The entropy of a source (prob. vector) is equal to the expected value of codelength if it satisfies:

$$\sum l \cdot 2^{-l} = H(p)$$

For this we need the probabilities equal  $2^{-l}$  for each  $l$

$\{2, 2, 3, 3, 3, 4, 4\}$  (binary  $\rightarrow 11 = 2$ )

$\{\frac{1}{4}, \frac{1}{4}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{16}, \frac{1}{16}\}$   $\rightarrow$  sums up to 1 to be a prob. vec.



6.

$$\underline{H(X_i | X_{i-1}, X_{i-2}, \dots, X_{i-n})} = \underline{H(X_i | X_{i+1}, X_{i+2}, \dots, X_{i+n})}$$




$$H(X_i, X_{i-1}, \dots, X_{i-n}) - H(X_{i-1}, X_{i-2}, \dots, X_{i-n})$$

$$\underline{(a)} \quad H(X_{i+n}, X_{i+n-1}, \dots, X_i) - H(X_{i+n-1}, X_{i+n-2}, \dots, X_i)$$

$$= H(X_i | X_{i+1}, \dots, X_{i+n})$$

(a) because of stationary we shift the seq.  
n times forward.





$$T = \begin{pmatrix} 1-P & P \\ q & 1-q \end{pmatrix} \begin{matrix} 0 \\ 1 \end{matrix}$$

To find the stationary distribution we should have,

$$\begin{pmatrix} 1-P & P \\ q & 1-q \end{pmatrix} \begin{pmatrix} \alpha \\ 1-\alpha \end{pmatrix} = \begin{pmatrix} \alpha \\ 1-\alpha \end{pmatrix} \Rightarrow \alpha = \frac{q}{P+q}$$

6)  $\rightarrow$  two-state Markov chain

$$H(X) = H(X_n | X_{n-1})$$

in order to maximise  $H(X)$  we have

$$H(X_n | X_{n-1}) \leq H(X_n) \leq 1$$

We can attain  $H(X) = 1$  if  $P = q = \frac{1}{2}$

\* Another approach would have to differentiate w.r.t.  $q$  and  $P$  and equate with zero to solve it.


c)

$$(i) H(X) = H(X_2 | X_1) = H(X_2 | X_1 = 0) P(X_1 = 0) + H(X_2 | X_1 = 1) P(X_1 = 1)$$

$$= \alpha H(p) + (1-\alpha) H(q)$$

$$\underline{q=1} \Rightarrow \alpha H(p)$$

entropy of going to state  $X_2=0$  or  $1$  when we observe state  $1$



$$S_1(n) = S_0(n-1)$$

$$S_0(n) = S(n-1)$$

once you see  $1$  the next r.v. is  $0$

the next r.v. can be either  $0$  or  $1$ .

(ii)

$$S_1(n) = S_0(n-1) = S(n-2)$$

using this we have

$$S(n) = S_0(n) + S_1(n) = S(n-1) + S(n-2)$$

the total number of  $0/1$  sequences

$$f(1) = S(1) = 2$$

$$f(2) = S(2) = 3$$

$$f(3) = S(3) = 2 + 3 = 5$$

$$f(4) = S(4) = 8$$

$$f(5) = S(5) = 13$$

$$\varphi = \frac{1 + \sqrt{5}}{2}$$

golden number

$$f(n) = \frac{p^n + (1-p)^n}{\sqrt{5}}$$

Fibonacci

entropy rate

$$(iii) H(X) = \frac{1}{n} H(X^n) \quad (X_1, \dots, X_n)$$

The maximum is attained when  $X_n$  follows a uniform distribution over its space

The space of  $X^n$  is the sequence of 0/1 with length  $n$  which is  $S_n$ .

$$\Rightarrow \max H(X) \leq \max \frac{H(X^n)}{n} = \frac{1}{n} \log |S_n| = \frac{1}{n} \log \frac{p^n + (1-p)^n}{2}$$

$$n \rightarrow \infty: \max_{n \rightarrow \infty} H(X) = \frac{1}{n} (n \log p - \frac{1}{2} \log 2) = \log p = \log \frac{1+\sqrt{5}}{2}$$

8.  $X_i \in \{A, B\} \sim \{0.9, 0.1\}$

$$H(X) = 0.9 \log 0.9 + 0.1 \log 0.1$$

$\{AA \quad AB \quad BA \quad BB\} \rightarrow$  use Huffman coding to design  
the codebook  
 $0.81 \quad 0.09 \quad 0.09 \quad 0.01$

obtain the average length of the codebook by  $\sum_{i=1}^4 (l_i p_i)$

$$\text{redun. } H(P) - E(L)$$